SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD

102A, 102B, Building 2, Shanghenglang New Industrial Zone, Shanghenglang Community, Dalang Street, Longhua District, Shenzhen, Guangdong, People's Republic of China, 518000

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V06
Report Template Revision Date: 2026-01-30

TEST REPORT

Report No.:	CQASZ20251203027E-03
Applicant:	Shenzhen Buzz Tech CO.,LTD
Address of Applicant:	10th Floor, Guang Chang Bldg, 74#, BaoMin 1st Rd, Bao An Shenzhen, Guangdong, China

Equipment Under Test (EUT):

Product:	AI Glasses
Model No.:	Q01
Test Model No.:	Q01
Brand Name:	N/A
FCC ID:	2AGFW-Q01
Standards:	47 CFR Part 15, Subpart C
	KDB558074 D01 15.247 Meas Guidance v05r02
	ANSI C63.10:2020
Date of Receipt:	2025-12-22
Date of Test:	2025-12-22 to 2026-02-08
Date of Issue:	2026-03-09
Test Result :	**PASS***

***In the configuration tested, the EUT complied with the standards specified above**

Tested By: lewis zhou

(Lewis Zhou)

Reviewed By: Timo Lei

(Timo Lei)

Approved By:

(Jack Ai)

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20251203027E-03	Rev.01	Initial report	2026-03-09

2 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15.203	N/A	PASS
AC Power Line Conducted Emission	47 CFR Part 15.207	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024	PASS
Conducted Peak & Average Output Power	47 CFR Part 15.247	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024	PASS
6dB Occupied Bandwidth	47 CFR Part 15.247	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024	PASS
Power Spectral Density	47 CFR Part 15.247	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15.247	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024	PASS
RF Conducted Spurious Emissions	47 CFR Part 15.247	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024	PASS
Radiated Spurious Emissions	47 CFR Part 15.209	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15.205/15.209	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024	PASS

Remark:

The tested sample(s) and the sample information are provided by the client.

Tx: In this whole report Tx (or tx) means Transmitter.

Rx: In this whole report Rx (or rx) means Receiver.

RF: In this whole report RF means Radiated Frequency.

CH: In this whole report CH means channel.

Volt: In this whole report Volt means Voltage.

Temp: In this whole report Temp means Temperature.

Humid: In this whole report Humid means humidity.

Press: In this whole report Press means Pressure.

N/A: In this whole report not application

3 Contents

Page

1 VERSION 2
2 TEST SUMMARY 3
3 CONTENTS 5
..... 6
4 GENERAL INFORMATION 7
4.1 CLIENT INFORMATION 7
4.2 GENERAL DESCRIPTION OF EUT 7
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD 7
4.4 TEST ENVIRONMENT AND MODE 10
4.5 DESCRIPTION OF SUPPORT UNITS 14
4.6 TEST LOCATION 14
4.7 TEST FACILITY 14
4.8 TEST CONFIGURATION 14
4.9 STATEMENT OF THE MEASUREMENT UNCERTAINTY 15
4.10 DEVIATION FROM STANDARDS 15
4.11 ABNORMALITIES FROM STANDARD CONDITIONS 15
4.12 OTHER INFORMATION REQUESTED BY THE CUSTOMER 15
4.13 EQUIPMENT LIST 16
5 TEST RESULTS AND MEASUREMENT DATA 17
5.1 ANTENNA REQUIREMENT 17
5.2 CONDUCTED EMISSIONS 18
5.3 CONDUCTED PEAK & AVERAGE OUTPUT POWER 22
Test Result 23
Note: Duty cycle correction factor details please see section 4.4. 23
When Duty cycle >98%, D.C.F is not required. 23
Test Graphs 24
5.4 99% OCCUPIED BANDWIDTH 28
Test Result 29
Test Graphs 30
5.5 6DB OCCUPIED BANDWIDTH 34
Test Result 35
Test Graphs 36
5.6 POWER SPECTRAL DENSITY 40
Test Result 41
Test Graphs 42
5.7 BAND-EDGE FOR RF CONDUCTED EMISSIONS 46
Test Result 47
5.7.1 Test Graphs 48
5.8 RF CONDUCTED SPURIOUS EMISSIONS 51
Test Result 52
Test Graphs 53
5.9 RADIATED SPURIOUS EMISSIONS 64
5.9.1 Radiated emission below 1GHz 67
5.9.2 Transmitter emission above 1GHz 69
5.10 RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY 75
6 PHOTOGRAPHS - EUT TEST SETUP 80
6.1 RADIATED SPURIOUS EMISSION 80

6.2 CONDUCTED EMISSION 81
6.3 RF CONDUCTED MEASUREMENT 82
7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS 83

4 General Information

4.1 Client Information

Applicant:	Shenzhen Buzz Tech CO.,LTD
Address of Applicant:	10th Floor, Guang Chang Bldg, 74#, BaoMin 1st Rd, Bao An Shenzhen, Guangdong, China
Manufacturer:	Shenzhen Buzz Tech CO.,LTD
Address of Manufacturer:	10th Floor, Guang Chang Bldg, 74#, BaoMin 1st Rd, Bao An Shenzhen, Guangdong, China
Factory:	Shenzhen Buzz Tech CO.,LTD
Address of Factory:	10th Floor, Guang Chang Bldg, 74#, BaoMin 1st Rd, Bao An Shenzhen, Guangdong, China

4.2 General Description of EUT

Product Name:	AI Glasses
Model No.:	Q01
Test Model No.:	Q01
Trade Mark:	N/A
Software Version:	V1.0
Hardware Version:	V1.0
Power Supply:	Li-ion battery DC 3.85V 270mAh, Charge by DC 5V for adapter
EUT Supports Radios application:	2.4GHz: Wi-Fi: 802.11b/g/n(HT20): 2412MHz~2462MHz;
Simultaneous Transmission	☒ Simultaneous TX is supported and evaluated in this report. ☐ Simultaneous TX is not supported.

4.3 Product Specification subjective to this standard

Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20) : OFDM (64QAM, 16QAM, QPSK, BPSK)
Transfer Rate:	IEEE for 802.11b: 1Mbps/2Mbps/5.5Mbps/11Mbps IEEE for 802.11g : 6Mbps/9Mbps/12Mbps/18Mbps/24Mbps/36Mbps/48Mbps/54Mbps IEEE for 802.11n(HT20) : 6.5Mbps/13Mbps/19.5Mbps/26Mbps/39Mbps/52Mbps/58.5Mbps/65Mbps
Product Type:	☐ Mobile ☒ Portable ☐ Fix Location
Test Software of EUT:	FCC Assist
Antenna Type:	Internal antenna

Antenna Gain:	0dBi

Operation Frequency each of channel(802.11b/g/n HT20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:
In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

For 802.11b/g/n (HT20):

Channel	Frequency
The Lowest channel	2412MHz
The Middle channel	2437MHz
The Highest channel	2462MHz

Note:
Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.4 Test Environment and Mode

Operating Environment:	
Radiated Emissions:	
Temperature:	25.3 °C
Humidity:	55 % RH
Atmospheric Pressure:	1009 mbar
Conducted Emissions:	
Temperature:	25.6 °C
Humidity:	60 % RH
Atmospheric Pressure:	1009 mbar
Radio conducted item test (RF Conducted test room):	
Temperature:	25.5 °C
Humidity:	52 % RH
Atmospheric Pressure:	1009 mbar
Test mode:	
Transmitting mode:	EUT is set in RF test mode in all supported modulation types, bandwidth and data rate, etc.
EUT Power level:	Class13
Run Software:	



Operated Mode for Worst Duty Cycle:				
Test Mode	On time [Ton] (ms)	Period [Ttotal] ms)	Duty Cycle(%)	Average correction factor(dB)
IEEE802.11b	0.99	1.01	98.02	0.09
IEEE802.11g	0.69	0.70	98.57	0.06
IEEE802.11n (HT20)	0.65	0.66	98.48	0.07

Remark:

1) Duty cycle= On Time/ Period;

2) Duty Cycle factor = 10 * log(1/ Duty cycle);

Test Graph_IEEE802.11b Duty Cycle:



Test Graph_IEEE802.11g Duty Cycle:



Test Graph_IEEE802.11 n (HT20) Duty Cycle:



4.5 Description of Support Units

The EUT has been tested with associated equipment below.

1) Support equipment

Description	Manufacturer	Model No.	Certification	Supplied by
Adapter	MI	/	/	CQA

2) Cable

Cable No.	Description	Manufacturer	Cable Type/Length	Supplied by
/	/	/	/	/

4.6 Test Location

All tests were performed at:

SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD

SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD 102A, 102B, Building 2, Shanghenglang New Industrial Zone, Shanghenglang Community, Dalang Street, Longhua District, Shenzhen, Guangdong, People's Republic of China, 518000

4.7 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 4742.01)**

SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD, Shenzhen EMC Laboratory is accredited by the
American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

- **FCC Registration No.: 522263**

SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD, Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

4.8 Test configuration



4.9 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

No.	Item	Uncertainty	Notes
1	Radiated Emission (Below 1GHz)	5.12dB	(1)
2	Radiated Emission (Above 1GHz)	4.60dB	(1)
3	Conducted Disturbance (0.15~30MHz)	3.34dB	(1)
4	Radio Frequency	3×10^{-8}	(1)
5	Duty cycle	0.6 %.	(1)
6	Occupied Bandwidth	1.1%	(1)
7	RF conducted power	0.86dB	(1)
8	RF power density	0.74	(1)
9	Conducted Spurious emissions	0.86dB	(1)
10	Temperature test	0.8℃	(1)
11	Humidity test	2.0%	(1)
12	Supply voltages	0.5 %.	(1)
13	Frequency Error	5.5 Hz	(1)

(1)This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

4.10 Deviation from Standards

None.

4.11 Abnormalities from Standard Conditions

None.

4.12 Other Information Requested by the Customer

None.

4.13 Equipment List

Test Equipment	Manufacturer	Model No.	Instrument No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESR7	CQA-005	2025/9/1	2026/8/31
Spectrum analyzer	R&S	FSU26	CQA-038	2025/9/1	2026/8/31
Spectrum analyzer	R&S	FSU40	CQA-075	2025/9/1	2026/8/31
Preamplifier	MITEQ	AFS4-00010300-18-10P-4	CQA-035	2025/9/1	2026/8/31
Preamplifier	MITEQ	AMF-6D-02001800-29-20P	CQA-036	2025/9/1	2026/8/31
Preamplifier	EMCI	EMC184055SE	CQA-089	2025/9/1	2026/8/31
Loop antenna	Schwarzbeck	FMZB1516	CQA-060	2023/9/8	2026/9/7
Bilog Antenna	R&S	HL562	CQA-011	2023/11/01	2026/10/31
Horn Antenna	R&S	HF906	CQA-012	2023/11/01	2026/10/31
Horn Antenna	Schwarzbeck	BBHA 9170	CQA-088	2023/9/7	2026/9/6
Coaxial Cable (Above 1GHz)	CQA	N/A	C007	2025/9/1	2026/8/31
Coaxial Cable (Below 1GHz)	CQA	N/A	C013	2025/9/1	2026/8/31
Antenna Connector	CQA	RFC-01	CQA-080	2025/9/1	2026/8/31
RF cable(9KHz~40GHz)	CQA	RF-01	CQA-079	2025/9/1	2026/8/31
Power meter	R&S	NRVD	CQA-029	2025/9/1	2026/8/31
Power divider	MIDWEST	PWD-2533-02-SMA-79	CQA-067	2025/9/1	2026/8/31
EMI Test Receiver	R&S	ESR7	CQA-005	2025/9/1	2026/8/31
LISN	R&S	ENV216	CQA-003	2025/9/1	2026/8/31
Coaxial cable	CQA	N/A	CQA-C009	2025/9/1	2026/8/31
DC power	KEYSIGHT	E3631A	CQA-028	2025/9/1	2026/8/31

Test software:

	Manufacturer	Software brand	Software version
Radiated Emissions test software	Tonscend	JS1120-3	Version:8
Conducted Emissions test software	Audix	e3	Version:9
RF Conducted test software	Audix	e3	V3.5.39

5 Test results and Measurement Data

5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
EUT Antenna:	
The antenna is internal antenna. The connection/connection type between the antenna to the EUT's antenna port is: permanently attachment. This is either permanently attachment or a unique coupling that satisfies the requirement.	

5.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207
Test Method:	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
Test Frequency Range:	150kHz to 30MHz
Limit:	

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

Test Procedure:

1) The mains terminal disturbance voltage test was conducted in a shielded room.
2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2020 on conducted measurement.

Test Setup:



Exploratory Test Mode:	Transmitting with all kind of modulations, data rates at lowest, middle and highest channel.
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate of 802.11b at middle channel is the worst case. Only the worst case is recorded in the report.
Test Voltage:	AC120V/60Hz
Test Results:	Pass

Measurement Data

Live Line:



		Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.155	11.73	9.69	21.42	55.73	-34.31	Average	Line
2		0.155	23.10	9.69	32.79	65.73	-32.94	QP	Line
3		0.225	11.56	9.58	21.14	52.63	-31.49	Average	Line
4		0.225	20.06	9.58	29.64	62.63	-32.99	QP	Line
5		0.520	9.92	9.72	19.64	46.00	-26.36	Average	Line
6		0.520	19.34	9.72	29.06	56.00	-26.94	QP	Line
7		1.010	10.53	9.73	20.26	46.00	-25.74	Average	Line
8		1.010	19.59	9.73	29.32	56.00	-26.68	QP	Line
9	AV	1.305	10.62	10.45	21.07	46.00	-24.93	Average	Line
10	PP	1.305	20.89	10.45	31.34	56.00	-24.66	QP	Line
11		1.510	9.62	10.86	20.48	46.00	-25.52	Average	Line
12		1.510	18.92	10.86	29.78	56.00	-26.22	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral Line:



		Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.160	13.92	9.68	23.60	55.46	-31.86	Average	Neutral
2		0.160	28.49	9.68	38.17	65.46	-27.29	QP	Neutral
3		0.190	12.54	9.62	22.16	54.04	-31.88	Average	Neutral
4		0.190	24.39	9.62	34.01	64.04	-30.03	QP	Neutral
5		0.225	12.49	9.57	22.06	52.63	-30.57	Average	Neutral
6		0.225	21.29	9.57	30.86	62.63	-31.77	QP	Neutral
7		0.470	11.65	9.67	21.32	46.51	-25.19	Average	Neutral
8		0.470	21.01	9.67	30.68	56.51	-25.83	QP	Neutral
9		0.990	11.72	9.71	21.43	46.00	-24.57	Average	Neutral
10	QP	0.990	21.55	9.71	31.26	56.00	-24.74	QP	Neutral
11	PP	1.320	11.84	9.72	21.56	46.00	-24.44	Average	Neutral
12		1.320	21.49	9.72	31.21	56.00	-24.79	QP	Neutral

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

5.3 Conducted Peak & Average Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
Test Setup:	*Setup for Power meter measurement method*  *Setup for Spectrum analyser measurement method* 
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Only the worst case is recorded in the report.
Limit:	30dBm
Test Results:	Pass

Test Result

Test Mode	Frequency[MHz]	Result [dBm]	Limit [dBm]	Verdict
11B	2412	-1.01	≤30.00	PASS
	2437	-0.91	≤30.00	PASS
	2462	-1.04	≤30.00	PASS
11G	2412	3.55	≤30.00	PASS
	2437	3.29	≤30.00	PASS
	2462	3.23	≤30.00	PASS
11N20SISO	2412	3.48	≤30.00	PASS
	2437	3.10	≤30.00	PASS
	2462	3.04	≤30.00	PASS

Note: Duty cycle correction factor details please see section 4.4.

When Duty cycle >98%, D.C.F is not required.

Test Graphs

11B_Ant1_2412



11B_Ant1_2437



11B_Ant1_2462



11G_Ant1_2412



11G_Ant1_2437



11G_Ant1_2462



11N20SISO_Ant1_2412



11N20SISO_Ant1_2437



11N20SISO_Ant1_2462



5.4 99% Occupied Bandwidth

Test Requirement:	47 CFR Part 15C
Test Method:	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Only the worst case is recorded in the report.
Test Results:	Pass

Test Result

TestMode	Channel Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]
11B	2412	15.225	2404.4076	2419.6324
	2437	15.305	2429.3277	2444.6324
	2462	15.265	2454.3277	2469.5924
11G	2412	16.823	2403.6084	2420.4316
	2437	16.863	2428.6084	2445.4715
	2462	16.823	2453.6084	2470.4316
11N20SISO	2412	17.542	2403.2488	2420.7912
	2437	18.062	2428.1289	2446.1908
	2462	17.742	2452.9690	2470.7113

Test Graphs

11B_Ant1_2412



11B_Ant1_2437



11B_Ant1_2462



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.461041 GHz	-10.53 dBm		
T1		1	2.4543277 GHz	-22.31 dBm	Occ Bw	15.264735265 MHz
T2		1	2.4695924 GHz	-21.89 dBm		

Date: 3.FEB.2026 14:13:29

11G_Ant1_2412



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.41196 GHz	-2.75 dBm		
T1		1	2.4036084 GHz	-11.76 dBm	Occ Bw	16.823176823 MHz
T2		1	2.4204316 GHz	-11.96 dBm		

Date: 3.FEB.2026 14:18:14

11G_Ant1_2437



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.433084 GHz	-3.51 dBm		
T1		1	2.4286084 GHz	-12.05 dBm	Occ Bw	16.863136863 MHz
T2		1	2.4454715 GHz	-11.70 dBm		

Date: 3.FEB.2026 14:20:06

11G_Ant1_2462



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.459363 GHz	-3.44 dBm		
T1		1	2.4536084 GHz	-11.77 dBm	Occ Bw	16.823176823 MHz
T2		1	2.4704316 GHz	-11.88 dBm		

Date: 3.FEB.2026 14:21:15

11N20SISO_Ant1_2412



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.41196 GHz	-3.35 dBm		
T1		1	2.4032488 GHz	-12.21 dBm	Occ Bw	17.542457542 MHz
T2		1	2.4207912 GHz	-12.94 dBm		

Date: 3.FEB.2026 14:22:36

11N20SISO_Ant1_2437



11N20SISO_Ant1_2462



5.5 6dB Occupied Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Only the worst case is recorded in the report.
Limit:	≥ 500 kHz
Test Results:	Pass

Test Result

TestMode	Antenna	Channel	DTS BW [MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	10.16	0.5	PASS
		2437	11.24	0.5	PASS
		2462	12.60	0.5	PASS
11G	Ant1	2412	16.44	0.5	PASS
		2437	16.64	0.5	PASS
		2462	16.00	0.5	PASS
11N20SISO	Ant1	2412	15.72	0.5	PASS
		2437	15.20	0.5	PASS
		2462	15.80	0.5	PASS

Test Graphs

11B_Ant1_2412



11B_Ant1_2437



11B_Ant1_2462



11G_Ant1_2412



11G_Ant1_2437



11G_Ant1_2462



11N20SISO_Ant1_2412



11N20SISO_Ant1_2437



11N20SISO_Ant1_2462



5.6 Power Spectral Density

Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Only the worst case is recorded in the report.
Limit:	≤8.00dBm/3kHz
Test Results:	Pass

Test Result

TestMode	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	2412	-28.50	≤8.00	PASS
	2437	-28.25	≤8.00	PASS
	2462	-28.36	≤8.00	PASS
11G	2412	-18.64	≤8.00	PASS
	2437	-18.46	≤8.00	PASS
	2462	-18.72	≤8.00	PASS
11N20SISO	2412	-20.50	≤8.00	PASS
	2437	-20.92	≤8.00	PASS
	2462	-20.93	≤8.00	PASS

Note: Duty cycle correction factor details please see section 4.4.
When Duty cycle >98%, D.C.F is not required.

Test Graphs

11B_Ant1_2412



11B_Ant1_2437



11B_Ant1_2462



11G_Ant1_2412



11G_Ant1_2437



11G_Ant1_2462



11N20SISO_Ant1_2412



11N20SISO_Ant1_2437



11N20SISO_Ant1_2462



5.7 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
. Final Test Mode:	Only the worst case is recorded in the report.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass

Test Result

TestMode	ChName	Frequency[MHz]	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
11B	Low	2412	-12.22	-49.17	≤-42.22	PASS
	High	2462	-12.02	-50.93	≤-42.02	PASS
11G	Low	2412	-7.21	-49.87	≤-37.21	PASS
	High	2462	-7.57	-52.01	≤-37.57	PASS
11N20SISO	Low	2412	-6.91	-50.14	≤-36.91	PASS
	High	2462	-6.99	-51.35	≤-36.99	PASS

5.7.1 Test Graphs

11B_Ant1_Low_2412



11B_Ant1_High_2462



11G_Ant1_Low_2412



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.41448 GHz	-7.21 dBm		
M2		1	2.4 GHz	-49.97 dBm		
M3		1	2.39 GHz	-54.60 dBm		
M4		1	2.399855 GHz	-49.87 dBm		

Date: 3.FEB.2026 14:18:35

11G_Ant1_High_2462



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.46444 GHz	-7.57 dBm		
M2		1	2.4835 GHz	-54.79 dBm		
M3		1	2.5 GHz	-56.50 dBm		
M4		1	2.503449 GHz	-52.01 dBm		

Date: 3.FEB.2026 14:21:36

11N20SISO_Ant1_Low_2412



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.41203 GHz	-6.91 dBm		
M2		1	2.4 GHz	-49.37 dBm		
M3		1	2.39 GHz	-53.50 dBm		
M4		1	2.399855 GHz	-50.14 dBm		

Date: 3.FEB.2026 14:22:57

11N20SISO_Ant1_High_2462



5.8 RF Conducted Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Only the worst case is recorded in the report.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass

Test Result

TestMode	Frequency[MHz]	FreqRange [Mhz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
11B	2412	Reference	-12.70	-12.70	---	PASS
		30~1000	-12.70	-50.57	≤-42.7	PASS
		1000~26500	-12.70	-48.19	≤-42.7	PASS
	2437	Reference	-12.93	-12.93	---	PASS
		30~1000	-12.93	-49.99	≤-42.93	PASS
		1000~26500	-12.93	-46.79	≤-42.93	PASS
	2462	Reference	-12.66	-12.66	---	PASS
		30~1000	-12.66	-52.1	≤-42.66	PASS
		1000~26500	-12.66	-48.09	≤-42.66	PASS
11G	2412	Reference	-10.38	-10.38	---	PASS
		30~1000	-10.38	-50.86	≤-40.38	PASS
		1000~26500	-10.38	-47.19	≤-40.38	PASS
	2437	Reference	-11.54	-11.54	---	PASS
		30~1000	-11.54	-51.08	≤-41.54	PASS
		1000~26500	-11.54	-46.89	≤-41.54	PASS
	2462	Reference	-8.17	-8.17	---	PASS
		30~1000	-8.17	-51.64	≤-38.17	PASS
		1000~26500	-8.17	-47.69	≤-38.17	PASS
11N20SISO	2412	Reference	-9.68	-9.68	---	PASS
		30~1000	-9.68	-51.7	≤-39.68	PASS
		1000~26500	-9.68	-46.18	≤-39.68	PASS
	2437	Reference	-10.32	-10.32	---	PASS
		30~1000	-10.32	-51.93	≤-40.32	PASS
		1000~26500	-10.32	-48.41	≤-40.32	PASS
	2462	Reference	-11.10	-11.10	---	PASS
		30~1000	-11.10	-52.27	≤-41.1	PASS
		1000~26500	-11.10	-47.81	≤-41.1	PASS

Test Graphs

11B_Ant1_2412_0~Reference



11B_Ant1_2412_30~1000



11B_Ant1_2412_1000~26500



11B_Ant1_2437_0~Reference



11B_Ant1_2437_30~1000



11B_Ant1_2437_1000~26500



11B_Ant1_2462_0~Reference



11B_Ant1_2462_30~1000



11B_Ant1_2462_1000~26500



11G_Ant1_2412_0~Reference



11G_Ant1_2412_30~1000



11G_Ant1_2412_1000~26500



11G_Ant1_2437_0~Reference



11G_Ant1_2437_30~1000



11G_Ant1_2437_1000~26500



11G_Ant1_2462_0~Reference



11G_Ant1_2462_30~1000



11G_Ant1_2462_1000~26500



11N20SISO_Ant1_2412_0~Reference



11N20SISO_Ant1_2412_30~1000



11N20SISO_Ant1_2412_1000~26500



11N20SISO_Ant1_2437_0~Reference



11N20SISO_Ant1_2437_30~1000



11N20SISO_Ant1_2437_1000~26500



11N20SISO_Ant1_2462_0~Reference



11N20SISO_Ant1_2462_30~1000



11N20SISO_Ant1_2462_1000~26500



Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.

5.9 Radiated Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205
Test Method:	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)

Receiver Setup:

Frequency	Detector	RBW	VBW	Remark
0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

Limit:

Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
1.705MHz-30MHz	30	-	-	30
30MHz-88MHz	100	40.0	Quasi-peak	3
88MHz-216MHz	150	43.5	Quasi-peak	3
216MHz-960MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1GHz	500	54.0	Average	3

Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

Test Setup:	



Figure 1. Below 30MHz



Figure 2. 30MHz to 1GHz



Figure 3. Above 1 GHz

Test Procedure:	a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation. Note: For the radiated emission test above 1GHz: Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

	d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters(for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode,And found the X axis positioning which it is worse case . i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates at lowest, middle and highest channel.
Final Test Mode:	Only the worst case is recorded in the report.
Test Results:	Pass

5.9.1 Radiated emission below 1GHz

30MHz~1GHz
Vertical



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase	APos	TPos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB			cm	deg
1	30.42	22.84	8.18	31.02	40.00	-8.98	Peak	VERTICAL	100	61
2	56.20	9.85	12.65	22.50	40.00	-17.50	Peak	VERTICAL	100	144
3	110.96	9.86	11.69	21.55	43.50	-21.95	Peak	VERTICAL	100	77
4	236.64	11.43	14.87	26.30	46.00	-19.70	Peak	VERTICAL	100	120
5	501.18	15.47	20.94	36.41	46.00	-9.59	Peak	VERTICAL	100	355
6 pp	878.32	10.11	28.94	39.05	46.00	-6.95	Peak	VERTICAL	100	349

Remark:
The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Factor= Antenna Factor + Cable Factor – Preamplifier Factor,
Level = Read Level + Factor,
Over Limit=Level-Limit Line.

Horizontal



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase	APos	TPos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB			cm	deg
1	356.68	8.59	18.31	26.90	46.00	-19.10	Peak	HORIZONTAL	100	166
2	501.18	10.27	20.94	31.21	46.00	-14.79	Peak	HORIZONTAL	100	217
3	588.91	10.72	22.04	32.76	46.00	-13.24	Peak	HORIZONTAL	100	64
4	704.23	9.59	23.80	33.39	46.00	-12.61	Peak	HORIZONTAL	100	280
5 pp	897.00	9.69	29.05	38.74	46.00	-7.26	Peak	HORIZONTAL	100	3
6	989.54	10.68	28.24	38.92	54.00	-15.08	Peak	HORIZONTAL	100	117

Remark:
The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Factor= Antenna Factor + Cable Factor – Preamplifier Factor,
Level = Read Level + Factor,
Over Limit=Level-Limit Line.

5.9.2 Transmitter emission above 1GHz

Test mode:		802.11b(1Mbps)		Test channel:		Lowest			
Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Over (dB)	Detector Type	Ant. Pol. H/V	Antenna Height (m)	Table Angle (Degree)
4824.000	53.71	-4.26	49.45	74	-24.55	peak	H	1.5	25
4824.000	37.25	-4.26	32.99	54	-21.01	AVG	H	1.5	76
7236.000	51.39	1.18	52.57	74	-21.43	peak	H	1.5	259
7236.000	38.89	1.18	40.07	54	-13.93	AVG	H	1.5	48
4824.000	56.14	-4.26	51.88	74	-22.12	peak	V	1.5	312
4824.000	38.04	-4.26	33.78	54	-20.22	AVG	V	1.5	216
7236.000	50.34	1.18	51.52	74	-22.48	peak	V	1.5	27
7236.000	36.47	1.18	37.65	54	-16.35	AVG	V	1.5	236

Test mode:		802.11b(1Mbps)		Test channel:		Middle			
Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Over (dB)	Detector Type	Ant. Pol. H/V	Antenna Height (m)	Table Angle (Degree)
4874.000	51.92	-4.12	47.80	74	-26.20	peak	H	1.5	125
4874.000	37.12	-4.12	33.00	54	-21.00	AVG	H	1.5	23
7311.000	49.57	1.46	51.03	74	-22.97	peak	H	1.5	309
7311.000	36.51	1.46	37.97	54	-16.03	AVG	H	1.5	62
4874.000	52.91	-4.12	48.79	74	-25.21	peak	V	1.5	108
4874.000	36.05	-4.12	31.93	54	-22.07	AVG	V	1.5	152
7311.000	49.00	1.46	50.46	74	-23.54	peak	V	1.5	220
7311.000	36.43	1.46	37.89	54	-16.11	AVG	V	1.5	107

Test mode:		802.11b(1Mbps)		Test channel:		Highest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
4924.000	52.06	-4.03	48.03	74	-25.97	peak	H	1.5	110
4924.000	38.39	-4.03	34.36	54	-19.64	AVG	H	1.5	214
7386.000	50.33	1.66	51.99	74	-22.01	peak	H	1.5	109
7386.000	37.10	1.66	38.76	54	-15.24	AVG	H	1.5	326
4924.000	54.74	-4.03	50.71	74	-23.29	peak	V	1.5	150
4924.000	38.74	-4.03	34.71	54	-19.29	AVG	V	1.5	235
7386.000	50.72	1.66	52.38	74	-21.62	peak	V	1.5	204
7386.000	37.57	1.66	39.23	54	-14.77	AVG	V	1.5	74

Remark:

1) The 1Mbps of rate of 802.11b is the worst case.
2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
   Final Test Level =Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
3) Scan from 9kHz to 25GHz,The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

Test mode:		802.11g(6Mbps)		Test channel:		Lowest			
Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Over (dB)	Detector Type	Ant. Pol. H/V	Antenna Height (m)	Table Angle (Degree)
4824.000	53.63	-4.26	49.37	74	-24.63	peak	H	1.5	346
4824.000	36.01	-4.26	31.75	54	-22.25	AVG	H	1.5	149
7236.000	51.74	1.18	52.92	74	-21.08	peak	H	1.5	39
7236.000	37.22	1.18	38.40	54	-15.60	AVG	H	1.5	151
4824.000	55.31	-4.26	51.05	74	-22.95	peak	V	1.5	334
4824.000	39.49	-4.26	35.23	54	-18.77	AVG	V	1.5	241
7236.000	51.65	1.18	52.83	74	-21.17	peak	V	1.5	227
7236.000	34.98	1.18	36.16	54	-17.84	AVG	V	1.5	257

Test mode:		802.11g(6Mbps)		Test channel:		Middle			
Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Over (dB)	Detector Type	Ant. Pol. H/V	Antenna Height (m)	Table Angle (Degree)
4874.000	53.02	-4.12	48.90	74	-25.10	peak	H	1.5	155
4874.000	37.22	-4.12	33.10	54	-20.90	AVG	H	1.5	337
7311.000	48.72	1.46	50.18	74	-23.82	peak	H	1.5	14
7311.000	36.90	1.46	38.36	54	-15.64	AVG	H	1.5	286
4874.000	52.90	-4.12	48.78	74	-25.22	peak	V	1.5	39
4874.000	37.73	-4.12	33.61	54	-20.39	AVG	V	1.5	283
7311.000	48.91	1.46	50.37	74	-23.63	peak	V	1.5	259
7311.000	36.36	1.46	37.82	54	-16.18	AVG	V	1.5	190

Test mode:		802.11g(6Mbps)		Test channel:		Highest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
4924.000	52.70	-4.03	48.67	74	-25.33	peak	H	1.5	67
4924.000	38.11	-4.03	34.08	54	-19.92	AVG	H	1.5	215
7386.000	49.86	1.66	51.52	74	-22.48	peak	H	1.5	236
7386.000	36.91	1.66	38.57	54	-15.43	AVG	H	1.5	119
4924.000	55.07	-4.03	51.04	74	-22.96	peak	V	1.5	25
4924.000	37.41	-4.03	33.38	54	-20.62	AVG	V	1.5	331
7386.000	50.07	1.66	51.73	74	-22.27	peak	V	1.5	360
7386.000	37.83	1.66	39.49	54	-14.51	AVG	V	1.5	25

Remark:

1) The 6Mbps of rate of 802.11g is the worst case.
2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

   Final Test Level =Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
3) Scan from 9kHz to 25GHz,The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

Test mode:		802.11n20(6.5Mbps)		Test channel:		Lowest			
Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Over (dB)	Detector Type	Ant. Pol. H/V	Antenna Height (m)	Table Angle (Degree)
4824.000	53.17	-4.26	48.91	74	-25.09	peak	H	1.5	320
4824.000	37.83	-4.26	33.57	54	-20.43	AVG	H	1.5	23
7236.000	51.61	1.18	52.79	74	-21.21	peak	H	1.5	7
7236.000	38.47	1.18	39.65	54	-14.35	AVG	H	1.5	166
4824.000	55.17	-4.26	50.91	74	-23.09	peak	V	1.5	266
4824.000	38.18	-4.26	33.92	54	-20.08	AVG	V	1.5	108
7236.000	50.37	1.18	51.55	74	-22.45	peak	V	1.5	26
7236.000	36.27	1.18	37.45	54	-16.55	AVG	V	1.5	150

Test mode:		802.11n20(6.5Mbps)		Test channel:		Middle			
Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Over (dB)	Detector Type	Ant. Pol. H/V	Antenna Height (m)	Table Angle (Degree)
4874.000	53.04	-4.12	48.92	74	-25.08	peak	H	1.5	54
4874.000	36.60	-4.12	32.48	54	-21.52	AVG	H	1.5	255
7311.000	49.81	1.46	51.27	74	-22.73	peak	H	1.5	157
7311.000	35.25	1.46	36.71	54	-17.29	AVG	H	1.5	226
4874.000	52.35	-4.12	48.23	74	-25.77	peak	V	1.5	309
4874.000	36.50	-4.12	32.38	54	-21.62	AVG	V	1.5	24
7311.000	48.63	1.46	50.09	74	-23.91	peak	V	1.5	130
7311.000	35.89	1.46	37.35	54	-16.65	AVG	V	1.5	179

Test mode:		802.11n20(6.5Mbps)		Test channel:		Highest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
4924.000	53.12	-4.03	49.09	74	-24.91	peak	H	1.5	322
4924.000	36.98	-4.03	32.95	54	-21.05	AVG	H	1.5	15
7386.000	50.66	1.66	52.32	74	-21.68	peak	H	1.5	70
7386.000	36.60	1.66	38.26	54	-15.74	AVG	H	1.5	246
4924.000	53.92	-4.03	49.89	74	-24.11	peak	V	1.5	337
4924.000	38.73	-4.03	34.70	54	-19.30	AVG	V	1.5	239
7386.000	50.91	1.66	52.57	74	-21.43	peak	V	1.5	11
7386.000	37.22	1.66	38.88	54	-15.12	AVG	V	1.5	243

Remark:

1) The MCS0 of rate of 802.11n20 is the worst case.
2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

   Final Test Level =Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
3) Scan from 9kHz to 25GHz,The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

5.10 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205
Test Method:	ANSI C63.10 2020
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)
Limit:	

Frequency	Limit (dBuV/m @3m)	Remark
30MHz-88MHz	40.0	Quasi-peak Value
88MHz-216MHz	43.5	Quasi-peak Value
216MHz-960MHz	46.0	Quasi-peak Value
960MHz-1GHz	54.0	Quasi-peak Value
Above 1GHz	54.0	Average Value
	74.0	Peak Value

Test Setup:



Figure 1. 30MHz to 1GHz



Figure 2. Above 1 GHz

Test Procedure:

a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
Note: For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and

	then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel g. Test the EUT in the lowest channel, the middle channel, the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode,And found the X axis positioning which it is worse case . i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates. Transmitting mode.
Final Test Mode:	Pretest the EUT at Transmitting mode, found the Transmitting mode which it is worse case. Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20). Only the worst case is recorded in the report.
Test Results:	Pass

Test data:

Worse case mode:		802.11b(1Mbps)		Test channel:		Lowest			
Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Over (dB)	Detector Type	Ant. Pol. H/V	Antenna Height (m)	Table Angle (Degree)
2390.000	58.90	-9.2	49.70	74	-24.30	peak	H	1.5	17
2390.000	44.33	-9.2	35.13	54	-18.87	AVG	H	1.5	224
2400.000	60.04	-9.39	50.65	74	-23.35	peak	H	1.5	356
2400.000	46.49	-9.39	37.10	54	-16.90	AVG	H	1.5	0
2390.000	58.32	-9.2	49.12	74	-24.88	peak	V	1.5	360
2390.000	44.88	-9.2	35.68	54	-18.32	AVG	V	1.5	231
2400.000	59.65	-9.39	50.26	74	-23.74	peak	V	1.5	51
2400.000	46.27	-9.39	36.88	54	-17.12	AVG	V	1.5	350

Worse case mode:		802.11b(1Mbps)		Test channel:		Highest			
Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Over (dB)	Detector Type	Ant. Pol. H/V	Antenna Height (m)	Table Angle (Degree)
2483.500	57.48	-9.29	48.19	74	-25.81	peak	H	1.5	342
2483.500	44.44	-9.29	35.15	54	-18.85	AVG	H	1.5	344
2483.500	57.53	-9.29	48.24	74	-25.76	peak	V	1.5	98
2483.500	45.61	-9.29	36.32	54	-17.68	AVG	V	1.5	310

Worse case mode:		802.11g(6Mbps)		Test channel:		Lowest			
Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Over (dB)	Detector Type	Ant. Pol. H/V	Antenna Height (m)	Table Angle (Degree)
2390.000	58.95	-9.2	49.75	74	-24.25	peak	H	1.5	186
2390.000	44.19	-9.2	34.99	54	-19.01	AVG	H	1.5	360
2400.000	59.91	-9.39	50.52	74	-23.48	peak	H	1.5	303
2400.000	46.17	-9.39	36.78	54	-17.22	AVG	H	1.5	192
2390.000	58.73	-9.2	49.53	74	-24.47	peak	V	1.5	347
2390.000	44.68	-9.2	35.48	54	-18.52	AVG	V	1.5	18
2400.000	59.30	-9.39	49.91	74	-24.09	peak	V	1.5	228
2400.000	46.79	-9.39	37.40	54	-16.60	AVG	V	1.5	199

Worse case mode:		802.11g(6Mbps)		Test channel:		Highest			
Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Over (dB)	Detector Type	Ant. Pol. H/V	Antenna Height (m)	Table Angle (Degree)
2483.500	57.87	-9.29	48.58	74	-25.42	peak	H	1.5	29
2483.500	44.28	-9.29	34.99	54	-19.01	AVG	H	1.5	188
2483.500	57.84	-9.29	48.55	74	-25.45	peak	V	1.5	305
2483.500	46.00	-9.29	36.71	54	-17.29	AVG	V	1.5	354

Worse case mode:		802.11n(HT20)(6.5Mbps)		Test channel:		Lowest			
Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Over (dB)	Detector Type	Ant. Pol. H/V	Antenna Height (m)	Table Angle (Degree)
2390.000	59.19	-9.2	49.99	74	-24.01	peak	H	1.5	327
2390.000	44.16	-9.2	34.96	54	-19.04	AVG	H	1.5	123
2400.000	59.43	-9.39	50.04	74	-23.96	peak	H	1.5	102
2400.000	46.56	-9.39	37.17	54	-16.83	AVG	H	1.5	39
2390.000	59.08	-9.2	49.88	74	-24.12	peak	V	1.5	280
2390.000	44.69	-9.2	35.49	54	-18.51	AVG	V	1.5	330
2400.000	60.10	-9.39	50.71	74	-23.29	peak	V	1.5	105
2400.000	46.31	-9.39	36.92	54	-17.08	AVG	V	1.5	81

Worse case mode:		802.11n(HT20)(6.5Mbps)		Test channel:		Highest			
Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Over (dB)	Detector Type	Ant. Pol. H/V	Antenna Height (m)	Table Angle (Degree)
2483.500	58.38	-9.29	49.09	74	-24.91	peak	H	1.5	50
2483.500	44.46	-9.29	35.17	54	-18.83	AVG	H	1.5	321
2483.500	57.79	-9.29	48.50	74	-25.50	peak	V	1.5	300
2483.500	45.74	-9.29	36.45	54	-17.55	AVG	V	1.5	22

Note:
The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

6 Photographs - EUT Test Setup

6.1 Radiated Spurious Emission

9kHz~30MHz:



30MHz~1GHz:



Above 1GHz:

6.2 Conducted Emission

6.3 RF Conducted measurement



7 Photographs - EUT Constructional Details

Refer to PHOTOGRAPHS OF EUT for CQASZ20251203027E-01.

*** END OF REPORT ***