



849 NW STATE ROAD 45
NEWBERRY, FL 32669 USA

PH: 888.472.2424 OR
352.472.5500

FAX: 352.472.2030

EMAIL: INFO@TIMCOENGR.COM
[HTTP://WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

RF Exposure Evaluation Report

APPLICANT	ROHILL ENGINEERING B.V.
	Edisonstraat 12 7903 AN Hoogeveen The Netherlands
FCC ID	2AGJ3R-8070-800MHZ
MODEL NUMBER	R-8070-800
PRODUCT DESCRIPTION	TETRA TRANSCEIVER
STANDARD APPLIED	CFR 47 Part 2.1091
PREPARED BY	Cory Leverett

We, TIMCO ENGINEERING, INC. would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and meets the requirements.

The attached report shall not be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

GENERAL REMARKS

Attestations

This equipment has been evaluated in accordance with the standards identified in this report. To the best of my knowledge and belief, these evaluations were performed using the procedures described in this report.

I attest that the necessary evaluations were made, under my supervision, at:

Timco Engineering Inc.
849 NW State Road 45
Newberry, FL 32669

Authorized Signatory Name:

Cory Leverett

Engineering Project Manager

Date: 3/11/2016



RF Exposure Requirements

General information

Device type: TETRA TRANSCEIVER

Devices that operate under Part 90 of this chapter are subject to RF exposure evaluation prior to equipment authorization or use.

Antenna

The manufacturer does not specify an antenna, but a typical antenna has a gain of 0 dBi.

Configuration	Antenna p/n	Type	Max. Gain (dBi)
Fixed mounted	Any	omni	11

MPE Calculation:

The minimum separation distance is calculated as follows:

$E(V/m) = \frac{\sqrt{30 \times P \times G}}{d}$	Power density: $P_d(mW/cm^2) = \frac{E^2}{3770}$
--	--

The limit for general uncontrolled exposure environment is shown in FCC rule Part 1.1310, Table 1.

**Minimum Separation Distance for Mobile or Fixed Devices
General Population/Uncontrolled Exposure**

Insert values in yellow highlighted boxes to determine Minimum Separation Distance

Max Power	43.4	W	<i>equals</i>	Max Power	43400	mW
Duty Cycle	100	%	<i>equals</i>	Duty Factor	1	numeric
Antenna Gain	11	dBi	<i>equals</i>	Gain numeric	12.58925	numeric
Coax Loss	2.6	dB		Gain - Coax Los	6.91831	numeric
Power Density	0.6	mW/cm ²				
Frequency	869	MHz				

Enter power Density from the chart to the right

Rule Part 1.1310, Table 1 (B)

Frequency rang	Power der	Enter this value
MHz	mW/cm ²	mW/cm ²
0.3-1.34	100	100
1.34-30	180/f ²	0.0
30-300	0.2	0.2
300-1,500	f/1500	0.6
1,500-100,000	1	1

f = frequency in MHz

Minimum Separation Distance	200 cm	2.00 m
------------------------------------	---------------	---------------

Minimum Separation in Inches 78.50524 Inches