


TEST REPORT

Application No.: BTEK260713005A01E02
Applicant: Videostrong Technology Co., Ltd
Address of Applicant: 604, Lushi industrial Building, 28 District, Bao'an District, Shenzhen, China
Manufacturer: Videostrong Technology Co., Ltd
Address of Manufacturer: 604, Lushi industrial Building, 28 District, Bao'an District, Shenzhen, China
Equipment Under Test (EUT):
EUT Name: Android TV Box
Test Model.: IPx Air1
Adding Model(s): IPx Air,IPx Air2,IPx Air3,EBI Air,EBI Air1,EBI Air2,EBI 1,WOW_W2,
WOW_SE,10S,14S,20S,30S,N1,N2,N3,M3,Air1,Air2,Air3
Trade Mark: /
FCC ID: 2AGKB-AIR
Standard(s) : 47 CFR Part 2 Subpart J Section 2.1091
447498 D01 General RF Exposure Guidance v06
Date of Receipt Sample(s): 2026-07-21
Date of Test: 2026-07-21 to 2026-08-12
Date of Issue: 2026-08-12

Test Result:	Pass*
---------------------	--------------



* In the configuration tested, the EUT complied with the standards specified above.



Alex Wang / Approved & Authorized
EMC Laboratory Manager



Revision Record			
Version	Issue Date	Revisions	Remarks
V0	2026-08-12	Initial	Valid

Authorized for issue by:			
			
		Zora Huang/ File Editor	
			
		June Li/Reviewer	

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.



2 Contents

	Page
1 Cover Page.....	1
2 Contents	3
3 General Information	4
3.1 Details of E.U.T.	4
3.2 Description of Support Units	5
3.3 Test Location	5
3.4 Deviation from Standards	5
3.5 Abnormalities from Standard Conditions	5
4 Test Requirement	6
4.1 Assessment Result	6



3 General Information

3.1 Details of E.U.T.

Power supply:	INPUT:100-240~50/60Hz 0.3A OUTPUT:5V $\overline{\text{---}}$ 2A 10W
BLE	
Frequency Range:	2402MHz to 2480MHz
Bluetooth Version:	V5.0
Modulation Type:	GFSK
Channel Spacing:	2MHz
Data Rate:	1Mbps, 2Mbps
Number of Channels:	40
Antenna Type:	Metal Antenna
Antenna Gain:	1.96dBi
BT	
Frequency Range:	2402MHz to 2480MHz
Bluetooth Version:	V5.0 classic
Modulation Type:	GFSK, π /4DQPSK, 8DPSK
Number of Channels:	79
Channel Spacing:	1MHz
Antenna Type:	Metal Antenna
Antenna Gain:	1.96dBi
2.4G WIFI	
Support Standards:	802.11b, 802.11g, 802.11n-HT20/40
Frequency Range:	2412-2462MHz for 802.11b/g/n(HT20/40)
Type of Modulation:	802.11b: DSSS; 802.11g/n: OFDM
Quantity of Channels	11 for 802.11b/g/n(HT20) 9 for 802.11b/g/n(HT40)
Channel Separation:	5MHz
Type of Antenna:	Metal Antenna
Antenna Gain:	1.96dBi
5G WIFI	
Support Standards:	802.11a, 802.11n(HT20) ,802.11n-HT40, 802.11ac-VHT20, 802.11ac-VHT40
Operation Frequency	U-NII-1:5180-5240MHz U-NII-3: 5745-5825MHz
Modulation Type:	OFDM
Channel Spacing:	802.11a/n(HT20)/ac(VHT20): 20MHz 802.11n(HT40)/ac(VHT40): 40MHz
Antenna Type:	Metal Antenna
Antenna Gain:	1.66dBi
Sample No.:	BTEK260713005-002
Model(s) Difference Statement	☐ Single Model.
	☒ Multi-Models:IPx Air1, IPx Air,IPx Air2,IPx Air3,EBI Air,EBI Air1,EBI Air2, EBI 1,WOW_W2,WOW_SE,10S,14S,20S,30S,N1,N2,N3,M3,Air1,Air2,Air3 Only the model IPx Air1 was tested. According to the declaration from the applicant, the electrical circuit design, layout, components used, internal wiring and functions of other models are identical for the above models, with



only difference on Model No and the color of the shell
--

3.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
/	/	/	/

3.3 Test Location

All tests were performed at:

Shenzhen BANTEK Testing Co., Ltd.,

A5&A6, Building B1&B2, No.45 Gangtou Road, Bogang Community, Shajing Street, Bao'an District,
Shenzhen, Guangdong, China 518103

Tel:0755-2334 4200 Fax: 0755-2334 4200

FCC Registration Number: 264293

Designation Number: CN1356

No tests were sub-contracted.

3.4 Deviation from Standards

None

3.5 Abnormalities from Standard Conditions

None



4 Test Requirement

According to §1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula: $Pd = (Pout \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW;

G = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

4.1 Assessment Result

☒ Passed ☐ Not Applicable

Frequency (MHz)	Type	Conducted Power (dBm)	Maximum Tune-up (dBm)	Power Density (mW/cm ²)	Simultaneous transmission (mW/cm ²)	Limit (mW/cm ²)	Result
2480	BLE-1M	3.55	4	0.0008	0.0295	1.0000	Pass
2480	BT-3DH5	6.02	6.5	0.0014		1.0000	Pass
2412	2.4G-Wi-Fi/n20	14.36	14.5	0.0088		1.0000	Pass
5200	5.2G-Wi-Fi/ac20	14.95	15.5	0.0103		1.0000	Pass
5755	5.8G-Wi-Fi/n40	14.13	14.5	0.0082		1.0000	Pass

Note: 1. The exposure evaluation safety distance is 20cm.

2. Only show the worst case in the test report.

3. The Simultaneous transmission Max. Power = 0.0295 (mW/cm²) < 1 (mW/cm²), so the extremity SAR test is exclusion.

- End of the Report -

