


TEST REPORT

Application No.: BTEK260713005A01E02
Applicant: Videostrong Technology Co., Ltd
Address of Applicant: 604, Lushi industrial Building, 28 District, Bao'an District, Shenzhen, China
Manufacturer: Videostrong Technology Co., Ltd
Address of Manufacturer: 604, Lushi industrial Building, 28 District, Bao'an District, Shenzhen, China
Equipment Under Test (EUT):
EUT Name: Android TV Box
Test Model.: IPx Air1
Adding Model(s): IPx Air, IPx Air2, IPx Air3, EBI Air, EBI Air1, EBI Air2, EBI 1, WOW_W2, WOW_SE, 10S, 14S, 20S, 30S, N1, N2, N3, M3, Air1, Air2, Air3
Trade Mark: /
FCC ID: 2AGKB-AIR
Standard(s) : 47 CFR Part 15, Subpart C 15.247
KDB558074 D01 15.247 Meas Guidance v05r02
ANSI C63.10:2020
Date of Receipt Sample(s): 2026-07-21
Date of Test: 2026-07-21 to 2026-08-12
Date of Issue: 2026-08-12

Test Result:	Pass*
---------------------	--------------


* In the configuration tested, the EUT complied with the standards specified above.



Alex Wang / Approved & Authorized
EMC Laboratory Manager



Revision Record			
Version	Issue Date	Revisions	Remarks
V0	2026-08-12	Initial	Valid

Authorized for issue by:			
			
		Zora Huang/ File Editor	
			
		June Li/Reviewer	

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.



2 Test Summary

Radio Spectrum Technical Requirement				
Standard	Item	Method	Requirement	Result
47 CFR Part 15, Subpart C 15.247	Antenna Requirement	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Standard	Item	Method	Requirement	Result
47 CFR Part 15, Subpart C 15.247	Conducted Emissions at AC Power Line (150kHz-30MHz)	ANSI C63.10 (2020) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
	Conducted Peak Output Power	ANSI C63.10 (2020) Section 11.9	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
	Minimum 6dB Bandwidth	ANSI C63.10 (2020) Section 11.8	47 CFR Part 15, Subpart C 15.247a(2)	Pass
	Power Spectrum Density	ANSI C63.10 (2020) Section 11.10	47 CFR Part 15, Subpart C 15.247(e)	Pass
	Conducted Band Edges Measurement	ANSI C63.10 (2020) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
	Conducted Spurious Emissions	ANSI C63.10 (2020) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
	Radiated Emissions which fall in the restricted bands	ANSI C63.10 (2020) Section 11.12	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
	Radiated Spurious Emissions	ANSI C63.10 (2020) Section 6.3 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass

Note:

E.U.T./EUT means Equipment Under Test.

Pass means the test result passed the test standard requirement, please find the detailed decision rule in the report relative section.



3 Contents

	Page
1 Cover Page.....	1
2 Test Summary	3
3 Contents	4
4 General Information	5
4.1 Details of E.U.T	5
4.2 EUT Test Mode and Test Condition	5
4.3 Measurement Uncertainty	6
4.4 Test Location	6
4.5 Deviation from Standards	6
4.6 Abnormalities from Standard Conditions	6
5 Equipment List	7
6 Radio Spectrum Technical Requirement	9
6.1 Antenna Requirement	9
6.1.1 Test Requirement:	9
6.1.2 Conclusion	9
7 Radio Spectrum Matter Test Results	10
7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)	10
7.1.1 Test Setup Diagram	10
7.1.2 Measurement Procedure and Data	10
7.2 Conducted Peak Output Power	13
7.2.1 Test Setup Diagram	13
7.2.2 Measurement Procedure and Data	13
7.3 Minimum 6dB Bandwidth	14
7.3.1 Test Setup Diagram	14
7.3.2 Measurement Procedure and Data	14
7.4 Power Spectrum Density	15
7.4.1 Test Setup Diagram	15
7.4.2 Measurement Procedure and Data	15
7.5 Conducted Band Edges Measurement	16
7.5.1 Test Setup Diagram	16
7.5.2 Measurement Procedure and Data	16
7.6 Conducted Spurious Emissions	17
7.6.1 Test Setup Diagram	17
7.6.2 Measurement Procedure and Data	17
7.7 Radiated Emissions which fall in the restricted bands	18
7.7.1 Test Setup Diagram	18
7.7.2 Measurement Procedure and Data	19
7.8 Radiated Spurious Emissions	21
7.8.1 Test Setup Diagram	21
7.8.2 Measurement Procedure and Data	22
8 Test Setup Photo	27
9 EUT Constructional Details (EUT Photos)	27



4 General Information

4.1 Details of E.U.T.

Power supply:	INPUT:100-240~50/60Hz 0.3A OUTPUT:5V= 2A 10W
Frequency Range:	2402MHz to 2480MHz
Bluetooth Version:	V5.0
Modulation Type:	GFSK
Channel Spacing:	2MHz
Data Rate:	1Mbps, 2Mbps
Number of Channels:	40
Antenna Type:	Metal Antenna
Antenna Gain:	1.96dBi
Sample No.:	BTEK260713005-002
Model(s) Difference Statement	☐ Single Model.
	☒ Multi-Models:IPx Air1, IPx Air,IPx Air2,IPx Air3,EBI Air,EBI Air1,EBI Air2, EBI 1,WOW_W2,WOW_SE,10S,14S,20S,30S,N1,N2,N3,M3,Air1,Air2,Air3 Only the model IPx Air1 was tested. According to the declaration from the applicant, the electrical circuit design, layout, components used, internal wiring and functions of other models are identical for the above models, with only difference on Model No and the color of the shell

4.2 EUT Test Mode and Test Condition

Test Mode	Description	Remark
1	Low/mid/High Channel	2402MHz/2440MHz/2480MHz
Remark:1.only show the worst case in the test report.		

Channel Frequency Tabel:

BLE	
Channel	Frequency (MHz)
00	2402
01	2404
19	2440
38	2478
39	2480

Test Conditions	
Temperature:	21.1 °C
Relative Humidity:	55 %
ATM Pressure:	1006 mbar



4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emissions at AC Power Line (150kHz-30MHz)	$\pm 3.12\text{dB}$
Conducted Peak Output Power	$\pm 0.75\text{dB}$
Minimum 6dB Bandwidth	$\pm 3\%$
Power Spectrum Density	$\pm 2.84\text{dB}$
Conducted Band Edges Measurement	$\pm 0.75\text{dB}$
Conducted Spurious Emissions	$\pm 0.75\text{dB}$
Radiated Emissions which fall in the restricted bands	$\pm 5.08\text{dB}$ (1GHz-6GHz); $\pm 5.14\text{dB}$ (above 6GHz)
Radiated Spurious Emissions (Below 1GHz)	$\pm 5.06\text{dB}$ (3m); $\pm 4.46\text{dB}$ (10m)
Radiated Spurious Emissions (Above 1GHz)	$\pm 5.08\text{dB}$ (1GHz-6GHz); $\pm 5.14\text{dB}$ (above 6GHz)

4.4 Test Location

All tests were performed at:

Shenzhen BANTEK Testing Co., Ltd.

A5&A6, Building B1&B2, No.45 Gangtuo Road, Bogang Community, Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Tel: +86 0755-2334 4200 Fax: +86 0755-2334 4200

FCC Registration Number: 264293

Designation Number: CN1356

No tests were sub-contracted.

4.5 Deviation from Standards

None

4.6 Abnormalities from Standard Conditions

None



5 Equipment List

Conducted Test					
Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Shielding Room	YIHENG ENELECTRONIC	9*5*3.3	YH-BT-220304-04	2025-02-15	2028-02-14
EMI Test Receiver	Rohde&Schwarz	ESCI	101021	2026-06-17	2027-06-16
Measurement Software	Fara	EZ EMC Ver. FA-03A2	N/A	N/A	N/A
LISN	Rohde&Schwarz	ENV216	101472	2026-06-17	2027-06-16
LISN	Schwarzbeck	NSLK 8128	05127	2026-06-17	2027-06-16

RF Conducted					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
Shielding Room	YIHENG ENELECTRONIC	5.5*3.1*3	YH-BT-220304-03	2025-02-15	2028-02-14
EXA Signal Analyzer	KEYSIGHT	N9020A	MY54230486	2026-06-17	2027-06-16
DC Power Supply	E3632A	E3642A	KR75304416	2026-06-17	2027-06-16
Attenuator	RswTech	SMA-JK-6dB	N/A	2026-06-17	2027-06-16
Attenuator	RswTech	SMA-JK-3dB	N/A	2026-06-17	2027-06-16
RF Control Unit	Techy	TR1029-1	N/A	2026-06-17	2027-06-16
RF Sensor Unit	Techy	TR1029-2	N/A	2026-06-17	2027-06-16
WIDEBAND RADIO COMMUNICATION TESTER	R&S	CMW 500	141258	2026-06-17	2027-06-16
MXG Vector Signal Generator	Agilent	N5182A	US46240522	2026-06-17	2027-06-16
Programmable Temperature&Humidity Chamber	GRT	GR-HWX1000	GR22051001	2026-06-17	2027-06-16
Measurement Software	TACHOY	RF TestSoft	N/A	N/A	N/A

RSE					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	YIHENG ENELECTRONIC	966	YH-BT-220304-01	2025-02-15	2028-02-14
EMI Test Receiver	Rohde&Schwarz	ESCI	100694	2026-06-17	2027-06-16
TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	01324	2026-06-17	2027-06-16
Pre-Amplifier	Schwarzbeck	BBV 9745	#180	2026-06-17	2027-06-16
Measurement Software	Fara	EZ EMC Ver. FA-03A2	N/A	2026-06-17	2027-06-16
EXA Signal Analyzer	Keysight	N9020A	MY54440290	2026-06-17	2027-06-16
Horn Antenna	Schwarzbeck	BBHA 9120D	02695	2026-06-17	2027-06-16
Pre-Amplifier	Tonscend	TAP0118045	AP20K806109	2026-06-17	2027-06-16
Horn Antenna	SCHWARZBECK	BBHA9170	1157	2026-06-17	2027-06-16
Low Noise Pre-amplifier	SKET	LNPA-1840G-50	SK2022032902	2026-06-17	2027-06-16
Signal analyzer	ROHDE&SCHWARZ	FSQ40	100010	2026-06-17	2027-06-16



Loop Antenna	ETS	6502	00201177	2026-06-17	2027-06-16
Cable	BTEK	LMR400UF-NMNM-7.00M	/	2026-06-17	2027-06-16
Cable	BTEK	LMR400UF-NMNM-2.50M	/	2026-06-17	2027-06-16
Cable	BTEK	LMR400UF-NMNM-3.00M	/	2026-06-17	2027-06-16
Cable	BTEK	SFT205PUR-MNSWSM-7.00M	/	2026-06-17	2027-06-16
Cable	BTEK	SFT205PUR-MNSWSM-2.50M	/	2026-06-17	2027-06-16
Cable	BTEK	SFT205PUR-MNSWSM-2.50M	/	2026-06-17	2027-06-16
Cable	BTEK	SFT205PUR-MNSWSM-0.30M	/	2026-06-17	2027-06-16



6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

This product has a Metal antenna, fulfill the requirement of this section.



7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2020) Section 6.2


Limit:

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz

7.1.1 Test Setup Diagram




7.1.2 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: LISN=Read Level+ Cable Loss+ LISN Factor, Margin=Level-Limit




Test Mode	Communication-TX	Polarity:	Neutral
-----------	------------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1680	38.76	19.44	58.20	65.06	-6.86	QP	P	
2	0.1680	21.49	19.44	40.93	55.06	-14.13	AVG	P	
3	0.2353	35.99	19.61	55.60	62.26	-6.66	QP	P	
4 *	0.2353	27.21	19.61	46.82	52.26	-5.44	AVG	P	
5	0.7661	27.03	19.50	46.53	56.00	-9.47	QP	P	
6	0.7661	15.10	19.50	34.60	46.00	-11.40	AVG	P	
7	2.8544	24.59	20.75	45.34	56.00	-10.66	QP	P	
8	2.8544	13.63	20.75	34.38	46.00	-11.62	AVG	P	
9	8.0340	22.09	21.20	43.29	60.00	-16.71	QP	P	
10	8.0340	10.82	21.20	32.02	50.00	-17.98	AVG	P	
11	17.0970	24.09	22.28	46.37	60.00	-13.63	QP	P	
12	17.0970	11.96	22.28	34.24	50.00	-15.76	AVG	P	





No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1590	40.42	19.54	59.96	65.52	-5.56	QP	P	
2	0.1590	21.48	19.54	41.02	55.52	-14.50	AVG	P	
3	0.2328	36.66	19.63	56.29	62.35	-6.06	QP	P	
4 *	0.2328	28.23	19.63	47.86	52.35	-4.49	AVG	P	
5	0.3523	28.50	19.72	48.22	58.91	-10.69	QP	P	
6	0.3523	16.63	19.72	36.35	48.91	-12.56	AVG	P	
7	0.5685	27.34	19.62	46.96	56.00	-9.04	QP	P	
8	0.5685	18.09	19.62	37.71	46.00	-8.29	AVG	P	
9	2.4090	21.18	20.91	42.09	56.00	-13.91	QP	P	
10	2.4090	9.73	20.91	30.64	46.00	-15.36	AVG	P	
11	13.8163	23.19	21.62	44.81	60.00	-15.19	QP	P	
12	13.8163	11.06	21.62	32.68	50.00	-17.32	AVG	P	



7.2 Conducted Peak Output Power


Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2020) Section 11.9

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.2.1 Test Setup Diagram



7.2.2 Measurement Procedure and Data


Please Refer to Appendix for Details



7.3 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)
Test Method: ANSI C63.10 (2020) Section 11.8
Limit: ≥ 500 kHz

7.3.1 Test Setup Diagram



7.3.2 Measurement Procedure and Data

Please Refer to Appendix for Details



7.4 Power Spectrum Density


Test Requirement 47 CFR Part 15, Subpart C 15.247(e)

Test Method: ANSI C63.10 (2020) Section 11.10

Limit:

$\leq 8\text{dBm}$ in any 3 kHz band during any time interval of continuous transmission

7.4.1 Test Setup Diagram



7.4.2 Measurement Procedure and Data

Please Refer to Appendix for Details



7.5 Conducted Band Edges Measurement


Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2020) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.5.1 Test Setup Diagram



7.5.2 Measurement Procedure and Data

Please Refer to Appendix for Details



7.6 Conducted Spurious Emissions


Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2020) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.6.1 Test Setup Diagram



7.6.2 Measurement Procedure and Data

Please Refer to Appendix for Details



7.7 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209


Test Method: ANSI C63.10 (2020) Section 11.12

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.7.1 Test Setup Diagram



7.7.2 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: $\text{Level} = \text{Read Level} + \text{Cable Loss} + \text{Antenna Factor} - \text{Preamp gain}$, $\text{Margin} = \text{Level} - \text{Limit}$

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

3. If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.



Horizontal; Modulation:GFSK; Channel:Low

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2310.00	67.64	-24.14	43.50	74.00	-30.50	peak	P
2	2310.00	58.02	-24.14	33.88	54.00	-20.12	Average	P
3	2390.00	73.24	-23.92	49.32	74.00	-24.68	peak	P
4	2390.00	64.53	-23.92	40.61	54.00	-13.39	Average	P
5	2400.00	64.19	-23.92	40.27	74.00	-33.73	peak	P
6	2400.00	55.54	-23.92	31.62	54.00	-22.38	Average	P

Polarity: Vertical; Modulation:GFSK; Channel:Low

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2310.00	67.23	-24.14	43.09	74.00	-30.91	peak	P
2	2310.00	57.9	-24.14	33.76	54.00	-20.24	Average	P
3	2390.00	70.12	-23.92	46.20	74.00	-27.80	peak	P
4	2390.00	61.29	-23.92	37.37	54.00	-16.63	Average	P
5	2400.00	68.1	-23.92	44.18	74.00	-29.82	peak	P
6	2400.00	57.49	-23.92	33.57	54.00	-20.43	Average	P

Polarity: Horizontal; Modulation:GFSK; Channel:High

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2483.50	70.36	-23.65	46.71	74.00	-27.29	peak	P
2	2483.50	58.64	-23.65	34.99	54.00	-19.01	Average	P
3	2500.00	72.74	-23.65	49.09	74.00	-24.91	peak	P
4	2500.00	58.74	-23.65	35.09	54.00	-18.91	Average	P

Polarity: Vertical; Modulation:GFSK; Channel:High

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	2483.50	66.19	-23.65	42.54	74.00	-31.46	peak	P
2	2483.50	59.79	-23.65	36.14	54.00	-17.86	Average	P
3	2500.00	70.7	-23.65	47.05	74.00	-26.95	peak	P
4	2500.00	60.97	-23.65	37.32	54.00	-16.68	Average	P




7.8 Radiated Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
Test Method: ANSI C63.10 (2020) Section 6.3,6.4,6.5,6.6
Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.8.1 Test Setup Diagram




7.8.2 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.




Spurious Emissions Below 1GHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 I	40.9880	45.96	-11.32	34.64	40.00	-5.36	QP	100	0	P	
2	148.4410	48.24	-11.99	36.25	43.50	-7.25	QP	100	0	P	
3 *	297.2240	54.85	-11.93	42.92	46.00	-3.08	QP	100	0	P	
4 I	742.2586	45.86	-4.26	41.60	46.00	-4.40	QP	100	0	P	
5 I	890.7277	44.46	-2.34	42.12	46.00	-3.88	QP	100	0	P	
6	962.1621	46.76	-0.77	45.99	54.00	-8.01	QP	100	0	P	





No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 !	38.8877	47.86	-11.36	36.50	40.00	-3.50	QP	100	0	P	
2	81.2116	49.36	-15.76	33.60	40.00	-6.40	QP	100	0	P	
3 !	110.5686	51.71	-13.02	38.69	43.50	-4.81	QP	100	0	P	
4 !	297.2240	52.95	-11.93	41.02	46.00	-4.98	QP	100	0	P	
5 *	593.0496	48.64	-5.79	42.85	46.00	-3.15	QP	100	0	P	
6 !	962.1621	49.36	-0.77	48.59	54.00	-5.41	QP	100	0	P	

Remark:

1) Through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.

2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Reading Level + Factor, Margin= Level-Limit. Factor= Cabel loss +Antenna factor-Pre_amplifier gain.

3) Scan from 9kHz to 1 GHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.



Above 1GHz

Polarity: Horizontal; Modulation:GFSK; Channel:Low

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	4802.94	56.97	-15.60	41.37	74.00	-32.63	peak	P
2	4804.60	42.64	-15.60	27.04	54.00	-26.96	Average	P
3	7207.59	54.05	-10.97	43.08	74.00	-30.92	peak	P
4	7203.76	43.87	-10.97	32.90	54.00	-21.10	Average	P

Polarity: Vertical; Modulation:GFSK; Channel:Low

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	4804.28	56.38	-15.09	41.29	74.00	-32.71	peak	P
2	4802.07	45.6	-15.16	30.44	54.00	-23.56	Average	P
3	7205.23	52.07	-10.77	41.30	74.00	-32.70	peak	P
4	7207.83	41.79	-11.58	30.21	74.00	-43.79	Average	P

Polarity: Horizontal; Modulation:GFSK; Channel:middle

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	4884.63	56.35	-15.27	41.08	74.00	-32.92	peak	P
2	4884.44	43.5	-15.62	27.88	54.00	-26.12	Average	P
3	7322.86	53.19	-10.64	42.55	74.00	-31.45	peak	P
4	7327.67	42.96	-10.65	32.31	54.00	-21.69	Average	P

Polarity: Vertical; Modulation:GFSK; Channel:middle

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	4884.27	56.08	-14.79	41.29	74.00	4884.270	peak	P
2	4887.41	45.08	-15.54	29.54	54.00	4887.410	Average	P
3	7321.48	53.58	-10.38	43.20	74.00	7321.480	peak	P
4	7317.49	41.54	-11.91	29.63	54.00	7317.490	Average	P

Polarity: Horizontal; Modulation:GFSK; Channel:High

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	4958.30	56.38	-16.02	40.36	74.00	-33.64	peak	P
2	4961.70	42.07	-15.55	26.52	54.00	-27.48	Average	P
3	7439.55	53.43	-10.91	42.52	74.00	-31.48	peak	P
4	7437.42	42.83	-10.77	32.06	54.00	-21.94	Average	P

Polarity: Vertical; Modulation:GFSK; Channel:High

No.	Frequency (MHz)	Reading (dBuv)	Factor (dB/m)	Level (dBuv/m)	Limit (dBuv/m)	Margin(dB)	Detector	P/F
1	4958.85	55.91	-16.05	39.86	74.00	-34.14	peak	P
2	4959.46	44.78	-15.78	29.00	54.00	-25.00	Average	P
3	7439.51	53.33	-11.43	41.90	74.00	-32.10	peak	P
4	7437.31	41.23	-11.00	30.23	54.00	-23.77	Average	P



Note:1. Testing is carried out with frequency rang 1GHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

2. If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

3. Final Test Level = Reading Level + Factor, Margin= Level-Limit. Factor= Cabel loss +Antenna factor-Pre_amplifier gain.



8 Test Setup Photo

Please refer to the Appendix Test Setup Photos

9 EUT Constructional Details (EUT Photos)

Please refer to the Appendix EUT Photos

- End of the Report -

