

6.5 Spurious Emissions at Antenna Terminals

Temperature	24°C
Relative Humidity	57%
Atmospheric Pressure	1015mbar
Test date :	December 15, 2015
Tested By :	Winnie Zhang


Requirement(s):

Spec	Item	Requirement	Applicable
§2.1051, §22.917(a)& §24.238(a) § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB	☒
Test Setup	Base Station Spectrum Analyzer EUT		
Test Procedure	- The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The Band Edges of low and high channels for the highest RF powers were measured. - Setting RBW as roughly BW/100.		
Remark			
Result	☒ Pass ☐ Fail		


Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A


Test Plots 30MHz-5GHz LTE Band 2 (Part 24E)




LTE Band 2 - Low Channel-1




LTE Band 2 - Low Channel-2




LTE Band 2 Middle Channel-1



LTE Band 2 Middle Channel-2




LTE Band 2 - High Channel-1




LTE Band 2 - High Channel-2


LTE Band 4 (Part27) result




LTE Band 4 - Low Channel-1




LTE Band 4 - Low Channel-2




LTE Band 4 - Middle Channel-1



LTE Band 4 - Middle Channel-2




LTE Band 4 - High Channel-1




LTE Band 4 - High Channel-2


LTE Band 5 (Part 22H)




LTE Band 5 - Low Channel-1




LTE Band 5 - Low Channel-2




LTE Band 5 - Middle Channel-1



LTE Band 5 - Middle Channel-2




LTE Band 5 - High Channel-1




LTE Band 5 - High Channel-2


LTE Band 12 (Part 27)




LTE Band 12 - Low Channel-1




LTE Band 12 - Low Channel-2




LTE Band 12 - Middle Channel-1



LTE Band 12 - Middle Channel-2




LTE Band 12 - High Channel-1




LTE Band 12 - High Channel-2


LTE Band 17 (Part 27)




LTE Band 17 - Low Channel-1




LTE Band 17 - Low Channel-2




LTE Band 17 - Middle Channel-1



LTE Band 17 - Middle Channel-2



LTE Band 17 - High Channel-1



LTE Band 17 - High Channel-2

6.6 Spurious Radiated Emissions

Temperature	23°C
Relative Humidity	56%
Atmospheric Pressure	1014mbar
Test date :	December 14, 2015
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1053, §22.917 & §24.238 § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.	☒

Test setup	
------------	--

Test Procedure	- The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable. - The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis. - Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. Sample Calculation: EUT Field Strength = Raw Amplitude (dBμV/m) – Amplifier Gain (dB) + Antenna Factor (dB) + Cable Loss (dB) + Filter Attenuation (dB, if used)
----------------	---

Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

LTE Band 2 (Part 24E) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3720	-45.67	V	10.25	2.73	-38.15	-13	-25.15
3720	-46.43	H	10.25	2.73	-38.91	-13	-25.91
43.8	-40.35	V	-4.2	0.11	-44.66	-13	-31.66
187.2	-49.21	H	4.6	0.18	-44.79	-13	-31.79

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-45.61	V	10.25	2.73	-38.09	-13	-25.09
3760	-46.37	H	10.25	2.73	-38.85	-13	-25.85
43.5	-40.25	V	-4.2	0.11	-44.56	-13	-31.56
187.6	-49.11	H	4.6	0.18	-44.69	-13	-31.69

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3800	-45.57	V	10.36	2.73	-37.94	-13	-24.94
3800	-46.43	H	10.36	2.73	-38.8	-13	-25.8
43.9	-40.38	V	-4.2	0.11	-44.69	-13	-31.69
187.5	-49.16	H	4.6	0.18	-44.74	-13	-31.74

Note:

1, The testing has been conformed to $10 \times 1907.5 \text{ MHz} = 19,075 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

LTE Band 4(Part27) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3440	-46.51	V	10.06	2.52	-38.97	-13	-25.97
3440	-47.25	H	10.06	2.52	-39.71	-13	-26.71
44.2	-40.86	V	-4.2	0.11	-45.17	-13	-32.17
186.5	-49.91	H	4.6	0.18	-45.49	-13	-32.49

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3465	-46.48	V	10.09	2.52	-38.91	-13	-25.91
3465	-47.13	H	10.09	2.52	-39.56	-13	-26.56
44.6	-40.81	V	-4.2	0.11	-45.12	-13	-32.12
186.2	-49.87	H	4.6	0.18	-45.45	-13	-32.45

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3490	-46.53	V	10.09	2.52	-38.96	-13	-25.96
3490	-47.08	H	10.09	2.52	-39.51	-13	-26.51
44.9	-40.71	V	-4.2	0.11	-45.02	-13	-32.02
186.4	-49.93	H	4.6	0.18	-45.51	-13	-32.51

Note:

1, The testing has been conformed to $10 \times 1752.5 \text{ MHz} = 17,525 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

LTE Band 5(Part22H) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1658	-43.81	V	7.95	0.78	-36.64	-13	-23.64
1658	-44.56	H	7.95	0.78	-37.39	-13	-24.39
43.8	-40.73	V	-4.2	0.11	-45.04	-13	-32.04
187.3	-49.58	H	4.6	0.18	-45.16	-13	-32.16

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1673	-43.76	V	7.95	0.78	-36.59	-13	-23.59
1673	-44.43	H	7.95	0.78	-37.26	-13	-24.26
43.5	-40.81	V	-4.2	0.11	-45.12	-13	-32.12
187.6	-49.66	H	4.6	0.18	-45.24	-13	-32.24

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1688	-43.85	V	7.95	0.78	-36.68	-13	-23.68
1688	-44.39	H	7.95	0.78	-37.22	-13	-24.22
43.8	-40.71	V	-4.2	0.11	-45.02	-13	-32.02
187.1	-49.76	H	4.6	0.18	-45.34	-13	-32.34

Note:

1, The testing has been conformed to $10 \times 846.5 \text{ MHz} = 8,465 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

LTE Band 12(Part27) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1408	-47.59	V	7.65	0.75	-40.69	-13	-27.69
1408	-47.91	H	7.65	0.75	-41.01	-13	-28.01
43.7	-50.63	V	6.5	0.36	-44.49	-13	-31.49
187.3	-50.77	H	6.8	0.44	-44.41	-13	-31.41

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1415	-47.54	V	7.65	0.75	-40.64	-13	-27.64
1415	-47.87	H	7.65	0.75	-40.97	-13	-27.97
43.8	-50.53	V	6.5	0.36	-44.39	-13	-31.39
187.2	-50.86	H	6.8	0.44	-44.5	-13	-31.50

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1422	-47.49	V	7.65	0.75	-40.59	-13	-27.59
1422	-47.81	H	7.65	0.75	-40.91	-13	-27.91
43.2	-50.46	V	6.5	0.36	-44.32	-13	-31.32
187.8	-50.75	H	6.8	0.44	-44.39	-13	-31.39

Note:

1, The testing has been conformed to $10 \times 715.3 \text{ MHz} = 7,153 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

LTE Band 17(Part27) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1418	-44.38	V	7.65	0.75	-37.48	-13	-24.48
1418	-44.94	H	7.65	0.75	-38.04	-13	-25.04
44.6	-40.13	V	-4.2	0.11	-44.44	-13	-31.44
188.2	-48.97	H	4.6	0.18	-44.55	-13	-31.55

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1420	-44.31	V	7.65	0.75	-37.41	-13	-24.41
1420	-44.89	H	7.65	0.75	-37.99	-13	-24.99
44.3	-40.05	V	-4.2	0.11	-44.36	-13	-31.36
188.6	-48.82	H	4.6	0.18	-44.4	-13	-31.40

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1422	-44.28	V	7.65	0.75	-37.38	-13	-24.38
1422	-44.95	H	7.65	0.75	-38.05	-13	-25.05
44.7	-40.12	V	-4.2	0.11	-44.43	-13	-31.43
188.5	-48.86	H	4.6	0.18	-44.44	-13	-31.44


Note:

- 1, The testing has been conformed to $10 \times 713.5 \text{ MHz} = 7,135 \text{ MHz}$
- 2, All other emissions more than 30 dB below the limit

6.7 Band Edge

Temperature	25°C
Relative Humidity	54%
Atmospheric Pressure	1012mbar
Test date :	December 12, 2015
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§22.917(a) §24.238(a) § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.	☒
Test setup	 The diagram illustrates the test setup. A Base Station (green box) is connected to a Spectrum Analyzer (green box) via a cable. The Spectrum Analyzer is then connected to the EUT (blue box) via a power divider (black box). The labels 'Base Station', 'Spectrum Analyzer', and 'EUT' are placed below their respective components.		
Procedure	- The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The Band Edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.		
Remark			
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

LTE Band 2 (Part 24E) result

BW(MHz)	Channel	Frequency (MHz)	Mode	Emission (dBm)	Limit (dBm)
1.4	18607	1850.7	QPSK	-22.552	-13
			16QAM	-21.714	-13
1.4	18900	1909.3	QPSK	-23.407	-13
			16QAM	-24.628	-13
3	18615	1851.5	QPSK	-17.618	-13
			16QAM	-17.984	-13
3	19185	1908.5	QPSK	-18.645	-13
			16QAM	-20.835	-13
5	18625	1852.5	QPSK	-16.620	-13
			16QAM	-16.797	-13
5	19175	1907.5	QPSK	-17.369	-13
			16QAM	-17.749	-13
10	18650	1855	QPSK	-20.031	-13
			16QAM	-20.805	-13
10	19150	1905	QPSK	-21.697	-13
			16QAM	-22.141	-13
15	18675	1857.5	QPSK	-22.707	-13
			16QAM	-22.454	-13
15	19125	1902.5	QPSK	-23.205	-13
			16QAM	-22.604	-13
20	18700	1860	QPSK	-23.881	-13
			16QAM	-24.351	-13
20	19100	1900	QPSK	-25.822	-13
			16QAM	-24.179	-13

LTE Band 4 (Part 27) result

BW(MHz)	Channel	Frequency (MHz)	Mode	Emission (dBm)	Limit (dBm)
1.4	19957	1710.7	QPSK	-29.572	-13
			16QAM	-28.545	-13
1.4	20393	1754.3	QPSK	-28.706	-13
			16QAM	-28.912	-13
3	19965	1711.5	QPSK	-17.729	-13
			16QAM	-18.335	-13
3	20385	1753.5	QPSK	-21.982	-13
			16QAM	-20.281	-13
5	19975	1712.5	QPSK	-17.112	-13
			16QAM	-16.484	-13
5	20375	1752.5	QPSK	-16.966	-13
			16QAM	-17.107	-13
10	20000	1715	QPSK	-22.542	-13
			16QAM	-21.757	-13
10	20350	1750	QPSK	-22.656	-13
			16QAM	-21.218	-13
15	20025	1717.5	QPSK	-23.392	-13
			16QAM	-23.537	-13
15	20325	1747.5	QPSK	-23.705	-13
			16QAM	-23.850	-13
20	20050	1720	QPSK	-28.099	-13
			16QAM	-26.014	-13
20	20300	1745	QPSK	-25.597	-13
			16QAM	-25.396	-13

LTE Band 5 (Part 22H) result

BW(MHz)	Channel	Frequency (MHz)	Mode	Emission (dBm)	Limit (dBm)
1.4	20407	824.7	QPSK	-25.142	-13
			16QAM	-24.489	-13
1.4	20643	848.3	QPSK	-29.186	-13
			16QAM	-29.184	-13
3	20415	825.5	QPSK	-19.259	-13
			16QAM	-18.451	-13
3	20635	847.5	QPSK	-19.162	-13
			16QAM	-22.057	-13
5	20425	826.5	QPSK	-17.286	-13
			16QAM	-15.985	-13
5	20625	846.5	QPSK	-17.570	-13
			16QAM	-19.980	-13
10	20450	829	QPSK	-19.418	-13
			16QAM	-19.939	-13
10	20800	844	QPSK	-20.670	-13
			16QAM	-21.215	-13

LTE Band 12 (Part 27) result


BW(MHz)	Channel	Frequency (MHz)	Mode	Emission (dBm)	Limit (dBm)
1.4	23017	699.7	QPSK	-20.166	-13
			16QAM	-21.034	-13
1.4	23173	715.3	QPSK	-21.783	-13
			16QAM	-21.567	-13
3	23025	700.5	QPSK	-16.720	-13
			16QAM	-17.025	-13
3	23165	714.5	QPSK	-17.420	-13
			16QAM	-16.913	-13
5	23035	701.5	QPSK	-17.166	-13
			16QAM	-17.550	-13
5	23155	713.5	QPSK	-18.996	-13
			16QAM	-18.513	-13
10	23060	704	QPSK	-20.573	-13
			16QAM	-20.062	-13
10	23130	711	QPSK	-28.879	-13
			16QAM	-30.288	-13

LTE Band 17 (Part 27) result

BW(MHz)	Channel	Frequency (MHz)	Mode	Emission (dBm)	Limit (dBm)
5	23755	706.5	QPSK	-19.506	-13
			16QAM	-19.143	-13
5	23825	713.5	QPSK	-22.454	-13
			16QAM	-23.275	-13
10	23780	709	QPSK	-16.620	-13
			16QAM	-16.155	-13
10	23800	711	QPSK	-18.414	-13
			16QAM	-19.829	-13


Test Plots

LTE Band 2 (Part 24E)




LTE Band 2 - Low Channel QPSK-1.4

Note: Offset=Cable loss (4.5) + 10log
(25.09/10)=4.5+4.0=8.5 dB




LTE Band 2 - High Channel QPSK-1.4

Note: Offset=Cable loss (4.5) + 10log
(16.55/10)=4.5+2.2=6.7 dB




LTE Band 2 - Low Channel 16QAM-1.4

Note: Offset=Cable loss (4.5) + 10log
(24.94/10)=4.5+4.0=8.5 dB




LTE Band 2 - High Channel 16QAM-1.4

Note: Offset=Cable loss (4.5) + 10log
(14.13/10)=4.5+1.5=6.0 dB




LTE Band 2 - Low Channel QPSK-3

Note: Offset=Cable loss (4.5) + 10log
(59.95/30)=4.5+2.0=7.5 dB



LTE Band 2 - High Channel QPSK-3

Note: Offset=Cable loss (4.5) + 10log
(47.91/30)=4.5+2.0=6.5 dB




LTE Band 2 - Low Channel 16QAM-3

Note: Offset=Cable loss (4.5) + 10log
(56.86/30)=4.5+2.8=7.3 dB



LTE Band 2 - High Channel 16QAM-3

Note: Offset=Cable loss (4.5) + 10log
(41.73/30)=4.5+1.4=5.9 dB



LTE Band 2 - Low Channel QPSK-5




LTE Band 2 - High Channel QPSK-5

Note: Offset=Cable loss (4.5) + 10log
(74.72/30)=4.5+4.0=8.5 dB




LTE Band 2 - Low Channel 16QAM-5

Note: Offset=Cable loss (4.5) + 10log
(74.55/30)=4.5+4.0=8.5 dB




LTE Band 2 - Low Channel QPSK-10



LTE Band 2 - Low Channel 16QAM-10

Note: Offset=Cable loss (4.5) + 10log
(72.16/30)=4.5+2.3=6.8 dB



LTE Band 2 - High Channel 16QAM-5


Note: Offset=Cable loss (4.5) + 10log
(71.98/30)=4.5+2.3=6.8 dB



LTE Band 2 - High Channel QPSK-10




LTE Band 2 - High Channel 16QAM-10




LTE Band 2 - Low Channel QPSK-15

Note: Offset=Cable loss (4.5) + 10log
(152.0/100)=4.5+1.8=6.3 dB




LTE Band 2 - High Channel QPSK-15

Note: Offset=Cable loss (4.5) + 10log
(150.5/100)=4.5+1.8=6.3 dB




LTE Band 2 - Low Channel 16QAM-15

Note: Offset=Cable loss (4.5) + 10log
(151.7/100)=4.5+1.8=6.3 dB




LTE Band 2 - High Channel 16QAM-15

Note: Offset=Cable loss (4.5) + 10log
(151.3/100)=4.5+1.8=6.3 dB




LTE Band 2 - Low Channel QPSK-20



LTE Band 2 - High Channel QPSK-20

Test Report	15071081-FCC-R5
Page	97 of 128


Note: Offset=Cable loss (4.5) + 10log
(195.5/100)=4.5+2.9=7.4 dB



LTE Band 2 - Low Channel 16QAM-20

Note: Offset=Cable loss (4.5) + 10log
(196.3/100)=4.5+2.9=7.4 dB


Note: Offset=Cable loss (4.5) + 10log
(197.0/100)=4.5+2.9=7.4 dB



LTE Band 2 - High Channel 16QAM-20


Note: Offset=Cable loss (4.5) + 10log
(197.0/100)=4.5+2.9=7.4 dB

LTE Band 4 (Part 27)




LTE Band 4 - Low Channel QPSK-1.4

Note: Offset=Cable loss (4.5) + 10log
(24.86/10)=4.5+4.0=8.5 dB




LTE Band 4 - High Channel QPSK-1.4

Note: Offset=Cable loss (4.5) + 10log
(17.27/10)=4.5+2.4=6.9 dB




LTE Band 4 - Low Channel 16QAM-1.4

Note: Offset=Cable loss (4.5) + 10log
(24.55/10)=4.5+3.9=8. dB




LTE Band 4 - High Channel 16QAM-1.4

Note: Offset=Cable loss (4.5) + 10log
(15.44/10)=4.5+1.9=6.4 dB




LTE Band 4 - Low Channel QPSK-3

Note: Offset=Cable loss (4.5) + 10log
(53.18/30)=4.5+2.5=7 dB



LTE Band 4 - High Channel QPSK-3

Note: Offset=Cable loss (4.5) + 10log
(47.69/30)=4.5+2.0=6.5 dB




LTE Band 4 - Low Channel 16QAM-3

Note: Offset=Cable loss (4.5) + 10log
(53.8/30)=4.5+2.6=7.1 dB




LTE Band 4 - High Channel 16QAM-3

Note: Offset=Cable loss (4.5) + 10log
(47.85/30)=4.5+2.0=6.5 dB



LTE Band 4 - Low Channel QPSK-5



LTE Band 4 - High Channel QPSK-5

Note: Offset=Cable loss (4.5) + 10log
(74.72/30)=4.5+4.0=8.5 dB




LTE Band 4 - Low Channel 16QAM-5

Note: Offset=Cable loss (4.5) + 10log
(72.89/30)=4.5+3.9=8.4 dB



LTE Band 4 - High Channel 16QAM-5

Note: Offset=Cable loss (4.5) + 10log
(74.73/30)=4.5+4.5=8.5 dB




LTE Band 4 - Low Channel QPSK-10

Note: Offset=Cable loss (4.5) + 10log
(72.65/30)=4.5+3.8=8.3 dB




LTE Band 4 - High Channel QPSK-10



LTE Band 4 - Low Channel 16QAM-10



LTE Band 4 - High Channel 16QAM-10



LTE Band 4 - Low Channel QPSK-15

Note: Offset=Cable loss (4.5) + 10log
(151.7/100)=4.5+1.8=6.3 dB




LTE Band 4 - High Channel QPSK-15

Note: Offset=Cable loss (4.5) + 10log
(152.3/100)=4.5+1.8=6.3 dB




LTE Band 4 - Low Channel 16QAM-15

Note: Offset=Cable loss (4.5) + 10log
(149.7/100)=4.5+1.8=6.3 dB




LTE Band 4 - High Channel 16QAM-15

Note: Offset=Cable loss (4.5) + 10log
(148.3/100)=4.5+1.7=6.2 dB



LTE Band 4 - Low Channel QPSK-20



LTE Band 4 - High Channel QPSK-20

Test Report	15071081-FCC-R5
Page	102 of 128


Note: Offset=Cable loss (4.5) + 10log
(196.9/100)=4.5+2.9=7.4 dB



LTE Band 4 - Low Channel 16QAM-20

Note: Offset=Cable loss (4.5) + 10log
(196.9/100)=4.5+2.9=7.4 dB


Note: Offset=Cable loss (4.5) + 10log
(196.1/100)=4.5+2.9=7.4 dB



LTE Band 4 - High Channel 16QAM-20


Note: Offset=Cable loss (4.5) + 10log
(197.7/100)=4.5+3.0=7.5 dB

LTE Band 5 (Part 22H)



LTE Band 5 - Low Channel QPSK-1.4

Note: Offset=Cable loss (4.5) + 10log
(22.65/10)=4.5+3.6=8.1 dB




LTE Band 5 - High Channel QPSK-1.4

Note: Offset=Cable loss (4.5) + 10log
(20.89/10)=4.5+3.2=7.7 dB



LTE Band 5 - Low Channel 16QAM-1.4

Note: Offset=Cable loss (4.5) + 10log
(24.97/10)=4.5+4.0=8.5 dB




LTE Band 5 - High Channel 16QAM-1.4

Note: Offset=Cable loss (4.5) + 10log
(21.03/10)=4.5+3.2=7.7 dB



LTE Band 5 - Low Channel QPSK-3

Note: Offset=Cable loss (4.5) + 10log
(53.63/30)=4.5+2.5=7.0 dB



LTE Band 5 - High Channel QPSK-3

Note: Offset=Cable loss (4.5) + 10log
(48.42/30)=4.5+2.1=6.6 dB



LTE Band 5 - Low Channel 16QAM-3

Note: Offset=Cable loss (4.5) + 10log
(53.02/30)=4.5+2.5=7.0 dB



LTE Band 5 - High Channel 16QAM-3

Note: Offset=Cable loss (4.5) + 10log
(48.42/30)=4.5+2.1=6.6 dB



LTE Band 5 - Low Channel QPSK-5




LTE Band 5 - High Channel QPSK-5

Note: Offset=Cable loss (4.5) + 10log
(74.72/30)=4.5+2.2=8.5 dB




LTE Band 5 - Low Channel 16QAM-5

Note: Offset=Cable loss (4.5) + 10log
(74.85/30)=4.5+4.0=8.5 dB



LTE Band 5 - Low Channel QPSK-10




LTE Band 5 - Low Channel 16QAM-10

Note: Offset=Cable loss (4.5) + 10log
(74.07/30)=4.5+2.2=8.4 dB



LTE Band 5 - High Channel 16QAM-5

Note: Offset=Cable loss (4.5) + 10log
(71.93/30)=4.5+3.8=8.3 dB




LTE Band 5 - High Channel QPSK-10



LTE Band 5 - High Channel 16QAM-10

LTE Band 12 (Part 27)




LTE Band 12 - Low Channel QPSK-1.4

Note: Offset=Cable loss (4.5) + 10log
(28.66/10)=4.5+4.4=8.9 dB




LTE Band 12 - High Channel QPSK-1.4

Note: Offset=Cable loss (4.5) + 10log
(27.23/10)=4.5+4.6=9.1 dB




LTE Band 12 - Low Channel 16QAM-1.4

Note: Offset=Cable loss (4.5) + 10log
(28.0/10)=4.5+4.4=8.9 dB



LTE Band 12 - High Channel 16QAM-1.4

Note: Offset=Cable loss (4.5) + 10log
(27.50/10)=4.5+4.6=9.1 dB




LTE Band 12 - Low Channel QPSK-3

Note: Offset=Cable loss (4.5) + 10log
(67.85/30)=4.5+3.5=8 dB



LTE Band 12 - High Channel QPSK-3

Note: Offset=Cable loss (4.5) + 10log
(69.74/30)=4.5+3.7=8.2 dB



LTE Band 12 - Low Channel 16QAM-3

Note: Offset=Cable loss (4.5) + 10log
(68.04/30)=4.5+3.6=8.1 dB



LTE Band 12 - High Channel 16QAM-3

Note: Offset=Cable loss (4.5) + 10log
(27.50/30)=4.5+3.7=8.2 dB



LTE Band 12 - Low Channel QPSK-5




LTE Band 12 - High Channel QPSK-5

Note: Offset=Cable loss (4.5) + 10log
(82.90/30)=4.5+4.4=8.9 dB




LTE Band 12 - Low Channel 16QAM-5

Note: Offset=Cable loss (4.5) + 10log
(82.09/30)=4.5+4.4=8.9 dB



LTE Band 12 - Low Channel QPSK-10




LTE Band 12 - Low Channel 16QAM-10

Note: Offset=Cable loss (4.5) + 10log
(83.18/30)=4.5+4.4=8.9 dB




LTE Band 12 - High Channel 16QAM-5

Note: Offset=Cable loss (4.5) + 10log
(83.21/30)=4.5+4.4=8.9 dB



LTE Band 12 - High Channel QPSK-10



LTE Band 12 - High Channel 16QAM-10

LTE Band 17 (Part 27)



LTE Band 17 - Low Channel QPSK-5

Note: Offset=Cable loss (4.0) + 10log
(82.82/30)=4.5+4.4=8.9 dB




LTE Band 17 - High Channel QPSK-5

Note: Offset=Cable loss (4.0) + 10log
(82.86/30)=4.5+4.4=8.9 dB



LTE Band 17 - Low Channel 16QAM-5

Note: Offset=Cable loss (4.0) + 10log
(83.11/30)=4.5+4.4=8.9 dB



LTE Band 17 - High Channel 16QAM-5


Note: Offset=Cable loss (4.0) + 10log
(82.97/30)=4.5+4.4=8.9 dB




LTE Band 17 - Low Channel QPSK-10



LTE Band 17 - High Channel QPSK-10



LTE Band 17 - Low Channel 16QAM-10




LTE Band 17 - High Channel 16QAM-10

6.8 Band Edge 27.53(m)

Temperature	23°C
Relative Humidity	56%
Atmospheric Pressure	1014mbar
Test date :	-----
Tested By :	-----

Requirement(s):

Spec	Requirement	Applicable
§27.53(m)	According to FCC 27.53(m)(4) specified that power of any emission outside of the channel edge must be attenuated below the transmitting power(P) by a factor shall be not less than $43+10\log(P)$ dB at the channel edge, the limit of emission equal to -13dBm. And $55+10\log(P)$ dB at 5.5MHz from the channel edges, the limit of emission equal to -25dBm. In the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.	☒
Test Setup	 Base Station Spectrum Analyzer EUT	
Test Procedure	- The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers.	
Remark		
Result	☐ Pass ☐ Fail ☒ N/A	

Test Data ☐ Yes ☐ N/A


Test Plot ☐ Yes (See below) ☐ N/A

6.9 Frequency Stability

Temperature	23°C
Relative Humidity	56%
Atmospheric Pressure	1014mbar
Test date :	December 14, 2015
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable																																
§2.1055, §22.355 & §24.235 § 27.5(h); § 27.54	a)	According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below: Frequency Tolerance for Transmitters in the Public Mobile Services <table border="1"> <thead> <tr> <th>Frequency Range (MHz)</th><th>Base, fixed (ppm)</th><th>Mobile ≤ 3 watts (ppm)</th><th>Mobile ≤ 3 watts (ppm)</th></tr> </thead> <tbody> <tr> <td>25 to 50</td><td>20.0</td><td>20.0</td><td>50.0</td></tr> <tr> <td>to 450</td><td>5.0</td><td>5.0</td><td>50.0</td></tr> <tr> <td>450 to 512</td><td>2.5</td><td>5.0</td><td>5 0</td></tr> <tr> <td>821 to 896</td><td>1.5</td><td>2.5</td><td>2.5</td></tr> <tr> <td>928 to 929.</td><td>5.0</td><td>N/A</td><td>N/A</td></tr> <tr> <td>929 to 960.</td><td>1.5</td><td>N/A</td><td>N/A</td></tr> <tr> <td>2110 to 2220</td><td>10.0</td><td>N/A</td><td>N/A</td></tr> </tbody> </table> According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized frequency block. According to §27.54, The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.	Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)	25 to 50	20.0	20.0	50.0	to 450	5.0	5.0	50.0	450 to 512	2.5	5.0	5 0	821 to 896	1.5	2.5	2.5	928 to 929.	5.0	N/A	N/A	929 to 960.	1.5	N/A	N/A	2110 to 2220	10.0	N/A	N/A	☒
Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)																																
25 to 50	20.0	20.0	50.0																																
to 450	5.0	5.0	50.0																																
450 to 512	2.5	5.0	5 0																																
821 to 896	1.5	2.5	2.5																																
928 to 929.	5.0	N/A	N/A																																
929 to 960.	1.5	N/A	N/A																																
2110 to 2220	10.0	N/A	N/A																																

Test setup	 Base Station EUT Thermal Chamber
Procedure	A communication link was established between EUT and base station. The frequency error was monitored and measured by base station under variation of ambient temperature and variation of primary supply voltage. Limit: The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.
Remark	Frequency Stability versus Temperature: The Frequency tolerance of the carrier signal shall be maintained within 2.5ppm of the operating frequency over a temperature variation of -10°C to $+55^{\circ}\text{C}$ at normal supply voltage.
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

LTE Band 2 (Part 24E) result

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	-7	0.0037	2.5
0		-11	0.0059	2.5
10		-7	0.0037	2.5
20		-10	0.0053	2.5
30		-10	0.0053	2.5
40		-8	0.0043	2.5
50		-11	0.0059	2.5
55		-9	0.0048	2.5
25	4.2	-11	0.0059	2.5
	3.5	-9	0.0048	2.5

LTE Band 4 (Part 27) result

Middle Channel, $f_0 = 1732.5$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	-12	0.0069	2.5
0		-11	0.0063	2.5
10		-11	0.0063	2.5
20		-12	0.0069	2.5
30		-12	0.0069	2.5
40		-10	0.0058	2.5
50		-14	0.0081	2.5
55		-12	0.0069	2.5
25	4.2	-11	0.0063	2.5
	3.5	-15	0.0087	2.5

LTE Band 5 (Part 22H) result

Middle Channel, $f_0 = 836.5$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	8	0.0096	2.5
0		7	0.0084	2.5
10		7	0.0084	2.5
20		8	0.0096	2.5
30		11	0.0132	2.5
40		12	0.0143	2.5
50		9	0.0108	2.5
55		9	0.0108	2.5
25	4.2	9	0.0108	2.5
	3.5	12	0.0143	2.5

LTE Band 12 (Part 27) result

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	-11	0.0059	2.5
0		-10	0.0053	2.5
10		-9	0.0048	2.5
20		-11	0.0059	2.5
30		-10	0.0053	2.5
40		-9	0.0048	2.5
50		-11	0.0059	2.5
55		-10	0.0053	2.5
25	4.2	-10	0.0053	2.5
	3.5	-12	0.0064	2.5

LTE Band 17 (Part 27) result


Middle Channel, $f_0 = 710$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	10	0.0141	2.5
0		9	0.0127	2.5
10		6	0.0085	2.5
20		8	0.0113	2.5
30		5	0.0070	2.5
40		10	0.0141	2.5
50		11	0.0155	2.5
55		8	0.0113	2.5
25	4.2	9	0.0127	2.5
	3.5	11	0.0155	2.5

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
RF Conducted Test					
Agilent ESA-E SERIES SPECTRUM ANALYZER	E4407B	MY45108319	09/17/2015	09/16/2016	☒
Power Splitter	1#	1#	09/01/2015	08/31/2016	☒
Universal Radio Communication Tester	CMU200	121393	09/25/2015	09/24/2016	☒
Wideband Radio Communication Tester	CMW500	120906	03/29/2015	03/28/2016	☒
Temperature/Humidity Chamber	UHL-270	001	10/09/2015	10/08/2016	☒
DC Power Supply	E3640A	MY40004013	09/17/2015	09/16/2016	☒
Radiated Emissions					
EMI test receiver	ESL6	100262	09/17/2015	09/16/2016	☒
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	09/01/2015	08/31/2016	☒
Microwave Preamplifier (0.5 ~ 18GHz)	PAM-118	443008	09/01/2015	08/31/2016	☒
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/21/2015	09/20/2016	☒
Bilog Antenna (30MHz~2GHz)	JB1	A112017	09/21/2015	09/20/2016	☒
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71259	09/24/2015	09/23/2016	☒
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/24/2015	09/23/2016	☒
SYNTHESIZED SIGNAL GENERATOR	8665B	3744A01293	09/17/2015	09/16/2016	☒
Tunable Notch Filter	3NF-800/1000-S	AA4	09/01/2015	08/31/2016	☒
Tunable Notch Filter	3NF-1000/2000-S	AM 4	09/01/2015	08/31/2016	☒

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo




Test Report	15071081-FCC-R5
Page	119 of 128




EUT - Top View



EUT - Bottom View



EUT - Left View



EUT - Right View

Annex B.ii. Photograph: EUT Internal Photo




Cover Off - Top View 1




Cover Off - Top View 2




Battery - Front View




Battery - Rear View




Mainboard with Shielding - Front View



Mainboard with Shielding - Rear View




Mainboard without shielding - Front View



Mainboard without shielding - Rear View




LCD - Front View



LCD - Rear View




GSM/PCS/UMTS-FDD - Antenna View



LTE - Antenna View

Test Report	15071081-FCC-R5
Page	122 of 128




WIFI/BT/BLE/GPS - Antenna View

Annex B.iii. Photograph: Test Setup Photo



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above
1GHz

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK

Block Configuration Diagram for Radiated Emissions



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Manufacturer	Equipment Description	Model	Serial No
MACATE GROUP CORPORATION	Adapter	A88-502000	CN15020403

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	JX120051317

Test Report	15071081-FCC-R5
Page	126 of 128

Annex C.ii. EUT OPERATING CONKITIONS

N/A

Test Report	15071081-FCC-R5
Page	127 of 128

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see attachment

Test Report	15071081-FCC-R5
Page	128 of 128

Annex E. DECLARATION OF SIMILARITY

N/A