

FCC REPORT

(Bluetooth)

Applicant: Grand Electronics INC.

Address of Applicant: 11650 Brentcross Dr, Tomball, Texas, 77377, USA

Equipment Under Test (EUT)

Product Name: K1s

Model No.: K1s, 63K1, 63K1N, 63K1H, 63K1R

Trade mark: neutab.

FCC ID: 2AGNKK1S

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of sample receipt: 10 May, 2017

Date of Test: 10 May, to 30 Jun., 2017

Date of report issued: 03 Jul., 2017

Test Result: PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang

Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	03 Jul., 2017	Original

Tested by:

Peter zhu

Date:

03 Jul., 2017

Test Engineer

Reviewed by:

Ryan.lee

Date:

03 Jul., 2017

Project Engineer

3 Contents

Page

1	COVER PAGE.....	1
2	VERSION	2
3	CONTENTS	3
4	TEST SUMMARY.....	4
5	GENERAL INFORMATION.....	5
5.1	CLIENT INFORMATION	5
5.2	GENERAL DESCRIPTION OF E.U.T.	5
5.3	TEST MODE	7
5.4	MEASUREMENT UNCERTAINTY.....	7
5.5	LABORATORY FACILITY.....	7
5.6	LABORATORY LOCATION	7
5.7	TEST INSTRUMENTS LIST.....	8
6	TEST RESULTS AND MEASUREMENT DATA	9
6.1	ANTENNA REQUIREMENT	9
6.2	CONDUCTED EMISSIONS	10
6.3	CONDUCTED OUTPUT POWER.....	13
6.4	20dB OCCUPY BANDWIDTH.....	17
6.5	CARRIER FREQUENCIES SEPARATION.....	21
6.6	HOPPING CHANNEL NUMBER	26
6.7	DWELL TIME.....	28
6.8	PSEUDORANDOM FREQUENCY HOPPING SEQUENCE	32
6.9	BAND EDGE.....	33
6.9.1	Conducted Emission Method.....	33
6.9.2	Radiated Emission Method.....	37
6.10	SPURIOUS EMISSION	50
6.10.1	Conducted Emission Method.....	50
6.10.2	Radiated Emission Method	57
7	TEST SETUP PHOTO	62
8	EUT CONSTRUCTIONAL DETAILS.....	63

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna Requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(1)	Pass
20dB Occupied Bandwidth	15.247 (a)(1)	Pass
Carrier Frequencies Separation	15.247 (a)(1)	Pass
Hopping Channel Number	15.247 (a)(1)	Pass
Dwell Time	15.247 (a)(1)	Pass
Radiated Emission	15.205/15.209	Pass
Band Edge	15.247(d)	Pass

Pass: The EUT complies with the essential requirements in the standard.

5 General Information

5.1 Client Information

Applicant:	Grand Electronics INC.
Address of Applicant:	11650 Brentcross Dr, Tomball, Texas, 77377, USA
Manufacturer/ Factory:	SHENZHEN YNC ELECTRONIC CO.,LTD
Address of Manufacturer/Factory:	5/F, building 9, longjun Industry area, Hepingxi Road, Longhua, shenzhen, china

5.2 General Description of E.U.T.

Product Name:	K1s
Model No.:	K1s, 63K1, 63K1N, 63K1H, 63K1R
Operation Frequency:	2402MHz~2480MHz
Transfer rate:	1/2/3 Mbits/s
Number of channel:	79
Modulation type:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Modulation technology:	FHSS
Antenna Type:	Internal Antenna
Antenna gain:	1.54 dBi
Power supply:	Rechargeable Li-ion Battery DC3.7V-4400mAh
AC adapter:	Model: HT-003-050200 Input: AC100-240V 50/60Hz 0.35A Output: DC 5.0V, 2A
Remark:	The No.: K1s, 63K1, 63K1N, 63K1H, 63K1R were identical inside, the electrical circuit design, layout, components used and internal wiring, with only difference being Model name.

Operation Frequency each of channel for GFSK, $\pi/4$ -DQPSK, 8DPSK							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	20	2422MHz	40	2442MHz	60	2462MHz
1	2403MHz	21	2423MHz	41	2443MHz	61	2463MHz
2	2404MHz	22	2424MHz	42	2444MHz	62	2464MHz
3	2405MHz	23	2425MHz	43	2445MHz	63	2465MHz
4	2406MHz	24	2426MHz	44	2446MHz	64	2466MHz
5	2407MHz	25	2427MHz	45	2447MHz	65	2467MHz
6	2408MHz	26	2428MHz	46	2448MHz	66	2468MHz
7	2409MHz	27	2429MHz	47	2449MHz	67	2469MHz
8	2410MHz	28	2430MHz	48	2450MHz	68	2470MHz
9	2411MHz	29	2431MHz	49	2451MHz	69	2471MHz
10	2412MHz	30	2432MHz	50	2452MHz	70	2472MHz
11	2413MHz	31	2433MHz	51	2453MHz	71	2473MHz
12	2414MHz	32	2434MHz	52	2454MHz	72	2474MHz
13	2415MHz	33	2435MHz	53	2455MHz	73	2475MHz
14	2416MHz	34	2436MHz	54	2456MHz	74	2476MHz
15	2417MHz	35	2437MHz	55	2457MHz	75	2477MHz
16	2418MHz	36	2438MHz	56	2458MHz	76	2478MHz
17	2419MHz	37	2439MHz	57	2459MHz	77	2479MHz
18	2420MHz	38	2440MHz	58	2460MHz	78	2480MHz
19	2421MHz	39	2441MHz	59	2461MHz		
Remark: Channel 0, 39 & 78 selected for GFSK, $\pi/4$ -DQPSK and 8DPSK.							

5.3 Test mode

Transmitting mode:	Keep the EUT in transmitting mode with worst case data rate.
Remark	GFSK (1 Mbps) is the worst case mode.
The sample was placed 0.8m(below 1GHz)/1.5m(above 1GHz) above the ground plane of 3m chamber*. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working with a fresh battery, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.	

5.4 Measurement Uncertainty

Items	Expanded Uncertainty (Confidence of 95%)
Conducted Emission (9kHz ~ 30MHz)	2.14 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	4.24 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	4.35 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	4.44 dB (k=2)
Radiated Emission (18GHz ~ 26.5GHz)	4.56 dB (k=2)

5.5 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Registration No.: 817957**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 817957, February 27, 2012.

● **IC - Registration No.: 10106A-1**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

5.6 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.
 Address: No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,
 Bao'an District, Shenzhen, Guangdong, China
 Website: <http://www.ccis-cb.com>
 Tel: +86-755-23118282
 Fax: +86-755-23116366
 Email: info@ccis-cb.com


5.7 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
1	3m SAC	SAEMC	9(L)*6(W)* 6(H)	CCIS0001	08-23-2014	08-22-2017
2	BiConiLog Antenna	SCHWARZBECK	VULB9163	CCIS0005	02-25-2017	02-24-2018
3	Horn Antenna	SCHWARZBECK	BBHA9120D	CCIS0006	02-25-2017	02-24-2018
4	Pre-amplifier (10kHz-1.3GHz)	HP	8447D	CCIS0003	02-25-2017	02-24-2018
5	Pre-amplifier (1GHz-18GHz)	Compliance Direction Systems Inc.	PAP-1G18	CCIS0011	02-25-2017	02-24-2018
6	Pre-amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	02-25-2017	02-24-2018
7	Horn Antenna	ETS-LINDGREN	3160	GTS217	02-25-2017	02-24-2018
8	Spectrum analyzer 9k-30GHz	Rohde & Schwarz	FSP30	CCIS0023	02-25-2017	02-24-2018
9	EMI Test Receiver	Rohde & Schwarz	ESRP7	CCIS0167	02-25-2017	02-24-2018
10	Loop antenna	Laplace instrument	RF300	EMC0701	02-25-2017	02-24-2018
11	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
12	Coaxial Cable	N/A	N/A	CCIS0018	02-25-2017	02-24-2018
13	Coaxial Cable	N/A	N/A	CCIS0020	02-25-2017	02-24-2018


Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
1	Shielding Room	ZhongShuo Electron	11.0(L)x4.0(W)x3.0(H)	CCIS0061	08-23-2014	08-22-2017
2	EMI Test Receiver	Rohde & Schwarz	ESCI	CCIS0002	02-25-2017	02-24-2018
3	LISN	CHASE	MN2050D	CCIS0074	02-25-2017	02-24-2018
4	Coaxial Cable	CCIS	N/A	CCIS0086	02-25-2017	02-24-2018
5	EMI Test Software	AUDIX	E3	N/A	N/A	N/A

6 Test results and Measurement Data

6.1 Antenna requirement


Standard requirement:	FCC Part 15 C Section 15.203 /247(c)
<i>15.203 requirement:</i> <i>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</i> <i>15.247(c) (1)(i) requirement:</i> <i>(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.</i>	
E.U.T Antenna:	
<i>The Bluetooth antenna is an integral antenna which permanently attached, and the best case gain of the antenna is 1.54 dBi.</i>	
	

6.2 Conducted Emissions

Test Requirement:	FCC Part 15 C Section 15.207		
Test Method:	ANSI C63.4:2014		
Test Frequency Range:	150 kHz to 30 MHz		
Class / Severity:	Class B		
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test setup:	 Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m		
Test procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement.		
Test Instruments:	Refer to section 5.7 for details		
Test mode:	Bluetooth (Continuous transmitting) mode		
Test results:	Pass		

Measurement Data:

Line:



Trace: 3


Site : CCIS Shielding Room
 Condition : FCC PART15 B QP LISN LINE
 EUT : K1s
 Model : K1s
 Test Mode : BT mode
 Power Rating : AC120V/60Hz
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa
 Test Engineer: Peter
 Remark :

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.198	41.66	0.15	10.76	52.57	63.71	-11.14	QP
2	0.198	15.26	0.15	10.76	26.17	53.71	-27.54	Average
3	0.238	39.02	0.15	10.75	49.92	62.17	-12.25	QP
4	0.253	11.73	0.16	10.75	22.64	51.64	-29.00	Average
5	0.354	33.60	0.21	10.73	44.54	58.87	-14.33	QP
6	0.398	11.77	0.24	10.72	22.73	47.90	-25.17	Average
7	0.449	31.25	0.24	10.74	42.23	56.89	-14.66	QP
8	0.489	12.46	0.24	10.76	23.46	46.19	-22.73	Average
9	0.783	30.32	0.30	10.81	41.43	56.00	-14.57	QP
10	2.474	25.46	0.33	10.94	36.73	56.00	-19.27	QP
11	2.839	9.70	0.33	10.93	20.96	46.00	-25.04	Average
12	3.964	7.80	0.34	10.89	19.03	46.00	-26.97	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss.

Neutral:



Trace: 1


Site : CCIS Shielding Room
 Condition : FCC PART15 B QP LISN NEUTRAL
 EUT : K1s
 Model : K1s
 Test Mode : BT mode
 Power Rating : AC120V/60Hz
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa
 Test Engineer: Peter
 Remark :

	Read	LISN	Cable	Limit	Over	
Freq	Level	Factor	Loss	Line	Limit	Remark
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dB	dBuV	dBuV	dB
1	0.162	44.76	0.13	10.77	55.66	65.34 -9.68 QP
2	0.198	18.77	0.15	10.76	29.68	53.71 -24.03 Average
3	0.202	42.12	0.15	10.76	53.03	63.54 -10.51 QP
4	0.246	12.42	0.17	10.75	23.34	51.91 -28.57 Average
5	0.277	38.30	0.18	10.74	49.22	60.90 -11.68 QP
6	0.299	10.14	0.19	10.74	21.07	50.28 -29.21 Average
7	0.350	35.06	0.21	10.73	46.00	58.96 -12.96 QP
8	0.426	32.98	0.23	10.73	43.94	57.33 -13.39 QP
9	0.449	10.81	0.24	10.74	21.79	46.89 -25.10 Average
10	0.502	11.46	0.24	10.76	22.46	46.00 -23.54 Average
11	2.500	25.98	0.29	10.94	37.21	56.00 -18.79 QP
12	2.527	11.85	0.29	10.94	23.08	46.00 -22.92 Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss.


6.3 Conducted Output Power

Test Requirement:	FCC Part 15 C Section 15.247 (b)(1)
Test Method:	ANSI C63.10:2013 and DA00-705
Receiver setup:	RBW=1MHz, VBW=3MHz, Detector=Peak (If 20dB BW $\leq$ 1 MHz) RBW=3MHz, VBW=10MHz, Detector=Peak (If 20dB BW > 1 MHz and < 3MHz)
Limit:	125 mW(21 dBm)
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 5.7 for details
Test mode:	Non-hopping mode
Test results:	Pass

Measurement Data:


GFSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	3.52	21.00	Pass
Middle	3.93	21.00	Pass
Highest	4.06	21.00	Pass
$\pi/4$ -DQPSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	3.32	21.00	Pass
Middle	3.41	21.00	Pass
Highest	3.44	21.00	Pass
8DPSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	3.19	21.00	Pass
Middle	3.50	21.00	Pass
Highest	3.53	21.00	Pass

Test plot as follows:




Date: 15.MAY.2017 09:49:16

Lowest channel



Date: 15.MAY.2017 09:48:10


Middle channel



Date: 15.MAY.2017 09:48:36


Highest channel

Modulation mode: $\pi/4$ -DQPSK




Date: 15.MAY.2017 09:50:08

Lowest channel



Date: 15.MAY.2017 09:51:47


Middle channel



Date: 15.MAY.2017 09:52:07


Highest channel

Modulation mode: 8DPSK




Date: 15.MAY.2017 09:52:40

Lowest channel



Date: 15.MAY.2017 09:52:56


Middle channel



Date: 15.MAY.2017 09:53:12

Highest channel


6.4 20dB Occupy Bandwidth

Test Requirement:	FCC Part 15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013 and DA00-705
Receiver setup:	RBW=30 kHz, VBW=100 kHz, detector=Peak
Limit:	NA
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.
Test Instruments:	Refer to section 5.7 for details
Test mode:	Non-hopping mode
Test results:	Pass

Measurement Data:


Test channel	20dB Occupy Bandwidth (kHz)		
	GFSK	$\pi/4$ -DQPSK	8DPSK
Lowest	832	1124	1164
Middle	832	1120	1164
Highest	828	1116	1164

Test plot as follows:




Date: 15.MAY.2017 10:03:32

Lowest channel



Date: 15.MAY.2017 10:04:34


Middle channel



Date: 15.MAY.2017 10:05:33


Highest channel

Modulation mode: $\pi/4$ -DQPSK




Date: 15.MAY.2017 10:07:48

Lowest channel



Date: 15.MAY.2017 10:09:13


Middle channel



Date: 15.MAY.2017 10:10:11


Highest channel

Modulation mode: 8DPSK




Date: 15.MAY.2017 10:12:07

Lowest channel



Date: 15.MAY.2017 10:13:00


Middle channel



Date: 15.MAY.2017 10:14:07

Highest channel

6.5 Carrier Frequencies Separation

Test Requirement:	FCC Part 15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013 and DA00-705
Receiver setup:	RBW=100 kHz, VBW=300 kHz, detector=Peak
Limit:	0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer, shown with a grid and a green trace, is connected to an E.U.T. (Equipment Under Test) box by a red cable. Both the Spectrum Analyzer and the E.U.T. are positioned on a 'Non-Conducted Table', which is a rectangular platform supported by two vertical legs. Below this table is a 'Ground Reference Plane', represented by a thick grey horizontal bar.
Test Instruments:	Refer to section 5.7 for details
Test mode:	Hopping mode
Test results:	Pass


Measurement Data:

GFSK mode			
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result
Lowest	1000	554.67	Pass
Middle	1000	554.67	Pass
Highest	1000	554.67	Pass
$\pi/4$ -DQPSK mode			
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result
Lowest	1000	749.33	Pass
Middle	1000	749.33	Pass
Highest	1004	749.33	Pass
8DPSK mode			
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result
Lowest	1008	776.00	Pass
Middle	1000	776.00	Pass
Highest	1000	776.00	Pass

Note: According to section 6.4


Mode	20dB bandwidth (kHz) (worse case)	Limit (kHz) (Carrier Frequencies Separation)
GFSK	832	554.67
$\pi/4$ -DQPSK	1124	749.33
8DPSK	1164	776.00

Test plot as follows:




Date: 15.MAY.2017 10:16:13

Lowest channel



Date: 15.MAY.2017 10:16:55


Middle channel



Date: 15.MAY.2017 10:17:40


Highest channel

Modulation mode: $\pi/4$ -DQPSK




Date: 15.MAY.2017 10:18:41

Lowest channel



Date: 15.MAY.2017 10:20:27


Middle channel



Date: 15.MAY.2017 10:21:32


Highest channel

Modulation mode: 8DPSK




Date: 15.MAY.2017 10:22:40

Lowest channel



Date: 15.MAY.2017 10:23:38


Middle channel



Date: 15.MAY.2017 10:24:51

Highest channel


6.6 Hopping Channel Number

Test Requirement:	FCC Part 15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013 and DA00-705
Receiver setup:	RBW=100 kHz, VBW=300 kHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak
Limit:	15 channels
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table. The table is supported by two vertical legs and sits on a Ground Reference Plane, which is represented by a thick grey bar at the bottom.
Test Instruments:	Refer to section 5.7 for details
Test mode:	Hopping mode
Test results:	Pass


Measurement Data:

Mode	Hopping channel numbers	Limit	Result
GFSK, $\pi/4$ -DQPSK, 8DPSK	79	15	Pass


Test plot as follows:



Date: 15.MAY.2017 10:28:15




Date: 15.MAY.2017 10:30:16



Date: 15.MAY.2017 10:32:16

6.7 Dwell Time

Test Requirement:	FCC Part 15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013 and KDB DA00-705
Receiver setup:	RBW=1 MHz, VBW=1 MHz, Span=0 Hz, Detector=Peak
Limit:	0.4 Second
Test setup:	
Test Instruments:	Refer to section 5.7 for details
Test mode:	Hopping mode
Test results:	Pass

Measurement Data (Worse case):

Mode	Packet	Dwell time (second)	Limit (second)	Result
GFSK	DH1	0.12480	0.4	Pass
	DH3	0.26688		
	DH5	0.31083		
$\pi/4$ -DQPSK	2-DH1	0.12672	0.4	Pass
	2-DH3	0.26656		
	2-DH5	0.31083		
8DPSK	3-DH1	0.12672	0.4	Pass
	3-DH3	0.26656		
	3-DH5	0.31168		

For GFSK, $\pi/4$ -DQPSK and 8DPSK:

The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

DH1 time slot = $0.390 \times (1600 / (2 \times 79)) \times 31.6 = 124.80 \text{ ms}$

DH3 time slot = $1.668 \times (1600 / (4 \times 79)) \times 31.6 = 266.88 \text{ ms}$

DH5 time slot = $2.914 \times (1600 / (6 \times 79)) \times 31.6 = 310.83 \text{ ms}$

2-DH1 time slot = $0.396 \times (1600 / (2 \times 79)) \times 31.6 = 126.72 \text{ ms}$

2-DH3 time slot = $1.666 \times (1600 / (4 \times 79)) \times 31.6 = 266.56 \text{ ms}$


2-DH5 time slot = $2.914 \times (1600 / (6 \times 79)) \times 31.6 = 310.83 \text{ ms}$

3-DH1 time slot = $0.396 \times (1600 / (2 \times 79)) \times 31.6 = 126.72 \text{ ms}$

3-DH3 time slot = $1.666 \times (1600 / (4 \times 79)) \times 31.6 = 266.56 \text{ ms}$


3-DH5 time slot = $2.922 \times (1600 / (6 \times 79)) \times 31.6 = 311.68 \text{ ms}$

Test plot as follows:




Date: 15.MAY.2017 10:35:18

DH1



Date: 15.MAY.2017 10:45:32


DH3



Date: 15.MAY.2017 10:48:15


DH5

Modulation mode: $\pi/4$ -DQPSK




Date: 15.MAY.2017 10:37:14

2-DH1




Date: 15.MAY.2017 10:46:39

2-DH3




Date: 15.MAY.2017 10:48:47

2-DH5




Date: 15.MAY.2017 10:44:40

3-DH1



Date: 15.MAY.2017 10:47:32



3-DH3



Date: 15.MAY.2017 10:51:58


3-DH5

6.8 Pseudorandom Frequency Hopping Sequence

Test Requirement:	FCC Part 15 C Section 15.247 (a)(1) requirement:
Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively. Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.	
EUT Pseudorandom Frequency Hopping Sequence	
The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones. • Number of shift register stages: 9 • Length of pseudo-random sequence: $2^9 - 1 = 511$ bits • Longest sequence of zeros: 8 (non-inverted signal)  <i>Linear Feedback Shift Register for Generation of the PRBS sequence</i> An example of Pseudorandom Frequency Hopping Sequence as follow:  Each frequency used equally on the average by each transmitter. The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.	


6.9 Band Edge

6.9.1 Conducted Emission Method

Test Requirement:	FCC Part 15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013 and DA00-705
Receiver setup:	RBW=100 kHz, VBW=300 kHz, Detector=Peak
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 5.7 for details
Test mode:	Non-hopping mode and hopping mode
Test results:	Pass


Test plot as follows:

GFSK Lowest Channel



Date: 15.MAY.2017 10:55:23


No-hopping mode



Date: 15.MAY.2017 10:58:18


Hopping mode

Highest Channel



Date: 15.MAY.2017 11:08:45

No-hopping mode




Date: 15.MAY.2017 11:10:54

Hopping mode


$\pi/4$ -DQPSK

Lowest Channel



Date: 15.MAY.2017 11:03:39


No-hopping mode



Date: 15.MAY.2017 11:01:24


Hopping mode

Highest Channel



Date: 16.MAY.2017 11:43:59

No-hopping mode




Date: 16.MAY.2017 11:45:41

Hopping mode


8DPSK

Lowest Channel



Date: 15.MAY.2017 11:04:26


No-hopping mode



Date: 15.MAY.2017 11:06:37


Hopping mode

Highest Channel



Date: 16.MAY.2017 11:48:14


No-hopping mode



Date: 16.MAY.2017 11:47:05

Hopping mode

6.9.2 Radiated Emission Method

Test Requirement:	FCC Part 15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	2.3GHz to 2.5GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	Above 1GHz	Peak RMS	1MHz 1MHz	3MHz 3MHz	Peak Value Average Value
Limit:	Frequency	Limit (dBuV/m @3m)		Remark	
	Above 1GHz	54.00 74.00		Average Value Peak Value	
Test setup:					
Test Procedure:	1. The EUT was placed on the top of a rotating table 1.5meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.				
Test Instruments:	Refer to section 5.7 for details				
Test mode:	Non-hopping mode				
Test results:	Passed				


Remark:

1. During the test, pre-scan the GFSK, $\pi/4$ -DQPSK, 8DPSK, and all data were shown in report.
2. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis is the worst case.

GFSK mode

Test channel: Lowest


Horizontal:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
 EUT : K1s
 Model : K1s
 Test mode : DH1-L Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: Peter
 REMARK :

	ReadAntenna	Cable	Preamp		Limit	Over	
Freq	Level	Factor	Loss	Factor	Level	Line	Limit
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1 2339.269	20.66	23.67	4.64	0.00	48.97	74.00	-25.03
2 2339.269	11.35	23.67	4.64	0.00	39.66	54.00	-14.34
3 2390.000	15.91	23.68	4.69	0.00	44.28	74.00	-29.72
4 2390.000	7.89	23.68	4.69	0.00	36.26	54.00	-17.74

Vertical:




Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL
 EUT : K1s
 Model : K1s
 Test mode : DH1-L Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: Peter
 REMARK :

	Read	Antenna	Cable	Preamp		Limit	Over	
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
-----MHz	-----dBuV	-----dB/m	-----dB	-----dB	-----dBuV/m	-----dBuV/m	-----dB	-----
1 2339.823	21.92	23.67	4.64	0.00	50.23	74.00	-23.77	Peak
2 2339.823	10.28	23.67	4.64	0.00	38.59	54.00	-15.41	Average
3 2390.000	18.54	23.68	4.69	0.00	46.91	74.00	-27.09	Peak
4 2390.000	7.89	23.68	4.69	0.00	36.26	54.00	-17.74	Average

Test channel: Highest


Horizontal:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
 EUT : K1s
 Model : K1s
 Test mode : DH1-H Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: Peter
 REMARK :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier	Level	Limit	Over	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	18.15	23.70	4.81	0.00	46.66	74.00	-27.34	Peak
2	2483.500	8.26	23.70	4.81	0.00	36.77	54.00	-17.23	Average
3	2485.766	20.35	23.70	4.81	0.00	48.86	74.00	-25.14	Peak
4	2485.766	10.73	23.70	4.81	0.00	39.24	54.00	-14.76	Average

Vertical:




Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL
 EUT : K1s
 Model : K1s
 Test mode : DH1-H Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: Peter
 REMARK :

	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over	
		Level	Factor	Loss	Factor	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2483.500	19.28	23.70	4.81	0.00	47.79	74.00	-26.21 Peak
2	2483.500	8.19	23.70	4.81	0.00	36.70	54.00	-17.30 Average
3	2494.614	21.49	23.70	4.82	0.00	50.01	74.00	-23.99 Peak
4	2494.614	11.31	23.70	4.82	0.00	39.83	54.00	-14.17 Average

$\pi/4$ -DQPSK mode

Test channel: Lowest


Horizontal:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
 EUT : K1s
 Model : K1s
 Test mode : 2DH1-L Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: Peter
 REMARK :

	Read	Antenna	Cable	Preamp		Limit	Over	
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2343.798	20.18	23.67	4.65	0.00	48.50	74.00	-25.50 Peak
2	2343.798	10.58	23.67	4.65	0.00	38.90	54.00	-15.10 Average
3	2390.000	16.71	23.68	4.69	0.00	45.08	74.00	-28.92 Peak
4	2390.000	7.87	23.68	4.69	0.00	36.24	54.00	-17.76 Average

Vertical:




Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL
 EUT : K1s
 Model : K1s
 Test mode : 2DH1-L Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: Peter
 REMARK :

	Freq	ReadAntenna	Cable	Preamp		Limit	Over	
		Level	Factor	Loss	Factor	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2340.285	20.82	23.67	4.64	0.00	49.13	74.00	-24.87 Peak
2	2340.285	9.14	23.67	4.64	0.00	37.45	54.00	-16.55 Average
3	2390.000	18.67	23.68	4.69	0.00	47.04	74.00	-26.96 Peak
4	2390.000	7.88	23.68	4.69	0.00	36.25	54.00	-17.75 Average

Test channel: Highest


Horizontal:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
 EUT : K1s
 Model : K1s
 Test mode : 2DH1-H Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: Peter
 REMARK :

	Freq	ReadAntenna	Cable	Preamplifier	Level	Limit	Over	
	MHz	Level	Factor	Loss	Factor	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2483.500	18.16	23.70	4.81	0.00	46.67	74.00	-27.33 Peak
2	2483.500	8.24	23.70	4.81	0.00	36.75	54.00	-17.25 Average
3	2497.526	20.59	23.70	4.82	0.00	49.11	74.00	-24.89 Peak
4	2497.526	11.29	23.70	4.82	0.00	39.81	54.00	-14.19 Average

Vertical:




Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL
 EUT : K1s
 Model : K1s
 Test mode : 2DH1-H Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: Peter
 REMARK :

	Freq	Read	Antenna	Cable	Preamp	Level	Limit	Over	
		Level	Factor	Loss	Factor		Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	19.54	23.70	4.81	0.00	48.05	74.00	-25.95	Peak
2	2483.500	8.18	23.70	4.81	0.00	36.69	54.00	-17.31	Average
3	2485.524	20.43	23.70	4.81	0.00	48.94	74.00	-25.06	Peak
4	2485.524	9.46	23.70	4.81	0.00	37.97	54.00	-16.03	Average

8DPSK mode

Test channel: Lowest


Horizontal:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
 EUT : K1s
 Model : K1s
 Test mode : 3DH1-L Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: Peter
 REMARK :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2348.243	21.50	23.67	4.65	0.00	49.82	74.00	-24.18	Peak
2	2348.243	10.08	23.67	4.65	0.00	38.40	54.00	-15.60	Average
3	2390.000	18.39	23.68	4.69	0.00	46.76	74.00	-27.24	Peak
4	2390.000	7.88	23.68	4.69	0.00	36.25	54.00	-17.75	Average

Vertical:




Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL
 EUT : K1s
 Model : K1s
 Test mode : 3DH1-L Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: Peter
 REMARK :

	Freq	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2337.608	20.18	23.67	4.64	0.00	48.49	74.00	-25.51	Peak
2	2337.608	11.79	23.67	4.64	0.00	40.10	54.00	-13.90	Average
3	2390.000	17.78	23.68	4.69	0.00	46.15	74.00	-27.85	Peak
4	2390.000	7.90	23.68	4.69	0.00	36.27	54.00	-17.73	Average

Test channel: Highest


Horizontal:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
 EUT : K1s
 Model : K1s
 Test mode : 3DH1-H Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: Peter
 REMARK :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Level	Limit	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	19.91	23.70	4.81	0.00	48.42	74.00	-25.58	Peak
2	2483.500	8.26	23.70	4.81	0.00	36.77	54.00	-17.23	Average
3	2487.458	20.74	23.70	4.81	0.00	49.25	74.00	-24.75	Peak
4	2487.458	9.48	23.70	4.81	0.00	37.99	54.00	-16.01	Average

Vertical:




Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL
 EUT : K1s
 Model : K1s
 Test mode : 3DH1-H Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: Peter
 REMARK :


	Freq	ReadAntenna	Cable	Preamp		Limit	Over	
		Level	Factor	Loss	Factor	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2483.500	19.06	23.70	4.81	0.00	47.57	74.00	-26.43 Peak
2	2483.500	8.20	23.70	4.81	0.00	36.71	54.00	-17.29 Average
3	2495.276	21.60	23.70	4.82	0.00	50.12	74.00	-23.88 Peak
4	2495.276	11.38	23.70	4.82	0.00	39.90	54.00	-14.10 Average

6.10 Spurious Emission

6.10.1 Conducted Emission Method


Test Requirement:	FCC Part 15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013 and DA00-705
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 The diagram illustrates the test setup for conducted emission measurement. A Spectrum Analyzer is connected via a red cable to an E.U.T (Equipment Under Test). Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 5.7 for details
Test mode:	Non-hopping mode
Test results:	Pass

Test plot as follows:




Date: 15.MAY.2017 21:11:36

30MHz~25GHz



Date: 15.MAY.2017 20:38:34


30MHz~25GHz



Date: 15.MAY.2017 20:39:15

30MHz~25GHz


$\pi/4$ -DQPSK Lowest channel



Date: 15.MAY.2017 20:40:29


30MHz~25GHz

Middle channel



Date: 15.MAY.2017 20:44:44


30MHz~25GHz



Date: 15.MAY.2017 20:45:39

30MHz~25GHz


8DPSK Lowest channel



Date: 15.MAY.2017 20:47:26


30MHz~25GHz

Middle channel



Date: 15.MAY.2017 20:48:32



30MHz~25GHz



Date: 15.MAY.2017 20:49:48

30MHz~25GHz

6.10.2 Radiated Emission Method

Test Requirement:	FCC Part 15 C Section 15.209				
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	9 kHz to 25 GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		RMS	1MHz	3MHz	Average Value
Limit:	Frequency		Limit (dBuV/m @3m)		Remark
	30MHz-88MHz		40.0		Quasi-peak Value
	88MHz-216MHz		43.5		Quasi-peak Value
	216MHz-960MHz		46.0		Quasi-peak Value
	960MHz-1GHz		54.0		Quasi-peak Value
	Above 1GHz	54.0		Average Value	
		74.0		Peak Value	
Test setup:	Below 1GHz				
					
	Above 1GHz				
					

Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8m(below 1GHz) /1.5m(above 1GHz) above the ground at a 3 meter chamber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 5.7 for details
Test mode:	Non-hopping mode
Test results:	Pass


Remark:

1. During the test, pre-scan the GFSK, $\pi/4$ -DQPSK, 8DPSK modulation, and found the GFSK modulation is the worst case.
2. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis is the worst case.
3. 9 kHz to 30 MHz is noise floor, so only shows the data of above 30MHz in this report.

Measurement data:

Below 1GHz


Vertical:



Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163(30M3G) VERTICAL
 EUT : K1s
 Model : K1s
 Test mode : BT Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: Peter
 REMARK :

	Freq	ReadAntenna	Cable Preamp		Limit	Over	
		Level Factor	Loss Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB
1	44.275	40.57	17.52	1.28	29.87	29.50	40.00 -10.50 QP
2	62.213	46.07	9.46	1.38	29.77	27.14	40.00 -12.86 QP
3	135.982	43.70	11.95	2.35	29.29	28.71	43.50 -14.79 QP
4	153.200	47.48	10.41	2.54	29.19	31.24	43.50 -12.26 QP
5	485.609	46.98	16.64	3.50	28.93	38.19	46.00 -7.81 QP
6	545.183	40.12	17.98	3.86	29.08	32.88	46.00 -13.12 QP

Horizontal:



Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163(30M3G) HORIZONTAL
 EUT : K1s
 Model : K1s
 Test mode : BT Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: Peter
 REMARK :

	Freq	ReadAntenna	Cable	Preamp	Limit	Over	
	Level	Factor	Loss	Factor	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB
1	30.531	50.55	12.26	0.78	29.98	33.61	40.00 -6.39 QP
2	61.995	43.27	9.46	1.38	29.77	24.34	40.00 -15.66 QP
3	147.404	38.29	10.91	2.49	29.23	22.46	43.50 -21.04 QP
4	322.189	36.40	13.34	3.01	28.50	24.25	46.00 -21.75 QP
5	401.839	35.04	15.91	3.08	28.78	25.25	46.00 -20.75 QP
6	467.235	41.63	16.41	3.34	28.90	32.48	46.00 -13.52 QP

Above 1GHz:

Test channel:			Lowest		Level:		Peak	
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	47.09	35.99	6.80	41.81	48.07	74.00	-25.93	Vertical
4804.00	47.50	35.99	6.80	41.81	48.48	74.00	-25.52	Horizontal
Test channel:			Lowest		Level:		Average	
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	32.57	35.99	6.80	41.81	33.55	54.00	-20.45	Vertical
4804.00	32.68	35.99	6.80	41.81	33.66	54.00	-20.34	Horizontal

Test channel:			Middle		Level:		Peak	
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882.00	47.48	36.38	6.86	41.84	48.88	74.00	-25.12	Vertical
4882.00	48.49	36.38	6.86	41.84	49.89	74.00	-24.11	Horizontal
Test channel:			Middle		Level:		Average	
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882.00	30.48	36.38	6.86	41.84	31.88	54.00	-22.12	Vertical
4882.00	32.67	36.38	6.86	41.84	34.07	54.00	-19.93	Horizontal

Test channel:			Highest		Level:		Peak	
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	48.49	36.71	6.91	41.87	50.24	74.00	-23.76	Vertical
4960.00	47.65	36.71	6.91	41.87	49.40	74.00	-24.60	Horizontal
Test channel:			Highest		Level:		Average	
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	32.47	36.71	6.91	41.87	34.22	54.00	-19.78	Vertical
4960.00	31.68	36.71	6.91	41.87	33.43	54.00	-20.57	Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.