RADIO TEST REPORT
FCC ID: 2AGP4PH701T

Product:	tablet
Trade Name:	N/A
Model No.:	PH701T
Serial Model:	N/A
Report No.:	NTEK-2016NT04195220F1
Issue Date:	10 May. 2016

Prepared for

QUALITY ONE WIRELESS, LLC.

1500 Tradeport Drive, ORLANDO, Florida, United States 32824

Prepared by

NTEK TESTING TECHNOLOGY CO., LTD.
1/F, Building E, Fenda Science Park, Sanwei Community,
Xixiang Street Bao'an District, Shenzhen, P.R. China
Tel.: +86-0755-61156588
Fax.: +86-0755-61156599
Website:www.ntek.org.cn

TABLE OF CONTENTS

1 TEST RESULT CERTIFICATION 3

2 SUMMARY OF TEST RESULTS 4

3 FACILITIES AND ACCREDITATIONS 5

3.1 FACILITIES 5
3.2 LABORATORY ACCREDITATIONS AND LISTINGS 5
3.3 MEASUREMENT UNCERTAINTY 5

4 GENERAL DESCRIPTION OF EUT 6

5 DESCRIPTION OF TEST MODES 8

6 SETUP OF EQUIPMENT UNDER TEST 10

6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM 10
6.2 SUPPORT EQUIPMENT 11
6.3 EQUIPMENTS LIST FOR ALL TEST ITEMS 12

7 TEST REQUIREMENTS 13

7.1 CONDUCTED EMISSIONS TEST 13
7.2 RADIATED SPURIOUS EMISSION 18
7.3 6DB BANDWIDTH 28
7.4 20DB BANDWIDTH 36
7.5 DUTY CYCLE 40
7.6 MAXIMUM OUTPUT POWER 44
7.7 POWER SPECTRAL DENSITY 52
7.8 CONDUCTED BAND EDGE MEASUREMENT 60
7.9 ANTENNA APPLICATION 66

1 TEST RESULT CERTIFICATION

Applicant's name.....:	Quality One Wireless, LLC.
Address .....:	1500 Tradeport Drive, ORLANDO, Florida, United States 32824
Manufacture's Name .....:	Haier International（HK）Limited
Address .....:	503, Unit 2, Building B, KeXing Science Park, Keyuan Road, Nanshan, Shenzhen, 518057 P.R.China
Product description	
Product name.....:	tablet
Model and/or type reference .....:	PH701T
Serial Model .....:	N/A

Measurement Procedure Used:

APPLICABLE STANDARDS	
APPLICABLE STANDARD/ TEST PROCEDURE	TEST RESULT
FCC 47 CFR Part 2, Subpart J:2015 FCC 47 CFR Part 15, Subpart C:2015 KDB 174176 D01 Line Conducted FAQ v01r01 ANSI C63.10-2013 FCC KDB 558074 D01 DTS Meas Guidance v03r04	Complied

This device described above has been tested by NTEK Testing Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.
This report shall not be reproduced except in full, without the written approval of NTEK Testing Technology Co., Ltd., this document may be altered or revised by NTEK Testing Technology Co., Ltd., personnel only, and shall be noted in the revision of the document.
The test results of this report relate only to the tested sample identified in this report.

Date of Test : 19 Apr. 2016 ~ 10 May. 2016

Testing Engineer : Allen Liu
(Allen Liu)

Technical Manager : Jason chen
(Jason Chen)

Authorized Signatory : Sam. Chen
(Sam Chen)

2 SUMMARY OF TEST RESULTS

FCC Part15 (15.247), Subpart C			
Standard Section	**Test Item**	**Verdict**	**Remark**
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Maximum Output Power	PASS	
15.247 (c)	Radiated Spurious Emission	PASS	
15.247 (d)	Power Spectral Density	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

Remark:
1. "N/A" denotes test is not applicable in this Test Report.
2. All test items were verified and recorded according to the standards and without any deviation during the test.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

3 FACILITIES AND ACCREDITATIONS

3.1 FACILITIES

All measurement facilities used to collect the measurement data are located at
1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.
The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

3.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

EMC Lab.	:	Accredited by CNAS, 2014.09.04 The certificate is valid until 2017.09.03 The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2005) The Certificate Registration Number is L5516. Accredited by Industry Canada, August 29, 2012 The Certificate Registration Number is 9270A-1. Accredited by FCC, September 06, 2013 The Certificate Registration Number is 238937.
Name of Firm	:	NTEK Testing Technology Co., Ltd
Site Location	:	1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

3.3 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power, conducted	±0.16dB
3	Spurious emissions, conducted	±0.21dB
4	All emissions, radiated(<1G)	±4.68dB
5	All emissions, radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%

4 GENERAL DESCRIPTION OF EUT

Product Feature and Specification	
Equipment	tablet
Trade Name	N/A
FCC ID	2AGP4PH701T
Model No.	PH701T
Serial Model	N/A
Model Difference	N/A
Operating Frequency	2412-2462MHz for 802.11b/g/11n(HT20); 2422-2452MHz for 802.11n(HT40);
Modulation	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
Number of Channels	11 channels for 802.11b/g/11n(HT20); 7 channels for 802.11n(HT40);
Antenna Type	FPCB Antenna
Antenna Gain	1 dBi
Power supply	☒DC supply: DC 3.7V/2800mAh from Li-ion Battery or DC 5V from USB Port.
	☒Adapter supply: Model: JK050200-S04USA Input: 100-240V~, 50/60Hz, 0.5A Output: 5.0V⎓, 2000mA
HW Version	N/A
SW Version	N/A

Note: Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.

Revision History

Report No.	Version	Description	Issued Date
NTEK-2016NT04195220F1	Rev.01	Initial issue of report	May 10, 2016

5 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.
The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (802.11b: 1 Mbps; 802.11g: 6 Mbps; 802.11n (HT20): MCS0; 802.11n (HT40): MCS0) were used for all test.
The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The Y-plane results were found as the worst case and were shown in this report.

Frequency and Channel list for 802.11b/g/n (HT20):

Channel	Frequency(MHz)
1	2412
2	2417
…	…
5	2432
6	2437
…	…
10	2457
11	2462

Note: fc=2412MHz+k×5MHz k=0 to 10

Frequency and Channel list for 802.11n (HT40):

Channel	Frequency(MHz)
3	2422
4	2427
5	2432
6	2437
7	2442
8	2447
9	2452

Note: fc=2422MHz+k×5MHz k=0 to 6

The following summary table is showing all test modes to demonstrate in compliance with the standard.

For AC Conducted Emission	
Final Test Mode	Description
Mode 5	Link Mode

Note: AC power line Conducted Emission was tested under maximum output power.

For Radiated Test Cases	
Final Test Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n HT20 CH1/ CH6/ CH11
Mode 4	802.11n HT40 CH3/ CH6/ CH9

Note: For radiated test cases, the worst mode data rate was reported only, because this data rate has the highest RF output power at preliminary tests, and no other significantly frequencies found in conducted spurious emission.

Those data rates (802.11b: 1 Mbps; 802.11g: 6 Mbps; 802.11n (HT20): MCS0; 802.11n (HT40): MCS0) were used for all test.

For Conducted Test Cases	
Final Test Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n HT20 CH1/ CH6/ CH11
Mode 4	802.11n HT40 CH3/ CH6/ CH9

Note: The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.

6 SETUP OF EQUIPMENT UNDER TEST

6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM

For AC Conducted Emission Mode



For Radiated Test Cases



For Conducted Test Cases



6.2 SUPPORT EQUIPMENT

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Note
1.	tablet	N/A	PH701T	2AGP4PH701T	EUT
2.	Adapter	N/A	JK050200-S04USA	N/A	Peripherals
3.	Earphone	N/A	L662	N/A	Peripherals
4.	N/A	N/A	N/A	N/A	Auxiliary equipment

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	USB Cable	NO	NO	1.0m
C-2	Earphone	NO	NO	0.8m
C-3	RF Cable	NO	NO	0.5m

Notes:

(1) The support equipment was authorized by Declaration of Confirmation.
(2) For detachable type I/O cable should be specified the length in cm in『Length』column.
(3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

6.3 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2015.07.06	2016.07.05	1 year
2	Test Receiver	R&S	ESPI	101318	2015.06.07	2016.06.06	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2015.07.06	2016.07.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2015.06.07	2016.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2015.06.07	2016.06.06	1 year
6	Horn Antenna	EM	EM-AH-10180	2011071402	2015.07.06	2016.07.05	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2015.07.06	2016.07.05	1 year
8	Amplifier	EM	EM-30180	060538	2015.12.22	2016.12.21	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2015.06.08	2016.06.07	1 year
10	Power Meter	R&S	NRVS	100696	2015.07.06	2016.07.05	1 year
11	Power Sensor	R&S	URV5-Z4	0395.1619.05	2015.07.06	2016.07.05	1 year
12	Test Cable	N/A	R-01	N/A	2015.07.06	2016.07.05	1 year
13	Test Cable	N/A	R-02	N/A	2015.07.06	2016.07.05	1 year

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2015.06.06	2016.06.05	1 year
2	LISN	R&S	ENV216	101313	2015.08.24	2016.08.23	1 year
3	LISN	EMCO	3816/2	00042990	2015.08.24	2016.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2015.06.07	2016.06.06	1 year
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	2015.06.07	2016.06.06	1 year
6	Absorbing clamp	R&S	MOS-21	100423	2015.06.08	2016.06.07	1 year
7	Test Cable	N/A	C01	N/A	2015.06.08	2016.06.07	1 year
8	Test Cable	N/A	C02	N/A	2015.06.08	2016.06.07	1 year
9	Test Cable	N/A	C03	N/A	2015.06.08	2016.06.07	1 year

1	Attenuation	MCE	24-10-34	BN9258	2015.06.08	2016.06.07	1 year

Note: Each piece of equipment is scheduled for calibration once a year.

7 TEST REQUIREMENTS

7.1 CONDUCTED EMISSIONS TEST

7.1.1 Applicable Standard

According to FCC Part 15.207(a) and KDB 174176 D01 Line Conducted FAQ v01r01

7.1.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. *Decreases with the logarithm of the frequency
2. The lower limit shall apply at the transition frequencies
3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

7.1.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.1.4 Test Configuration



7.1.5 Test Procedure

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.

7.1.6 Test Results



Site Phase: L1 Temperature: 22

Limit: FCC Part 15B_(0.15-30MHz) _Main_QP Power: AC 120V/60Hz Humidity: 51 %

Mode: Mode 5

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1620	40.91	10.07	50.98	65.36	-14.38	QP	
2		0.1620	26.62	10.07	36.69	55.36	-18.67	AVG	
3		0.2260	31.42	10.05	41.47	62.59	-21.12	QP	
4		0.2260	19.28	10.05	29.33	52.59	-23.26	AVG	
5		0.2938	24.35	10.12	34.47	60.41	-25.94	QP	
6		0.2938	15.53	10.12	25.65	50.41	-24.76	AVG	
7		0.6139	26.54	9.81	36.35	56.00	-19.65	QP	
8		0.6139	17.31	9.81	27.12	46.00	-18.88	AVG	
9	*	2.5499	33.48	9.74	43.22	56.00	-12.78	QP	
10		2.5499	15.59	9.74	25.33	46.00	-20.67	AVG	
11		22.6980	36.40	9.94	46.34	60.00	-13.66	QP	
12		22.6980	14.75	9.94	24.69	50.00	-25.31	AVG	

*:Maximum data x:Over limit !:over margin



Site Phase: N Temperature: 22

Limit: FCC Part 15B_(0.15-30MHz) _Main_QP Power: AC 120V/60Hz Humidity: 51 %

Mode: Mode 5

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1737	35.91	10.05	45.96	64.78	-18.82	QP	
2		0.1737	14.97	10.05	25.02	54.78	-29.76	AVG	
3		0.5858	28.27	9.82	38.09	56.00	-17.91	QP	
4		0.5858	18.51	9.82	28.33	46.00	-17.67	AVG	
5	*	2.4780	38.77	9.74	48.51	56.00	-7.49	QP	
6		2.4780	17.95	9.74	27.69	46.00	-18.31	AVG	
7		4.0739	32.26	9.72	41.98	56.00	-14.02	QP	
8		4.0739	19.60	9.72	29.32	46.00	-16.68	AVG	
9		19.9420	33.43	9.91	43.34	60.00	-16.66	QP	
10		19.9420	22.11	9.91	32.02	50.00	-17.98	AVG	
11		24.6818	27.81	9.97	37.78	60.00	-22.22	QP	
12		24.6818	17.14	9.97	27.11	50.00	-22.89	AVG	

*:Maximum data x:Over limit !:over margin



Site Phase: L1 Temperature: 22

Limit: FCC Part 15B_(0.15-30MHz) _Main_QP Power: AC 240V/50Hz Humidity: 51 %

Mode: Mode 5

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1779	33.04	10.05	43.09	64.58	-21.49	QP	
2		0.1779	18.06	10.05	28.11	54.58	-26.47	AVG	
3		0.2540	27.84	10.08	37.92	61.62	-23.70	QP	
4		0.2540	15.24	10.08	25.32	51.62	-26.30	AVG	
5		0.4859	30.87	9.85	40.72	56.24	-15.52	QP	
6		0.4859	14.84	9.85	24.69	46.24	-21.55	AVG	
7		1.3340	31.38	9.83	41.21	56.00	-14.79	QP	
8		1.3340	17.32	9.83	27.15	46.00	-18.85	AVG	
9	*	2.4060	32.88	9.74	42.62	56.00	-13.38	QP	
10		2.4060	16.95	9.74	26.69	46.00	-19.31	AVG	
11		20.0978	35.40	9.91	45.31	60.00	-14.69	QP	
12		20.0978	18.34	9.91	28.25	50.00	-21.75	AVG	

*:Maximum data x:Over limit !:over margin



Site Phase: N Temperature: 22

Limit: FCC Part 15B_(0.15-30MHz) _Main_QP Power: AC 240V/50Hz Humidity: 51 %

Mode: Mode 5

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1779	33.35	10.05	43.40	64.58	-21.18	QP	
2		0.1779	17.40	10.05	27.45	54.58	-27.13	AVG	
3		0.2300	30.66	10.05	40.71	62.45	-21.74	QP	
4		0.2300	16.64	10.05	26.69	52.45	-25.76	AVG	
5		0.5818	28.01	9.82	37.83	56.00	-18.17	QP	
6		0.5818	17.76	9.82	27.58	46.00	-18.42	AVG	
7		1.7258	33.35	9.78	43.13	56.00	-12.87	QP	
8		1.7258	18.57	9.78	28.35	46.00	-17.65	AVG	
9	*	2.4219	38.27	9.74	48.01	56.00	-7.99	QP	
10		2.4219	20.82	9.74	30.56	46.00	-15.44	AVG	
11		20.2658	34.42	9.91	44.33	60.00	-15.67	QP	
12		20.2658	22.34	9.91	32.25	50.00	-17.75	AVG	

*:Maximum data x:Over limit !:over margin

7.2 RADIATED SPURIOUS EMISSION

7.2.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and DA 00-705

7.2.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
According to FCC Part15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009~0.490	2400/F(KHz)	20 log (uV/m)	300
0.490~1.705	2400/F(KHz)	20 log (uV/m)	30
1.705~30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Remark :1. Emission level in dBuV/m=20 log (uV/m)
2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
3. Distance extrapolation factor =40log(Specific distance/ test distance)(dB);
Limit line=Specific limits(dBuV) + distance extrapolation factor.

7.2.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.2.4 Test Configuration

(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



7.2.5 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m.The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.
This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.
Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
b. The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:
For peak measurement:
Set RBW=100 kHz for f < 1 GHz; VBW⩾RBW; Sweep = auto; Detector function = peak; Trace = max hold;
Set RBW = 1 MHz, VBW= 3MHz for f⩾1 GHz
For average measurement:
VBW = 10 Hz, when duty cycle is no less than 98 percent.
VBW ⩾ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where RBWCF [dB] =10*lg(100 [kHz]/narrower RBW [kHz]). , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

7.2.6 Test Results

■ Spurious Emission below 30MHz (9KHz to 30MHz)

EUT:	tablet	Model No.:	PH701T
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode1/Mode2/Mode3/Mode4	Test By:	Allen Liu

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.
Distance extrapolation factor =20log(Specific distance/ test distance)(dB);
Limit line=Specific limits(dBuV) + distance extrapolation factor

■ Spurious Emission below 1GHz (30MHz to 1GHz)
All the modulation modes have been tested, and the worst result was report as below:



Site Polarization: *Vertical* Temperature: 24

Limit: FCC_PART15_B_03m_QP Power: AC 120V/60Hz Humidity: 50 %

Mode: WIFI

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		31.3992	13.32	19.07	32.39	40.00	-7.61	QP			
2		44.2751	18.36	12.38	30.74	40.00	-9.26	QP			
3	*	68.3906	25.45	8.23	33.68	40.00	-6.32	QP			
4		138.8735	24.88	11.00	35.88	43.50	-7.62	QP			
5		173.2050	23.42	12.40	35.82	43.50	-7.68	QP			
6		327.8872	17.18	13.56	30.74	46.00	-15.26	QP			



Site

Polarization: ***Horizontal***

Temperature: 24

Limit: FCC_PART15_B_03m_QP

Power: AC 120V/60Hz

Humidity: 50 %

Mode: WIFI

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	75.9770	20.96	9.57	30.53	40.00	-9.47	QP			
2		86.5027	15.82	9.31	25.13	40.00	-14.87	QP			
3		138.3873	13.66	11.00	24.66	43.50	-18.84	QP			
4		178.1323	21.03	12.06	33.09	43.50	-10.41	QP			
5		222.1698	17.85	10.88	28.73	46.00	-17.27	QP			
6		355.4273	14.45	14.23	28.68	46.00	-17.32	QP			

■ Spurious Emission Above 1GHz (1GHz to 27GHz)

EUT:	tablet	Model No.:	PH701T
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode1/Mode2/Mode3/Mode4	Test By:	Allen Liu

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark	Comment
Low Channel (2412 MHz)-Above 1G							
4824.337	53.53	10.44	63.97	74.00	-10.03	Pk	Vertical
4824.337	35.05	10.44	45.49	54.00	-8.51	AV	Vertical
7236.099	49.52	12.39	61.91	74.00	-12.09	Pk	Vertical
7236.099	30.11	12.39	42.50	54.00	-11.50	AV	Vertical
4824.157	50.25	10.44	60.69	74.00	-13.31	Pk	Horizontal
4824.157	29.45	10.44	39.89	54.00	-14.11	AV	Horizontal
7236.045	45.3	12.39	57.69	74.00	-16.31	Pk	Horizontal
7236.045	32.05	12.39	44.44	54.00	-9.56	AV	Horizontal
Mid Channel (2437 MHz)-Above 1G							
4874.529	54.37	10.40	64.77	74.00	-9.23	Pk	Vertical
4874.529	31.06	10.40	41.46	54.00	-12.54	AV	Vertical
7311.648	42.55	12.75	55.30	74.00	-18.70	Pk	Vertical
7311.648	29.02	12.75	41.77	54.00	-12.23	AV	Vertical
4874.011	51.35	10.40	61.75	74.00	-12.25	Pk	Horizontal
4874.011	30.19	10.40	40.59	54.00	-13.41	AV	Horizontal
7311.305	43.27	12.75	56.02	74.00	-17.98	Pk	Horizontal
7311.305	29.05	12.75	41.80	54.00	-12.20	AV	Horizontal
High Channel (2462 MHz)- Above 1G							
4924.391	50.74	10.39	61.13	74.00	-12.87	Pk	Vertical
4924.391	30.41	10.39	40.80	54.00	-13.20	AV	Vertical
7386.209	43.02	12.68	55.70	74.00	-18.30	Pk	Vertical
7386.209	30.11	12.68	42.79	54.00	-11.21	AV	Vertical
4924.169	49.05	10.39	59.44	74.00	-14.56	Pk	Horizontal
4924.169	31.24	10.39	41.63	54.00	-12.37	AV	Horizontal
7386.176	45.58	12.68	58.26	74.00	-15.74	Pk	Horizontal
7386.176	30.85	12.68	43.53	54.00	-10.47	AV	Horizontal

Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.
(3) Data of measurement within this frequency range shown " -- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission in Band Edge

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
802.11b							
2348.11	61.72	-13.06	48.66	74	-25.34	Pk	Vertical
2348.11	55.86	-13.06	42.8	54	-11.2	AV	Vertical
2400	64.53	-13.06	51.47	74	-22.53	Pk	Vertical
2400	56.26	-13.06	43.2	54	-10.8	AV	Vertical
2390.06	61.61	-13.06	48.55	74	-25.45	Pk	Horizontal
2390.06	55.8	-13.06	42.74	54	-11.26	AV	Horizontal
2400	64.82	-13.06	51.76	74	-22.24	Pk	Horizontal
2400	55.88	-13.06	42.82	54	-11.18	AV	Horizontal
2483.5	63.36	-12.78	50.58	74	-23.42	Pk	Vertical
2483.5	62.28	-12.78	49.5	54	-4.5	AV	Vertical
2483.5	61.72	-13.06	48.66	74	-25.34	Pk	Horizontal
2483.5	55.86	-13.06	42.8	54	-11.2	AV	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
802.11g							
2368.83	61.56	-13.06	48.5	74	-25.5	Pk	Vertical
2368.83	55.7	-13.06	42.64	54	-11.36	AV	Vertical
2400	64.37	-13.06	51.31	74	-22.69	Pk	Vertical
2400	56.1	-13.06	43.04	54	-10.96	AV	Vertical
2360.24	61.45	-13.06	48.39	74	-25.61	Pk	Horizontal
2360.24	55.64	-13.06	42.58	54	-11.42	AV	Horizontal
2400	64.66	-13.06	51.6	74	-22.4	Pk	Horizontal
2400	55.72	-13.06	42.66	54	-11.34	AV	Horizontal
2483.5	63.2	-12.78	50.42	74	-23.58	Pk	Vertical
2483.5	62.12	-12.78	49.34	54	-4.66	AV	Vertical
2483.5	63.13	-12.78	50.35	74	-23.65	Pk	Horizontal
2483.5	62.02	-12.78	49.24	54	-4.76	AV	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
802.11n(20)							
2381.21	62.03	-13.06	48.97	74	-25.03	Pk	Vertical
2381.21	55.24	-13.06	42.18	54	-11.82	AV	Vertical
2400	64.91	-13.06	51.85	74	-22.15	Pk	Vertical
2400	54.99	-13.06	41.93	54	-12.07	AV	Vertical
2362.45	61.92	-13.06	48.86	74	-25.14	Pk	Horizontal
2362.45	55.05	-13.06	41.99	54	-12.01	AV	Horizontal
2400	64.83	-13.06	51.77	74	-22.23	Pk	Horizontal
2400	55.93	-13.06	42.87	54	-11.13	AV	Horizontal
2483.5	63.22	-12.78	50.44	74	-23.56	Pk	Vertical
2483.5	62.23	-12.78	49.45	54	-4.55	AV	Vertical
2483.5	63	-12.78	50.22	74	-23.78	Pk	Horizontal
2483.5	62.09	-12.78	49.31	54	-4.69	AV	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
802.11n(40)							
2380.05	62.44	-13.06	49.38	74	-24.62	Pk	Vertical
2380.05	55.14	-13.06	42.08	54	-11.92	AV	Vertical
2400	65	-13.06	51.94	74	-22.06	Pk	Vertical
2400	55.91	-13.06	42.85	54	-11.15	AV	Vertical
2387.08	62.01	-13.06	48.95	74	-25.05	Pk	Horizontal
2387.08	55.67	-13.06	42.61	54	-11.39	AV	Horizontal
2400	65.42	-13.06	52.36	74	-21.64	Pk	Horizontal
2400	55.04	-13.06	41.98	54	-12.02	AV	Horizontal
2483.5	63.36	-12.78	50.58	74	-23.42	Pk	Vertical
2483.5	62.48	-12.78	49.7	54	-4.3	AV	Vertical
2483.5	63.3	-12.78	50.52	74	-23.48	Pk	Horizontal
2483.5	62.36	-12.78	49.58	54	-4.42	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.

■ Spurious Emission in Restricted Band 3260MMHz- 18000MHz

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
802.11b							
3260	61.02	-13.06	47.96	74	-26.04	Pk	Vertical
3260	28.36	-13.06	15.3	74	-58.70	Pk	Vertical
3332	59.45	-12.78	46.67	74	-27.33	Pk	Horizontal
3332	60.22	-12.78	47.44	74	-26.56	Pk	Horizontal
17857	63.24	-12.28	50.96	74.00	-23.04	Pk	Vertical
17857	63.18	-12.28	50.90	74.00	-23.10	Pk	Horizontal
802.11g							
3260	59.35	-13.06	46.29	74	-27.71	Pk	Vertical
3260	60.02	-13.06	46.96	74	-27.04	Pk	Vertical
3332	58.15	-12.78	45.37	74	-28.63	Pk	Horizontal
3332	59.35	-12.78	46.57	74	-27.43	Pk	Horizontal
17738	63.22	-12.28	50.94	74.00	-23.06	Pk	Vertical
17738	63.2	-12.28	50.92	74.00	-23.08	Pk	Horizontal
802.11n(20)							
3260	58.45	-13.06	45.39	74	-28.61	Pk	Vertical
3260	59.35	-13.06	46.29	74	-27.71	Pk	Vertical
3332	57.66	-12.78	44.88	74	-29.12	Pk	Horizontal
3332	59.02	-12.78	46.24	74	-27.76	Pk	Horizontal
17881	63.14	-12.28	50.86	74.00	-23.14	Pk	Vertical
17881	62.87	-12.28	50.59	74.00	-23.41	Pk	Horizontal
802.11n(40)							
3260	58.02	-13.06	44.96	74	-29.04	Pk	Vertical
3260	61.33	-13.06	48.27	74	-25.73	Pk	Vertical
3332	59.44	-12.78	46.66	74	-27.34	Pk	Horizontal
3332	58.55	-12.78	45.77	74	-28.23	Pk	Horizontal
17849	63.08	-12.28	50.80	74.00	-23.20	Pk	Vertical
17849	62.95	-12.28	50.67	74.00	-23.33	Pk	Horizontal

Note: (1) All other emissions more than 20dB below the limit.

7.3 6DB BANDWIDTH

7.3.1 Applicable Standard

According to FCC Part 15.247(a)(2) and KDB 558074 DTS 01 Meas. Guidance v03r04

7.3.2 Conformance Limit

The minimum permissible 6dB bandwidth is 500 kHz.

7.3.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.3.4 Test Setup

Please refer to Section 6.1 of this test report.

7.3.5 Test Procedure

The testing follows KDB 558074 DTS 01 Meas. Guidance v03r04
The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT was operating in controlled its channel.
Use the following spectrum analyzer settings:
Span = the frequency band of operation
RBW = 100KHz
VBW ≥ 3*RBW
Sweep = auto
Detector function = peak
Trace = max hold

7.3.6 Test Results

EUT:	tablet	Model No.:	PH701T
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode1/Mode2/Mode3/Mode4	Test By:	Allen Liu

Channel	Frequency (MHz)	6dB bandwidth (kHz)	Limit (kHz)	Result
802.11b				
1	2412	10046.000	500	Pass
6	2437	10080.000	500	Pass
11	2462	9625.000	500	Pass
802.11g				
1	2412	15176.000	500	Pass
6	2437	15183.000	500	Pass
11	2462	15177.000	500	Pass
802.11n HT20				
1	2412	15455.000	500	Pass
6	2437	15177.000	500	Pass
11	2462	15144.000	500	Pass
802.11n HT40				
3	2422	35269.000	500	Pass
6	2437	35257.000	500	Pass
9	2452	35283.000	500	Pass

6dB Bandwidth plot on channel 1	802.11b



6dB Bandwidth plot on channel 6	802.11b



6dB Bandwidth plot on channel 11	802.11b



6dB Bandwidth plot on channel 1	802.11g



6dB Bandwidth plot on channel 6	802.11g



6dB Bandwidth plot on channel 11	802.11g



6dB Bandwidth plot on channel 1	802.11n HT20



6dB Bandwidth plot on channel 6	802.11n HT20



6dB Bandwidth plot on channel 11	802.11n HT20



6dB Bandwidth plot on channel 3	802.11n HT40



6dB Bandwidth plot on channel 6	802.11n HT40



6dB Bandwidth plot on channel 9	802.11n HT40



7.4 20DB BANDWIDTH

7.4.1 Applicable Standard

According to FCC Part 15.247(a)(2) and KDB 558074 DTS 01 Meas. Guidance v03r04

7.4.2 Conformance Limit

No limit requirement.

7.4.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.4.4 Test Setup

Please refer to Section 6.1 of this test report.

7.4.5 Test Procedure

The testing follows KDB 558074 DTS 01 Meas. Guidance v03r04
The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT was operating in controlled its channel.
Use the following spectrum analyzer settings:
Span = the frequency band of operation
RBW = 100KHz
VBW $\geq$ 3*RBW
Sweep = auto
Detector function = peak
Trace = max hold

7.4.6 Test Results

EUT:	tablet	Model No.:	PH701T
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode1/Mode2/Mode3/Mode4	Test By:	Allen Liu

Band	Frequency (MHz)	20dB bandwidth (kHz)	Limit (kHz)	Result
802.11b	2437	14173.000	N/A	Pass
802.11g	2437	17724.000	N/A	Pass
802.11n HT20	2437	18373.000	N/A	Pass
802.11n HT40	2437	37235.000	N/A	Pass

20dB Bandwidth plot on channel 6	802.11b



20dB Bandwidth plot on channel 6	802.11g



20dB Bandwidth plot on channel 6	802.11n HT20



20dB Bandwidth plot on channel 6	802.11n HT40



7.5 DUTY CYCLE

7.5.1 Applicable Standard

According to KDB 558074)6)b), issued 06/09/2015

7.5.2 Conformance Limit

No limit requirement.

7.5.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.5.4 Test Setup

Please refer to Section 6.1 of this test report.

7.5.5 Test Procedure

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set RBW ⩾ OBW if possible; otherwise, set RBW to the largest available value. Set VBW ⩾ RBW. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if T ⩽ 16.7 microseconds.)

The transmitter output is connected to the Spectrum Analyzer. We tested accroding to the zero-span measurement method, 6.0)b) in KDB 558074(issued 06/09/2015)

The largest availble value of RBW is 8 MHz and VBW is 50 MHz. The zero-span method of measuring duty cycle shall not be used if T ⩽ 6.25 microseconds. (50/6.25 = 8)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are > 50/T.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT was operating in controlled its channel.
Use the following spectrum analyzer settings:
Span = Zero Span
RBW = 8MHz(the largest available value)
VBW = 8MHz (≥ RBW)
Number of points in Sweep >100
Detector function = peak
Trace = Clear write
Measure T_{total} and T_{on}
Calculate Duty Cycle = T_{on} / T_{total} and Duty Cycle Factor=10*log(1/Duty Cycle)

7.5.6 Test Results

EUT:	tablet	Model No.:	PH701T
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode1/Mode2/Mode3/Mode4	Test By:	Allen Liu

Mode	Data rate	Channel	T_{on}	T_{total}	Duty Cycle	1/T	VBW Setting
802.11b	1Mbps	6	-	-	-	-	10Hz
802.11g	6Mbps	6	1.392	1.433	0.9714	0.7184	1KHz
802.11n HT20	MCS0	6	1.300	1.333	0.9752	0.7692	1KHz
802.11n HT40	MCS0	6	0.650	0.685	0.9489	1.5385	3KHz

Note: All the modulation modes were tested, the data of the worst mode are described in the following table.

Duty Cycle plot on channel 6	802.11b



Duty Cycle plot on channel 6	802.11g



Duty Cycle plot on channel 6	802.11n HT20



Duty Cycle plot on channel 6	802.11n HT40



7.6 MAXIMUM OUTPUT POWER

7.6.1 Applicable Standard

According to FCC Part 15.247(b)(3) and KDB 558074 DTS 01 Meas. Guidance v03r04

7.6.2 Conformance Limit

The maximum peak conducted output power of the intentional radiator for systems using digital modulation in the 2400 - 2483.5 MHz bands shall not exceed: 1 Watt (30dBm). If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

7.6.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.6.4 Test Setup

Please refer to Section 6.1 of this test report.

7.6.5 Test Procedure

The testing follows KDB 558074 DTS 01 Meas. Guidance v03r04 section 9.2.2
The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT was operating in controlled its channel.
a) Set instrument center frequency to DTS channel center frequency.
b) Set span to at least 1.5 times the OBW.
c) Set RBW = 1-5% of the OBW, not to exceed 1MHz.
d) Set VBW ≥3 x RBW.
e) Number of points in sweep ≥ 2x span / RBW.
(This gives bin-to-bin spacing ≤ RBW/2, so that narrowband signals are not lost between frequency bins.)
f) Sweep time = auto.
g) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
h) If transmit duty cycle < 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98 %, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run”.
i) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
j) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

7.6.6 Test Results

EUT:	tablet	Model No.:	PH701T
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode1/Mode2/Mode3/Mode4	Test By:	Allen Liu

Test Channel	Frequency (MHz)	Power Setting	Average Output Power (dBm)	LIMIT (dBm)	Verdict
802.11b					
1	2412	Default	13.95	30	PASS
6	2437	Default	13.78	30	PASS
11	2462	Default	13.44	30	PASS
802.11g					
1	2412	Default	9.73	30	PASS
6	2437	Default	11.38	30	PASS
11	2462	Default	12.04	30	PASS
802.11n HT20					
1	2412	Default	9.37	30	PASS
6	2437	Default	11.23	30	PASS
11	2462	Default	11.47	30	PASS
802.11n HT40					
3	2422	Default	12.25	30	PASS
6	2437	Default	11.38	30	PASS
9	2452	Default	12.49	30	PASS

Output Power plot on channel 1	802.11b



Output Power plot on channel 6	802.11b



Output Power plot on channel 11	802.11b



Output Power plot on channel 1	802.11g



Output Power plot on channel 6	802.11g



Output Power plot on channel 11	802.11g



Output Power plot on channel 1	802.11n HT20



Output Power plot on channel 6	802.11n HT20



Output Power plot on channel 11	802.11n HT20



Output Power plot on channel 3	802.11n HT40



Output Power plot on channel 6	802.11n HT40



Output Power plot on channel 9	802.11n HT40



7.7 POWER SPECTRAL DENSITY

7.7.1 Applicable Standard

According to FCC Part 15.247(e) and KDB 558074 DTS 01 Meas. Guidance v03r04

7.7.2 Conformance Limit

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

7.7.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.7.4 Test Setup

Please refer to Section 6.1 of this test report.

7.7.5 Test Procedure

The testing follows Measurement Procedure 10.3 Method AVGPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r04
This procedure may be used when the maximum (average) conducted output power was used to demonstrate compliance to the output power limit. This is the baseline method for determining the maximum (average) conducted PSD level. If the instrument has an RMS power averaging detector, it must be used; otherwise, use the sample detector. The EUT must be configured to transmit continuously (duty cycle ≥ 98%); otherwise sweep triggering/signal gating must be implemented to ensure that measurements are made only when the EUT is transmitting at its maximum power control level (no transmitter off time is to be considered).
The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT was operating in controlled its channel.
a) Set instrument center frequency to DTS channel center frequency.
b) Set span to at least 1.5 times the OBW.
c) Set RBW to: 3 kHz ≤ RBW ≤ 100 kHz. .
d) Set VBW ≥3 x RBW.
e) Detector = power averaging (RMS) or sample detector (when RMS not available).
f) Ensure that the number of measurement points in the sweep ≥ 2 x span/RBW.
g) Sweep time = auto couple.
h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
i) Use the peak marker function to determine the maximum amplitude level.
j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducin

7.7.6 Test Results

EUT:	tablet	Model No.:	PH701T
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode1/Mode2/Mode3/Mode4	Test By:	Allen Liu

Test Channel	Frequency (MHz)	Power Density (dBm/3KHz)	Limit (dBm/3KHz)	Verdict
802.11b				
1	2412	-16.95	8	PASS
6	2437	-16.81	8	PASS
11	2462	-17.66	8	PASS
802.11g				
1	2412	-22.68	8	PASS
6	2437	-21.55	8	PASS
11	2462	-24.49	8	PASS
802.11n HT20				
1	2412	-23.50	8	PASS
6	2437	-21.83	8	PASS
11	2462	-21.45	8	PASS
802.11n HT40				
3	2422	-24.93	8	PASS
6	2437	-26.09	8	PASS
9	2452	-25.32	8	PASS

Power spectral density plot on channel 1	802.11b



Power spectral density plot on channel 6	802.11b



Power spectral density plot on channel 11	802.11b



Power spectral density plot on channel 1	802.11g



Power spectral density plot on channel 6	802.11g



Power spectral density plot on channel 11	802.11g



Power spectral density plot on channel 1	802.11n HT20



Power spectral density plot on channel 6	802.11n HT20



Power spectral density plot on channel 11	802.11n HT20



Power spectral density plot on channel 3	802.11n HT40



Power spectral density plot on channel 6	802.11n HT40



Power spectral density plot on channel 9	802.11n HT40



7.8 CONDUCTED BAND EDGE MEASUREMENT

7.8.1 Applicable Standard

According to FCC Part 15.247(d) and KDB 558074 DTS 01 Meas. Guidance v03r04

7.8.2 Conformance Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

7.8.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.8.4 Test Setup

Please refer to Section 6.1 of this test report.

7.8.5 Test Procedure

The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r04.
The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT was operating in controlled its channel.
Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
Repeat above procedures until all measured frequencies were complete.

7.8.6 Test Results

EUT:	tablet	Model No.:	PH701T
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode1/Mode2/Mode3/Mode4	Test By:	Allen Liu

Frequency Band	Delta Peak to band emission(dBc)	＞Limit(dBc)	Verdict
802.11b			
2400	48.32	20	Pass
2483.5	53.84	20	Pass
802.11g			
2400	36.08	20	Pass
2483.5	45.74	20	Pass
802.11n HT20			
2400	33.39	20	Pass
2483.5	41.35	20	Pass
802.11n HT40			
2400	33.09	20	Pass
2483.5	38.24	20	Pass

802.11b: Band Edge-Low Channel



802.11b: Band Edge-High Channel



802.11g: Band Edge-Low Channel



802.11g: Band Edge-High Channel



802.11n HT20: Band Edge-Low Channel



802.11n HT20: Band Edge-High Channel



802.11n HT40: Band Edge-Low Channel



802.11n HT40: Band Edge-High Channel



7.9 ANTENNA APPLICATION

7.9.1 Antenna Requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

7.9.2 Result

The EUT antenna is permanent attached antenna. It comply with the standard requirement.

END OF REPORT