

FCC ID: 2AGPF-K1625BE

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

EDR: Left ear:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	1.936	1.56	1±1	2.00	1.58	<5	0.49127	3.00	YES
	2.441	4.099	2.57	4±1	5.00	3.16	<5	0.98813	3.00	YES
	2.480	3.005	2.00	3±1	4.00	2.51	<5	0.79114	3.00	YES
π /4DQPSK	2.402	2.697	1.86	2±1	3.00	2.00	<5	0.61847	3.00	YES
	2.441	4.848	3.05	4±1	5.00	3.16	<5	0.98813	3.00	YES
	2.480	3.491	2.23	3±1	4.00	2.51	<5	0.79114	3.00	YES

EDR: Right ear

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	2.016	1.59	2±1	3.00	2.00	<5	0.61847	3.00	YES
	2.441	4.158	2.60	4±1	5.00	3.16	<5	0.98813	3.00	YES
	2.480	3.049	2.02	3±1	4.00	2.51	<5	0.79114	3.00	YES
π /4DQPSK	2.402	2.792	1.90	2±1	3.00	2.00	<5	0.61847	3.00	YES
	2.441	4.78	3.01	4±1	5.00	3.16	<5	0.98813	3.00	YES
	2.480	3.522	2.25	3±1	4.00	2.51	<5	0.79114	3.00	YES

Left ear:

BLE:1M

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	1.841	1.53	1±1	2.00	1.58	<5	0.49127	3.00	YES
	2.44	3.952	2.48	3±1	4.00	2.51	<5	0.78474	3.00	YES
	2.480	2.901	1.95	2±1	3.00	2.00	<5	0.62843	3.00	YES

BLE:2M

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	1.918	1.56	1±1	2.00	1.58	<5	0.49127	3.00	YES
	2.44	4.063	2.55	4±1	5.00	3.16	<5	0.98793	3.00	YES
	2.480	2.997	1.99	2±1	3.00	2.00	<5	0.62843	3.00	YES

Right ear:

BLE:1M

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	1.726	1.49	1±1	2.00	1.58	<5	0.49127	3.00	YES
	2.44	3.664	2.32	3±1	4.00	2.51	<5	0.78474	3.00	YES
	2.480	2.714	1.87	2±1	3.00	2.00	<5	0.62843	3.00	YES

BLE:2M

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	1.722	1.49	1±1	2.00	1.58	<5	0.49127	3.00	YES
	2.44	3.872	2.44	4±1	5.00	3.16	<5	0.98793	3.00	YES
	2.480	2.896	1.95	2±1	3.00	2.00	<5	0.62843	3.00	YES

Conclusion:For the max result : $0.98813 \leq \text{FCC Limit } 3.0$ for 1g SAR.