Shenzhen GTI Technology Co., Ltd.

1F,2 Block, Jiaquan Building, Guanlan High-tech Park Baoan District,
Shenzhen, Guangdong, China.
Tel: +86-755-27559792
Fax: +86-755-86116468

TEST REPORT

Product Name .....: CAMERA

Trademark .....: EIE

Model/Type reference .....: Explorer Pro

Listed Model(s) .....: /

FCC ID .....: 2AGUA-EXPLORERPRO

Test Standards .....: **FCC Part 15.247: Operation within the bands 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz**

Applicant .....: HK ELEPHONE COMMUNICATION TECH CO.,LIMITED

Address of applicant .....: UNIT 04,7/F BRIGHT WAY TOWER NO.33 MONG KOK RD KL, Hong Kong

Date of Receipt .....: Mar. 03, 2016

Date of Test Date .....: Mar. 03, 2016 - Apr. 27, 2016

Data of issue. .....: Apr. 27, 2016

Test result	**Pass ***

* In the configuration tested, the EUT complied with the standards specified above

GENERAL DESCRIPTION OF EUT	
Equipment:	CAMERA
Model Name:	Explorer Pro
Manufacturer:	HK ELEPHONE COMMUNICATION TECH CO.,LIMITED
Manufacturer Address:	UNIT 04,7/F BRIGHT WAY TOWER NO.33 MONG KOK RD KL, Hong Kong
Power Rating:	DC 3.7V form 1050mAh by rechargeable battery DC 5.0V form USB Port

Compiled By: (Sevin Li)

Reviewed By: (Tony Wang)

Approved By: (Walter Chen)

This test report consists of 51 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by GTI. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of compiler, reviewer and approver. Any objections must be raised to GTI within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.

Table of Contents Page

1. SUMMARY 4

1.1. TEST STANDARDS 4
1.2. TEST DESCRIPTION 4
1.3. TEST FACILITY 5
1.4. MEASUREMENT UNCERTAINTY 5

2. GENERAL INFORMATION 6

2.1. ENVIRONMENTAL CONDITIONS 6
2.2. GENERAL DESCRIPTION OF EUT 6
2.3. DESCRIPTION OF TEST MODES 7
2.1. MEASUREMENT INSTRUMENTS LIST 8
2.2. TEST CONDITIONS AND RESULTS 9
2.3. CONDUCTED EMISSION (AC MAIN) 9
2.4. RADIATED EMISSION 12
2.5. MAXIMUM CONDUCTED OUTPUT POWER 19
2.6. POWER SPECTRAL DENSITY 20
2.7. 6DB BANDWIDTH 23
2.8. BAND EDGE COMPLIANCE OF RF EMISSION 26
2.9. SPURIOUS RF CONDUCTED EMISSION 30
2.10. ANTENNA REQUIREMENT 40

3. EUT TEST PHOTO 41

4. PHOTOGRAPHS OF EUT CONSTRUCTIONAL 42

1. SUMMARY

1.1. Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices

1.2. Test Description

FCC PART 15 15.247		
FCC Part 15.207	AC Power Conducted Emission	PASS
FCC Part 15.247(a)(2)	6dB Bandwidth	PASS
FCC Part 15.247(d)	Spurious RF Conducted Emission	PASS
FCC Part 15.247(b)	Maximum Conducted Output Power	PASS
FCC Part 15.247(e)	Power Spectral Density	PASS
FCC Part 15.109/ 15.205/ 15.209	Radiated Emissions	PASS
FCC Part 15.247(d)	Band Edge	PASS
FCC Part 15.203/15.247 (b)	Antenna Requirement	PASS

Remark: The measurement uncertainty is not included in the test result.

1.3. Test Facility

1.3.1 Address of the test laboratory

Shenzhen General Testing & Inspection Technology Co., Ltd.

Add: 1F, 2 Block,Jiaquan Building, Guanlan High-tech Park Baoan District, Shenzhen, Guangdong,China

1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

IC Registration No.: 9783A

The 3m alternate test site of Shenzhen GTI Technology Co., Ltd.EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration NO.: 9783A on Aug, 2011.

FCC-Registration No.: 214666

Shenzhen GTI Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 214666, Sep 19, 2011

1.4. Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements and is documented in the Shenzhen General Testing & Inspection Technology Co., Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for General Testing & Inspection laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)
Transmitter power Radiated	2.20 dB	(1)
Conducted spurious emission 9KHz-40 GHz	1.60 dB	(1)
Radiated spurious emission 9KHz-40 GHz	2.20 dB	(1)
Conducted Emission 9KHz-30MHz	3.39 dB	(1)
Radiated Emission 30~1000MHz	4.24 dB	(1)
Radiated Emission 1~18GHz	5.16 dB	(1)
Radiated Emission 18-40GHz	5.54 dB	(1)
Occupied Bandwidth	---------	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

2. GENERAL INFORMATION

2.1. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35°C
Relative Humidity:	30~60 %
Air Pressure:	950~1050mba

2.2. General Description of EUT

Product Name:	CAMERA
Model/Type reference:	Explorer Pro
List Model:	/
Power supply:	DC 3.7V form 1050mAh by rechargeable battery or DC 5.0V form USB Cable
Hardware Version:	V2.3
Software Version:	V1.0
WIFI :	
Supported type:	802.11b/802.11g/802.11n(H20)
Modulation:	802.11b: DSSS 802.11g/802.11n(H20): OFDM
Operation frequency:	802.11b/802.11g/802.11n(H20): 2412MHz~2462MHz
Channel number:	802.11b/802.11g/802.11n(H20): 11
Channel separation:	5MHz
Antenna type:	PCB Antenna
Antenna gain:	2.0dBi

Note: For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.3. Description of Test Modes

Peripheral equipment list

Name:	Model:	Serial	Manufacture	Remark
AC Adapter	D12-501000F	MUCSB2WH1	STK	Input:100-240V, 50/60Hz, 0.2A Output:5V, 1A

WIFI Operation Frequency

The Applicant provides engineering files to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) mode for testing.

Note: The engineering sample had fixed the transmit parameter by the fixed files that the manufacture supplied. The fixed parameter: modulation style, channel, power level, bandwidth

For example 802.11b-Low channel is a single file, the 802.11b-middle is a single file, the same as others.

Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	**2412**	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	**11**	**2462**
5	2432		
6	**2437**		
7	2442		

Data Rate Used:

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel
Maximum Peak Conducted Output Power Power Spectral Density 6dB Bandwidth Spurious RF conducted emission Radiated Emission 9kHz~1GHz& Radiated Emission 1GHz~10th Harmonic	11b/DSSS	1 Mbps	1/6/11
	11g/OFDM	6 Mbps	1/6/11
	11n(20MHz)/OFDM	6.5Mbps	1/6/11
Band Edge	11b/DSSS	1 Mbps	1/11
	11g/OFDM	6 Mbps	1/11
	11n(20MHz)/OFDM	6.5Mbps	1/11

2.1. Measurement Instruments List

Maximum Conducted Output Power/Power Spectral Density / 6dB Bandwidth / Band Edge Compliance of RF Emission / Spurious RF Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	Power Meter	Anritsu	ML2487B	110553	July 10,2016
2	Power Sensor	Anritsu	MA2411B	100345	July 10,2016
3	Spectrum Analyzer	Rohde & Schwarz	FSU	100105	Jan 04,2017
4	RF Cable	Schwarzbeck	AH32D4	SF0150	Jan 04,2017
5	Temporary Antenna connector	Schwarzbeck	SMA24D	ED1201	Jan 04,2017
Note: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.					

Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrate until
1	LISN	R&S	ENV216	101112	Jan. 07, 2016
2	LISN	R&S	ENV216	101113	Jan. 07, 2016
3	EMI Test Receiver	R&S	ESCI	100920	Jan. 07, 2016
4	Cable	Schwarzbeck	AK9515E	33156	Jan. 07, 2016

Radiated Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	EMI Test Receiver	R&S	ESCI	100967	Jan 04,2017
2	High pass filter	micro-tranics	HPM50111	34202	Jan 04,2017
3	Log-Bicon Antenna	Schwarzbeck	CBL6141A	4180	Jan 04,2017
4	Ultra-Broadband Antenna	ShwarzBeck	BBHA9170	25841	Jan 07,2017
5	Loop Antenna	LAPLAC	RF300	9138	Jan 07,2017
6	Spectrum Analyzer	Rohde & Schwarz	FSU	100105	Jan 04,2017
7	Horn Antenna	Schwarzbeck	BBHA 9120D	648	Jan 07,2017
8	Pre-Amplifier	HP	8447D	1937A03050	Jan 04,2017
9	Pre-Amplifier	EMCI	EMC051835	980075	Jan 04,2017
10	Antenna Mast	UC	UC3000	N/A	N/A
11	Turn Table	UC	UC3000	N/A	N/A
12	Cable Below 1GHz	Schwarzbeck	AK9515E	33155	Jan 04,2017
13	Cable Above 1GHz	Hubersuhner	SUCOFLEX102	DA1580	Jan 04,2017

Note: 1. The Cal.Interval was one year.
2. The cable loss has calculated in test result which connection between each test instruments.

2.2. TEST CONDITIONS AND RESULTS

2.3. Conducted Emission (AC Main)

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
2. Support equipment, if needed, was placed as per ANSI C63.10-2013
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
4. The EUT received DC5V power from the adapter, the adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST RESULTS

Note: We tested all modes, recorded the worst case at wifi 802.11b mode L Channel

LINE	L

SCAN TABLE: "Vol(9K-30M)FIN-N"

Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "W 3 L_fin"

3/4/2016 11:21AM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.450000	48.70	9.8	57	8.2	QP	L1	GND
0.950000	42.40	10.0	56	13.6	QP	L1	GND
1.016000	42.80	10.0	56	13.2	QP	L1	GND

MEASUREMENT RESULT: "W 3 L_fin2"

3/4/2016 11:21AM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.458000	39.00	9.8	47	7.7	AV	L1	GND
0.944000	35.40	10.0	46	10.6	AV	L1	GND
0.986000	32.10	10.0	46	13.9	AV	L1	GND

LINE	N

SCAN TABLE: "Vol(9K-30M)FIN-N"

Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "W 3 N_fin"

3/4/2016 11:23AM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.451500	44.70	9.5	57	12.1	QP	N	GND
0.882500	37.50	9.7	56	18.5	QP	N	GND
0.909500	37.50	9.7	56	18.5	QP	N	GND

MEASUREMENT RESULT: "W 3 N_fin2"

3/4/2016 11:23AM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.447000	38.10	9.5	47	8.8	AV	N	GND
1.013000	33.40	9.8	46	12.6	AV	N	GND
1.080500	31.60	9.8	46	14.4	AV	N	GND

2.4. Radiated Emission

Limit

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the100kHz bandwidth within the band that contains the highest level of desired power.

The frequency spectrum above 1 GHz for Transmitter was investigated. All emission not reported are much lower than the prescribed limits. Set the RBW=1MHz, VBW=3MHz for Peak Detector while the RBW=1MHz, VBW=10Hz for Average Detector, Readings are both peak and average values. The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos.

Frequency (MHz)	Distance (Meters)	Radiated (dBuV/m)	Radiated (μV/m)
0.009-0.49	3	20log(2400/F(KHz))+40log(300/3)	2400/F(KHz)
0.49-1.705	3	20log(24000/F(KHz))+ 40log(30/3)	24000/F(KHz)
1.705-30	3	20log(30)+ 40log(30/3)	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

Test Procedure

1. For below 1GHz test, The EUT was placed on a turn table which is 0.8m above ground plane. For Above 1GHz test, The EUT was placed on a turn table which is 1.5m above ground plane;
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0℃ to 360℃ to acquire the highest emissions from EUT
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.

Note: For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CL – AG

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

For example

Frequency (MHz)	FS (dBμV/m)	RA (dBμV/m)	AF (dB)	CL (dB)	AG (dB)	Transd (dB)
150.00	40	58.1	12.2	1.6	31.90	-18.1

Transd=AF +CL-AG

Test Configuration

For the actual test configuration, please refer to the related Item –EUT Test Photos.

Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



Test Results

Remark:

1. We tested three channels for each mode and recorded worst case at low channel of 802.11b Mode below 1GHz

For 9 KHz-30MHz

Frequency (MHz)	Corrected Reading (dBuV/m)@3m	FCC Limit (dBuV/m) @3m	Margin (dB)	Detector	Result
0.21	54.62	101.16	46.54	QP	PASS
1.15	18.24	66.39	48.15	QP	PASS
13.56	36.02	69.54	33.52	QP	PASS
25.01	48.03	69.54	21.51	QP	PASS

For 30MHz-1GHz

Horizontal



Mark	Frequency MHz	Level dBuV/m	Factor dB/m	Reading dBuV	Limit dBuV/m	Margin dB	Polarization	Detector
1	59.65	29.47	-19.27	48.74	40.00	10.53	HORIZONTAL	Peak
2	216.02	29.26	-17.77	47.03	46.00	16.74	HORIZONTAL	Peak
3	504.71	34.79	-11.48	46.27	46.00	11.21	HORIZONTAL	Peak

Vertical



Mark	Frequency MHz	Level dBuV/m	Factor dB/m	Reading dBuV	Limit dBuV/m	Margin dB	Polarization	Detector
1	216.02	38.83	-17.77	56.60	46.00	7.17	VERTICAL	Peak
2	263.82	39.89	-17.51	57.40	46.00	6.11	VERTICAL	Peak
3	504.71	42.33	-11.48	53.81	46.00	3.67	VERTICAL	Peak

For 1GHz to 25GHz

802.11b Mode (above 1GHz)

Frequency(MHz):				2412			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	4824	50.24	PK	74.00	23.76	1.00	107	48.14	31.6	7.00	36.5	2.10
1	4824	45.02	AV	54.00	8.98	1.00	107	42.92	31.6	7.00	36.5	2.10
2	7236	45.13	PK	74.00	28.87	1.00	107	34.20	37.33	8.90	35.3	10.93
2	7236	37.69	AV	54.00	16.31	1.00	107	26.76	37.33	8.90	35.3	10.93

Frequency(MHz):				2412			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	4824	50.16	PK	74.00	23.84	1.00	214	48.06	31.60	7.00	36.50	2.10
1	4824	44.08	AV	54.00	9.92	1.00	214	41.98	31.60	7.00	36.50	2.10
2	7236	41.21	PK	74.00	32.79	1.00	214	30.28	37.33	8.90	35.30	10.93
2	7236	35.21	AV	54.00	18.79	1.00	214	24.28	37.33	8.90	35.30	10.93

Frequency(MHz):				2437			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	4874.00	51.29	PK	74.00	22.71	1.00	101	49.17	31.02	7.60	36.5	2.12
1	4874.00	43.57	AV	54.00	10.43	1.00	101	41.45	31.02	7.60	36.5	2.12
2	7311.00	43.58	PK	74.00	30.42	1.00	101	32.50	37.28	8.60	34.8	11.08
2	7311.00	35.45	AV	54.00	18.55	1.00	101	24.37	37.28	8.60	34.8	11.08

Frequency(MHz):				2437			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	4874.00	50.64	PK	74.00	23.36	1.00	224	48.52	31.02	7.60	36.5	2.12
1	4874.00	44.97	AV	54.00	9.03	1.00	224	42.85	31.02	7.60	36.5	2.12
2	7311.00	42.17	PK	74.00	31.83	1.00	224	31.09	37.28	8.60	34.8	11.08
2	7311.00	36.38	AV	54.00	17.62	1.00	224	25.30	37.28	8.60	34.8	11.08

Frequency(MHz):				2462			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	4924.00	51.14	PK	74.00	22.86	1.00	119	47.94	31.58	7.82	36.2	3.20
1	4924.00	44.67	AV	54.00	9.33	1.00	119	41.47	31.58	7.82	36.2	3.20
2	7386.00	42.48	PK	74.00	31.52	1.00	119	30.54	38.51	8.73	35.3	11.94
2	7386.00	37.64	AV	54.00	16.36	1.00	92	25.70	38.51	8.73	35.3	11.94

Frequency(MHz):				2462			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	4924.00	50.91	PK	74.00	23.09	1.00	210	47.71	31.58	7.82	36.2	3.20
1	4924.00	44.37	AV	54.00	9.63	1.00	210	41.17	31.58	7.82	36.2	3.20
2	7386.00	42.34	PK	74.00	31.66	1.00	210	30.40	38.51	8.73	35.3	11.94
2	7386.00	36.10	AV	54.00	17.90	1.00	210	24.16	38.51	8.73	35.3	11.94

802.11g Mode (above 1GHz)

Frequency(MHz):				2412			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	4824	49.63	PK	74.00	24.37	1.00	142	47.53	31.6	7.00	36.5	2.10
1	4824	41.97	AV	54.00	12.03	1.00	142	39.87	31.6	7.00	36.5	2.10
2	7236	44.63	PK	74.00	29.37	1.00	142	33.70	37.33	8.90	35.3	10.93
2	7236	35.22	AV	54.00	18.78	1.00	142	24.29	37.33	8.90	35.3	10.93

Frequency(MHz):				2412			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	4824	51.21	PK	74.00	22.79	1.00	189	49.11	31.60	7.00	36.50	2.10
1	4824	43.22	AV	54.00	10.78	1.00	189	41.12	31.60	7.00	36.50	2.10
2	7236	46.39	PK	74.00	27.61	1.00	189	35.46	37.33	8.90	35.30	10.93
2	7236	38.18	AV	54.00	15.82	1.00	189	27.25	37.33	8.90	35.30	10.93

Frequency(MHz):				2437			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	4874.00	49.55	PK	74.00	24.45	1.00	136	47.43	31.02	7.60	36.5	2.12
1	4874.00	40.82	AV	54.00	13.18	1.00	136	38.70	31.02	7.60	36.5	2.12
2	7311.00	43.41	PK	74.00	30.59	1.00	136	32.33	37.28	8.60	34.8	11.08
2	7311.00	33.32	AV	54.00	20.68	1.00	136	22.24	37.28	8.60	34.8	11.08

Frequency(MHz):				2437			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	4874.00	49.85	PK	74.00	24.15	1.00	199	47.73	31.02	7.60	36.5	2.12
1	4874.00	41.34	AV	54.00	12.66	1.00	199	39.22	31.02	7.60	36.5	2.12
2	7311.00	45.04	PK	74.00	28.96	1.00	199	33.96	37.28	8.60	34.8	11.08
2	7311.00	35.71	AV	54.00	18.29	1.00	199	24.63	37.28	8.60	34.8	11.08

Frequency(MHz):				2462			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	4924.00	49.99	PK	74.00	24.01	1.00	199	46.79	31.58	7.82	36.2	3.20
1	4924.00	41.90	AV	54.00	12.10	1.00	199	38.70	31.58	7.82	36.2	3.20
2	7386.00	45.53	PK	74.00	28.47	1.00	199	33.59	38.51	8.73	35.3	11.94
2	7386.00	35.74	AV	54.00	18.26	1.00	199	23.80	38.51	8.73	35.3	11.94

Frequency(MHz):				2462			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	4924.00	50.03	PK	74.00	23.97	1.00	185	46.83	55.70	7.82	36.2	3.20
1	4924.00	42.12	AV	54.00	11.88	1.00	185	38.92	49.20	7.82	36.2	3.20
2	7386.00	47.25	PK	74.00	26.75	1.00	185	35.31	50.45	8.73	35.3	11.94
2	7386.00	35.91	AV	54.00	18.09	1.00	185	23.97	41.28	8.73	35.3	11.94

802.11n20 Mode (above 1GHz)

Frequency(MHz):				2412			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	4824	47.77	PK	74.00	26.23	1.00	130	45.67	31.6	7.00	36.5	2.10
1	4824	41.47	AV	54.00	12.53	1.00	130	39.37	31.6	7.00	36.5	2.10
2	7236	42.73	PK	74.00	31.27	1.00	130	31.80	37.33	8.90	35.3	10.93
2	7236	33.19	AV	54.00	20.81	1.00	130	22.26	37.33	8.90	35.3	10.93

Frequency(MHz):				2412			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	4824	50.29	PK	74.00	23.71	1.00	174	48.19	31.60	7.00	36.50	2.10
1	4824	41.19	AV	54.00	12.81	1.00	174	39.09	31.60	7.00	36.50	2.10
2	7236	44.99	PK	74.00	29.01	1.00	174	34.06	37.33	8.90	35.30	10.93
2	7236	37.05	AV	54.00	16.95	1.00	174	26.12	37.33	8.90	35.30	10.93

Frequency(MHz):				2437			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	4874.00	48.02	PK	74.00	25.98	1.00	130	45.90	56.38	7.60	36.5	2.12
1	4874.00	39.40	AV	54.00	14.60	1.00	130	37.28	48.60	7.60	36.5	2.12
2	7311.00	43.14	PK	74.00	30.86	1.00	130	32.06	51.34	8.60	34.8	11.08
2	7311.00	34.25	AV	54.00	19.75	1.00	130	23.17	43.25	8.60	34.8	11.08

Frequency(MHz):				2437			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	4874.00	47.16	PK	74.00	26.84	1.00	204	45.04	31.02	7.60	36.5	2.12
1	4874.00	41.71	AV	54.00	12.29	1.00	204	39.59	31.02	7.60	36.5	2.12
2	7311.00	43.15	PK	74.00	30.85	1.00	204	32.07	37.28	8.60	34.8	11.08
2	7311.00	35.61	AV	54.00	18.39	1.00	204	24.53	37.28	8.60	34.8	11.08

Frequency(MHz):				2462			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	4924.00	48.06	PK	74.00	25.94	1.00	209	44.86	31.58	7.82	36.2	3.20
1	4924.00	43.39	AV	54.00	10.61	1.00	209	40.19	31.58	7.82	36.2	3.20
2	7386.00	44.34	PK	74.00	29.66	1.00	209	32.40	38.51	8.73	35.3	11.94
2	7386.00	36.43	AV	54.00	17.57	1.00	209	24.49	38.51	8.73	35.3	11.94

Frequency(MHz):				2462			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	4924.00	49.07	PK	74.00	24.93	1.00	179	45.87	31.58	7.82	36.2	3.20
1	4924.00	42.42	AV	54.00	11.58	1.00	179	39.22	31.58	7.82	36.2	3.20
2	7386.00	46.03	PK	74.00	27.97	1.00	179	34.09	38.51	8.73	35.3	11.94
2	7386.00	35.24	AV	54.00	18.76	1.00	179	23.30	38.51	8.73	35.3	11.94

2.5. Maximum Conducted Output Power

Limit

30dBm for digital modulation systems.

Test Procedure

1. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Power Meter.
2. Ensure EUT transmitting with a duty cycle ≥ 98 %.
3. Record the value of Power Meter.

Test Configuration



Test Results

WIFI

Type	Channel	Output power PK(dBm)	Limit (dBm)	Result
802.11b	01	8.93	30.00	Pass
	06	8.75		
	11	8.37		
802.11g	01	8.49	30.00	Pass
	06	8.32		
	11	8.13		
802.11n(H20)	01	7.69	30.00	Pass
	06	7.78		
	11	7.53		

Note: 1.The test results including the cable lose.

2.6. Power Spectral Density

Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Test Procedure

- This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance to the output power limit.
  1. Set analyzer center frequency to DTS channel center frequency.
  2. Set the span to 1.5 times the DTS bandwidth.
  3. Set the RBW to: 3 kHz ≤ RBW ≤ 100 kHz.
  4. Set the VBW ≥ 3 × RBW.
  5. Detector = peak.
  6. Sweep time = auto couple.
  7. Trace mode = max hold.
  8. Allow trace to fully stabilize.
  9. Use the peak marker function to determine the maximum amplitude level within the RBW.
  10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat

Test Configuration



Test Results

WIFI

Type	Channel	Power Spectral Density (dBm/30KHz)	Limit (dBm/3KHz)	Result
802.11b	01	-6.390	8.00	Pass
	06	-6.390		
	11	-6.900		
802.11g	01	-7.440	8.00	Pass
	06	-7.330		
	11	-7.610		
802.11n(HT20)	01	-8.590	8.00	Pass
	06	-8.550		
	11	-8.940		

Test plot as follows:

802.11b



802.11g



CH01



CH01



CH06



CH06



CH11

CH11

802.11n(HT20)



CH01



CH06



CH11

2.7. 6dB Bandwidth

Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz

Test Procedure

1. The transmitter output was connected to the spectrum analyzer.
2. Set SA as follow:
   a) RBW: 100 kHz.
   b) VBW: ≥ 3 × RBW.
   c) Detector: Peak.
   d) Trace mode: max hold.
   e) Sweep: auto couple.
3. Allow the trace to stabilize.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Test Configuration



Test Results

WIFI

Type	Channel	6dB Bandwidth (MHz)	Limit (KHz)	Result
802.11b	01	9.231	≥500	Pass
	06	9.227		
	11	9.810		
802.11g	01	16.410	≥500	Pass
	06	16.292		
	11	16.271		
802.11n(HT20)	01	17.582	≥500	Pass
	06	17.436		
	11	17.585		

Note: Because of resolution issues it is impossible to set the markers exactly at the -6dB points. the closest frequencies have been choosen.

802.11b



802.11g



CH01



CH01



CH06



CH06



CH11

CH11

802.11n(HT20)



CH01



CH06



CH11

2.8. Band Edge Compliance of RF Emission

Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)

Test Procedure

Test Procedure tor conducted method

- Use this procedure when the maximum (average) conducted output power was used to demonstrate compliance to the output power limit.
  1. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a spectrum analyzer
  2. Turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
  1. Set spectrum analyzer RBW =100 kHz, VBW=300 kHz, Detector=peak, Sweep time=Auto, trace=maxhold
  3. Marker the highest point which fall into restricted frequency bands
  4. Repeat above procedures until all measured frequencies were complete.

Test Procedure tor radiated method

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel
7. Test the EUT in the lowest channel, the highest channel
8. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.
9. Repeat above procedures until all frequencies measured was complete.

Test Results

A. Conducted measurements

802.11b			
Frequency (MHz)	**Delta Peak to Band emission (dBc)**	**Limit (dBc)**	**Verdict**
2371.487	42.921	20	PASS
2496.861	41.807	20	PASS



2412



2462

802.11g			
Frequency (MHz)	**Delta Peak to Band emission (dBc)**	**Limit (dBc)**	**Verdict**
2345.756	38.506	20	PASS
2490.858	38.292	20	PASS



2412



2462

802.11n20			
Frequency (MHz)	**Delta Peak to Band emission (dBc)**	**Limit (dBc)**	**Verdict**
2352.668	37.511	20	PASS
2494.701	37.465	20	PASS
			
2412		2462	

B. **Radiated measurements**

802.11b

Frequency(MHz):			**2412**			**Polarity:**			**HORIZONTAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2390.00	57.22	PK	74.00	16.78	1.00	130	62.53	27.49	3.32	36.12	-5.31
2390.00	49.13	AV	54.00	4.87	1.00	130	54.44	27.49	3.32	36.12	-5.31
Frequency(MHz):			**2412**			**Polarity:**			**VERTICAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2390.00	55.76	PK	74.00	18.24	1.00	45	61.07	27.49	3.32	36.12	-5.31
2390.00	46.91	AV	54.00	7.09	1.00	45	52.22	27.49	3.32	36.12	-5.31
Frequency(MHz):			**2462**			**Polarity:**			**HORIZONTAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.50	53.72	PK	74.00	20.28	1.00	170	59.44	27.45	3.38	36.55	-5.72
2483.50	45.17	AV	54.00	8.83	1.00	170	50.89	27.45	3.38	36.55	-5.72
Frequency(MHz):			**2462**			**Polarity:**			**VERTICAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.50	51.35	PK	74.00	22.65	1.00	145	57.07	27.45	3.38	36.55	-5.72
2483.50	45.48	AV	54.00	8.52	1.00	145	51.20	27.45	3.38	36.55	-5.72

802.11g

Frequency(MHz):			2412			Polarity:			HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2390.00	53.21	PK	74.00	20.79	1.00	105	58.52	27.49	3.32	36.12	-5.31
2390.00	44.40	AV	54.00	9.60	1.00	105	49.71	27.49	3.32	36.12	-5.31
Frequency(MHz):			**2412**			**Polarity:**			**VERTICAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2390.00	53.22	PK	74.00	20.78	1.00	243	58.53	27.49	3.32	36.12	-5.31
2390.00	42.08	AV	54.00	11.92	1.00	243	47.39	27.49	3.32	36.12	-5.31
Frequency(MHz):			**2462**			**Polarity:**			**HORIZONTAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.50	52.78	PK	74.00	21.22	1.00	110	58.50	27.45	3.38	36.55	-5.72
2483.50	42.3	AV	54.00	11.70	1.00	110	48.02	27.45	3.38	36.55	-5.72
Frequency(MHz):			**2462**			**Polarity:**			**VERTICAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.50	51.14	PK	74.00	22.86	1.00	233	56.86	27.45	3.38	36.55	-5.72
2483.50	41.23	AV	54.00	12.77	1.00	233	46.95	27.45	3.38	36.55	-5.72

802.11n20

Frequency(MHz):			2412			Polarity:			HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2390.00	52.84	PK	74.00	21.16	1.00	100	58.15	27.49	3.32	36.12	-5.31
2390.00	41.46	AV	54.00	12.54	1.00	100	46.77	27.49	3.32	36.12	-5.31
Frequency(MHz):			**2412**			**Polarity:**			**VERTICAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2390.00	52.12	PK	74.00	21.88	1.00	238	57.43	27.49	3.32	36.12	-5.31
2390.00	41.22	AV	54.00	12.78	1.00	238	46.53	27.49	3.32	36.12	-5.31
Frequency(MHz):			**2462**			**Polarity:**			**HORIZONTAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.50	51.13	PK	74.00	22.87	1.00	110	56.85	27.45	3.38	36.55	-5.72
2483.50	42.51	AV	54.00	11.49	1.00	110	48.23	27.45	3.38	36.55	-5.72
Frequency(MHz):			**2462**			**Polarity:**			**VERTICAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.50	53.11	PK	74.00	20.89	1.00	253	58.83	27.45	3.38	36.55	-5.72
2483.50	41.32	AV	54.00	12.68	1.00	253	47.04	27.45	3.38	36.55	-5.72

2.9. Spurious RF Conducted Emission

Limit

1. Below -20dB of the highest emission level in operating band.
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

Test Procedure

The transmitter output was connected to the spectrum analyzer through a low loss RF cable. Spurious RF Conducted Emission was measured by spectrum analyzer with100 KHz RBW and 300KHz VBW, measurement frequency range from 30MHz to 26.5GHz.

Test Configuration



Test Results

Remark: The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandage measurement data.

Test plot as follows:

Test Mode:	802.11b	Test channel :	01



Reference level



30MHz-3GHz



3GHz-5GHz



5GHz-10GHz



10GHz-15GHz



15GHz-25GHz

Test Mode:	802.11b	Test channel :	06



Reference level



30MHz-3GHz



3GHz-5GHz



5GHz-10GHz



10GHz-15GHz



15GHz-25GHz

Test Mode:	802.11b	Test channel :	11



Reference level



30MHz-3GHz



3GHz-5GHz



5GHz-10GHz



10GHz-15GHz



15GHz-25GHz

Test Mode:	802.11g	Test channel :	01



Reference level



30MHz-3GHz



3GHz-5GHz



5GHz-10GHz



10GHz-15GHz



15GHz-25GHz

Test Mode:	802.11g	Test channel :	06



Reference level



30MHz-3GHz



3GHz-5GHz



5GHz-10GHz



10GHz-15GHz



15GHz-25GHz

Test Mode:	802.11g	Test channel :	11



Reference level



30MHz-3GHz



3GHz-5GHz



5GHz-10GHz



10GHz-15GHz



15GHz-25GHz

Test Mode:	802.11n(HT20)	Test channel :	01



Reference level



30MHz-3GHz



3GHz-5GHz



5GHz-10GHz



10GHz-15GHz



15GHz-25GHz

Test Mode:	802.11n(HT20)	Test channel :	06



Reference level



30MHz-3GHz



3GHz-5GHz



5GHz-10GHz



10GHz-15GHz



15GHz-25GHz

Test Mode:	802.11n(HT20)	Test channel :	11



Reference level



30MHz-3GHz



3GHz-5GHz



5GHz-10GHz



10GHz-15GHz



15GHz-25GHz

2.10. Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203:
An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited

FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1) (I):
(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

Test Result:
The maximum gain of WIFI antenna was 2.0dBi.
Antenna Style: PCB Antenna, Antenna port: welding



3. EUT TEST PHOTO

Radiated Emission (30MHz-1GHz)



Radiated Emission (1GHz-25GHz)



Conducted Emission

4. PHOTOGRAPHS OF EUT CONSTRUCTIONAL

External Photos of EUT




cm 1 2 3 4 5 6 7 8
32 INCH 1 2 3

HDMI
MICRO SD
cm 1 2 3 4 5 6
32 INCH 1 2

OK
cm 1 2 3 4 5 6 7
32 INCH 1 2

cm 1 2 3 4 5 6

Internal Photos of EUT

RECHARGEABLE LI-ION BATTERY.
Made in China




WF03-L
cm 1 2 3 4 5


cm 1 2 3 4 5
32 INCH 1


cm 1 2 3 4
32 INCH 1











**********THE END**********