



FCC RF EXPOSURE REPORT

Applicant : Pablo Inc.

Address : 888 Marin Street, San Francisco, California, United States, 94124

Equipment : Bluetooth Speaker

Model No. : UMA

Trade Name : **Pablo®**

FCC ID. : 2AGV2UMAV2

I HEREBY CERTIFY THAT :

The sample was received on Jan. 11, 2022 and the testing was completed on Jan. 21, 2022 at CerpPASS Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of CerpPASS Technology Corp., the test report shall not be reproduced except in full.

Approved by:

Leevin Li / Supervisor



Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation)
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm ²) ☒ General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Evaluation applied	☒ MPE Evaluation* ☐ SAR Evaluation ☐ N/A

TEST RESULTS

No non-compliance noted.

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{3770}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

**Maximum Permissible Exposure**

Test Mode	Frequency band (MHz)	Measured power(dBm)	Max.Tuneup Power(dBm)	Peak output power(mW)	Antenna gain (Numeric)	Distance (cm)	Power density (mW/cm ²)	Limit (mW/cm ²)
Bluetooth EDR	2402-2480	5.82	6.82	4.808	1.00	20	0.00095687	1
BLE	2402-2480	3.51	4.51	2.825	1.00	20	0.000562151	1

Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

----- End of the report -----