



**BUREAU
VERITAS**

Test Report No.: FS170316N005

RF EXPOSURE REPORT

Applicant	SHANTOU QSTTOYS CO.,LTD
Address	Tongyi Rd, Chenghai District, Shantou, Guangdong, China

Manufacturer or Supplier	SHANTOU QSTTOYS CO.,LTD
Address	Tongyi Rd, Chenghai District, Shantou, Guangdong, China
Product	FOLDING WIFI DRONE SERIES
Brand Name	N/A
Model	DRW477B
Additional Model & Model Difference	QST1810, QST1811, QST1812, QST1813, QST1814, QST1815, QST1816, QST1817, QST1819, QST511, QST512, QST513, QST514, QST516, QST517, QST518, QST519, QST801, QST802, QST803, QST804, QST805, QST806, QST807, QST808, QST809
Date of tests	Mar. 27, 2017 ~ Apr. 11, 2017

☒ **FCC Part 2 (Section 2.1091)**

☒ **KDB 447498 D01**

☒ **IEEE C95.1**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Glyn He
Supervisor / EMC Department

Approved by Chris Chen
Manager / EMC Department

Date: Apr. 18, 2017

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



Table of Contents

RELEASE CONTROL RECORD	3
1. CERTIFICATION.....	4
2. RF EXPOSURE LIMIT	5
3. MPE CALCULATION FORMULA.....	5
4. CLASSIFICATION	5
5. ANTENNA GAIN	6
6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	6



Test Report No.: FS170316N005

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FS170316N005	Original release	Apr. 18, 2017

Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



Test Report No.: FS170316N005

1. CERTIFICATION

FCC ID:	2AGYKQST1811DR477B
PRODUCT:	FOLDING WIFI DRONE SERIES
BRAND NAME:	N/A
MODEL NO.:	DRW477B
ADDITIONAL NO.:	QST1810, QST1811, QST1812, QST1813, QST1814, QST1815, QST1816, QST1817, QST1819, QST511, QST512, QST513, QST514, QST516, QST517, QST518, QST519, QST801, QST802, QST803, QST804, QST805, QST806, QST807, QST808, QST809
TEST SAMPLE:	Engineering Sample
APPLICANT:	SHANTOU QSTTOYS CO.,LTD
STANDARDS:	FCC Part 2 (Section 2.1091)
	KDB 447498 D01
	IEEE C95.1



2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

3. MPE CALCULATION FORMULA

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Peak Gain (dBi)	Antenna Type
Chain 0	1	Wire Antenna

6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

The tuned conducted Average Power (declared by client)

Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
2412-2462	17	+3	14	20

The measured conducted Average Power

Mode	Frequency (MHz)	Averaged Power (dBm)
802.11b	2462	18.62
802.11g	2412	17.38
802.11n(20MHz)	2412	16.86
802.11n(40MHz)	2422	17.28

FREQUENCY BAND (MHz)	MAX AVERAGE POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2412-2462	20	1	20	0.02505	1.0

--- END ---