

TESTING CERTIFICATE



CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9871
Fax: +82-31-624-9501

Certificate No.:
CTK-2015-01649
Page (1) / (26) Pages

1. Client

- Name : INNOSYS CO., LTD
- Address : 218, Song building, Aejiwon, 1731, Deogyong-daero, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea
- Date of Receipt : 2015-12-07

2. Manufacturer

- Name : INNOSYS CO., LTD
- Address : 218, Song building, Aejiwon, 1731, Deogyong-daero, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea

3. Use of Report : For FCC certification

4. Test Sample / Model: Bluetooth CCT Controller / CCT-202B, DIM-201B and CCT-202A


5. Date of Test : 2015-12-07

6. Test Standard(method) used : FCC Part 15 Subpart B

7. Testing Environment: refer to 12 pages

8. Test Results : refer to 13 pages

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This Test Report cannot be reproduced, except in full.

Affirmation	Tested by	Approved by
	 Park Sangkyun: (Signature) EMC Test Engineer	 Lee Eunwon: (Signature) Technical Manager

2015-12-21

Republic of KOREA **CTK Co., Ltd.**



CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9871
Fax: +82-31-624-9501

Certificate No.:
CTK-2015-01649
Page (2) / (26) Pages

REPORT REVISION HISTORY

Date	Revision	Page No
2015-12-21	Issued (CTK-2015-01649)	All

This report shall not be reproduced except in full, without the written approval of CTK Co., Ltd. This document may be altered or revised by CTK Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by CTK Co., Ltd. will constitute fraud and shall nullify the document.

TABLE OF CONTENTS

REPORT REVISION HISTORY	2
1.0 General Product Description	4
1.1 Model Differences	4
1.2 Device Modifications	4
1.3 EUT Configuration(s)	5
1.4 Test Software	5
1.5 EUT Operating Mode(s)	5
1.6 Configuration	6
1.7 Calibration Details of Equipment Used for Measurement	7
1.8 Test Facility	7
1.9 Measurement Procedure	7
1.10 Laboratory Accreditations and Listings	8
1.11 Measurement Uncertainty	8
2.0 EMC Test Regulations/Standards	9
3.0 Results of Individual Test	10
3.1 Conducted Voltage Emissions of Mains ports	10
3.2 Radiated Electric Field Emissions (Below 1 GHz)	12
3.3 Radiated Electric Field Emissions (Above 1 GHz)	17
APPENDIX A - Test Setup Photos and Configuration	18
Conducted Voltage Emissions of Mains Ports	19
Radiated Electric Field Emissions (Below 1 GHz)	20
Radiated Electric Field Emissions (Above 1 GHz)	21
APPENDIX B – EUT Photographs	22
EUT External Photographs	23
EUT Internal Photographs	25
PCB	26

 CTK Co., Ltd. The Prime Leader of Global Regulatory Certification	CTK Co., Ltd. (Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9871 Fax: +82-31-624-9501	Certificate No.: CTK-2015-01649 Page (4) / (26) Pages	
---	---	---	--

1.0 General Product Description

No.	ITEM	APPLICATION	
1	Test Sample		Bluetooth CCT Controller
2	Model		CCT-202B
3	Variant Model		DIM-201B and CCT-202A
4	Dimensions (W x L x H)		25 mm × 67 mm × 15 mm
5	Mobility	☒ Table-top	☐ Floor-standing ☐ Built-in ☐ Portable
6	Maximum Clock Frequency		32 MHz
7	Electrical Ratings	Input:	DC 12 V
		Output:	-
8	Test Voltage / Frequency	Voltage:	DC 12 V
		Frequency:	-

1.1 Model Differences

These models are identical except for as below;

- CCT-202B is Basic model.
- DIM-201B and CCT-202A are identical with CCT-202B except for model designations at requests of a buyer.

1.2 Device Modifications

The following modifications were necessary for compliance:

Not applicable

 CTK Co., Ltd. The Prime Leader of Global Regulatory Certification	CTK Co., Ltd. (Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9871 Fax: +82-31-624-9501	Certificate No.: CTK-2015-01649 Page (5) / (26) Pages	
---	---	---	--

1.3 EUT Configuration(s)

See Appendix A for individual test set-up configuration(s). The following peripheral devices and/or interface cables were connected during the measurement:

☒ Peripheral Devices

Device	Model No.	Serial No.	Manufacturer
LED	-	-	-
DC POWER SUPPLY	E3632A	MY40000004	Agilent

☒ Cable Description

No.	From		To		Type of Cable		
	Device	I/O Port	Device	I/O Port	Length (m)	Shielded or Unshielded	Ferrite Core [Y/N]
1	EUT	DC IN	DC POWER SUPPLY	DC OUT	1.0	U	N
2		Control/DC	LED	Control/DC IN	1.0	U	N
3	DC POWER SUPPLY	AC IN	AC MIANS	-	1.0	U	N

* Shielded or Unshielded : Unshielded=U, Shielded=S

1.4 Test Software

- ☐ EMC Test V 1.0
☐ Display Test Patterns – V1.5
☐ Ping.exe
☒ Not applicable


1.5 EUT Operating Mode(s)

Equipment under test was operated during the measurement under the following conditions:

☒ Maximum, Minimum light output mode (Dimming)

* This EUT is tested with length of cable, configuration and specification that the manufacturer request.

1.6 Configuration



 CTK Co., Ltd. The Prime Leader of Global Regulatory Certification	CTK Co., Ltd. (Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9871 Fax: +82-31-624-9501	Certificate No.: CTK-2015-01649 Page (7) / (26) Pages	
--	---	---	--

1.7 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less. All test equipment calibrations are traceable to the Korea Research Institute of Standards and Science (KRISS), therefore, all test data recorded in this report is traceable to KRISS.

1.8 Test Facility

The measurement facility is located at (Ho-dong) 113, Yejik-ro, Cheoin-gu, Yong-in-si, Gyeonggi-do, Korea. The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

1.9 Measurement Procedure

Preliminary AC power line conducted emissions tests were performed shielded room. To find worst mode, several typical mode and typical cable position were tested. Final AC power line conducted emissions test was performed shielded room. (location is same as Preliminary test)
Based on the preliminary tests of the EUT, final test was proceeded worst case test mode and cable configuration.

Preliminary radiated emissions test were performed Semi-Anechoic Chamber or anechoic chamber (Distance of antenna and EUT was 3 m). To find worst mode, several typical mode and typical cable position were tested and peak level and frequency were recorded.

Final radiated emissions test was performed Semi-Anechoic Chamber.
Based on the preliminary tests of the EUT, final test was proceeded worst case test mode and cable configuration.

* Measurement procedures was In accordance with ANSI C63.4-2009 7.3.3, 7.3.4, 8.3.1.1, 8.3.1.2, 8.3.2.1, 8.3.2.2

 CTK Co., Ltd. The Prime Leader of Global Regulatory Certification	CTK Co., Ltd. (Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9871 Fax: +82-31-624-9501	Certificate No.: CTK-2015-01649 Page (8) / (26) Pages	
---	---	---	--

1.10 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Registration Number	Logo
USA	FCC	FCC Part 15 & 18 EMI (Electromagnetic Interference / Emission)	805871	
JAPAN	VCCI	VCCI V-3 EMI (Electromagnetic Interference / Emission)	C-986 T-1843 R-3627 G-387	
KOREA	MSIP	EMI (Electromagnetic Interference / Emission) EMS (Electromagnetic Susceptibility / Immunity)	KR0025	

1.11 Measurement Uncertainty

Compliance of the product is based on the measured value.

However, the measurement uncertainty is included for information purposes.

The measurement uncertainties given below are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

Measurement Type	Frequency Range	Expanded Uncertainty
Conducted Emission	9 kHz to 150 kHz	2.78 dB (C.L.: Approx. 95 %, $k=2$)
Conducted Emission	150 kHz to 30 MHz	2.70 dB (C.L.: Approx. 95 %, $k=2$)
Disturbance Power	30 MHz to 300 MHz	3.74 dB (C.L.: Approx. 95 %, $k=2$)
Radiated Emission	30 MHz to 1000 MHz	3.66 dB (C.L.: Approx. 95 %, $k=2$)
Radiated Emission	1 GHz Above	4.16 dB (C.L.: Approx. 95 %, $k=2$)

 CTK Co., Ltd. The Prime Leader of Global Regulatory Certification	CTK Co., Ltd. (Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9871 Fax: +82-31-624-9501	Certificate No.: CTK-2015-01649 Page (9) / (26) Pages	
---	---	---	--

2.0 EMC Test Regulations/Standards

The tests were performed according to following regulations:

Applied standard	Title	Applied	Test Result
FCC Part 15 Subpart B ☐ Class A ☒ Class B	Conducted Voltage Emissions	☐	☐ MET ☐ NOT MET
	Radiated Electric Field Emissions	☒	☒ MET ☐ NOT MET

3.0 Results of Individual Test

3.1 Conducted Voltage Emissions of Mains ports

Test Date

Not applicable

Test Location

Shielded Room

Test Equipment

Name of Equipment	Model No.	Manufacturer	Serial No.	Due Date	Applied
EMI Test Receiver	ESCI3	Rohde & Schwarz	100032	2016-02-02	☐
LISN	ENV216	Rohde & Schwarz	101235	2016-05-14	☐
LISN	ENV216	Rohde & Schwarz	101236	2016-05-14	☐
EMI Test Receiver	ESR7	Rohde & Schwarz	101088	2016-06-12	☐
LISN	ENV216	Rohde & Schwarz	101151	2016-11-02	☐
LISN	ESH3-Z5	Rohde & Schwarz	100207	2016-11-02	☐
EMI Test Receiver	ESCI7	Rohde & Schwarz	100816	2016-11-02	☐
LISN	ENV216	Rohde & Schwarz	101760	2016-02-02	☐
LISN	NNLK 8121	SCHWARZBECK	8121-644	2016-05-15	☐
Pulse Limiter	VTSD 9561-F	SCHWARZBECK	9561-F064	2016-05-15	☐
LISN	ENV216	Rohde & Schwarz	101150	2016-02-02	☐

Test Software

ESCI7, ESCI3 : EMC32 Ver. 8.50.0

ESR7 : EMC32 Ver. 8.53.0

Frequency Range of Measurement

150 kHz to 30 MHz

Instrument Setting

IF Band Width: 9 kHz

Climate Condition

Temperature:

Relative Humidity:

Atmospheric Pressure:

 CTK Co., Ltd. The Prime Leader of Global Regulatory Certification	CTK Co., Ltd. (Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9871 Fax: +82-31-624-9501	Certificate No.: CTK-2015-01649 Page (11) / (26) Pages	
---	---	--	--

Test Result

The requirements are: ☐ MET ☐ NOT MET

Frequency (MHz)	Measured Data (dBμV)	Margin (dB)	Remark

The Result is calculated by using the following formula;

- * Result = Limit – Margin (Result included the correction factor)
- * Correction factor = Cable Loss + Insertion loss of LISN

Test Data



CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9871
Fax: +82-31-624-9501

Certificate No.:
CTK-2015-01649
Page (12) / (26) Pages

3.2 Radiated Electric Field Emissions (Below 1 GHz)

Test Date

2015-12-07

Test Location

10 m SAC (test distance : ☐ 10 m, ☒ 3 m)

Test Equipment

Name of Equipment	Model No.	Manufacturer	Serial No.	Due Date	Applied
EMI Test Receiver	ESCI7	Rohde & Schwarz	100814	2016-11-02	☒
Bilog Antenna	CBL6111C	Schaffner	2551	2017-04-24	☒
6dB Attenuator	DNF	Rohde & Schwarz	272.4110.50-2	2016-11-03	☒
Amplifier	310	Sonoma Instrument Co.	291721	2016-02-02	☒

Test Software

TOYO EMI software Ver. 5.1.0

Frequency Range of Measurement

30 MHz to 1 GHz

Instrument Setting

IF Band Width: 120 kHz

Climate Condition

Temperature: (23 ± 1) °C

Relative Humidity: (45 ± 1) %

Atmospheric Pressure: 100 kPa

Test Result

The requirements are: ☒ MET ☐ NOT MET

[Maximum]

Frequency (MHz)	Measured Data (dBμV/m)	Margin (dB)	Remark
38.730	28.2	11.8	Quasi-peak

[Half]

Frequency (MHz)	Measured Data (dBμV/m)	Margin (dB)	Remark
38.124	24.5	15.5	Quasi-peak

[Minimum]

Frequency (MHz)	Measured Data (dBμV/m)	Margin (dB)	Remark
49.885	25.9	14.1	Quasi-peak


The Result is calculated by using the following formula;

* Result = Reading + Correction factor

* Correction factor = Antenna Factor + Cable Loss + 6 dB attenuator – Amp Gain

Test Data


[Maximum]



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]
1	37.275	V	41.3	-13.2	28.1	40.0	11.9	100.0	51.0
2	38.730	V	41.0	-12.8	28.2	40.0	11.8	100.0	237.0
3	49.643	V	34.1	-12.7	21.4	40.0	18.6	400.0	123.0
4	55.220	H	38.8	-13.1	25.7	40.0	14.3	100.0	122.0
5	55.584	V	38.2	-13.1	25.1	40.0	14.9	293.0	349.0
6	167.983	V	34.3	-10.5	23.8	43.5	19.7	100.0	200.0


[Half]



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]
1	38.124	V	37.4	-12.9	24.5	40.0	15.5	100.0	349.0
2	49.643	V	34.1	-12.7	21.4	40.0	18.6	293.0	0.0
3	55.341	H	34.7	-13.1	21.6	40.0	18.4	100.0	0.0
4	55.705	V	34.2	-13.1	21.1	40.0	18.9	293.0	51.0
5	107.964	V	36.4	-13.5	22.9	43.5	20.6	100.0	51.0
6	167.983	V	33.9	-10.5	23.4	43.5	20.1	100.0	51.0

[Minimum]



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]
1	38.245	V	38.6	-12.9	25.7	40.0	14.3	100.0	51.0
2	49.885	V	38.6	-12.7	25.9	40.0	14.1	400.0	122.0
3	55.341	H	38.8	-13.1	25.7	40.0	14.3	100.0	308.0
4	55.584	V	37.7	-13.1	24.6	40.0	15.4	293.0	126.0
5	57.645	V	36.8	-13.3	23.5	40.0	16.5	293.0	51.0
6	167.983	V	34.3	-10.5	23.8	43.5	19.7	100.0	200.0

 CTK Co., Ltd. The Prime Leader of Global Regulatory Certification	CTK Co., Ltd. (Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9871 Fax: +82-31-624-9501	Certificate No.: CTK-2015-01649 Page (17) / (26) Pages	
---	---	--	--

3.3 Radiated Electric Field Emissions (Above 1 GHz)

Test Date

Not applicable

Test Location

3 m SAC

Test Equipment

Name of Equipment	Model No.	Manufacturer	Serial No.	Due Date	Applied
EMI Test Receiver	ESCI7	Rohde & Schwarz	100816	2016-11-02	☐
Double Ridged Guide Antenna	3117	ETS-Lindgren	00154525	2017-09-02	☐
Preamplifier	8449B	Agilent Technologies	3008A02307	2016-10-01	☐

Test Software

TOYO EMI software Ver. 5.1.0

Frequency Range of Measurement

1 GHz to 6 GHz

Instrument Setting

IF Band Width: 1 MHz

Climate Condition

Temperature:

Relative Humidity:

Atmospheric Pressure:

Test Result

The requirements are: ☐ MET ☐ NOT MET

Frequency (MHz)	Measured Data (dBμV/m)	Margin (dB)	Remark

The Result is calculated by using the following formula;

* Result = Reading + Correction factor

* Correction factor = Antenna Factor + Cable Loss- Amp Gain

Test Data

 CTK Co., Ltd. The Prime Leader of Global Regulatory Certification	CTK Co., Ltd. (Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9871 Fax: +82-31-624-9501	Certificate No.: CTK-2015-01649 Page (18) / (26) Pages	
---	---	--	--



APPENDIX A - Test Setup Photos and Configuration

 CTK Co., Ltd. The Prime Leader of Global Regulatory Certification	CTK Co., Ltd. (Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9871 Fax: +82-31-624-9501	Certificate No.: CTK-2015-01649 Page (19) / (26) Pages	
---	--	---	--

Conducted Voltage Emissions of Mains Ports

Not Applicable

Radiated Electric Field Emissions (Below 1 GHz)



 CTK Co., Ltd. The Prime Leader of Global Regulatory Certification	CTK Co., Ltd. (Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9871 Fax: +82-31-624-9501	Certificate No.: CTK-2015-01649 Page (21) / (26) Pages	
--	---	--	--

Radiated Electric Field Emissions (Above 1 GHz)

Not Applicable

 CTK Co., Ltd. The Prime Leader of Global Regulatory Certification	CTK Co., Ltd. (Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9871 Fax: +82-31-624-9501	Certificate No.: CTK-2015-01649 Page (22) / (26) Pages	
---	---	--	--

APPENDIX B – EUT Photographs

EUT External Photographs





CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9871
Fax: +82-31-624-9501

Certificate No.:
CTK-2015-01649
Page (24) / (26) Pages





Certificate No.:
CTK-2015-01649
Page (26) / (26) Pages

