

1. Effective (Isotropic) Radiated Power Output Data

1.1 Test Result

1.1.1 GSM850_ERP

Band: GSM850								
ENV	Mode		Frequency (MHz)	Conducted Power (dBm)	Gain (dBi)	ERP (dBm)		Verdict
	Network	Subset				Result	Limit	
NTNV	GSM	GSM	824.2	32.39	-4.1	26.14	<=38.45	Pass
			836.6	32.56	-4.1	26.31	<=38.45	Pass
			848.8	32.99	-4.1	26.74	<=38.45	Pass
	EGPRS	1 TX Slot	824.2	25.44	-4.1	19.19	<=38.45	Pass
		2 TX Slots	824.2	22.35	-4.1	16.10	<=38.45	Pass
		3 TX Slots	824.2	20.36	-4.1	14.11	<=38.45	Pass
		4 TX Slots	824.2	18.72	-4.1	12.47	<=38.45	Pass
		1 TX Slot	836.6	27.97	-4.1	21.72	<=38.45	Pass
		2 TX Slots	836.6	21.92	-4.1	15.67	<=38.45	Pass
		3 TX Slots	836.6	20.01	-4.1	13.76	<=38.45	Pass
		4 TX Slots	836.6	18.31	-4.1	12.06	<=38.45	Pass
		1 TX Slot	848.8	25.37	-4.1	19.12	<=38.45	Pass
		2 TX Slots	848.8	22.24	-4.1	15.99	<=38.45	Pass
		3 TX Slots	848.8	22.87	-4.1	16.62	<=38.45	Pass
		4 TX Slots	848.8	18.46	-4.1	12.21	<=38.45	Pass
Note1: ERP=Conducted Power+Antenna Gain-2.15								

- End of the Report -