

1. Effective (Isotropic) Radiated Power Output Data

1.1 Test Result

1.1.1 PCS1900_EIRP

Band: PCS1900								
ENV	Mode		Frequency (MHz)	Conducted Power (dBm)	Gain (dBi)	EIRP (dBm)		Verdict
	Network	Subset				Result	Limit	
NTNV	GSM	GSM	1850.2	28.82	2.67	31.49	<=33.00	Pass
			1880	29.22	2.67	31.89	<=33.00	Pass
			1909.8	29.27	2.67	31.94	<=33.00	Pass
	EGPRS	1 TX Slot	1850.2	23.68	2.67	26.35	<=33.00	Pass
		2 TX Slots	1850.2	20.98	2.67	23.65	<=33.00	Pass
		3 TX Slots	1850.2	18.98	2.67	21.65	<=33.00	Pass
		4 TX Slots	1850.2	17.58	2.67	20.25	<=33.00	Pass
		1 TX Slot	1880	25.62	2.67	28.29	<=33.00	Pass
		2 TX Slots	1880	21.40	2.67	24.07	<=33.00	Pass
		3 TX Slots	1880	19.46	2.67	22.13	<=33.00	Pass
		4 TX Slots	1880	18.48	2.67	21.15	<=33.00	Pass
		1 TX Slot	1909.8	23.50	2.67	26.17	<=33.00	Pass
		2 TX Slots	1909.8	21.03	2.67	23.70	<=33.00	Pass
		3 TX Slots	1909.8	19.04	2.67	21.71	<=33.00	Pass
		4 TX Slots	1909.8	17.85	2.67	20.52	<=33.00	Pass
Note1: EIRP=Conducted Power+Antenna Gain								

- End of the Report -