

1. Effective (Isotropic) Radiated Power Output Data

1.1 Test Result

1.1.1 PCS1900_EIRP

Band: PCS1900								
ENV	Mode		Frequency (MHz)	Conducted Power (dBm)	Gain (dBi)	EIRP (dBm)		Verdict
	Network	Subset				Result	Limit	
NTNV	GSM	GSM	1850.2	28.40	1.2	29.60	<=33.00	Pass
			1880	29.02	1.2	30.22	<=33.00	Pass
			1909.8	29.22	1.2	30.42	<=33.00	Pass
	EGPRS	1 TX Slot	1850.2	23.52	1.2	24.72	<=33.00	Pass
		2 TX Slots	1850.2	20.61	1.2	21.81	<=33.00	Pass
		3 TX Slots	1850.2	18.68	1.2	19.88	<=33.00	Pass
		4 TX Slots	1850.2	17.40	1.2	18.60	<=33.00	Pass
		1 TX Slot	1880	25.28	1.2	26.48	<=33.00	Pass
		2 TX Slots	1880	21.03	1.2	22.23	<=33.00	Pass
		3 TX Slots	1880	19.20	1.2	20.40	<=33.00	Pass
		4 TX Slots	1880	18.33	1.2	19.53	<=33.00	Pass
		1 TX Slot	1909.8	23.33	1.2	24.53	<=33.00	Pass
		2 TX Slots	1909.8	20.60	1.2	21.80	<=33.00	Pass
		3 TX Slots	1909.8	18.60	1.2	19.80	<=33.00	Pass
		4 TX Slots	1909.8	17.53	1.2	18.73	<=33.00	Pass
Note1: EIRP=Conducted Power+Antenna Gain								

- End of the Report -