

TEST REPORT

Application No.: SUCR2603000174TL
Applicant: Shanghai Sunmi Technology Co.,Ltd.
Address of Applicant: Room 505,No.388,Song Hu Road,Yang Pu District,Shanghai,China
Manufacturer: Shanghai Sunmi Technology Co.,Ltd.
Address of Manufacturer: Room 505,No.388,Song Hu Road,Yang Pu District,Shanghai,China
Equipment Under Test (EUT):
EUT Name: Wireless Data Terminal
Model No.: TFB1A
Trade Mark: SUNMI
FCC ID: 2AH25M3WH
Standard(s) : 47 CFR Part 15, Subpart C 15.225
Date of Receipt: 2026-03-04
Date of Test: 2026-05-12
Date of Issue: 2026-05-19

Test Result:
Pass*

* In the configuration tested, the EUT complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone:(86-755) 8307 1443, or email: CN.Doccheck@sgs.com



Revision Record			
Version	Description	Date	Remark
00	Original	2026-05-19	/

Authorized for issue by:			
Tested By			
		Hayley Zhang/Project Engineer	
Approved By			
		Cedar Cheng /Reviewer	



2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.225	N/A	47 CFR Part 15, Subpart C 15.203	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Emission Mask	47 CFR Part 15, Subpart C 15.225	ANSI C63.10-2020/Cor1-2023 Section 6.4	47 CFR Part 15, Subpart C 15.225(a)&(b)&(C)	Pass
Radiated Emissions (9kHz-30MHz)		ANSI C63.10-2020/Cor1-2023 Section 6.4	47 CFR Part 15, Subpart C 15.225(d) & 15.209	Pass
Radiated Emissions (30MHz-1GHz)		ANSI C63.10-2020/Cor1-2023 Section 6.5	47 CFR Part 15, Subpart C 15.225(d) & 15.209	Pass

Remark :

This test report (Report No.: SUCR260300017405 issue on 2026-05-19) is based on the original test report (Report No.: SUCR250500042208 issue on 2025-06-11).

Review this report and original report, this report just changing the parts according to the declaration letter from client.

Therefore in this report only Emission Mask and Radiated Spurious Emissions is performed, and other test data in this report are refer to the previous report with report number SUCR250500042208 issue on 2025-06-11.

3 Contents

	Page
1 COVER PAGE	1
2 Test Summary	3
3 Contents.....	4
4 General Information.....	5
4.1 Details of E.U.T.	5
4.2 Environment Parameter	5
4.3 Description of Support Units	5
4.4 Measurement Uncertainty & Decision Rule	5
4.5 Test Location	6
4.6 Test Facility	6
4.7 Deviation from Standards.....	6
4.8 Abnormalities from Standard Conditions.....	6
5 Equipment List	7
6 Radio Spectrum Technical Requirement.....	8
6.1 Antenna Requirement	8
7 Radio Spectrum Matter Test Results	9
7.1 Emission Mask	9
7.2 Radiated Emissions (9kHz-30MHz)	13
7.3 Radiated Emissions (30MHz-1GHz)	17
8 Test Setup Photo	21
9 EUT Constructional Details (EUT Photos).....	21

4 General Information

4.1 Details of E.U.T.

Power supply:	3.87V from battery
Operation Frequency:	13.56MHz
Modulation Type:	ASK
Antenna Type:	FPC Antenna

4.2 Environment Parameter

Environment Parameter	Selected Values During Tests	
Relative Humidity	42%	
Value	Temperature(°C)	Voltage(V)
NTNV	21	3.87
Note: NV:Normal Voltage LV:Low Extreme Test Voltage HV:High Extreme Test Voltage NT:Normal Temperature LT:Low Extreme Test Temperature HT:High Extreme Test Temperature		

4.3 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
--	--	--	--
The EUT has been tested as an independent unit.			

4.4 Measurement Uncertainty & Decision Rule

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 7.25 \times 10^{-8}$
2	Duty cycle	$\pm 0.37\%$
3	Occupied Bandwidth	$\pm 3\%$
4	Conduction emission	$\pm 3.0\text{dB}$ (150kHz to 30MHz)
5	RF conducted power	$\pm 0.75\text{dB}$
6	RF power density	$\pm 2.84\text{dB}$
7	Conducted Spurious emissions	$\pm 0.75\text{dB}$
8	RF Radiated power	$\pm 1.56\text{dB}$ (9KHz-30MHz)
		$\pm 4.80\text{dB}$ (30MHz-1GHz)
		$\pm 4.80\text{dB}$ (1GHz-18GHz)
		$\pm 4.80\text{dB}$ (18GHz-40GHz)
9	Temperature test	$\pm 1^\circ\text{C}$
10	Humidity test	$\pm 3\%$
11	Supply voltages	$\pm 1\%$
12	Time	$\pm 3\%$

Remark:

The U_{lab} (lab Uncertainty) is less than $U_{\text{CISPR/ETSI}}$ (CISPR/ETSI Uncertainty), so the test results
 – compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
 – non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu)
Pilot Free Trade Zone

No tests were sub-contracted.

Note:

1.SGS is not responsible for wrong test results due to incorrect information (e.g., max. internal working frequency, antenna gain, cable loss, etc) is provided by the applicant. (If applicable).

2.SGS is not responsible for the authenticity, integrity and the validity of the conclusion based on results of the data provided by applicant. (If applicable).

3. Sample source: sent by customer.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **A2LA (Certificate No. 6336.01)**

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.is accredited by the American Association for Laboratory Accreditation (A2LA).

• **FCC (Designation Number: CN1312)**

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd. has been recognized as an accredited testing laboratory. Test Firm Registration Number:717327

• **ISED (CAB Identifier: CN0120)**

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd. has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory.

Company Number: 27594

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Conditions

None

5 Equipment List

Item	Equipment	Manufacturer	Model	Inventory No	Cal Date	Cal. Due Date
RF Radiated Test						
1	Semi-Anechoic Chamber	Brilliant-emc	N/A	SUWI-04-02-01	2023/6/3	2026/6/2
2	Signal Analyzer	ROHDE&SCHWARZ	FSW43	SUWI-01-02-04	2026/1/14	2027/1/13
3	Signal Analyzer	KEYSIGHT	N9020A	SUWI-01-02-07	2025/11/20	2026/11/19
4	Test receiver	ROHDE&SCHWARZ	ESR7	SUWI-01-10-01	2026/1/14	2027/1/13
5	Signal Generator	ROHDE&SCHWARZ	SMW100A	SUWI-01-18-01	2026/1/14	2027/1/13
6	Receiving antenna	SCHWRZBECK MESS-ELEKTRONIK	VULB 9168	SUWI-01-11-04	2025/11/29	2027/11/28
7	Receiving antenna	SCHWRZBECK MESS-ELEKTRONIK	BBHA 9120D	SUWI-01-11-02	2025/5/7	2027/5/6
8	Receiving antenna	SCHWRZBECK MESS-ELEKTRONIK	BBHA 9170	SUWI-01-11-03	2025/5/7	2027/5/6
9	Active Loop Antenna	SCHWRZBECK MESS-ELEKTRONIK	FMZB 1519B	SUWI-01-21-01	2025/5/7	2027/5/6
10	Amplifier	Tonscend	TAP9K3G40	SUWI-01-14-01	2026/1/14	2027/1/13
11	Amplifier	Tonscend	TAP01018050	SUWI-01-14-02	2026/1/14	2027/1/13
12	Amplifier	Tonscend	TAP18040048	SUWI-01-14-03	2026/1/14	2027/1/13
13	Wideband Radio Communication Tester	Anritsu	MT8820C	SUWI-01-26-01	2025/8/25	2026/8/24
14	Wideband Radio Communication Tester	Anritsu	MT8821C	SUWI-01-26-03	2025/8/25	2026/8/24
15	Wideband Radio Communication Tester	ROHDE&SCHWARZ	CMW500	SUWI-01-16-09	2025/8/26	2026/8/25
16	Radio Communication Analyzer	StarPoint	SP9500E	SUWI-01-28-06	2025/11/21	2026/11/20
17	Signal Generator	ROHDE&SCHWARZ	SMB100A	SUWI-01-08-01	2026/1/14	2027/1/13
18	DC Power Supply	HYELEC	HY3005B	SUWI-01-18-01	2026/1/14	2027/1/13
19	Temperature and humidity meter	MingGao	TH101B	SUWI-01-01-05	2026/2/11	2027/2/10
20	Measurement Software	Tonscend	JS32-RE 4.0.0.0	SUWI-02-09-06	NCR	NCR
21	RF Control unit	Tonscend	JS0806-1	SUWI-02-20-01	NCR	NCR
22	RFCables	Tonscend	NA	SUWI-01-03-02	1/15/2026	1/14/2027

Remark: NCR=No Calibration Requirement.



6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203

6.1.2 Conclusion

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is FPC Antenna and no consideration of replacement.

Antenna location: Refer to Internal photos



7 Radio Spectrum Matter Test Results

7.1 Emission Mask

Test Requirement 47 CFR Part 15, Subpart C 15.225(a)&(b)&(C)

Test Method: ANSI C63.10-2020/Cor1-2023 Section 6.4

Limit:

- (a) The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.
- (b) Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.
- (c) Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.
- (d) The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in § 15.209.

Below 30MHz

The limit at 3m test distance is below:

$$FS_{\text{limit}} = FS_{\text{max}} - 40 \log \left(\frac{d_{\text{limit}}}{d_{\text{measure}}} \right)$$

where

FS_{limit} is the calculation of field strength at the limit distance, expressed in dB μ V/m
 FS_{max} is the measured field strength, expressed in dB μ V/m
 d_{measure} is the distance of the measurement point from the EUT
 d_{limit} is the reference distance or the distance of the $\lambda/2\pi$ point

The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 124dB μ V/m at 3 meters.

7.1.1 E.U.T. Operation


Operating Environment:

Temperature: 21 °C Humidity: 42 % RH Atmospheric Pressure: 1001 mbar

7.1.2 Test Mode Description


Pre-scan / Final test	Mode Code	Description
Final test	12	TX mode with modulation

7.1.3 Test Setup Diagram



7.1.4 Measurement Procedure and Data

For testing performed with the loop antenna, the center of the loop was positioned 1 m above the ground and positioned with its plane vertical at the specified distance from the EUT. During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane. Only the worst position of vertical was shown in the report.




Final Data List

NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Polarity
1	13.5596	27.53	20.04	0.69	48.26	124.00	75.74	100	Coaxial

Remark:

1. The Quasi-Peak measurements were performed on the EUT.
2. Value = Reading + Antenna Factor + Factor.
3. Factor=Cable loss.



Final Data List

NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Polarity
1	13.5586	27.62	20.04	0.69	48.35	124.00	75.65	100	Coplanar

Remark:

1. The Quasi-Peak measurements were performed on the EUT.
2. Value = Reading + Antenna Factor + Factor.
3. Factor=Cable loss.

7.2 Radiated Emissions (9kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.225(d) & 15.209

Test Method: ANSI C63.10-2020/Cor1-2023 Section 6.4

Limit:

Frequency(MHz)	Field strength (microvolts/meter)	Limit (dBuV/m)	Detector	Measurement Distance (meters)
0.009-0.490	2400/F(kHz)	-	-	300
0.490-1.705	24000/F(kHz)	-	-	30
1.705-30	30	-	-	30

Note

1. The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

2. At frequencies below 1GHz, measurements may be performed at a distance different to specified in the regulations.

Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor+ Aux Factor (if applicable)

The aux factor needs to be added when measurements are performed at a distance other than the limit distance provided.

EX. Below 30MHz, Aux Factor = 40 dB/decade of distance, the aux factor is $40\log(3/300) = -80\text{dB}$ (for 3m test distance).

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 21 °C


Humidity: 42 % RH

Atmospheric Pressure: 1001 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	12	TX mode with modulation

7.2.3 Test Setup Diagram




7.2.4 Measurement Procedure and Data

- For below 30MHz, the EUT was placed on the top of a rotating table 0.8m above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3m away from the interference-receiving antenna which was mounted on the antenna tower 1m above the ground.
- For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:

- Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only below points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.




Final Data List

NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity
4	0.5679	17.69	20.01	0.44	38.14	72.52	34.38	100	138	Coaxial
5	1.0156	20.13	20.10	0.45	40.68	67.47	26.79	100	250	Coaxial
6*	13.5526	22.56	20.04	0.69	43.29	69.54	26.25	100	274	Coaxial
NO.	Frequency [MHz]	AV Reading [dBμV]	AF [dB/m]	Factor [dB]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	0.0245	4.93	19.70	0.43	25.06	119.81	94.75	100	199	Coaxial
2	0.0747	3.01	19.90	0.43	23.34	110.13	86.79	100	169	Coaxial
3	0.2097	18.28	19.92	0.43	38.63	101.17	62.54	100	298	Coaxial

Remark:

1. The Quasi-Peak measurements were performed on the EUT.
2. Value = Reading + Antenna Factor + Factor.
3. Factor=Cable loss.
- 6* is NFC signal which can be ignored.



Final Data List

NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity
4	0.5679	19.65	20.01	0.44	40.10	72.52	32.42	100	290	Coplanar
5	1.0455	14.82	20.10	0.45	35.37	67.22	31.85	100	114	Coplanar
6*	13.5526	23.59	20.04	0.69	44.32	69.54	25.22	100	290	Coplanar
NO.	Frequency [MHz]	AV Reading [dBμV]	AF [dB/m]	Factor [dB]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	0.0217	4.98	19.70	0.43	25.11	120.87	95.76	100	117	Coplanar
2	0.0946	1.59	19.92	0.43	21.94	108.08	86.14	100	158	Coplanar
3	0.2694	17.74	19.93	0.43	38.10	98.99	60.89	100	259	Coplanar

Remark:

1. The Quasi-Peak measurements were performed on the EUT.
2. Value = Reading + Antenna Factor + Factor.
3. Factor=Cable loss.
- 6* is NFC signal which can be ignored.

7.3 Radiated Emissions (30MHz-1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.225(d) & 15.209

Test Method: ANSI C63.10-2020/Cor1-2023 Section 6.5

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

Note

1. At frequencies below 1GHz, measurements may be performed at a distance different to specified in the regulations.

Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor+ Aux Factor (if applicable)

The aux factor needs to be added when measurements are performed at a distance other than the limit distance provided.

EX. Above 30MHz, Aux Factor = 20 dB/decade of distance, the aux factor is $20\log(10/3) = 10.46\text{dB}$ (for 10m test distance).

7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 21 °C


Humidity: 42 % RH

Atmospheric Pressure: 1001 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	12	TX mode with modulation

7.3.3 Test Setup Diagram




7.3.4 Measurement Procedure and Data

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8m above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3m or 10m away from the interference-receiving antenna, which was mounted on the variable-height antenna tower.
- The antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1m to 4m and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:

- The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the worst-case test curve is displayed.




Final Data List

NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity
1	46.005	41.31	20.40	-41.06	20.65	40.00	19.35	133	143	Horizontal
2	94.7475	44.19	15.97	-40.42	19.74	43.50	23.76	162	155	Horizontal
3	190.7775	48.2	16.57	-39.35	25.42	43.50	18.08	196	92	Horizontal
4	295.0525	45.48	19.30	-38.33	26.45	46.00	19.55	157	61	Horizontal
5	762.5925	36.32	25.30	-35.23	26.39	46.00	19.61	126	224	Horizontal
6	1000	36.06	28.10	-33.68	30.48	54.00	23.52	155	129	Horizontal

Remark:

1. The Quasi-Peak measurements were performed on the EUT.
2. Final Value Level = Reading + Antenna Factor + Factor.
3. Factor=Cable loss – Preamplifier Factor.



Final Data List

NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity
1	41.8825	45.41	19.06	-41.15	23.32	40.00	16.68	133	207	Vertical
2	54.735	47.45	19.95	-40.97	26.43	40.00	13.57	174	201	Vertical
3	94.7475	46.8	15.97	-40.42	22.35	43.50	21.15	156	107	Vertical
4	180.835	44.12	16.30	-39.30	21.12	43.50	22.38	189	23	Vertical
5	357.86	37.55	20.47	-37.90	20.12	46.00	25.88	142	150	Vertical
6	999.7575	35.22	28.10	-33.68	29.64	54.00	24.36	153	113	Vertical

Remark:

1. The Quasi-Peak measurements were performed on the EUT.
2. Final Value Level = Reading + Antenna Factor + Factor.
3. Factor=Cable loss – Preamplifier Factor.



Report No.: SUCR260300017405

Page: 21 of 21

8 Test Setup Photo

Refer to Appendix_Photos of Test Setup for SUCR2603000174TL

9 EUT Constructional Details (EUT Photos)

Refer to Appendix_External Photos for SUCR2603000174TL and Appendix_Internal Photos for SUCR2603000174TL

- End of the Report -