

SAR TEST REPORT

Application No.: SUCR2607000646TL
Applicant: Shanghai Sunmi Technology Co., Ltd.
Address of Applicant: Room 505, No. 388, Song Hu Road, Yang Pu District, Shanghai, China
Manufacturer: Shanghai Sunmi Technology Co., Ltd.
Address of Manufacturer: Room 505, No. 388, Song Hu Road, Yang Pu District, Shanghai, China
EUT Description: Wireless data POS System
Model No.: T5F1A
Trade Mark: SUNMI
FCC ID: 2AH25T5F1AB
Standards: FCC 47CFR §2.1093
Date of Receipt: 2026-07-14
Date of Test: 2026-07-20 to 2026-08-18
Date of Issue: 2026-10-13

Test Result :	PASS *
----------------------	---------------

* In the configuration tested, the EUT detailed in this report complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Revision Record			
Version	Description	Date	Remark
00		2026-10-13	

Authorized for issue by:		
Prepared By		
		<div>Leon Liu/ Project Engineer</div>
Approved By		
		<div>Nick Hu/ Reviewer</div>

TEST SUMMARY

Frequency Band	Maximum Reported SAR(W/kg)
	Extremity SAR
GSM850	1.20
GSM1900	2.13
WCDMA Band II	2.41
WCDMA Band IV	1.90
WCDMA Band V	1.22
LTE Band 7	2.70
LTE Band 12(17)	1.13
LTE Band 13	1.21
LTE Band 25(2)	2.20
LTE Band 26(5)	1.05
LTE Band 30	1.96
LTE Band 41(38)	2.87
LTE Band 66(4)	1.69
LTE Band 71	0.77
WiFi 2.4G	0.30
WiFi 5G	0.78
BT	<0.10
SAR Limited(W/kg)	4.0
Maximum Simultaneous Transmission SAR (W/kg)	
Scenario	Extremity SAR
Sum SAR	3.99
SPLSR	/
SPLSR Limited	0.10

Note:

According to the October 2014 TCB Workshop “RF Exposure Procedures Update (Overlapping Bands)”: SAR for LTE Bands 2/4/5/17/38 are covered by LTE Bands 25/66/26/12/41 respectively. Because the frequency ranges are similar, the maximum tune-up limits are the same, and the channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band.

Remark:

This test report (Report No.: SUCR260700064601 issue on 2026/10/14) is based on the original test report (Report No.: SUCR260700064201 issue on 2026/08/25).

Review this report and original report, this report just changing the parts according to the declaration letter from client.

Therefore in this report all items do not need to retest and all test data in this report are based on the previous report with report number SUCR260700064201 issue on 2026/08/25.

Contents

1	General Information	6
1.1	General Description of EUT	6
1.2	Test Specification.....	8
1.3	RF exposure limits	9
1.4	Test Location	10
1.5	Test Engineer.....	10
1.6	Test Facility	10
2	Laboratory Environment.....	11
3	SAR Measurements System Configuration.....	12
3.1	The SAR Measurement System.....	12
3.2	Isotropic E-field Probe EX3DV4	14
3.3	Data Acquisition Electronics (DAE)	15
3.4	SAM Twin Phantom	15
3.5	ELI Phantom	16
3.6	Device Holder for Transmitters	17
3.7	Measurement Procedure.....	18
	3.7.1 Scanning procedure.....	18
	3.7.2 Data storage	20
	3.7.3 Data Evaluation by SEMCAD	20
4	SAR measurement variability and uncertainty	22
4.1	SAR measurement variability	22
4.2	SAR measurement uncertainty	22
5	Description of Test Position.....	23
5.1	Hand-held usage of the device, not at the head or torso.....	23
6	SAR System Verification Procedure.....	24
6.1	Tissue Simulate Liquid.....	24
	6.1.1 Recipes for Tissue Simulate Liquid.....	24
	6.1.2 Measurement for Tissue Simulate Liquid.....	25
6.2	SAR System Check.....	26
	6.2.1 Justification for Extended SAR Dipole Calibrations	27
	6.2.2 Summary System Check Result(s)	28
	6.2.3 Detailed System Check Results.....	28
7	Test Configuration	29
7.1	Operation Configurations	29
	7.1.1 GSM Test Configuration	29
	7.1.2 WCDMA Test Configuration.....	29
	7.1.3 WIFI Test Configuration	36
	7.1.4 BT Test Configuration	43
	7.1.5 LTE Test Configuration	44
8	Test Result.....	47
8.1	DUT Antenna Locations (Back View)	47

8.2	Measurement of RF Conducted Power	47
8.3	Measurement of SAR Data	48
8.3.1	SAR Result of GSM850	49
8.3.2	SAR Result of GSM1900	49
8.3.3	SAR Result of WCDMA Band II	50
8.3.4	SAR Result of WCDMA Band IV	50
8.3.5	SAR Result of WCDMA Band V	50
8.3.6	SAR Result of LTE Band 7	51
8.3.7	SAR Result of LTE Band 12(17)	52
8.3.8	SAR Result of LTE Band 13	53
8.3.9	SAR Result of LTE Band 25(2)	54
8.3.10	SAR Result of LTE Band 26(5)	55
8.3.11	SAR Result of LTE Band 30	56
8.3.12	SAR Result of LTE Band 41(38)	57
8.3.13	SAR Result of LTE Band 66(4)	58
8.3.14	SAR Result of LTE Band 71	59
8.3.15	SAR Result of WiFi 2.4G	60
8.3.16	SAR Result of WiFi 5G	61
8.3.17	SAR Result of BT	62
8.4	Multiple Transmitter Evaluation	63
8.4.1	Simultaneous SAR test evaluation	63
8.4.2	Simultaneous Transmission SAR Summation Scenario	64
9	Equipment list	66
10	Calibration certificate	67
11	Photographs	67
	Appendix A: Detailed System Check Results	67
	Appendix B: Detailed Test Results	67
	Appendix C: Calibration certificate	67
	Appendix D: Photographs	67
	Appendix E: Conducted RF Output Power	67

1 General Information

1.1 General Description of EUT

Product Name:	Wireless data POS System		
Model No.:	T5F1A		
Trade Mark:	SUNMI		
Product Phase:	production unit		
Device Type:	portable device		
Exposure Category:	uncontrolled environment / general population		
IMEI:	860959080001098 860959080002690		
Antenna Type:	FPC Antenna		
Device Operating Configurations:			
Test Mode Configuration:	GSM: GMSK,8PSK; WCDMA: QPSK,16QAM LTE: QPSK,16QAM,64QAM WIFI: DSSS,OFDM; BT: GFSK, π/4DQPSK,8DPSK		
Device Class:	B		
GPRS Multi-slots Class:	33	EGPRS Multi-slots Class:	33
HSDPA UE Category:	24	HSUPA UE Category:	7
DC-HSDPA UE Category:	24		
Power Class:	4, tested with power level 5(GSM850)		
	1, tested with power level 0(GSM1900)		
	3, tested with power control “all 1”(WCDMA Band)		
	3, tested with power control “max power”(LTE Band)		
Frequency Bands:	Band	Tx(MHz)	
	GSM850	824~849	
	GSM1900	1850~1910	
	WCDMA Band II	1850~1910	
	WCDMA Band IV	1710~1755	
	WCDMA Band V	824~849	
	LTE Band 2	1850~1910	
	LTE Band 4	1710~1755	
	LTE Band 5	824~849	
	LTE Band 7	2500~2570	
	LTE Band 12	699~716	
	LTE Band 13	777~787	
	LTE Band 17	704~716	
	LTE Band 25	1850~1915	

	LTE Band 26	814~849
	LTE Band 30	2305~2315
	LTE Band 38	2570~2620
	LTE Band 41	2496~2690
	LTE Band 66	1710~1780
	LTE Band 71	663~698
	WIFI 2.4G	2412~2462
	WIFI 5G	5150~5250
		5250~5350
		5470~5725
		5725~5850
	BT	2402~2480
RF Cable:	☒ Provided by applicant ☐ Provided by the laboratory	
Battery Information:	Model:	FHPT 2ICP5/60/65
	Normal Voltage:	7.74V
	Rated capacity:	3000mAh
	Manufacturer:	Guangdong Fenghua New Energy Co., Ltd.
<p>Note:</p> <p>Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, SGS is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.</p>		

1.2 Test Specification

Identity	Document Title
FCC 47CFR §2.1093	Radiofrequency Radiation Exposure Evaluation: Portable Devices
ANSI/IEEE C95.1-1992	IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz – 300 GHz.
IEEE 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
KDB 941225 D01	3G SAR Measurement Procedures v03r01
KDB 941225 D05	SAR for LTE Devices v02r05
KDB 941225 D05A	LTE Rel.10 KDB Inquiry Sheet v01r02
KDB 248227 D01	SAR Guidance for IEEE 802.11 Wi-Fi SAR v02r02
KDB 447498 D04	Interim General RF Exposure Guidance v01
KDB 865664 D01	SAR Measurement 100 MHz to 6 GHz v01r04
KDB 865664 D02	RF Exposure Reporting v01r02
KDB 690783 D01	SAR Listings on Grants v01r03

1.3 RF exposure limits

Human Exposure	Uncontrolled Environment General Population	Controlled Environment Occupational
Spatial Peak SAR* (Brain*Trunk)	1.60 W/kg	8.00 W/kg
Spatial Average SAR** (Whole Body)	0.08 W/kg	0.40 W/kg
Spatial Peak SAR*** (Hands/Feet/Ankle/Wrist)	4.00 W/kg	20.00 W/kg

Notes:

* The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

** The Spatial Average value of the SAR averaged over the whole body.

*** The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

1.4 Test Location

All tests were performed at:

SGS Tongfang Technical Services (Suzhou) Co., Ltd.

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu)
Pilot Free Trade Zone

No tests were sub-contracted.

1.5 Test Engineer

Test Engineer: Leon Xu

1.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 6336.01)**

SGS Tongfang Technical Services (Suzhou) Co., Ltd. is accredited by the American Association for Laboratory Accreditation (A2LA).

- **FCC (Designation Number: CN1312)**

SGS Tongfang Technical Services (Suzhou) Co., Ltd. has been recognized as an accredited testing laboratory. Test Firm Registration Number: 717327

- **ISED (CAB Identifier: CN0120)**

SGS Tongfang Technical Services (Suzhou) Co., Ltd. has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory.

Company Number: 27594

2 Laboratory Environment

Temperature	Min. = 18°C, Max. = 25 °C
Relative humidity	Min. = 30%, Max. = 70%
Ground system resistance	< 0.5 Ω
Ambient noise is checked and found very low and in compliance with requirement of standards.	
Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

3 SAR Measurements System Configuration

3.1 The SAR Measurement System

This SAR Measurement System uses a Computer-controlled 3-D stepper motor system (SPEAG DASY professional system). A E-field probe is used to determine the internal electric fields. The SAR can be obtained from the equation $SAR = \sigma (|E|^2) / \rho$ where σ and ρ are the conductivity and mass density of the tissue-Simulate.


The DASY system for performing compliance tests consists of the following items:

A standard high precision 6-axis robot (Stabile RX family) with controller, teach pendant and software. An arm extension for accommodation the data acquisition electronics (DAE).

A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.

A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.

The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.



F-1. SAR Measurement System Configuration

- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows system.
- DASY software.

- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand, right-hand and Body Worn usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing to validating the proper functioning of the system.

3.2 Isotropic E-field Probe EX3DV4

	<p>Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)</p>
Calibration	ISO/IEC 17025 calibration service available.
Frequency	4 MHz - 10 GHz Linearity: ± 0.2 dB (30 MHz - 10 GHz)
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)
Dynamic Range	10 μ W/g - 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)
Dimensions	Overall length: 337 mm (Tip: 9 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 10 GHz with precision of better 30%.
Compatibility	DASY52 SAR and higher, EASY4/MRI

3.3 Data Acquisition Electronics (DAE)

Model	DAE	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4mV,400mV)	
Input Offset Voltage	< 5μV (with auto zero)	
Input Bias Current	< 50 f A	
Dimensions	60 x 60 x 68 mm	

3.4 SAM Twin Phantom

Material	Vinylester, glass fiber reinforced (VE-GF)	
Liquid Compatibility	Compatible with all SPEAG tissue simulating liquids (incl. DGBE type)	
Shell Thickness	2 ± 0.2 mm (6 ± 0.2 mm at ear point)	
Dimensions (incl. Wooden Support)	Length: 1000 mm Width: 500 mm Height: adjustable feet	
Filling Volume	approx.. 25 liters	
Wooden Support	SPEAG standard phantom table	

The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.

Twin SAM V5.0 has the same shell geometry and is manufactured from the same material as Twin SAM V4.0, but has reinforced top structure.

3.5 ELI Phantom

Material	Vinylester, glass fiber reinforced (VE-GF)	
Liquid Compatibility	Compatible with all SPEAG tissue simulating liquids (incl. DGBE type)	
Shell Thickness	2.0 ± 0.2 mm(bottom plate)	
Dimensions	Major axis: 600 mm Minor axis: 400 mm	
Filling Volume	approx.. 30 liters	
Wooden Support	SPEAG standard phantom table	
<p>Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 4 MHz to 10 GHz. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.</p> <p>ELI V5.0 has the same shell geometry and is manufactured from the same material as ELI4 but has reinforced top structure.</p>		

3.6 Device Holder for Transmitters



F-2. Device Holder for Transmitters

- The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation centres for both scales are the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.
- The DASY device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon=3$ and loss tangent $\delta=0.02$. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.

3.7 Measurement Procedure

3.7.1 Scanning procedure

Step 1: Power reference measurement

The “reference” and “drift” measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure.

Step 2: Area scan

The SAR distribution at the exposed side of the head was measured at a distance of 4mm from the inner surface of the shell. The area covered the entire dimension of the head and the horizontal grid spacing was 15mm*15mm or 12mm*12mm or 10mm*10mm. Based on the area scan data, the area of the maximum absorption was determined by spline interpolation.

Step 3: Zoom scan

Around this point, a volume of 32mm*32mm*30mm ($f \leq 2\text{GHz}$), 30mm*30mm*30mm (f for 2-3GHz) and 24mm*24mm*22mm (f for 5-6GHz) was assessed by measuring 5x5x7 points ($f \leq 2\text{GHz}$), 7x7x7 points (f for 2-3GHz) and 7x7x12 points (f for 5-6GHz). On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure:

The data at the surface was extrapolated, since the centre of the dipoles is 2.0mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.2mm. (This can be variable. Refer to the probe specification). The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip. The maximum interpolated value was searched with a straight-forward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1g or 10g) were computed using the 3D-Spline interpolation algorithm. The volume was integrated with the trapezoidal algorithm. One thousand points were interpolated to calculate the average. All neighbouring volumes were evaluated until no neighboring volume with a higher average value was found.

If the zoom scan measured as specified in the preceding paragraphs complies with both i) and ii), or if the psSAR is below 0,1 W/kg, no additional measurements are needed.

i) The smallest horizontal distance from the local SAR peaks to all points 3 dB below the SAR peak shall be larger than the horizontal grid steps in both x- and y-directions (Δx , Δy). This shall be checked for the measured zoom scan plane conformal to the phantom at the distance zM1. The minimum distance shall be recorded in the SAR test report.

ii) The ratio of the SAR at the second measured point (M2) to the SAR at the closest measured point (M1) at the x-y location of the measured maximum SAR value shall be at least 30 %. This ratio (in %) shall be recorded in the SAR test report.

			$\leq 3 \text{ GHz}$	$> 3 \text{ GHz}$
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			$5 \pm 1 \text{ mm}$	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5 \text{ mm}$
Maximum probe angle from probe axis to phantom surface normal at the measurement location			$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$			$\leq 2 \text{ GHz: } \leq 15 \text{ mm}$ $2 - 3 \text{ GHz: } \leq 12 \text{ mm}$	$3 - 4 \text{ GHz: } \leq 12 \text{ mm}$ $4 - 6 \text{ GHz: } \leq 10 \text{ mm}$
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			$\leq 2 \text{ GHz: } \leq 8 \text{ mm}$ $2 - 3 \text{ GHz: } \leq 5 \text{ mm}^*$	$3 - 4 \text{ GHz: } \leq 5 \text{ mm}^*$ $4 - 6 \text{ GHz: } \leq 4 \text{ mm}^*$
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		$\leq 5 \text{ mm}$	$3 - 4 \text{ GHz: } \leq 4 \text{ mm}$ $4 - 5 \text{ GHz: } \leq 3 \text{ mm}$ $5 - 6 \text{ GHz: } \leq 2 \text{ mm}$
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	$\leq 4 \text{ mm}$	$3 - 4 \text{ GHz: } \leq 3 \text{ mm}$ $4 - 5 \text{ GHz: } \leq 2.5 \text{ mm}$ $5 - 6 \text{ GHz: } \leq 2 \text{ mm}$
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		$\geq 30 \text{ mm}$	$3 - 4 \text{ GHz: } \geq 28 \text{ mm}$ $4 - 5 \text{ GHz: } \geq 25 \text{ mm}$ $5 - 6 \text{ GHz: } \geq 22 \text{ mm}$

Step 4: Power reference measurement (drift)

The Power Drift Measurement job measures the field at the same location as the most recent power reference measurement job within the same procedure, and with the same settings. The indicated drift is mainly the variation of the DUT's output power and should vary max $\pm 5 \%$.

3.7.2 Data storage

The DASY software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension "DAE". The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated. The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [m W/g], [m W/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

3.7.3 Data Evaluation by SEMCAD

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	Normi, ai0, ai1, ai2
- Conversion factor	ConvFi	
- Diode compression point	Dcpi	
Device parameters:	- Frequency	f
- Crest factor	cf	
Media parameters:	- Conductivity	ε
- Density	ρ	

These parameters must be set correctly in the software. They can be found in the component documents, or they can be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics.

If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot cf / dcpi$$

With V_i = compensated signal of channel I (I = x, y, z)

U_i = input signal of channel I (I = x, y, z)

cf = crest factor of exciting field (DASY parameter)

dcpi = diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes:

$$E_i = (V_i / Norm_i \cdot ConvF)^{1/2}$$

H-field probes:

$$H_i = (V_i)^{1/2} \cdot (ai0 + ai1 f + ai2 f^2) / f$$

With V_i = compensated signal of channel I (I = x, y, z)

Normi = sensor sensitivity of channel I (I = x, y, z)

[mV/(V/m)²] for E-field Probes

ConvF = sensitivity enhancement in solution

a_{ij} = sensor sensitivity factors for H-field probes

f = carrier frequency [GHz]

E_i = electric field strength of channel i in V/m

H_i = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = (E_x^2 + E_y^2 + E_z^2)^{1/2}$$

The primary field data are used to calculate the derived field units.

$$SAR = (E_{tot}^2 \cdot \sigma) / (\epsilon \cdot 1000)$$

with SAR = local specific absorption rate in mW/g

E_{tot} = total field strength in V/m

σ = conductivity in [mho/m] or [Siemens/m]

ϵ = equivalent tissue density in g/cm³

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid. The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{pwe} = E_{tot}^2 / 3770 \text{ or } P_{pwe} = H_{tot}^2 \cdot 37.7$$

with P_{pwe} = equivalent power density of a plane wave in mW/cm²

E_{tot} = total electric field strength in V/m

H_{tot} = total magnetic field strength in A/m

4 SAR measurement variability and uncertainty

4.1 SAR measurement variability

Per KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r04, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.


4.2 SAR measurement uncertainty

Per KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

5 Description of Test Position

5.1 Hand-held usage of the device, not at the head or torso

When SAR measurement is necessary for hand-held devices that do not transmit while at the head or torso, a flat phantom may be used. To assess this type of device, the device shall be placed directly against the flat phantom as shown in the below Figure, for the sides of the device that are in contact with the hand for the intended use.



a) Test position for hand-held devices, not used at the head or torso

6 SAR System Verification Procedure

6.1 Tissue Simulate Liquid

6.1.1 Recipes for Tissue Simulate Liquid

The following tables give the recipes for tissue simulating liquids to be used in different frequency bands:

Ingredients (% by weight)	Frequency (MHz)				
	450	700-1000	1700-2000	2300-2500	2500-2700
Water	38.56	40.30	55.24	55.00	54.92
Salt (NaCl)	3.95	1.38	0.31	0.2	0.23
Sucrose	56.32	57.90	0	0	0
HEC	0.98	0.24	0	0	0
Bactericide	0.19	0.18	0	0	0
Tween	0	0	44.45	44.80	44.85
Salt: 99+% Pure Sodium Chloride Water: De-ionized, 16 MΩ+ resistivity Tween: Polyoxyethylene (20) sorbitan monolaurate Sucrose: 98+% Pure Sucrose HEC: Hydroxyethyl Cellulose					
1. Head Tissue Simulate Liquid (HBBL600-10000V6) is composed of the following ingredients : (Manufactured by SPEAG) Water: 50-65% Mineral oil: 10-30% Emulsifiers: 8-25% Sodium salt: 0-1.5%					

Table 1 : Recipe of Tissue Simulate Liquid

6.1.2 Measurement for Tissue Simulate Liquid

The Conductivity (σ) and Permittivity (ϵ_r) are listed in Table 2. For the SAR measurement given in this report.


The temperature variation of the Tissue Simulate Liquids was $22 \pm 2^\circ\text{C}$.

Tissue Type	Measured Frequency (MHz)	Measured Tissue		Target Tissue ($\pm 5\%$)		Deviation (Within $\pm 5\%$)		Liquid Temp. ($^\circ\text{C}$)	Test Date
		ϵ_r	$\sigma(\text{S/m})$	ϵ_r	$\sigma(\text{S/m})$	ϵ_r	$\sigma(\text{S/m})$		
13 Head	13	55.806	0.752	55.00	0.75	1.47%	0.27%	22.4	2026/8/18
750 Head	750	42.583	0.907	41.90	0.89	1.63%	1.91%	22.4	2026/7/20
835 Head	835	42.244	0.918	41.50	0.90	1.79%	2.00%	22.3	2026/7/22
835 Head	835	42.336	0.921	41.50	0.90	2.01%	2.33%	22.5	2026/8/17
1750 Head	1750	38.921	1.339	40.10	1.37	-2.94%	-2.26%	22.4	2026/7/24
1950 Head	1950	38.630	1.365	40.00	1.40	-3.42%	-2.50%	22.6	2026/7/26
2300 Head	2300	39.027	1.666	39.50	1.67	-1.20%	-0.24%	22.4	2026/7/28
2450 Head	2450	38.858	1.801	39.20	1.80	-0.87%	0.06%	22.3	2026/8/1
2600 Head	2600	38.372	1.953	39.00	1.96	-1.61%	-0.36%	22.5	2026/7/30
5250 Head	5250	36.113	4.746	35.90	4.71	0.59%	0.76%	22.4	2026/8/3
5600 Head	5600	35.254	5.132	35.50	5.07	-0.69%	1.22%	22.3	2026/8/4
5750 Head	5750	35.075	5.327	35.40	5.22	-0.92%	2.05%	22.4	2026/8/5

Table 2 : Measurement result of Tissue electric parameters

6.2 SAR System Check

The microwave circuit arrangement for system Check is sketched in F-12. The daily system accuracy verification occurs within the flat section of the SAM phantom. A SAR measurement was performed to see if the measured SAR was within $\pm 10\%$ from the target SAR values. The tests were conducted on the same days as the measurement of the EUT. The obtained results from the system accuracy verification are displayed in the following table (A power level of 250mW (below 3GHz) or 100mW (3GHz or higher) was input to the dipole antenna). During the tests, the ambient temperature of the laboratory was in the range $22\pm 2^\circ\text{C}$, the relative humidity was in the range 60% and the liquid depth above the ear reference points was above $15\pm 0.5\text{ cm}$ in all the cases. It is seen that the system is operating within its specification, as the results are within acceptable tolerance of the reference values.



F-12. The microwave circuit arrangement used for SAR system Check

6.2.1 Justification for Extended SAR Dipole Calibrations

1) Instead of the typical annual calibration recommended by measurement standards, longer calibration intervals of up to three years may be considered when it is demonstrated that the SAR target, impedance and return loss of a dipole have remain stable according to the following requirements. Each measured dipole is expected to evaluate with the following criteria at least on annual interval in Appendix C.

- a) There is no physical damage on the dipole;
- b) System check with specific dipole is within 10% of calibrated value;
- c) Return-loss is within 20% of calibrated measurement;
- d) Impedance is within 5Ω from the previous measurement.

2) Network analyzer probe calibration against air, distilled water and a shorting block performed before measuring liquid parameters.

6.2.2 Summary System Check Result(s)

Validation Kit	Measured SAR 250mW	Measured SAR 250mW	Measured SAR (normalized to 1W)	Measured SAR (normalized to 1W)	Target SAR (normalized to 1W)	Target SAR (normalized to 1W)	Deviation (Within ±10%)		Liquid Temp. (°C)	Test Date
	1g (W/kg)	10g (W/kg)	1g (W/kg)	10g (W/kg)	1-g(W/kg)	10-g(W/kg)	1-g(W/kg)	10- g(W/kg)		
CLA13 Head	0.112	0.072	0.45	0.29	0.42	0.27	7.14%	7.41%	22.4	2026/8/18
D750V3 Head	2.16	1.47	8.64	5.88	8.54	5.80	1.17%	1.38%	22.4	2026/7/20
D835V2 Head	2.47	1.59	9.88	6.36	9.60	6.16	2.92%	3.25%	22.3	2026/7/22
D835V2 Head	2.41	1.53	9.64	6.12	9.60	6.16	0.42%	-0.65%	22.5	2026/8/17
D1750V2 Head	8.74	4.68	34.96	18.72	36.30	19.30	-3.69%	-3.01%	22.4	2026/7/24
D1950V3 Head	9.52	4.93	38.08	19.72	40.70	21.20	-6.44%	-6.98%	22.6	2026/7/26
D2300V2 Head	11.60	5.52	46.40	22.08	49.00	23.50	-5.31%	-6.04%	22.4	2026/7/28
D2450V2 Head	12.50	5.84	50.00	23.36	52.70	24.60	-5.12%	-5.04%	22.3	2026/8/1
D2600V2 Head	13.60	6.13	54.40	24.52	55.20	24.70	-1.45%	-0.73%	22.5	2026/7/30
Validation Kit	Measured SAR 100mW	Measured SAR 100mW	Measured SAR (normalized to 1W)	Measured SAR (normalized to 1W)	Target SAR (normalized to 1W)	Target SAR (normalized to 1W)	Deviation (Within ±10%)		Liquid Temp. (°C)	Test Date
	1g (W/kg)	10g (W/kg)	1g (W/kg)	10g (W/kg)	1-g(W/kg)	10-g(W/kg)	1-g(W/kg)	10- g(W/kg)		
D5GHzV2_5.25G Head	7.54	2.15	75.40	21.50	77.20	21.90	-2.33%	-1.83%	22.4	2026/8/3
D5GHzV2_5.6G Head	7.91	2.23	79.10	22.30	81.10	22.80	-2.47%	-2.19%	22.3	2026/8/4
D5GHzV2_5.75G Head	7.84	2.19	78.40	21.90	77.80	21.70	0.77%	0.92%	22.4	2026/8/5

Table 3 : SAR System Check Result

6.2.3 Detailed System Check Results

Please see the Appendix A

7 Test Configuration

7.1 Operation Configurations

7.1.1 GSM Test Configuration

SAR tests for GSM frequency band, a communication link is set up with a base station by air link. Using Radio Communication Analyzer, the power level is set to “5” or “0” in SAR of GSM frequency band. The tests in the GSM frequency band are performed in the mode of GPRS/EGPRS function.

SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power specified for production units. The data mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power, the higher number time-slot configuration should be tested.

When SAR tests for EGPRS mode is necessary, GMSK modulation should be used to minimize SAR measurement error due to higher peak-to-average power (PAR) ratios inherent in 8-PSK.

The 3G SAR test reduction procedure is applied to 8-PSK EDGE with GMSK GPRS/EDGE as the primary mode.

For SAR the time based average power is relevant. The difference in between depends on the duty cycle of the TDMA signal:

No. of timeslots	1	2	3	4
Duty Cycle	1:8.3	1:4.15	1:2.77	1:2.075
Time based avg. power compared to slotted avg. power	-9.19	-6.18	-4.42	-3.17

The frame-averaged power is linearly proportion to the slot number configured and it is linearly scaled the maximum burst-averaged power based on time slots. The calculated method is shown as below:

Frame-averaged power = 10 x log (Burst-averaged power mW x Slot used / 8).

7.1.2 WCDMA Test Configuration

1) Output Power Verification

Maximum output power is verified on the high, middle and low channels according to procedures described in section 5.2 of 3GPP TS 34.121, using the appropriate RMC or AMR with TPC (transmit power control) set to all “1’s” for WCDMA/HSDPA or by applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HSDPA, HSPA) are required in the SAR report. All configurations that are not supported by the handset or cannot be measured due to technical or equipment limitations must be clearly identified.

2) Head SAR

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all “1’s”. The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest reported SAR configuration in 12.2 kbps RMC for head exposure.

3) Body SAR

SAR for body configurations is measured using a 12.2 kbps RMC with TPC bits configured to all “1’s”. The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCHn configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCHn, for the highest reported body-worn accessory exposure SAR configuration in 12.2 kbps RMC. When more than 2 DPDCHn are supported by the handset, it may be necessary to configure additional DPDCHn using FTM (Factory Test Mode) or other chipset based test approaches with parameters similar to those used in 384 kbps and 768 kbps RMC.

4) HSDPA / HSUPA

RMC 12.2kbps setting is used to evaluate SAR. If the maximum output power for production units in HSDPA / HSUPA is ≤ ¼ dB higher than RMC 12.2Kbps or when the highest measured SAR of the RMC12.2Kbps is

scaled by the ratio of specified maximum output power of HSDPA / HSUPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.5 W/kg, SAR measurement is not required for HSDPA / HSUPA.

a) HSDPA

HSDPA is configured according to the applicable UE category of a test device. The number of HS-DSCH/HS-PDSCHs, HARQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the H-set. To maintain a consistent test configuration and stable transmission conditions, QPSK is used in the H-set for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 4 ms and a CQI repetition factor of 2 to maintain a constant rate of active CQI slots. DPCCH and DPDCH gain factors (β_c , β_d), and HS-DPCCH power offset parameters (Δ_{ACK} , Δ_{NACK} , Δ_{CQI}) are set according to values indicated in the following table. The CQI value is determined by the UE category, transport block size, number of HS-PDSCHs and modulation used in the H-set.

Sub-test	β_c	Bd	β_d (SF)	β_c/β_d	β_{hs}	CM(dB)	MPR (dB)
1	2/15	15/15	64	2/15	4/15	0.0	0
2	12/15(3)	15/15(3)	64	12/15(3)	24/15	1.0	0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8$ Ahs = $\beta_{hs}/\beta_c = 30/15$ $\beta_{hs} = 30/15 * \beta_c$

Note2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1.A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 8$ (Ahs=30/15) with $\beta_{hs} = 30/15 * \beta_c$, and $\Delta_{CQI} = 7$ (Ahs=24/15) with $\beta_{hs} = 24/15 * \beta_c$.

Note3: CM=1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

The measurements were performed with a Fixed Reference Channel (FRC) and H-Set 1 QPSK.

Parameter	Value
Nominal average inf. bit rate	534 kbit/s
Inter-TTI Distance	3 TTI"s
Number of HARQ Processes	2 Processes
Information Bit Payload	3202 Bits
MAC-d PDU size	336 Bits
Number Code Blocks	1 Block
Binary Channel Bits Per TTI	4800 Bits
Total Available SMLs in UE	19200 SMLs
Number of SMLs per HARQ Process	9600 SMLs
Coding Rate	0.67
Number of Physical Channel Codes	5

Table 4 : settings of required H-Set 1 QPSK acc. to 3GPP 34.121

HS-DSCH Category	MaximumHS-DSCH Codes Received	Minimum Inter-TTI Interval	MaximumHS-DSCH TransportBlockBits/HS-DSCH TTI	TotalSoft Channel Bits
1	5	3	7298	19200
2	5	3	7298	28800
3	5	2	7298	28800
4	5	2	7298	38400
5	5	1	7298	57600
6	5	1	7298	67200
7	10	1	14411	115200
8	10	1	14411	134400
9	15	1	25251	172800
10	15	1	27952	172800
11	5	2	3630	14400
12	5	1	3630	28800
13	15	1	34800	259200
14	15	1	42196	259200
15	15	1	23370	345600
16	15	1	27952	345600

Table 5 : HSDPA UE category

b) HSUPA

Due to inner loop power control requirements in HSUPA, a commercial communication test set should be used for the output power and SAR tests. The 12.2 kbps RMC, FRC H-set 1 and E-DCH configurations for HSUPA should be configured according to the values indicated below as well as other applicable procedures described in the WCDMA Handset and Release 5 HSUPA Data Device sections of 3G device.

Sub-test ^⓪	β_c ^⓪	β_d ^⓪	β_d (SF) ^⓪	β_c/β_d ^⓪	β_{hs} ⁽¹⁾ ^⓪	β_{ac} ^⓪	β_{ad} ^⓪	β_c (SF) ^⓪	β_{ad} (code) ^⓪	CM ⁽²⁾ (dB) ^⓪	MP R ^⓪ (dB) ^⓪	AG ⁽⁴⁾ Inde ^x ^⓪	E-TFC I ^⓪
1 ^⓪	11/15 ⁽³⁾ ^⓪	15/15 ⁽³⁾ ^⓪	64 ^⓪	11/15 ⁽³⁾ ^⓪	22/15 ^⓪	209/225 ^⓪	1039/225 ^⓪	4 ^⓪	1 ^⓪	1.0 ^⓪	0.0 ^⓪	20 ^⓪	75 ^⓪
2 ^⓪	6/15 ^⓪	15/15 ^⓪	64 ^⓪	6/15 ^⓪	12/15 ^⓪	12/15 ^⓪	94/75 ^⓪	4 ^⓪	1 ^⓪	3.0 ^⓪	2.0 ^⓪	12 ^⓪	67 ^⓪
3 ^⓪	15/15 ^⓪	9/15 ^⓪	64 ^⓪	15/9 ^⓪	30/15 ^⓪	30/15 ^⓪	$\beta_{ad1}:47/15$ $\beta_{ad2}:47/15$ ^⓪	4 ^⓪	2 ^⓪	2.0 ^⓪	1.0 ^⓪	15 ^⓪	92 ^⓪
4 ^⓪	2/15 ^⓪	15/15 ^⓪	64 ^⓪	2/15 ^⓪	4/15 ^⓪	2/15 ^⓪	56/75 ^⓪	4 ^⓪	1 ^⓪	3.0 ^⓪	2.0 ^⓪	17 ^⓪	71 ^⓪
5 ^⓪	15/15 ⁽⁴⁾ ^⓪	15/15 ⁽⁴⁾ ^⓪	64 ^⓪	15/15 ⁽⁴⁾ ^⓪	30/15 ^⓪	24/15 ^⓪	134/15 ^⓪	4 ^⓪	1 ^⓪	1.0 ^⓪	0.0 ^⓪	21 ^⓪	81 ^⓪
Note 1: ΔACK , $\Delta NACK$ and $\Delta CQI=8$ $A_{hs} = \beta_{hs}/\beta_c = 30/15$ $\beta_{hs} = 30/15 * \beta_c$ Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference ^⓪ Note 3 : For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$ ^⓪ Note 4 : For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14/15$ and $\beta_d = 15/15$ ^⓪ Note 5 : Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g ^⓪ Note 6: β_{ad} can not be set directly; it is set by Absolute Grant Value. ^⓪													

Table 6 : Subtests for UMTS Release 6 HSUPA

UE E-DCH Category	Maximum E-DCH Codes Transmitted	Number of HARQ Processes	E-DCH TTI(ms)	Minimum Spreading Factor	Maximum E-DCH Transport Block Bits	Max Rate (Mbps)
1	1	4	10	4	7110	0.7296
2	2	8	2	4	2798	1.4592
	2	4	10	4	14484	
3	2	4	10	4	14484	1.4592
4	2	8	2	2	5772	2.9185
	2	4	10	2	20000	2.00
5	2	4	10	2	20000	2.00
6 (No DPDCH)	4	8	10	2SF2&2SF	11484	5.76
	4	4	2	4	20000	2.00
7 (No DPDCH)	4	8	2	2SF2&2SF	22996	?
	4	4	10	4	20000	?
NOTE: When 4 codes are transmitted in parallel, two codes shall be transmitted with SF2 and two with SF4.UE categories 1 to 6 support QPSK only. UE category 7 supports QPSK and 16QAM.(TS25.306-7.3.0).						

Table 7 : HSUPA UE category

c) DC-HSDPA

SAR is required for Rel. 8 DC-HSDPA when SAR is required for Rel. 5 HSDPA; otherwise, the 3G SAR test reduction procedure is applied to DC-HSDPA with 12.2 kbps RMC as the primary mode. Power is measured for DC-HSDPA according to the H-Set 12, FRC configuration in Table C.8.1.12 of 3GPP TS 34.121-1 to determine SAR test reduction. A primary and a Second serving HS-DSCH Cell are required to perform the power measurement and for the results to be acceptable.

The following tests were completed according to procedures in section 7.3.13 of 3GPP TS 34.108 v9.5.0.

A summary of these settings are illustrated below:

Downlink Physical Channels are set as per 3GPP TS34.121-1 v9.0.0 E.5.0

Table E.5.0: Levels for HSDPA connection setup

Parameter During Connection setup	Unit	Value
P-CPICH_Ec/Ior	dB	-10
P-CCPCH and SCH_Ec/Ior	dB	-12
PICH_Ec/Ior	dB	-15
HS-PDSCH	dB	off
HS-SCCH_1	dB	off
DPCH_Ec/Ior	dB	-5
OCNS_Ec/Ior	dB	-3.1

Call is set up as per 3GPP TS34.108 v9.5.0 sub clause 7.3.13.

The configurations of the fixed reference channels for HSDPA RF tests are described in 3GPP TS 34.121, annex C for FDD and 3GPP TS 34.122.

The measurements were performed with a Fixed Reference Channel (FRC) H-Set 12 with QPSK.

Parameter	Value
Nominal average inf. bit rate	60 kbit/s
Inter-TTI Distance	1 TTI's
Number of HARQ Processes	6 Processes
Information Bit Payload	120 Bits
Number Code Blocks	1 Block
Binary Channel Bits Per TTI	960 Bits
Total Available SMLs in UE	19200 SMLs
Number of SMLs per HARQ Process	3200 SMLs
Coding Rate	0.15
Number of Physical Channel Codes	1

Table 8 : settings of required H-Set 12 QPSK acc. To 3GPP 34.121

Note:

1. The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table above.
2. Maximum number of transmission is limited to 1,i.e.,retransmission is not allowed. The redundancy and constellation version 0 shall be used.




Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)

The following 4 Sub-tests for HSDPA were completed according to Release 5 procedures. A summary of subtest settings are illustrated below:

Sub-test ^o	β_c ^o	β_d ^o	β_d (SF) ^o	β_c/β_d ^o	$\beta_{hs}(1)$ ^o	CM(dB)(2) ^o	MPR (dB) ^o
1 ^o	2/15 ^o	15/15 ^o	64 ^o	2/15 ^o	4/15 ^o	0.0 ^o	0 ^o
2 ^o	12/15(3) ^o	15/15(3) ^o	64 ^o	12/15(3) ^o	24/15 ^o	1.0 ^o	0 ^o
3 ^o	15/15 ^o	8/15 ^o	64 ^o	15/8 ^o	30/15 ^o	1.5 ^o	0.5 ^o
4 ^o	15/15 ^o	4/15 ^o	64 ^o	15/4 ^o	30/15 ^o	1.5 ^o	0.5 ^o
Note 1: Δ ACK, Δ NACK and Δ CQI=8 $A_{hs} = \beta_{hs}/\beta_c = 30/15$ $\beta_{hs} = 30/15 * \beta_c$ Note 2: CM=1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases. Note 3: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$							

Up commands are set continuously to set the UE to Max power.

Note:

1. The Dual Carriers transmission only applies to HSDPA physical channels
2. The Dual Carriers belong to the same Node and are on adjacent carriers.
3. The Dual Carriers do not support MIMO to serve Ues configured for dual cell operation
4. The Dual Carriers operate in the same frequency band.
5. The device doesn't support the modulation of 16QAM in uplink but 64QAM in downlink for DC-HSDPA mode.
6. The device doesn't support carrier aggregation for it just can operate in Release 8.

d) HSPA+

SAR is required for Rel. 7 HSPA+ when SAR is required for Rel. 6 HSPA; otherwise, the 3G SAR test reduction procedure is applied to (uplink) HSPA+ with 12.2 kbps RMC as the primary mode. Power is measured for HSPA+ that supports uplink 16 QAM according to configurations in Table C.11.1.4 of 3GPP TS 34.121-1 to determine SAR test reduction.

Table C.11.1.4: β values for transmitter characteristics tests with HS-DPCCH and E-DCH with 16QAM

Sub-test	β_c (Note 3)	β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (2xSF2) (Note 4)	β_{ed} (2xSF4) (Note 4)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 4)	E-TFCI (Note 5)	E-TFCI (boost)
1	1	0	30/15	30/15	β_{ed1} : 30/15 β_{ed2} : 30/15	β_{ed3} : 24/15 β_{ed4} : 24/15	3.5	2.5	14	105	105
<p>Note 1: Δ_{ACK}, Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{HS} = 30/15 * \beta_c$.</p> <p>Note 2: CM = 3.5 and the MPR is based on the relative CM difference, $MPR = \text{MAX}(CM-1, 0)$.</p> <p>Note 3: DPDCH is not configured, therefore the β_c is set to 1 and $\beta_d = 0$ by default.</p> <p>Note 4: β_{ed} can not be set directly; it is set by Absolute Grant Value.</p> <p>Note 5: All the sub-tests require the UE to transmit 2SF2+2SF4 16QAM EDCH and they apply for UE using E-DPDCH category 7. E-DCH TTI is set to 2ms TTI and E-DCH table index = 2. To support these E-DCH configurations DPDCH is not allocated. The UE is signalled to use the extrapolation algorithm.</p>											

5) 3G SAR Test Reduction Procedure

According to KDB 941225D01, in the following procedures, the mode tested for SAR is referred to as the primary mode. The equivalent modes considered for SAR test reduction are denoted as secondary modes. Both primary and secondary modes must be in the same frequency band. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq 1/4$ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode. This is referred to as the 3G SAR test reduction procedure in the following SAR test guidance, where the primary mode is identified in the applicable wireless mode test procedures and the secondary mode is wireless mode being considered for SAR test reduction by that procedure. When the 3G SAR test reduction procedure is not satisfied, it is identified as "otherwise" in the applicable procedures; SAR measurement is required for the secondary mode.


7.1.3 WIFI Test Configuration

A Wi-Fi device must be configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools for SAR measurement.

7.1.3.1 Duty cycle


1) Wi-Fi 2.4GHz 802.11b:

Duty cycle=98.49%



2) Wi-Fi 5GHz 802.11ac VHT80:

Duty cycle=92.81%



7.1.3.2 Initial Test Position SAR Test Reduction Procedure

DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures. The initial test position procedure is described in the following:

- 1) . When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other (remaining) test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band. SAR is also not required for that exposure configuration in the subsequent test configuration(s).
- 2) . When the reported SAR of the initial test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position using subsequent highest extrapolated or estimated 1-g SAR conditions determined by area scans or next closest/smallest test separation distance and maximum RF coupling test positions based on manufacturer justification, on the highest maximum output power channel, until the reported SAR is ≤ 0.8 W/kg or all required test positions (left, right, touch, tilt or subsequent surfaces and edges) are tested.
- 3) . For all positions/configurations tested using the initial test position and subsequent test positions, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested. a) Additional power measurements may be required for this step, which should be limited to those necessary for identifying the subsequent highest output power channels.

7.1.3.3 Subsequent Test Configuration Procedures

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units. The initial test position procedure is applied to next to the ear, UMPC mini-tablet and hotspot mode configurations. When the same maximum output power is specified for multiple transmission modes, additional power measurements may be required to determine if SAR measurements are required for subsequent highest output power channels in a subsequent test configuration. The subsequent test configuration and SAR measurement procedures are described in the following.

- 1) . When SAR test exclusion provisions of KDB Publication 447498 are applicable and SAR measurement is not required for the initial test configuration, SAR is also not required for the next highest maximum output power transmission mode subsequent test configuration(s) in that frequency band or aggregated band and exposure configuration.
- 2) . When the highest reported SAR for the initial test configuration (when applicable, include subsequent highest output channels), according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for that subsequent test configuration.
- 3) . The number of channels in the initial test configuration and subsequent test configuration can be different due to differences in channel bandwidth. When SAR measurement is required for a subsequent test configuration and the channel bandwidth is smaller than that in the initial test configuration, all channels in the subsequent test configuration that overlap with the larger bandwidth channel tested in the initial test configuration should be used to determine the highest maximum output power channel. This step requires additional power measurement to identify the highest maximum output power channel in the subsequent test configuration to determine SAR test reduction.
 - a) SAR should first be measured for the channel with highest measured output power in the subsequent test configuration.
 - b) SAR for subsequent highest measured maximum output power channels in the subsequent test configuration is required only when the reported SAR of the preceding higher maximum output power channel(s) in the subsequent test configuration is > 1.2 W/kg or until all required channels are tested. i) For channels with the same measured maximum output power, SAR should be measured using the channel closest to the center frequency of the larger channel bandwidth channel in the initial test configuration.
- 4) . SAR measurements for the remaining highest specified maximum output power OFDM transmission mode configurations that have not been tested in the initial test configuration (highest maximum output) or subsequent test configuration(s) (subsequent next highest maximum output power) is determined by recursively applying the subsequent test configuration procedures in this section to the remaining configurations according to the following:
 - a) replace “subsequent test configuration” with “next subsequent test configuration” (i.e., subsequent next highest specified maximum output power configuration)
 - b) replace “initial test configuration” with “all tested higher output power configurations”

7.1.3.4 2.4 GHz WiFi SAR Procedures

Separate SAR procedures are applied to DSSS and OFDM configurations in the 2.4 GHz band to simplify DSSS test requirements. For 802.11b DSSS SAR measurements, DSSS SAR procedure applies to fixed exposure test position and initial test position procedure applies to multiple exposure test positions. When SAR measurement is required for an OFDM configuration, the initial test configuration, subsequent test configuration and initial test position procedures are applied. The SAR test exclusion requirements for 802.11g/n OFDM configurations are described in following.

- **802.11b DSSS SAR Test Requirements**

SAR is measured for 2.4 GHz 802.11b DSSS using either a fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) . When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) . When the reported SAR is > 0.8 W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

- **2.4 GHz 802.11g/n OFDM SAR Test Exclusion Requirements**

When SAR measurement is required for 2.4 GHz 802.11g/n OFDM configurations, the measurement and test reduction procedures for OFDM are applied (section 5.3, including sub-sections). SAR is not required for the following 2.4 GHz OFDM conditions.

- 1) . When KDB Publication 447498 SAR test exclusion applies to the OFDM configuration.
- 2) . When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

- **SAR Test Requirements for OFDM configurations**

When SAR measurement is required for 802.11 g/n OFDM configurations, each standalone and frequency aggregated band is considered separately for SAR test reduction. In applying the initial test configuration and subsequent test configuration procedures, the 802.11 transmission configuration with the highest specified maximum output power and the channel within a test configuration with the highest measured maximum output power should be clearly distinguished to apply the procedures.

7.1.3.5 5 GHz WiFi SAR Procedures

- **U-NII-1 and U-NII-2A Bands**

For devices that operate in only one of the U-NII-1 and U-NII-2A bands, the normally required SAR procedures for OFDM configurations are applied. For devices that operate in both U-NII bands using the same transmitter and antenna(s), SAR test reduction is determined according to the following:

- 1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, both bands are tested independently for SAR.
- 2) When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for the band with lower maximum output power in that test configuration; otherwise, both bands are tested independently for SAR.
- 3) The two U-NII bands may be aggregated to support a 160 MHz channel on channel number 50. Without additional testing, the maximum output power for this is limited to the lower of the maximum output power certified for the two bands. When SAR measurement is required for at least one of the bands and the highest reported SAR adjusted by the ratio of specified maximum output power of aggregated to standalone band is > 1.2 W/kg, SAR is required for the 160 MHz channel. This procedure does not apply to an aggregated band with maximum output higher than the standalone band(s); the aggregated band must be tested independently for SAR. SAR is not required when the 160 MHz channel is operating at a reduced maximum power and also qualifies for SAR test exclusion.

- **U-NII-2C and U-NII-3 Bands**

The frequency range covered by these bands is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. When Terminal Doppler Weather Radar (TDWR) restriction applies, all channels that operate at 5.60 – 5.65 GHz must be included to apply the SAR test reduction and measurement procedures.

When the same transmitter and antenna(s) are used for U-NII-2C band and U-NII-3 band or 5.8 GHz band of §15.247, the bands may be aggregated to enable additional channels with 20, 40 or 80 MHz bandwidth to span across the band gap, as illustrated in Appendix B. The maximum output power for the additional band gap channels is limited to the lower of those certified for the bands. Unless band gap channels are permanently disabled, they must be considered for SAR testing. The frequency range covered by these bands is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. To maintain SAR measurement accuracy and to facilitate test reduction, the channels in U-NII-2C band above 5.65 GHz may be grouped with the 5.8 GHz channels in U-NII-3 or §15.247 band to enable two SAR probe calibration frequency points to cover the bands, including the band gap channels. When band gap channels are supported and the bands are not aggregated for SAR testing, band gap channels must be considered independently in each band according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

OFDM Transmission Mode SAR Test Configuration and Channel Selection Requirements

The initial test configuration for 5 GHz OFDM transmission modes is determined by the 802.11 configuration with the highest maximum output power specified for production units, including tune-up tolerance, in each standalone and aggregated frequency band. SAR for the initial test configuration is measured using the highest maximum output power channel determined by the default power measurement procedures. When multiple configurations in a frequency band have the same specified maximum output power, the initial test configuration is determined according to the following steps applied sequentially.

- 1) The largest channel bandwidth configuration is selected among the multiple configurations with the same specified maximum output power.
- 2) If multiple configurations have the same specified maximum output power and largest channel bandwidth, the lowest order modulation among the largest channel bandwidth configurations is selected.
- 3) If multiple configurations have the same specified maximum output power, largest channel bandwidth and lowest order modulation, the lowest data rate configuration among these configurations is selected.
- 4) When multiple transmission modes (802.11a/g/n/ac) have the same specified maximum output power, largest channel bandwidth, lowest order modulation and lowest data rate, the lowest order 802.11 mode is selected; i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n. After an initial test configuration is determined, if multiple test channels have the same measured maximum output power, the channel chosen for SAR measurement is determined according to the following. These channel selection procedures apply to both the initial test configuration and subsequent test configuration(s), with respect to the default power measurement procedures or additional power measurements required for further SAR test reduction. The same procedures also apply to subsequent highest output power channel(s) selection.
 - a) The channel closest to mid-band frequency is selected for SAR measurement.
 - b) For channels with equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.


• SAR Test Requirements for OFDM configurations

When SAR measurement is required for 802.11 a/n/ac OFDM configurations, each standalone and frequency aggregated band is considered separately for SAR test reduction. When the same transmitter and antenna(s) are used for U-NII-1 and U-NII-2A bands, additional SAR test reduction applies. When band gap channels between U-NII-2C band and 5.8 GHz U-NII-3 or §15.247 band are supported, the highest maximum output power transmission mode configuration and maximum output power channel across the bands must be used to determine SAR test reduction, according to the initial test configuration and subsequent test configuration requirements. In applying the initial test configuration and subsequent test configuration procedures, the 802.11 transmission configuration with the highest specified maximum output power and the channel within a test configuration with the highest measured maximum output power should be clearly distinguished to apply the procedures.

7.1.4 BT Test Configuration

For the Bluetooth SAR tests, a communication link is set up with the test mode software for BT mode test. Bluetooth USES frequency hopping technology to divide the transmitted data into packets and transmit the packets respectively through 79 designated Bluetooth channels, frequency hops at 1600 hops/second per the Bluetooth standard, the EUT is operated at the RF continuous emission mode.

BT 3DH5 Duty Cycle=77.65%



7.1.5 LTE Test Configuration

LTE modes were tested according to FCC KDB 941225 D05 publication. Please see notes after the tabulated SAR data for required test configurations. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The Radio Communication Analyzer was used for LTE output power measurements and SAR testing. Max power control was used so the UE transmits with maximum output power during SAR testing. SAR must be measured with the maximum TTI (transmit time interval) supported by the device in each LTE configuration.

TDD LTE test consideration

For Time-Division Duplex (TDD) systems, SAR must be tested using a fixed periodic duty factor according to the highest transmission duty factor implemented for the device and supported by the defined 3GPP LTE TDD configurations.

SAR was tested with the highest transmission duty factor (63.33%) using Uplink-downlink configuration 0 and Special subframe configuration 7.

LTE TDD Band support 3GPP TS 36.211 section 4.2 for Type 2 Frame Structure and Table 4.2-2 for uplink-downlink configurations and Table 4.2-1 for Special subframe configurations.

Frame structure type 2:




Table 4.2-1: Configuration of special subframe (lengths of DwPTS/GP/UpPTS).

Special subframe configuration	Normal cyclic prefix in downlink			Extended cyclic prefix in downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
0	6592.Ts	2192.Ts	2560.Ts	7680.Ts	2192.Ts	2560.Ts
1	19760.Ts			20480.Ts		
2	21952.Ts			23040.Ts		
3	24144.Ts			25600.Ts		
4	26336.Ts			7680.Ts	4384.Ts	5120.Ts
5	6592.Ts	4384.Ts	5120.Ts	20480.Ts		
6	19760.Ts			23040.Ts		
7	21952.Ts			25600.Ts		
8	24144.Ts			-	-	-
9	13168.Ts			-	-	-

Table 4.2-2: Uplink-downlink configurations.

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

Calculated Duty Cycle=[Extended cyclic prefix in uplink x (Ts) x # of S + # of U]/10ms

Uplink-Downlink Configuration	Downlink-to-Uplink Switch-point Periodicity	Subframe Number										Calculated Duty Cycle (%)
		0	1	2	3	4	5	6	7	8	9	
0	5 ms	D	S	U	U	U	D	S	U	U	U	63.33
1	5 ms	D	S	U	U	D	D	S	U	U	D	43.33
2	5 ms	D	S	U	D	D	D	S	U	D	D	23.33
3	10 ms	D	S	U	U	U	D	D	D	D	D	31.67
4	10 ms	D	S	U	U	D	D	D	D	D	D	21.67
5	10 ms	D	S	U	D	D	D	D	D	D	D	11.67
6	5 ms	D	S	U	U	U	D	S	U	U	D	53.33

A) Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

B) MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

Modulation	Channel bandwidth/Transmission bandwidth						MPR (dB)
	1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	0
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	1
16QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	1
16QAM	> 5	> 4	> 8	> 12	> 16	> 18	2
64QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	2
64QAM	> 5	> 4	> 8	> 12	> 16	> 18	3
256QAM	≥ 1						5

C) A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

D) Largest channel bandwidth standalone SAR test requirements

1) QPSK with 1 RB allocation

Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.

2) QPSK with 50% RB allocation

The procedures required for 1 RB allocation in 1) are applied to measure the SAR for QPSK with 50% RB allocation.

3) QPSK with 100% RB allocation

For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation in 1) and 2) are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

4) Higher order modulations

For each modulation besides QPSK; e.g., 16-QAM, 64-QAM, apply the QPSK procedures in above sections to determine the QAM configurations that may need SAR measurement. For each configuration identified as required for testing, SAR is required only when the highest maximum output power for the configuration in the higher order modulation is $> \frac{1}{2}$ dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg.

E) Other channel bandwidth standalone SAR test requirements

For the other channel bandwidths used by the device in a frequency band, apply all the procedures required for the largest channel bandwidth in section A) to determine the channels and RB configurations that need SAR testing and only measure SAR when the highest maximum output power of a configuration requiring testing in the smaller channel bandwidth is $> \frac{1}{2}$ dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is > 1.45 W/kg.

8 Test Result

8.1 DUT Antenna Locations (Back View)

The DUT Antenna Locations can be referred to Appendix D

8.2 Measurement of RF Conducted Power

The detailed power data can be referred to Appendix E Conducted RF Output Power.

8.3 Measurement of SAR Data

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph results refer to Appendix B.
- 2) Testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - $\leq 0.8\text{W/kg}$ for 1-g or 2.0W/kg for 10-g respectively, when the transmission band is $\leq 100\text{MHz}$.
 - $\leq 0.6\text{ W/kg}$ or 1.5 W/kg , for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz.
 - $\leq 0.4\text{ W/kg}$ or 1.0 W/kg , for 1-g or 10-g respectively, when the transmission band is $\geq 200\text{ MHz}$.
- 3) The device does not support DTM function.
- 4) For WiFi SAR test, as the highest reported SAR is smaller than 1.2 W/kg , and the tune-up of the other 802.11 modes are not higher than SAR measurement mode, therefore the adjusted SAR is $\leq 1.2\text{ W/kg}$ for other 802.11 modes, SAR test for the other 802.11 modes are not required. For extremity 10gSAR the highest reported SAR is smaller than 3.0 W/kg , SAR test for the other 802.11 modes are also not required.
- 5) According to the October 2014 TCB Workshop “RF Exposure Procedures Update (Overlapping Bands)”: SAR for LTE Bands 2/4/5/17/38 are covered by LTE Bands 25/66/26/12/41 respectively. Because the frequency ranges are similar, the maximum tune-up limits are the same, and the channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band.

8.3.1 SAR Result of GSM850

Ant1										
Test position	Test mode	Test ch./Freq.	Duty Cycle	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test data(Separate 0mm)										
Front side	GPRS 4TS	190/836.6	1:2.075	0.101	-0.01	28.44	30.00	1.432	0.145	22.3
Back side	GPRS 4TS	190/836.6	1:2.075	0.408	0.12	28.44	30.00	1.432	0.584	22.3
Left side	GPRS 4TS	190/836.6	1:2.075	0.064	0.05	28.44	30.00	1.432	0.092	22.3
Right side	GPRS 4TS	190/836.6	1:2.075	0.836	-0.08	28.44	30.00	1.432	1.197	22.3
Top side	GPRS 4TS	190/836.6	1:2.075	0.084	-0.10	28.44	30.00	1.432	0.120	22.3
Bottom side	GPRS 4TS	190/836.6	1:2.075	0.000	0.00	28.44	30.00	1.432	0.000	22.3

8.3.2 SAR Result of GSM1900

Ant1										
Test position	Test mode	Test ch./Freq.	Duty Cycle	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test data(Separate 0mm)										
Front side	GPRS 3TS	661/1880	1:2.77	0.049	-0.16	27.53	29.00	1.403	0.069	22.6
Back side	GPRS 3TS	661/1880	1:2.77	0.430	0.11	27.53	29.00	1.403	0.603	22.6
Left side	GPRS 3TS	661/1880	1:2.77	0.156	-0.11	27.53	29.00	1.403	0.219	22.6
Right side	GPRS 3TS	661/1880	1:2.77	1.520	0.19	27.53	29.00	1.403	2.133	22.6
Right side	GPRS 3TS	512/1850.2	1:2.77	1.470	-0.13	27.47	29.00	1.422	2.090	22.6
Right side	GPRS 3TS	810/1909.8	1:2.77	1.290	0.08	27.06	29.00	1.563	2.016	22.6
Top side	GPRS 3TS	661/1880	1:2.77	0.178	0.15	27.53	29.00	1.403	0.250	22.6
Bottom side	GPRS 3TS	661/1880	1:2.77	0.000	0.00	27.53	29.00	1.403	0.000	22.6

8.3.3 SAR Result of WCDMA Band II

Ant1										
Test position	Test mode	Test ch./Freq.	Duty Cycle	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test data(Separate 0mm)										
Front side	RMC	9400/1880	1:1	0.065	0.15	22.99	24.00	1.262	0.082	22.6
Back side	RMC	9400/1880	1:1	0.547	-0.15	22.99	24.00	1.262	0.690	22.6
Left side	RMC	9400/1880	1:1	0.064	-0.15	22.99	24.00	1.262	0.081	22.6
Right side	RMC	9400/1880	1:1	1.910	-0.09	22.99	24.00	1.262	2.410	22.6
Right side	RMC	9262/1852.4	1:1	1.890	-0.14	22.96	24.00	1.271	2.402	22.6
Right side	RMC	9538/1907.6	1:1	1.850	-0.13	22.93	24.00	1.279	2.366	22.6
Top side	RMC	9400/1880	1:1	0.386	0.08	22.99	24.00	1.262	0.487	22.6
Bottom side	RMC	9400/1880	1:1	0.000	0.00	22.99	24.00	1.262	0.000	22.6

8.3.4 SAR Result of WCDMA Band IV

Ant1										
Test position	Test mode	Test ch./Freq.	Duty Cycle	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test data(Separate 0mm)										
Front side	RMC	1412/1732.4	1:1	0.055	0.09	23.04	24.00	1.247	0.069	22.4
Back side	RMC	1412/1732.4	1:1	0.602	0.06	23.04	24.00	1.247	0.751	22.4
Left side	RMC	1412/1732.4	1:1	0.067	0.06	23.04	24.00	1.247	0.084	22.4
Right side	RMC	1412/1732.4	1:1	1.520	-0.19	23.04	24.00	1.247	1.895	22.4
Top side	RMC	1412/1732.4	1:1	0.229	-0.03	23.04	24.00	1.247	0.286	22.4
Bottom side	RMC	1412/1732.4	1:1	0.000	0.00	23.04	24.00	1.247	0.000	22.4

8.3.5 SAR Result of WCDMA Band V

Ant1										
Test position	Test mode	Test ch./Freq.	Duty Cycle	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test data(Separate 0mm)										
Front side	RMC	4182/836.4	1:1	0.122	-0.02	23.13	24.00	1.222	0.149	22.3
Back side	RMC	4182/836.4	1:1	0.458	-0.03	23.13	24.00	1.222	0.560	22.3
Left side	RMC	4182/836.4	1:1	0.044	-0.12	23.13	24.00	1.222	0.054	22.3
Right side	RMC	4182/836.4	1:1	0.998	-0.09	23.13	24.00	1.222	1.220	22.3
Top side	RMC	4182/836.4	1:1	0.056	-0.17	23.13	24.00	1.222	0.068	22.3
Bottom side	RMC	4182/836.4	1:1	0.000	0.00	23.13	24.00	1.222	0.000	22.3

8.3.6 SAR Result of LTE Band 7

Ant1											
Test position	BW.	Test mode	Test ch./Freq.	Duty Cycle	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test data (Separate 0mm 1RB)											
Front side	20	QPSK 1_0	21100/2535	1:1	0.037	0.12	23.77	24.00	1.054	0.039	22.5
Back side	20	QPSK 1_0	21100/2535	1:1	0.675	-0.05	23.77	24.00	1.054	0.711	22.5
Left side	20	QPSK 1_0	21100/2535	1:1	0.069	0.11	23.77	24.00	1.054	0.073	22.5
Right side	20	QPSK 1_0	21100/2535	1:1	2.560	-0.01	23.77	24.00	1.054	2.698	22.5
Right side-repeated	20	QPSK 1_0	21100/2535	1:1	2.530	0.09	23.77	24.00	1.054	2.667	22.5
Right side	20	QPSK 1_0	20850/2510	1:1	2.500	0.04	23.71	24.00	1.069	2.673	22.5
Right side	20	QPSK 1_0	21350/2560	1:1	2.520	-0.04	23.73	24.00	1.064	2.681	22.5
Top side	20	QPSK 1_0	21100/2535	1:1	0.235	-0.17	23.77	24.00	1.054	0.248	22.5
Bottom side	20	QPSK 1_0	21100/2535	1:1	0.000	0.00	23.77	24.00	1.054	0.000	22.5
Extremity Test data (Separate 0mm 50%RB)											
Front side	20	QPSK 50_0	21100/2535	1:1	0.031	0.06	22.72	23.00	1.067	0.033	22.5
Back side	20	QPSK 50_0	21100/2535	1:1	0.650	0.15	22.72	23.00	1.067	0.694	22.5
Left side	20	QPSK 50_0	21100/2535	1:1	0.069	0.18	22.72	23.00	1.067	0.074	22.5
Right side	20	QPSK 50_0	21100/2535	1:1	2.410	-0.02	22.72	23.00	1.067	2.571	22.5
Right side	20	QPSK 50_0	20850/2510	1:1	2.360	0.17	22.65	23.00	1.084	2.558	22.5
Right side	20	QPSK 50_0	21350/2560	1:1	2.380	0.03	22.71	23.00	1.069	2.544	22.5
Top side	20	QPSK 50_0	21100/2535	1:1	0.256	0.18	22.72	23.00	1.067	0.273	22.5
Bottom side	20	QPSK 50_0	21100/2535	1:1	0.000	0.00	22.72	23.00	1.067	0.000	22.5
Extremity Test data (Separate 0mm 100%RB)											
Right side	20	QPSK 100_0	21100/2535	1:1	2.390	-0.10	22.67	23.00	1.079	2.579	22.5

Test Position	Test ch./Freq.	Measured SAR (W/kg)	1 st Repeated	Ratio	2 nd Repeated	3 rd Repeated
Right side 0mm	21100/2535	2.560	2.530	1.012	N/A	N/A

Note: 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.

2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).

3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

5) The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds. The repeated measurement results must be clearly identified in the SAR report.

8.3.7 SAR Result of LTE Band 12(17)

Ant1											
Test position	BW.	Test mode	Test ch./Freq.	Duty Cycle	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test data (Separate 0mm 1RB)											
Front side	10	QPSK 1_0	23095/707.5	1:1	0.087	0.19	22.94	24.00	1.276	0.111	22.4
Back side	10	QPSK 1_0	23095/707.5	1:1	0.513	-0.17	22.94	24.00	1.276	0.655	22.4
Left side	10	QPSK 1_0	23095/707.5	1:1	0.112	-0.09	22.94	24.00	1.276	0.143	22.4
Right side	10	QPSK 1_0	23095/707.5	1:1	0.885	0.03	22.94	24.00	1.276	1.129	22.4
Top side	10	QPSK 1_0	23095/707.5	1:1	0.207	-0.06	22.94	24.00	1.276	0.264	22.4
Bottom side	10	QPSK 1_0	23095/707.5	1:1	0.000	0.00	22.94	24.00	1.276	0.000	22.4
Extremity Test data (Separate 0mm 50%RB)											
Front side	10	QPSK 25_0	23095/707.5	1:1	0.069	-0.03	22.25	23.00	1.189	0.082	22.4
Back side	10	QPSK 25_0	23095/707.5	1:1	0.433	-0.15	22.25	23.00	1.189	0.515	22.4
Left side	10	QPSK 25_0	23095/707.5	1:1	0.076	0.04	22.25	23.00	1.189	0.090	22.4
Right side	10	QPSK 25_0	23095/707.5	1:1	0.754	0.05	22.25	23.00	1.189	0.897	22.4
Top side	10	QPSK 25_0	23095/707.5	1:1	0.175	-0.03	22.25	23.00	1.189	0.208	22.4
Bottom side	10	QPSK 25_0	23095/707.5	1:1	0.000	0.00	22.25	23.00	1.189	0.000	22.4

8.3.8 SAR Result of LTE Band 13

Ant1											
Test position	BW.	Test mode	Test ch./Freq.	Duty Cycle	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test data (Separate 0mm 1RB)											
Front side	10	QPSK 1_0	23230/782	1:1	0.064	0.07	23.70	24.00	1.072	0.069	22.4
Back side	10	QPSK 1_0	23230/782	1:1	0.638	0.05	23.70	24.00	1.072	0.684	22.4
Left side	10	QPSK 1_0	23230/782	1:1	0.069	-0.04	23.70	24.00	1.072	0.074	22.4
Right side	10	QPSK 1_0	23230/782	1:1	1.130	-0.02	23.70	24.00	1.072	1.211	22.4
Top side	10	QPSK 1_0	23230/782	1:1	0.172	-0.11	23.70	24.00	1.072	0.184	22.4
Bottom side	10	QPSK 1_0	23230/782	1:1	0.000	0.00	23.70	24.00	1.072	0.000	22.4
Extremity Test data (Separate 0mm 50%RB)											
Front side	10	QPSK 25_0	23230/782	1:1	0.053	-0.01	22.44	23.00	1.138	0.060	22.4
Back side	10	QPSK 25_0	23230/782	1:1	0.501	0.01	22.44	23.00	1.138	0.570	22.4
Left side	10	QPSK 25_0	23230/782	1:1	0.044	0.01	22.44	23.00	1.138	0.050	22.4
Right side	10	QPSK 25_0	23230/782	1:1	0.923	0.18	22.44	23.00	1.138	1.050	22.4
Top side	10	QPSK 25_0	23230/782	1:1	0.130	-0.08	22.44	23.00	1.138	0.148	22.4
Bottom side	10	QPSK 25_0	23230/782	1:1	0.000	0.00	22.44	23.00	1.138	0.000	22.4

8.3.9 SAR Result of LTE Band 25(2)

Ant1											
Test position	BW.	Test mode	Test ch./Freq.	Duty Cycle	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test data (Separate 0mm 1RB)											
Front side	20	QPSK 1_0	26365/1882.5	1:1	0.073	-0.04	23.27	24.00	1.183	0.086	22.6
Back side	20	QPSK 1_0	26365/1882.5	1:1	0.547	0.11	23.27	24.00	1.183	0.647	22.6
Left side	20	QPSK 1_0	26365/1882.5	1:1	0.076	0.02	23.27	24.00	1.183	0.090	22.6
Right side	20	QPSK 1_0	26365/1882.5	1:1	1.860	0.01	23.27	24.00	1.183	2.200	22.6
Right side	20	QPSK 1_0	26140/1860	1:1	1.830	-0.15	23.23	24.00	1.194	2.185	22.6
Right side	20	QPSK 1_0	26590/1905	1:1	1.810	-0.03	23.22	24.00	1.197	2.167	22.6
Top side	20	QPSK 1_0	26365/1882.5	1:1	0.422	-0.15	23.27	24.00	1.183	0.499	22.6
Bottom side	20	QPSK 1_0	26365/1882.5	1:1	0.000	0.00	23.27	24.00	1.183	0.000	22.6
Extremity Test data (Separate 0mm 50%RB)											
Front side	20	QPSK 50_0	26365/1882.5	1:1	0.069	0.18	22.26	23.00	1.186	0.082	22.6
Back side	20	QPSK 50_0	26365/1882.5	1:1	0.505	-0.03	22.26	23.00	1.186	0.599	22.6
Left side	20	QPSK 50_0	26365/1882.5	1:1	0.072	0.03	22.26	23.00	1.186	0.085	22.6
Right side	20	QPSK 50_0	26365/1882.5	1:1	1.770	-0.07	22.26	23.00	1.186	2.099	22.6
Right side	20	QPSK 50_0	26140/1860	1:1	1.730	0.16	22.21	23.00	1.199	2.074	22.6
Right side	20	QPSK 50_0	26590/1905	1:1	1.690	0.10	22.16	23.00	1.213	2.050	22.6
Top side	20	QPSK 50_0	26365/1882.5	1:1	0.404	-0.16	22.26	23.00	1.186	0.479	22.6
Bottom side	20	QPSK 50_0	26365/1882.5	1:1	0.000	0.00	22.26	23.00	1.186	0.000	22.6
Extremity Test data (Separate 0mm 100%RB)											
Right side	20	QPSK 100_0	26365/1882.5	1:1	1.710	-0.10	22.23	23.00	1.194	2.042	22.6

8.3.10 SAR Result of LTE Band 26(5)

Ant1											
Test position	BW.	Test mode	Test ch./Freq.	Duty Cycle	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test data (Separate 0mm 1RB)											
Front side	15	QPSK 1_0	26865/831.5	1:1	0.076	-0.05	23.37	24.00	1.156	0.088	22.3
Back side	15	QPSK 1_0	26865/831.5	1:1	0.401	-0.19	23.37	24.00	1.156	0.464	22.3
Left side	15	QPSK 1_0	26865/831.5	1:1	0.028	0.12	23.37	24.00	1.156	0.032	22.3
Right side	15	QPSK 1_0	26865/831.5	1:1	0.910	-0.02	23.37	24.00	1.156	1.052	22.3
Top side	15	QPSK 1_0	26865/831.5	1:1	0.070	-0.08	23.37	24.00	1.156	0.081	22.3
Bottom side	15	QPSK 1_0	26865/831.5	1:1	0.000	0.00	23.37	24.00	1.156	0.000	22.3
Extremity Test data (Separate 0mm 50%RB)											
Front side	15	QPSK 36_0	26865/831.5	1:1	0.066	0.16	22.32	23.00	1.169	0.077	22.3
Back side	15	QPSK 36_0	26865/831.5	1:1	0.316	-0.15	22.32	23.00	1.169	0.369	22.3
Left side	15	QPSK 36_0	26865/831.5	1:1	0.023	0.08	22.32	23.00	1.169	0.027	22.3
Right side	15	QPSK 36_0	26865/831.5	1:1	0.733	-0.16	22.32	23.00	1.169	0.857	22.3
Top side	15	QPSK 36_0	26865/831.5	1:1	0.055	0.13	22.32	23.00	1.169	0.064	22.3
Bottom side	15	QPSK 36_0	26865/831.5	1:1	0.000	0.00	22.32	23.00	1.169	0.000	22.3

8.3.11 SAR Result of LTE Band 30

Ant1											
Test position	BW.	Test mode	Test ch./Freq.	Duty Cycle	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test data (Separate 0mm 1RB)											
Front side	10	QPSK 1_0	27710/2310	1:1	0.031	0.10	23.38	24.00	1.153	0.036	22.4
Back side	10	QPSK 1_0	27710/2310	1:1	0.605	-0.18	23.38	24.00	1.153	0.698	22.4
Left side	10	QPSK 1_0	27710/2310	1:1	0.080	-0.09	23.38	24.00	1.153	0.092	22.4
Right side	10	QPSK 1_0	27710/2310	1:1	1.700	-0.02	23.38	24.00	1.153	1.960	22.4
Top side	10	QPSK 1_0	27710/2310	1:1	0.415	-0.02	23.38	24.00	1.153	0.478	22.4
Bottom side	10	QPSK 1_0	27710/2310	1:1	0.000	0.00	23.38	24.00	1.153	0.000	22.4
Extremity Test data (Separate 0mm 50%RB)											
Front side	10	QPSK 25_0	27710/2310	1:1	0.026	0.10	22.66	23.00	1.081	0.028	22.4
Back side	10	QPSK 25_0	27710/2310	1:1	0.477	0.04	22.66	23.00	1.081	0.516	22.4
Left side	10	QPSK 25_0	27710/2310	1:1	0.064	0.04	22.66	23.00	1.081	0.069	22.4
Right side	10	QPSK 25_0	27710/2310	1:1	1.440	0.06	22.66	23.00	1.081	1.557	22.4
Top side	10	QPSK 25_0	27710/2310	1:1	0.325	-0.06	22.66	23.00	1.081	0.351	22.4
Bottom side	10	QPSK 25_0	27710/2310	1:1	0.000	0.00	22.66	23.00	1.081	0.000	22.4

8.3.12 SAR Result of LTE Band 41(38)

Ant1											
Test position	BW.	Test mode	Test ch./Freq.	Duty Cycle	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test data (Separate 0mm 1RB)											
Front side	20	QPSK 1_0	40620/2593	1:1.58	0.051	0.02	23.95	24.50	1.135	0.058	22.5
Back side	20	QPSK 1_0	40620/2593	1:1.58	1.056	0.05	23.95	24.50	1.135	1.199	22.5
Left side	20	QPSK 1_0	40620/2593	1:1.58	0.066	0.06	23.95	24.50	1.135	0.075	22.5
Right side	20	QPSK 1_0	40620/2593	1:1.58	2.530	-0.15	23.95	24.50	1.135	2.872	22.5
Right side-repeated	20	QPSK 1_0	40620/2593	1:1.58	2.490	0.03	23.95	24.50	1.135	2.826	22.5
Right side	20	QPSK 1_0	39750/2506	1:1.58	2.430	-0.03	23.84	24.50	1.164	2.829	22.5
Right side	20	QPSK 1_0	40185/2549.5	1:1.58	2.300	0.05	23.67	24.50	1.211	2.785	22.5
Right side	20	QPSK 1_0	41055/2636.5	1:1.58	2.490	-0.01	23.92	24.50	1.143	2.846	22.5
Right side	20	QPSK 1_0	41490/2680	1:1.58	2.250	-0.17	23.60	24.50	1.230	2.768	22.5
Top side	20	QPSK 1_0	40620/2593	1:1.58	0.199	0.08	23.95	24.50	1.135	0.226	22.5
Bottom side	20	QPSK 1_0	40620/2593	1:1.58	0.000	0.00	23.95	24.50	1.135	0.000	22.5
Extremity Test data (Separate 0mm 50%RB)											
Front side	20	QPSK 50_0	40620/2593	1:1.58	0.032	-0.04	22.95	23.50	1.135	0.036	22.5
Back side	20	QPSK 50_0	40620/2593	1:1.58	0.822	-0.09	22.95	23.50	1.135	0.933	22.5
Left side	20	QPSK 50_0	40620/2593	1:1.58	0.050	-0.13	22.95	23.50	1.135	0.057	22.5
Right side	20	QPSK 50_0	40620/2593	1:1.58	1.970	-0.04	22.95	23.50	1.135	2.236	22.5
Right side	20	QPSK 50_0	39750/2506	1:1.58	1.640	0.19	22.81	23.50	1.172	1.922	22.5
Right side	20	QPSK 50_0	40185/2549.5	1:1.58	1.500	-0.02	22.63	23.50	1.222	1.833	22.5
Right side	20	QPSK 50_0	41055/2636.5	1:1.58	1.770	0.19	22.97	23.50	1.130	2.000	22.5
Right side	20	QPSK 50_0	41490/2680	1:1.58	1.470	-0.05	22.57	23.50	1.239	1.821	22.5
Top side	20	QPSK 50_0	40620/2593	1:1.58	0.161	0.19	22.95	23.50	1.135	0.183	22.5
Bottom side	20	QPSK 50_0	40620/2593	1:1.58	0.000	0.00	22.95	23.50	1.135	0.000	22.5
Extremity Test data (Separate 0mm 100%RB)											
Right side	20	QPSK 100_0	40620/2593	1:1.58	1.770	0.13	22.89	23.50	1.151	2.037	22.5

Test Position	Test ch./Freq.	Measured SAR (W/kg)	1 st Repeated	Ratio	2 nd Repeated	3 rd Repeated
Right side 0mm	40620/2593	2.530	2.490	1.016	N/A	N/A

Note: 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.

2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).

3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

5) The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds. The repeated measurement results must be clearly identified in the SAR report.

8.3.13 SAR Result of LTE Band 66(4)

Ant1											
Test position	BW.	Test mode	Test ch./Freq.	Duty Cycle	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test data (Separate 0mm 1RB)											
Front side	20	QPSK 1_0	132322/1745	1:1	0.069	0.00	23.89	24.00	1.026	0.071	22.4
Back side	20	QPSK 1_0	132322/1745	1:1	0.675	0.16	23.89	24.00	1.026	0.693	22.4
Left side	20	QPSK 1_0	132322/1745	1:1	0.076	0.12	23.89	24.00	1.026	0.078	22.4
Right side	20	QPSK 1_0	132322/1745	1:1	1.650	-0.05	23.89	24.00	1.026	1.693	22.4
Top side	20	QPSK 1_0	132322/1745	1:1	0.255	0.19	23.89	24.00	1.026	0.262	22.4
Bottom side	20	QPSK 1_0	132322/1745	1:1	0.000	0.00	23.89	24.00	1.026	0.000	22.4
Extremity Test data (Separate 0mm 50%RB)											
Front side	20	QPSK 50_0	132322/1745	1:1	0.057	-0.18	22.95	23.00	1.012	0.058	22.4
Back side	20	QPSK 50_0	132322/1745	1:1	0.536	0.14	22.95	23.00	1.012	0.542	22.4
Left side	20	QPSK 50_0	132322/1745	1:1	0.057	0.08	22.95	23.00	1.012	0.058	22.4
Right side	20	QPSK 50_0	132322/1745	1:1	1.340	0.04	22.95	23.00	1.012	1.356	22.4
Top side	20	QPSK 50_0	132322/1745	1:1	0.244	0.09	22.95	23.00	1.012	0.247	22.4
Bottom side	20	QPSK 50_0	132322/1745	1:1	0.000	0.00	22.95	23.00	1.012	0.000	22.4

8.3.14 SAR Result of LTE Band 71

Ant1											
Test position	BW.	Test mode	Test ch./Freq.	Duty Cycle	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test data (Separate 0mm 1RB)											
Front side	20	QPSK 1_0	133322/683	1:1	0.096	-0.09	23.45	24.00	1.135	0.109	22.4
Back side	20	QPSK 1_0	133322/683	1:1	0.411	-0.19	23.45	24.00	1.135	0.466	22.4
Left side	20	QPSK 1_0	133322/683	1:1	0.070	-0.18	23.45	24.00	1.135	0.079	22.4
Right side	20	QPSK 1_0	133322/683	1:1	0.679	0.17	23.45	24.00	1.135	0.771	22.4
Top side	20	QPSK 1_0	133322/683	1:1	0.158	0.10	23.45	24.00	1.135	0.179	22.4
Bottom side	20	QPSK 1_0	133322/683	1:1	0.000	0.00	23.45	24.00	1.135	0.000	22.4
Extremity Test data (Separate 0mm 50%RB)											
Front side	20	QPSK 50_0	133322/683	1:1	0.084	-0.19	22.63	23.00	1.089	0.091	22.4
Back side	20	QPSK 50_0	133322/683	1:1	0.355	-0.19	22.63	23.00	1.089	0.387	22.4
Left side	20	QPSK 50_0	133322/683	1:1	0.060	-0.11	22.63	23.00	1.089	0.065	22.4
Right side	20	QPSK 50_0	133322/683	1:1	0.604	0.04	22.63	23.00	1.089	0.658	22.4
Top side	20	QPSK 50_0	133322/683	1:1	0.143	-0.11	22.63	23.00	1.089	0.156	22.4
Bottom side	20	QPSK 50_0	133322/683	1:1	0.000	0.00	22.63	23.00	1.089	0.000	22.4

8.3.15 SAR Result of WiFi 2.4G

Ant2											
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test data (Separate 0mm)											
Front side	802.11b	1/2412	98.49%	1.015	0.051	0.05	18.02	19.00	1.253	0.065	22.3
Back side	802.11b	1/2412	98.49%	1.015	0.028	0.05	18.02	19.00	1.253	0.036	22.3
Left side	802.11b	1/2412	98.49%	1.015	0.000	0.00	18.02	19.00	1.253	0.000	22.3
Right side	802.11b	1/2412	98.49%	1.015	0.233	-0.05	18.02	19.00	1.253	0.296	22.3
Top side	802.11b	1/2412	98.49%	1.015	0.000	0.00	18.02	19.00	1.253	0.000	22.3
Bottom side	802.11b	1/2412	98.49%	1.015	0.029	0.03	18.02	19.00	1.253	0.037	22.3

8.3.16 SAR Result of WiFi 5G

Ant2											
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test Data of U-NII-2A (Separate 0mm)											
Front side	802.11ac VHT80	58/5290	92.81%	1.077	0.048	0.19	17.96	19.00	1.271	0.066	22.4
Back side	802.11ac VHT80	58/5290	92.81%	1.077	0.125	-0.07	17.96	19.00	1.271	0.171	22.4
Left side	802.11ac VHT80	58/5290	92.81%	1.077	0.000	0.00	17.96	19.00	1.271	0.000	22.4
Right side	802.11ac VHT80	58/5290	92.81%	1.077	0.571	-0.02	17.96	19.00	1.271	0.782	22.4
Top side	802.11ac VHT80	58/5290	92.81%	1.077	0.000	0.00	17.96	19.00	1.271	0.000	22.4
Bottom side	802.11ac VHT80	58/5290	92.81%	1.077	0.000	0.00	17.96	19.00	1.271	0.000	22.4
Extremity Test Data of U-NII-2C (Separate 0mm)											
Front side	802.11ac VHT80	106/5530	92.81%	1.077	0.037	0.15	18.20	19.00	1.202	0.048	22.3
Back side	802.11ac VHT80	106/5530	92.81%	1.077	0.164	0.10	18.20	19.00	1.202	0.212	22.3
Left side	802.11ac VHT80	106/5530	92.81%	1.077	0.025	-0.10	18.20	19.00	1.202	0.032	22.3
Right side	802.11ac VHT80	106/5530	92.81%	1.077	0.500	0.05	18.20	19.00	1.202	0.647	22.3
Top side	802.11ac VHT80	106/5530	92.81%	1.077	0.000	0.00	18.20	19.00	1.202	0.000	22.3
Bottom side	802.11ac VHT80	106/5530	92.81%	1.077	0.000	0.00	18.20	19.00	1.202	0.000	22.3
Extremity Test Data of U-NII-3 (Separate 0mm)											
Front side	802.11ac VHT80	155/5775	92.81%	1.077	0.000	0.00	10.02	11.00	1.253	0.000	22.4
Back side	802.11ac VHT80	155/5775	92.81%	1.077	0.000	0.00	10.02	11.00	1.253	0.000	22.4
Left side	802.11ac VHT80	155/5775	92.81%	1.077	0.000	0.00	10.02	11.00	1.253	0.000	22.4
Right side	802.11ac VHT80	155/5775	92.81%	1.077	0.072	-0.18	10.02	11.00	1.253	0.097	22.4
Top side	802.11ac VHT80	155/5775	92.81%	1.077	0.000	0.00	10.02	11.00	1.253	0.000	22.4
Bottom side	802.11ac VHT80	155/5775	92.81%	1.077	0.000	0.00	10.02	11.00	1.253	0.000	22.4

8.3.17 SAR Result of BT

Ant2											
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test data (Separate 0mm)											
Front side	3DH5	39/2441	77.65%	1.288	0.000	0.00	9.39	10.00	1.151	0.000	22.3
Back side	3DH5	39/2441	77.65%	1.288	0.000	0.00	9.39	10.00	1.151	0.000	22.3
Left side	3DH5	39/2441	77.65%	1.288	0.000	0.00	9.39	10.00	1.151	0.000	22.3
Right side	3DH5	39/2441	77.65%	1.288	0.025	0.09	9.39	10.00	1.151	0.037	22.3
Top side	3DH5	39/2441	77.65%	1.288	0.000	0.00	9.39	10.00	1.151	0.000	22.3
Bottom side	3DH5	39/2441	77.65%	1.288	0.000	0.00	9.39	10.00	1.151	0.000	22.3

8.4 Multiple Transmitter Evaluation

8.4.1 Simultaneous SAR test evaluation

No.	Simultaneous Tx Combination	Extremity
1	WWAN+Bluetooth+WLAN2.4G+WLAN5G	Yes

8.4.2 Simultaneous Transmission SAR Summation Scenario

Extremity 0mm:

Test position		SARmax (W/kg)				Summed SAR
		Main Ant1	WiFi 2.4G Ant2(chain0)	WiFi 5G Ant2(chain0)	BT	
		1	2	3	5	
		1	2	3	5	1+2+3+5
GSM850	Front side	0.145	0.065	0.066	0.000	0.276
	Back side	0.584	0.036	0.212	0.000	0.832
	Left side	0.092	0.000	0.032	0.000	0.124
	Right side	1.197	0.296	0.782	0.037	2.312
	Top side	0.120	0.000	0.000	0.000	0.120
	Bottom side	0.000	0.037	0.000	0.000	0.037
GSM1900	Front side	0.069	0.065	0.066	0.000	0.200
	Back side	0.603	0.036	0.212	0.000	0.851
	Left side	0.219	0.000	0.032	0.000	0.251
	Right side	2.133	0.296	0.782	0.037	3.248
	Top side	0.250	0.000	0.000	0.000	0.250
	Bottom side	0.000	0.037	0.000	0.000	0.037
WCDMA II	Front side	0.082	0.065	0.066	0.000	0.213
	Back side	0.690	0.036	0.212	0.000	0.938
	Left side	0.081	0.000	0.032	0.000	0.113
	Right side	2.410	0.296	0.782	0.037	3.525
	Top side	0.487	0.000	0.000	0.000	0.487
	Bottom side	0.000	0.037	0.000	0.000	0.037
WCDMA IV	Front side	0.069	0.065	0.066	0.000	0.200
	Back side	0.751	0.036	0.212	0.000	0.999
	Left side	0.084	0.000	0.032	0.000	0.116
	Right side	1.895	0.296	0.782	0.037	3.010
	Top side	0.286	0.000	0.000	0.000	0.286
	Bottom side	0.000	0.037	0.000	0.000	0.037
WCDMA V	Front side	0.149	0.065	0.066	0.000	0.280
	Back side	0.560	0.036	0.212	0.000	0.808
	Left side	0.054	0.000	0.032	0.000	0.086
	Right side	1.220	0.296	0.782	0.037	2.335
	Top side	0.068	0.000	0.000	0.000	0.068
	Bottom side	0.000	0.037	0.000	0.000	0.037
LTE B7	Front side	0.039	0.065	0.066	0.000	0.170
	Back side	0.711	0.036	0.212	0.000	0.959
	Left side	0.074	0.000	0.032	0.000	0.106
	Right side	2.698	0.296	0.782	0.037	3.813
	Top side	0.273	0.000	0.000	0.000	0.273
	Bottom side	0.000	0.037	0.000	0.000	0.037
LTE B12(17)	Front side	0.111	0.065	0.066	0.000	0.242
	Back side	0.655	0.036	0.212	0.000	0.903
	Left side	0.143	0.000	0.032	0.000	0.175
	Right side	1.129	0.296	0.782	0.037	2.244
	Top side	0.264	0.000	0.000	0.000	0.264
	Bottom side	0.000	0.037	0.000	0.000	0.037
LTE B13	Front side	0.069	0.065	0.066	0.000	0.200
	Back side	0.684	0.036	0.212	0.000	0.932
	Left side	0.074	0.000	0.032	0.000	0.106
	Right side	1.211	0.296	0.782	0.037	2.326
	Top side	0.184	0.000	0.000	0.000	0.184
	Bottom side	0.000	0.037	0.000	0.000	0.037
LTE B25(2)	Front side	0.086	0.065	0.066	0.000	0.217
	Back side	0.647	0.036	0.212	0.000	0.895
	Left side	0.090	0.000	0.032	0.000	0.122
	Right side	2.200	0.296	0.782	0.037	3.315
	Top side	0.499	0.000	0.000	0.000	0.499
	Bottom side	0.000	0.037	0.000	0.000	0.037
LTE B26(5)	Front side	0.088	0.065	0.066	0.000	0.219
	Back side	0.464	0.036	0.212	0.000	0.712

	Left side	0.032	0.000	0.032	0.000	0.064
	Right side	1.052	0.296	0.782	0.037	2.167
	Top side	0.081	0.000	0.000	0.000	0.081
	Bottom side	0.000	0.037	0.000	0.000	0.037
LTE B30	Front side	0.036	0.065	0.066	0.000	0.167
	Back side	0.698	0.036	0.212	0.000	0.946
	Left side	0.092	0.000	0.032	0.000	0.124
	Right side	1.960	0.296	0.782	0.037	3.075
	Top side	0.478	0.000	0.000	0.000	0.478
	Bottom side	0.000	0.037	0.000	0.000	0.037
LTE B41(38)	Front side	0.058	0.065	0.066	0.000	0.189
	Back side	1.199	0.036	0.212	0.000	1.447
	Left side	0.075	0.000	0.032	0.000	0.107
	Right side	2.872	0.296	0.782	0.037	3.987
	Top side	0.226	0.000	0.000	0.000	0.226
	Bottom side	0.000	0.037	0.000	0.000	0.037
LTE B66	Front side	0.071	0.065	0.066	0.000	0.202
	Back side	0.693	0.036	0.212	0.000	0.941
	Left side	0.078	0.000	0.032	0.000	0.110
	Right side	1.693	0.296	0.782	0.037	2.808
	Top side	0.262	0.000	0.000	0.000	0.262
	Bottom side	0.000	0.037	0.000	0.000	0.037
LTE B71	Front side	0.109	0.065	0.066	0.000	0.240
	Back side	0.466	0.036	0.212	0.000	0.714
	Left side	0.079	0.000	0.032	0.000	0.111
	Right side	0.771	0.296	0.782	0.037	1.886
	Top side	0.179	0.000	0.000	0.000	0.179
	Bottom side	0.000	0.037	0.000	0.000	0.037

9 Equipment list

Test Platform		SPEAG DASY Professional				
Software Reference		DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)				
Hardware Reference						
Equipment		Manufacturer	Model	Serial Number	Calibration Date	Due date of calibration
☒	Test Phantom	SPEAG	SAM Twin	1609	NCR	NCR
☒	Test Phantom	SPEAG	ELI V5.0	1239	NCR	NCR
☒	DAE	SPEAG	DAE4	1245	2025-09-08	2026-09-07
☒	DAE	SPEAG	DAE4	1374	2026-02-02	2027-02-01
☒	E-Field Probe	SPEAG	EX3DV4	3982	2025-11-07	2026-11-06
☒	E-Field Probe	SPEAG	EX3DV4	3923	2026-01-12	2027-01-11
☒	Validation Kits	SPEAG	CLA13	1032	2026-02-18	2029-02-17
☒	Validation Kits	SPEAG	D750V3	1214	2025-04-01	2028-03-31
☒	Validation Kits	SPEAG	D835V2	4d161	2023-08-25	2026-08-24
☒	Validation Kits	SPEAG	D1750V2	1105	2023-11-03	2026-11-02
☒	Validation Kits	SPEAG	D1950V3	1138	2025-10-15	2028-10-15
☒	Validation Kits	SPEAG	D2300V2	1096	2025-04-01	2028-03-31
☒	Validation Kits	SPEAG	D2450V2	922	2023-08-28	2026-08-27
☒	Validation Kits	SPEAG	D2600V2	1158	2025-03-31	2028-03-30
☒	Validation Kits	SPEAG	D5GHzV2	1174	2023-08-23	2026-08-22
☒	Dielectric parameter probes	SPEAG	DAKS-3.5	1120	2025-08-25	2026-08-24
☒	Vector Network Analyzer and Vector Reflectometer	SPEAG	DAKS_VNA R140	50920	2025-08-25	2026-08-24
☒	Universal Radio Communication Tester	R&S	CMW500	111637	2026-01-15	2027-01-14
☒	RF Bi-Directional Coupler	Agilent	86205-60001	MY31400031	NCR	NCR
☒	Signal Generator	R&S	SMB100A	182393	2026-01-14	2027-01-13
☒	Preamplifier	Qiji	YX28980933	202104001	NCR	NCR
☒	USB Average Power Sensor	Keysight	U2002H	MY5639004	2025-08-25	2026-08-24
☒	USB Average Power Sensor	Agilent	U2002H	MY48200110	2025-11-20	2026-11-19
☒	Attenuator	SHX	TS2-3dB	30704	NCR	NCR
☒	Coaxial low pass filter	Mini-Circuits	VLF-2500(+)	NA	NCR	NCR
☒	Coaxial low pass filter	Microlab Fxr	LA-F13	NA	NCR	NCR
☒	DC POWER SUPPLY	SAKO	SK1730SL5A	NA	NCR	NCR
☒	Speed reading thermometer	DTM SPEZLAL	DTM3000	NA	2025-09-17	2026-09-16
☒	Humidity and Temperature Indicator	ASONE	THA-02L	2201-1017	2025-09-16	2026-09-15

Note: All the equipment are within the valid period when the tests are performed.



Report No.: SUCR260700064601
Page: 67 of 67

10 Calibration certificate

Please see the Appendix C

11 Photographs

Please see the Appendix D

Appendix A: Detailed System Check Results

Appendix B: Detailed Test Results

Appendix C: Calibration certificate

Appendix D: Photographs

Appendix E: Conducted RF Output Power

--- End of report ---