

WCDMA Band V Front Side Mode Middle 0mm

Date/Time: 2024/1/15

Electronics: DAE4 Sn1244

Medium parameters used: $f = 837 \text{ MHz}$; $\sigma = 0.922 \text{ S/m}$; $\epsilon_r = 40.613$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 20.9°C Liquid Temperature: 20.0°C

Communication System: WCDMA Band V; Frequency: 836.6 MHz ; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(10.66, 10.66, 10.66) @ 836.6 MHz

WCDMA Band V Front Side Mode Middle 0mm/Area Scan (7x11x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.903 W/kg

WCDMA Band V Front Side Mode Middle 0mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 17.09 V/m ; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 1.25 W/kg

SAR(1 g) = 0.706 W/kg ; SAR(10 g) = 0.431 W/kg

Maximum value of SAR (measured) = 1.05 W/kg




Figure A.1-10 WCDMA Band V Front Side Mode Middle 0mm

LTE B2 20MHz 1RB 50offset Front Side Mode High 5mm

Date/Time: 2024/1/16

Electronics: DAE4 Sn1244

Medium parameters used: $f = 1900 \text{ MHz}$; $\sigma = 1.434 \text{ S/m}$; $\epsilon_r = 39.341$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 21.1°C Liquid Temperature: 20.1°C

Communication System: LTE B2 1900MHz; Frequency: 1900 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(8.67, 8.67, 8.67) @ 1900 MHz

LTE B2 20MHz 1RB 50offset Front Side Mode High 5mm/Area Scan (7x11x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.995 W/kg

LTE B2 20MHz 1RB 50offset Front Side Mode High 5mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.60 V/m ; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 1.43 W/kg

SAR(1 g) = 0.831 W/kg ; SAR(10 g) = 0.477 W/kg

Maximum value of SAR (measured) = 1.16 W/kg




Figure A.1-11 LTE B2 20MHz 1RB 50offset Front Side Mode High 5mm

LTE B2 20MHz 1RB 50offset Front Side Mode Middle 0mm

Date/Time: 2024/1/16

Electronics: DAE4 Sn1244

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.423 \text{ S/m}$; $\epsilon_r = 39.377$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 21.1°C Liquid Temperature: 20.1°C

Communication System: LTE B2 1900MHz; Frequency: 1880 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(8.67, 8.67, 8.67) @ 1880 MHz

LTE B2 20MHz 1RB 50offset Front Side Mode Middle 0mm/Area Scan (7x11x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 2.08 W/kg

LTE B2 20MHz 1RB 50offset Front Side Mode Middle 0mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 7.778 V/m ; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 4.06 W/kg

SAR(1 g) = 2.1 W/kg ; SAR(10 g) = 1.08 W/kg

Maximum value of SAR (measured) = 3.24 W/kg




Figure A.1-12 LTE B2 20MHz 1RB 50offset Front Side Mode Middle 0mm

LTE B4 20MHz 1RB 50offset Front Side Mode High 5mm

Date/Time: 2024/1/15

Electronics: DAE4 Sn1244

Medium parameters used: $f = 1745 \text{ MHz}$; $\sigma = 1.339 \text{ S/m}$; $\epsilon_r = 39.588$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 20.9°C Liquid Temperature: 20.0°C

Communication System: LTE B4 1900MHz; Frequency: 1745 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(8.96, 8.96, 8.96) @ 1745 MHz

LTE B4 20MHz 1RB 50offset Front Side Mode High 5mm/Area Scan (7x11x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 1.06 W/kg

LTE B4 20MHz 1RB 50offset Front Side Mode High 5mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.89 V/m ; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.33 W/kg

SAR(1 g) = 0.786 W/kg ; SAR(10 g) = 0.456 W/kg

Maximum value of SAR (measured) = 1.11 W/kg




Figure A.1-13 LTE B4 20MHz 1RB 50offset Front Side Mode High 5mm

LTE B4 20MHz 1RB 50offset Front Side Mode Middle 0mm

Date/Time: 2024/1/15

Electronics: DAE4 Sn1244

Medium parameters used (interpolated): $f = 1732.5 \text{ MHz}$; $\sigma = 1.332 \text{ S/m}$; $\epsilon_r = 39.606$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 20.9°C Liquid Temperature: 20.0°C

Communication System: LTE B4 1900MHz; Frequency: 1732.5 MHz ; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(8.96, 8.96, 8.96) @ 1732.5 MHz

LTE B4 20MHz 1RB 50offset Front Side Mode Middle 0mm/Area Scan (7x11x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 2.10 W/kg

LTE B4 20MHz 1RB 50offset Front Side Mode Middle 0mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 8.670 V/m ; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 3.80 W/kg

SAR(1 g) = 1.99 W/kg ; SAR(10 g) = 1.04 W/kg

Maximum value of SAR (measured) = 2.93 W/kg




Figure A.1-14 LTE B4 20MHz 1RB 50offset Front Side Mode Middle 0mm

LTE B5 10MHz 25RB 0offset Right Side Mode High 5mm

Date/Time: 2024/1/2

Electronics: DAE4 Sn1244

Medium parameters used: $f = 844 \text{ MHz}$; $\sigma = 0.921 \text{ S/m}$; $\epsilon_r = 41.801$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 21.3°C Liquid Temperature: 20.2°C

Communication System: LTE B5 900MHz; Frequency: 844 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(10.66, 10.66, 10.66) @ 844 MHz

LTE B5 10MHz 25RB 0offset Right Side Mode High 5mm/Area Scan (5x11x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.800 W/kg

LTE B5 10MHz 25RB 0offset Right Side Mode High 5mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 11.09 V/m ; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.70 W/kg

SAR(1 g) = 0.879 W/kg ; SAR(10 g) = 0.473 W/kg

Maximum value of SAR (measured) = 1.32 W/kg




Figure A.1-15 LTE B5 10MHz 25RB 0offset Right Side Mode High 5mm

LTE B5 10MHz 1RB 25offset Right Side Mode Middle 0mm

Date/Time: 2024/1/2

Electronics: DAE4 Sn1244

Medium parameters used (interpolated): $f = 836.5 \text{ MHz}$; $\sigma = 0.918 \text{ S/m}$; $\epsilon_r = 41.829$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 21.3°C Liquid Temperature: 20.2°C

Communication System: LTE B5 900MHz; Frequency: 836.5 MHz ; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(10.66, 10.66, 10.66) @ 836.5 MHz

LTE B5 10MHz 1RB 25offset Right Side Mode Middle 0mm/Area Scan (5x11x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 2.03 W/kg

LTE B5 10MHz 1RB 25offset Right Side Mode Middle 0mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 12.23 V/m ; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 4.11 W/kg

SAR(1 g) = 1.99 W/kg ; SAR(10 g) = 1.03 W/kg

Maximum value of SAR (measured) = 3.29 W/kg




Figure A.1-16 LTE B5 10MHz 1RB 25offset Right Side Mode Middle 0mm

LTE B7 20MHz 1RB 50offset Front Side Mode Low 5mm

Date/Time: 2023/12/28

Electronics: DAE4 Sn1244

Medium parameters used: $f = 2510 \text{ MHz}$; $\sigma = 1.856 \text{ S/m}$; $\epsilon_r = 38.101$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 21.4°C Liquid Temperature: 20.3°C

Communication System: LTE B7 2600MHz; Frequency: 2510 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(8.07, 8.07, 8.07) @ 2510 MHz

LTE B7 20MHz 1RB 50offset Front Side Mode Low 5mm/Area Scan (7x11x1):

Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Maximum value of SAR (measured) = 0.880 W/kg

LTE B7 20MHz 1RB 50offset Front Side Mode Low 5mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 7.439 V/m ; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 1.35 W/kg

SAR(1 g) = 0.707 W/kg ; SAR(10 g) = 0.372 W/kg

Maximum value of SAR (measured) = 1.08 W/kg




Figure A.1-17 LTE B7 20MHz 1RB 50offset Front Side Mode Low 5mm

LTE B7 20MHz 1RB 50offset Right Side Mode Middle 0mm

Date/Time: 2023/12/28

Electronics: DAE4 Sn1244

Medium parameters used: $f = 2535 \text{ MHz}$; $\sigma = 1.875 \text{ S/m}$; $\epsilon_r = 38.058$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 21.4°C Liquid Temperature: 20.3°C

Communication System: LTE B7 2600MHz; Frequency: 2535 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(8.07, 8.07, 8.07) @ 2535 MHz

LTE B7 20MHz 1RB 50offset Right Side Mode Middle 0mm/Area Scan (5x11x1):

Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Maximum value of SAR (measured) = 2.60 W/kg

LTE B7 20MHz 1RB 50offset Right Side Mode Middle 0mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 0 V/m ; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 3.19 W/kg

SAR(1 g) = 1.43 W/kg ; SAR(10 g) = 0.610 W/kg

Maximum value of SAR (measured) = 2.58 W/kg




Figure A.1-18 LTE B7 20MHz 1RB 50offset Right Side Mode Middle 0mm

LTE B41 20MHz 1RB 50offset Right Side Mode Middle 5mm

Date/Time: 2023/12/28

Electronics: DAE4 Sn1244

Medium parameters used: $f = 2595 \text{ MHz}$; $\sigma = 1.924 \text{ S/m}$; $\epsilon_r = 37.957$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 21.4°C Liquid Temperature: 20.3°C

Communication System: LTE B41 120M 2600MHz; Frequency: 2595 MHz ; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(7.86, 7.86, 7.86) @ 2595 MHz

LTE B41 20MHz 1RB 50offset Right Side Mode Middle 5mm/Area Scan (5x11x1):

Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Maximum value of SAR (measured) = 0.737 W/kg

LTE B41 20MHz 1RB 50offset Right Side Mode Middle 5mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 1.572 V/m ; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 1.16 W/kg

SAR(1 g) = 0.573 W/kg ; SAR(10 g) = 0.269 W/kg

Maximum value of SAR (measured) = 0.966 W/kg




Figure A.1-19 LTE B41 20MHz 1RB 50offset Right Side Mode Middle 5mm

LTE B41 20MHz 1RB 50offset Right Side Mode Middle 16mm

Date/Time: 2023/12/28

Electronics: DAE4 Sn1244

Medium parameters used: $f = 2595 \text{ MHz}$; $\sigma = 1.924 \text{ S/m}$; $\epsilon_r = 37.957$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 21.4°C Liquid Temperature: 20.3°C

Communication System: LTE Band 41 Professional 2450MHz; Duty Cycle: 1:2

Probe: EX3DV4 - SN7633ConvF(7.86, 7.86, 7.86) @ 2595 MHz

LTE B41 20MHz 1RB 50offset Right Side Mode Middle 16mm/Area Scan (5x11x1):

Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Maximum value of SAR (measured) = 0.776 W/kg

LTE B41 20MHz 1RB 50offset Right Side Mode Middle 16mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 3.833 V/m ; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.25 W/kg

SAR(1 g) = 0.643 W/kg ; SAR(10 g) = 0.332 W/kg

Maximum value of SAR (measured) = 1.02 W/kg




Figure A.1-20 LTE B41 20MHz 1RB 50offset Right Side Mode Middle 16mm

LTE B41 20MHz 1RB 50offset Right Side Mode Middle 0mm

Date/Time: 2023/12/28

Electronics: DAE4 Sn1244

Medium parameters used: $f = 2595 \text{ MHz}$; $\sigma = 1.924 \text{ S/m}$; $\epsilon_r = 37.957$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 21.4°C Liquid Temperature: 20.3°C

Communication System: LTE B41 120M 2600MHz; Frequency: 2595 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(7.86, 7.86, 7.86) @ 2595 MHz

LTE B41 20MHz 1RB 50offset Right Side Mode Middle 0mm/Area Scan (5x11x1):

Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Maximum value of SAR (measured) = 1.08 W/kg

LTE B41 20MHz 1RB 50offset Right Side Mode Middle 0mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 1.080 V/m ; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 2.86 W/kg

SAR(1 g) = 1.26 W/kg ; SAR(10 g) = 0.522 W/kg

Maximum of SAR (measured) = 2.29 W/kg




Figure A.1-21 LTE B41 20MHz 1RB 50offset Right Side Mode Middle 0mm

Wi-Fi 2.4G 802.11b Right Side Mode Middle 5mm

Date/Time: 2024/1/2

Electronics: DAE4 Sn1244

Medium parameters used: $f = 2437 \text{ MHz}$; $\sigma = 1.773 \text{ S/m}$; $\epsilon_r = 38.187$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 21.2°C Liquid Temperature: 20.0°C

Communication System: WLAN 2450 2600MHz; Frequency: 2437 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(8.07, 8.07, 8.07) @ 2437 MHz

Wi-Fi 2.4G 802.11b Right Side Mode Middle 5mm/Area Scan (5x11x1):

Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Maximum value of SAR (measured) = 0.531 W/kg

Wi-Fi 2.4G 802.11b Right Side Mode Middle 5mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 10.75 V/m ; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.32 W/kg

SAR(1 g) = 0.566 W/kg ; SAR(10 g) = 0.236 W/kg

Maximum of SAR (measured) = 0.957 W/kg




Figure A.1-22 Wi-Fi 2.4G 802.11b Right Side Mode Middle 5mm

Wi-Fi 2.4G 802.11b Right Side Mode Middle 0mm

Date/Time: 2024/1/2

Electronics: DAE4 Sn1244

Medium parameters used: $f = 2437 \text{ MHz}$; $\sigma = 1.773 \text{ S/m}$; $\epsilon_r = 38.187$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 21.2°C Liquid Temperature: 20.0°C

Communication System: WLAN 2450 2600MHz; Frequency: 2437 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(8.07, 8.07, 8.07) @ 2437 MHz

Wi-Fi 2.4G 802.11b Right Side Mode Middle 0mm/Area Scan (5x11x1):

Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Maximum value of SAR (measured) = 0.921 W/kg

Wi-Fi 2.4G 802.11b Right Side Mode Middle 0mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 3.751 V/m ; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 2.11 W/kg

SAR(1 g) = 0.800 W/kg ; SAR(10 g) = 0.321 W/kg

Maximum of SAR (measured) = 1.43 W/kg




Figure A.1-23 Wi-Fi 2.4G 802.11b Right Side Mode Middle 0mm

Wi-Fi 5G U-NII-1 802.11a Right Side Mode Middle 5mm

Date/Time: 2024/1/2

Electronics: DAE4 Sn1244

Medium parameters used: $f = 5180 \text{ MHz}$; $\sigma = 4.674 \text{ S/m}$; $\epsilon_r = 35.591$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 20.9°C Liquid Temperature: 20.0°C

Communication System: 5G-U-NII-1 5GHz; Frequency: 5180 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(5.72, 5.72, 5.72) @ 5180 MHz

Wi-Fi 5G U-NII-1 802.11a Right Side Mode Middle 5mm/Area Scan (5x11x1):

Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Maximum value of SAR (measured) = 0.251 W/kg

Wi-Fi 5G U-NII-1 802.11a Right Side Mode Middle 5mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 2.544 V/m ; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.38 W/kg

SAR(1 g) = 0.209 W/kg ; SAR(10 g) = 0.062 W/kg

Maximum of SAR (measured) = 0.808 W/kg




Figure A.1-24 Wi-Fi 5G U-NII-1 802.11a Right Side Mode Middle 5mm

Wi-Fi 5G U-NII-1 802.11a Right Side Mode Middle 0mm

Date/Time: 2024/1/2

Electronics: DAE4 Sn1244

Medium parameters used: $f = 5180 \text{ MHz}$; $\sigma = 4.674 \text{ S/m}$; $\epsilon_r = 35.591$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 20.9°C Liquid Temperature: 20.0°C

Communication System: 5G-U-NII-1 5GHz; Frequency: 5180 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(5.72, 5.72, 5.72) @ 5180 MHz

Wi-Fi 5G U-NII-1 802.11a Right Side Mode Middle 0mm/Area Scan (5x11x1):

Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Maximum value of SAR (measured) = 0.482 W/kg

Wi-Fi 5G U-NII-1 802.11a Right Side Mode Middle 0mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 1.167 V/m ; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 2.88 W/kg

SAR(1 g) = 0.669 W/kg ; SAR(10 g) = 0.182 W/kg

Maximum of SAR (measured) = 1.49 W/kg




Figure A.1-25 Wi-Fi 5G U-NII-1 802.11a Right Side Mode Middle 0mm

Wi-Fi 5G U-NII-2A 802.11a Right Side Mode High 5mm

Date/Time: 2024/1/2

Electronics: DAE4 Sn1244

Medium parameters used: $f = 5320$ MHz; $\sigma = 4.829$ S/m; $\epsilon_r = 35.291$; $\rho = 1000$ kg/m³

Ambient Temperature: 20.9°C Liquid Temperature: 20.0°C

Communication System: 5G-U-NII-2A 5GHz; Frequency: 5320 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(5.72, 5.72, 5.72) @ 5320 MHz

Wi-Fi 5G U-NII-2A 802.11a Right Side Mode High 5mm/Area Scan (5x11x1):

Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 0.175 W/kg

Wi-Fi 5G U-NII-2A 802.11a Right Side Mode High 5mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 6.023 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 1.40 W/kg

SAR(1 g) = 0.247 W/kg; SAR(10 g) = 0.071 W/kg

Maximum of SAR (measured) = 0.647 W/kg




Figure A.1-26 Wi-Fi 5G U-NII-2A 802.11a Right Side Mode High 5mm

Wi-Fi 5G U-NII-2A 802.11a Right Side Mode High 0mm

Date/Time: 2024/1/2

Electronics: DAE4 Sn1244

Medium parameters used: $f = 5320 \text{ MHz}$; $\sigma = 4.829 \text{ S/m}$; $\epsilon_r = 35.291$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 20.9°C Liquid Temperature: 20.0°C

Communication System: 5G-U-NII-2A 5GHz; Frequency: 5320 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(5.72, 5.72, 5.72) @ 5320 MHz

Wi-Fi 5G U-NII-2A 802.11a Right Side Mode High 0mm/Area Scan (5x11x1):

Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Maximum value of SAR (measured) = 0.479 W/kg

Wi-Fi 5G U-NII-2A 802.11a Right Side Mode High 0mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 2.423 V/m ; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 4.00 W/kg

SAR(1 g) = 0.802 W/kg ; SAR(10 g) = 0.196 W/kg

Maximum of SAR (measured) = 1.91 W/kg




Figure A.1-27 Wi-Fi 5G U-NII-2A 802.11a Right Side Mode High 0mm

Wi-Fi 5G U-NII-2C 802.11a Right Side Mode High 5mm

Date/Time: 2024/1/2

Electronics: DAE4 Sn1244

Medium parameters used: $f = 5700 \text{ MHz}$; $\sigma = 5.271 \text{ S/m}$; $\epsilon_r = 34.495$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 20.9°C Liquid Temperature: 20.0°C

Communication System: 5G-U-NII-2C 5GHz; Frequency: 5700 MHz ; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(5.17, 5.17, 5.17) @ 5700 MHz

Wi-Fi 5G U-NII-2C 802.11a Right Side Mode High 5mm/Area Scan (5x11x1):

Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Maximum value of SAR (measured) = 0.201 W/kg

Wi-Fi 5G U-NII-2C 802.11a Right Side Mode High 5mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 0 V/m ; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 1.60 W/kg

SAR(1 g) = 0.241 W/kg ; SAR(10 g) = 0.072 W/kg

Maximum of SAR (measured) = 0.574 W/kg




Figure A.1-28 Wi-Fi 5G U-NII-2C 802.11a Right Side Mode High 5mm

Wi-Fi 5G U-NII-2C 802.11a Right Side Mode High 0mm

Date/Time: 2024/1/2

Electronics: DAE4 Sn1244

Medium parameters used: $f = 5700 \text{ MHz}$; $\sigma = 5.271 \text{ S/m}$; $\epsilon_r = 34.495$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 20.9°C Liquid Temperature: 20.0°C

Communication System: 5G-U-NII-2C 5GHz; Frequency: 5700 MHz ; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(5.17, 5.17, 5.17) @ 5700 MHz

Wi-Fi 5G U-NII-2C 802.11a Right Side Mode High 0mm/Area Scan (5x11x1):

Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Maximum value of SAR (measured) = 0.400 W/kg

Wi-Fi 5G U-NII-2C 802.11a Right Side Mode High 0mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 0 V/m ; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 6.88 W/kg

SAR(1 g) = 0.887 W/kg ; SAR(10 g) = 0.207 W/kg

Maximum of SAR (measured) = 1.88 W/kg




Figure A.1-29 Wi-Fi 5G U-NII-2C 802.11a Right Side Mode High 0mm

Wi-Fi 5G U-NII-3 802.11a Right Side Mode Low 5mm

Date/Time: 2024/1/2

Electronics: DAE4 Sn1244

Medium parameters used: $f = 5745 \text{ MHz}$; $\sigma = 5.329 \text{ S/m}$; $\epsilon_r = 34.412$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 20.9°C Liquid Temperature: 20.0°C

Communication System: 5G-U-NII-3 5GHz; Frequency: 5745 MHz ; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(5.22, 5.22, 5.22) @ 5745 MHz

Wi-Fi 5G U-NII-3 802.11a Right Side Mode Low 5mm/Area Scan (5x11x1):

Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Maximum value of SAR (measured) = 0.206 W/kg

Wi-Fi 5G U-NII-3 802.11a Right Side Mode Low 5mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 0 V/m ; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 1.47 W/kg

SAR(1 g) = 0.234 W/kg ; SAR(10 g) = 0.074 W/kg

Maximum of SAR (measured) = 0.600 W/kg




Figure A.1-30 Wi-Fi 5G U-NII-3 802.11a Right Side Mode Low 5mm

Wi-Fi 5G U-NII-3 802.11a Right Side Mode Low 0mm

Date/Time: 2024/1/2

Electronics: DAE4 Sn1244

Medium parameters used: $f = 5745 \text{ MHz}$; $\sigma = 5.329 \text{ S/m}$; $\epsilon_r = 34.412$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 20.9°C Liquid Temperature: 20.0°C

Communication System: 5G-U-NII-3 5GHz; Frequency: 5745 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(5.22, 5.22, 5.22) @ 5745 MHz

Wi-Fi 5G U-NII-3 802.11a Right Side Mode Low 0mm/Area Scan (5x11x1):

Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Maximum value of SAR (measured) = 0.446 W/kg

Wi-Fi 5G U-NII-3 802.11a Right Side Mode Low 0mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 0 V/m ; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 6.10 W/kg

SAR(1 g) = 0.912 W/kg ; SAR(10 g) = 0.219 W/kg

Maximum of SAR (measured) = 1.86 W/kg




Figure A.1-31 Wi-Fi 5G U-NII-3 802.11a Right Side Mode Low 0mm

BT DH5 Right Side Mode High 5mm

Date/Time: 2024/1/2

Electronics: DAE4 Sn1244

Medium parameters used: $f = 2480 \text{ MHz}$; $\sigma = 1.799 \text{ S/m}$; $\epsilon_r = 38.159$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 20.9°C Liquid Temperature: 20.0°C

Communication System: Bluetooth 2600MHz; Frequency: 2480 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(8.07, 8.07, 8.07) @ 2480 MHz

BT DH5 Right Side Mode High 5mm/Area Scan (5x11x1):

Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Maximum value of SAR (measured) = 0.116 W/kg

BT DH5 Right Side Mode High 5mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 4.437 V/m ; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.254 W/kg

SAR(1 g) = 0.102 W/kg ; SAR(10 g) = 0.041 W/kg

Maximum of SAR (measured) = 0.194 W/kg




Figure A.1-32 BT DH5 Right Side Mode High 5mm

BT DH5 Right Side Mode High 0mm

Date/Time: 2024/1/2

Electronics: DAE4 Sn1244

Medium parameters used: $f = 2480 \text{ MHz}$; $\sigma = 1.799 \text{ S/m}$; $\epsilon_r = 38.159$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 20.9°C Liquid Temperature: 20.0°C

Communication System: Bluetooth 2600MHz; Frequency: 2480 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(8.07, 8.07, 8.07) @ 2480 MHz

BT DH5 Right Side Mode High 0mm/Area Scan (5x11x1):

Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Maximum value of SAR (measured) = 0.154 W/kg

BT DH5 Right Side Mode High 0mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 3.892 V/m ; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.464 W/kg

SAR(1 g) = 0.148 W/kg ; SAR(10 g) = 0.054 W/kg

Maximum of SAR (measured) = 0.333 W/kg




Figure A.1-33 BT DH5 Right Side Mode High 0mm

A.2 System Check Graph Results

System Check 835MHz

Date/Time: 2024/1/2

Electronics: DAE4 Sn1244

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.918 \text{ S/m}$; $\epsilon_r = 41.834$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 21.2°C Liquid Temperature: 20.2°C

Communication System: CW 900MHz; Frequency: 835 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(10.66, 10.66, 10.66) @ 835 MHz

System Check 835MHz/Area Scan (7x13x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 2.85 W/kg

System Check 835MHz/Zoom Scan (7x7x7) (5x5x7)/Cube 0:

Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 60.37 V/m ; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 3.73 W/kg

SAR(1 g) = 2.35 W/kg ; SAR(10 g) = 1.51 W/kg

Maximum value of SAR (measured) = 3.24 W/kg




Figure A.2-1 System Check 835MHz

System Check 835MHz

Date/Time: 2024/1/15

Electronics: DAE4 Sn1244

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.921 \text{ S/m}$; $\epsilon_r = 40.617$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 20.9°C Liquid Temperature: 20.0°C

Communication System: CW 900MHz; Frequency: 835 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(10.66, 10.66, 10.66) @ 835 MHz

System Check 835MHz/Area Scan (7x13x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 2.97 W/kg

System Check 835MHz/Zoom Scan (7x7x7) (5x5x7)/Cube 0:

Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 61.64 V/m ; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 3.84 W/kg

SAR(1 g) = 2.42 W/kg ; SAR(10 g) = 1.56 W/kg

Maximum value of SAR (measured) = 3.34 W/kg




Figure A.2-2 System Check 835MHz

System Check 1750MHz

Date/Time: 2024/1/15

Electronics: DAE4 Sn1244

Medium parameters used: $f = 1750 \text{ MHz}$; $\sigma = 1.342 \text{ S/m}$; $\epsilon_r = 39.581$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 20.9°C Liquid Temperature: 20.0°C

Communication System: CW 1750MHz; Frequency: 1750 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(8.96, 8.96, 8.96) @ 1750 MHz

System Check 1750MHz/Area Scan (8x7x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 10.1 W/kg

System Check 1750MHz/Zoom Scan (7x7x7) (5x5x7)/Cube 0:

Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 105.9 V/m ; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 17.5 W/kg

SAR(1 g) = 9.46 W/kg ; SAR(10 g) = 5.01 W/kg

Maximum value of SAR (measured) = 14.6 W/kg




Figure A.2-3 System Check 1750MHz

System Check 1900MHz

Date/Time: 2024/1/2

Electronics: DAE4 Sn1244

Medium parameters used: $f = 1900 \text{ MHz}$; $\sigma = 1.413 \text{ S/m}$; $\epsilon_r = 38.748$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 21.2°C Liquid Temperature: 20.2°C

Communication System: CW 1750MHz; Frequency: 1900 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(8.67, 8.67, 8.67) @ 1900 MHz

System Check 1900MHz/Area Scan (8x7x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 12.7 W/kg

System Check 1900MHz/Zoom Scan (7x7x7) (7x7x7)/Cube 0:

Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 105.1 V/m ; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 19.2 W/kg

SAR(1 g) = 10 W/kg ; SAR(10 g) = 5.16 W/kg

Maximum value of SAR (measured) = 15.7 W/kg




Figure A.2-4 System Check 1900MHz

System Check 1900MHz

Date/Time: 2024/1/16

Electronics: DAE4 Sn1244

Medium parameters used: $f = 1900 \text{ MHz}$; $\sigma = 1.434 \text{ S/m}$; $\epsilon_r = 39.341$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 21.1°C Liquid Temperature: 20.1°C

Communication System: CW 1750MHz; Frequency: 1900 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(8.67, 8.67, 8.67) @ 1900 MHz

System Check 1900MHz/Area Scan (8x7x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 12.8 W/kg

System Check 1900MHz/Zoom Scan (7x7x7) (7x7x7)/Cube 0:

Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 105.1 V/m ; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 19.1 W/kg

SAR(1 g) = 9.92 W/kg ; SAR(10 g) = 5.11 W/kg

Maximum value of SAR (measured) = 15.6 W/kg




Figure A.2-5 System Check 1900MHz

System Check 2450MHz

Date/Time: 2024/1/2

Electronics: DAE4 Sn1244

Medium parameters used: $f = 2450 \text{ MHz}$; $\sigma = 1.779 \text{ S/m}$; $\epsilon_r = 38.163$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 21.2°C Liquid Temperature: 20.2°C

Communication System: CW 2450MHz; Frequency: 2450 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(8.07, 8.07, 8.07) @ 2450 MHz

System Check 2450MHz/Area Scan (9x9x1):

Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Maximum value of SAR (measured) = 12.3 W/kg

System Check 2450MHz/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 88.10 V/m ; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 28.1 W/kg

SAR(1 g) = 13.4 W/kg ; SAR(10 g) = 6.2 W/kg

Maximum value of SAR (measured) = 15.2 W/kg




Figure A.2-6 System Check 2450MHz

System Check 2600MHz

Date/Time: 2023/12/28

Electronics: DAE4 Sn1244

Medium parameters used: $f = 2600 \text{ MHz}$; $\sigma = 1.928 \text{ S/m}$; $\epsilon_r = 37.948$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 21.4°C Liquid Temperature: 20.3°C

Communication System: CW 2450MHz; Frequency: 2600 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(7.86, 7.86, 7.86) @ 2600 MHz

System Check 2600MHz/Area Scan (8x8x1):

Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Maximum value of SAR (measured) = 19.3 W/kg

System Check 2600MHz/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 109.2 V/m ; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 29.5 W/kg

SAR(1 g) = 13.8 W/kg ; SAR(10 g) = 6.24 W/kg

Maximum value of SAR (measured) = 23.6 W/kg




Figure A.2-7 System Check 2600MHz

System Check 5200MHz

Date/Time: 2024/1/2

Electronics: DAE4 Sn1244

Medium parameters used: $f = 5200 \text{ MHz}$; $\sigma = 4.696 \text{ S/m}$; $\epsilon_r = 35.552$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 21.2°C Liquid Temperature: 20.2°C

Communication System: CW 5GHz; Frequency: 5200 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(5.72, 5.72, 5.72) @ 5200 MHz

System Check 5200MHz/Area Scan (8x8x1):

Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Maximum value of SAR (measured) = 17.8 W/kg

System Check 5200MHz/Zoom Scan (4x4x1.4mm, graded), dist=1.4mm (7x7x7)/Cube 0:

Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 62.55 V/m ; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 30.4 W/kg

SAR(1 g) = 7.72 W/kg ; SAR(10 g) = 2.22 W/kg

Maximum of SAR (measured) = 19.4 W/kg




Figure A.2-8 System Check 5200MHz

System Check 5300MHz

Date/Time: 2024/1/2

Electronics: DAE4 Sn1244

Medium parameters used: $f = 5300 \text{ MHz}$; $\sigma = 4.806 \text{ S/m}$; $\epsilon_r = 35.336$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 21.2°C Liquid Temperature: 20.2°C

Communication System: CW 5GHz; Frequency: 5300 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(5.72, 5.72, 5.72) @ 5300 MHz

System Check 5300MHz/Area Scan (10x10x1):

Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Maximum value of SAR (measured) = 15.0 W/kg

System Check 5300MHz/Zoom Scan (4x4x1.4mm, graded), dist=1.4mm (7x7x7)/Cube 0:

Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 69.25 V/m ; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 32.7 W/kg

SAR(1 g) = 8.05 W/kg ; SAR(10 g) = 2.31 W/kg

Maximum value of SAR (measured) = 20.4 W/kg




Figure A.2-9 System Check 5300MHz

System Check 5600MHz

Date/Time: 2024/1/2

Electronics: DAE4 Sn1244

Medium parameters used: $f = 5600 \text{ MHz}$; $\sigma = 5.155 \text{ S/m}$; $\epsilon_r = 34.721$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 21.2°C Liquid Temperature: 20.2°C

Communication System: CW 5GHz; Frequency: 5600 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(5.17, 5.17, 5.17) @ 5600 MHz

System Check 5600MHz/Area Scan (10x10x1):

Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Maximum value of SAR (measured) = 14.3 W/kg

System Check 5600MHz/Zoom Scan (4x4x1.4mm, graded), dist=1.4mm (7x7x7)/Cube 0:

Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 70.98 V/m ; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 34.4 W/kg

SAR(1 g) = 8.34 W/kg ; SAR(10 g) = 2.38 W/kg

Maximum value of SAR (measured) = 21.8 W/kg




Figure A.2-10 System Check 5600MHz

System Check 5800MHz

Date/Time: 2024/1/2

Electronics: DAE4 Sn1244

Medium parameters used: $f = 5800 \text{ MHz}$; $\sigma = 5.396 \text{ S/m}$; $\epsilon_r = 34.317$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 21.2°C Liquid Temperature: 20.2°C

Communication System: CW 5GHz; Frequency: 5800 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN7633ConvF(5.22, 5.22, 5.22) @ 5800 MHz

System Check 5800MHz/Area Scan (10x10x1):

Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Maximum value of SAR (measured) = 14.3 W/kg

System Check 5800MHz/Zoom Scan (4x4x1.4mm, graded), dist=1.4mm (7x7x7)/Cube 0:

Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 66.36 V/m ; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 33.6 W/kg

SAR(1 g) = 7.68 W/kg ; SAR(10 g) = 2.19 W/kg

Maximum value of SAR (measured) = 20.4 W/kg




Figure A.2-11 System Check 5800MHz

Annex B: Calibration Certificate



Add: No.52 HuaYuanBei Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2117
E-mail: cmf@caict.ac.cn <http://www.caict.ac.cn>



中国认可
国际互认
校准
CALIBRATION
CNAS L0570

Client : **3in**

Certificate No: **J23Z60207**

CALIBRATION CERTIFICATE

Object **DAE4 - SN: 1244**

Calibration Procedure(s) **FF-Z11-002-01
Calibration Procedure for the Data Acquisition Electronics (DAEx)**



Calibration date: **April 10, 2023**

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Process Calibrator 753	1971018	14-Jun-22 (CTTL, No.J22X04180)	Jun-23

	Name	Function	Signature
Calibrated by:	Yu Zongying	SAR Test Engineer	
Reviewed by:	Lin Hao	SAR Test Engineer	
Approved by:	Qi Dianyuan	SAR Project Leader	

Issued: April 11, 2023

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: J23Z60207

Page 1 of 3



In Collaboration with
s p e a g
CALIBRATION LABORATORY



Add: No.52 HuaYuanBei Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2117
E-mail: emf@caict.ac.cn <http://www.caict.ac.cn>

Glossary:

DAE data acquisition electronics
Connector angle information used in DASY system to align probe sensor X to the robot coordinate system.

Methods Applied and Interpretation of Parameters:

- *DC Voltage Measurement:* Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- *Connector angle:* The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The report provide only calibration results for DAE, it does not contain other performance test results.



In Collaboration with
s p e a g
CALIBRATION LABORATORY



Add: No.52 HuaYuanBei Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2117
E-mail: emf@caict.ac.cn <http://www.caict.ac.cn>

DC Voltage Measurement

A/D - Converter Resolution nominal

High Range: 1LSB = 6.1 μ V, full range = -100...+300 mV

Low Range: 1LSB = 61nV, full range = -1.....+3mV

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

Calibration Factors	X	Y	Z
High Range	403.859 $\pm$ 0.15% (k=2)	403.585 $\pm$ 0.15% (k=2)	404.504 $\pm$ 0.15% (k=2)
Low Range	3.95256 $\pm$ 0.7% (k=2)	3.97026 $\pm$ 0.7% (k=2)	3.97966 $\pm$ 0.7% (k=2)

Connector Angle

Connector Angle to be used in DASY system	23.5° $\pm$ 1°
---	----------------



Add: No.52 HuaYuanBei Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2117
E-mail: emf@caict.ac.cn http://www.caict.ac.cn



中国认可
国际互认
校准
CALIBRATION
CNAS L0570

Client **3in**

Certificate No: **J23Z60208**

CALIBRATION CERTIFICATE

Object **EX3DV4 - SN : 7633**

Calibration Procedure(s)
FF-Z11-004-02
Calibration Procedures for Dosimetric E-field Probes


Calibration date: **April 28, 2023**

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRP2	101919	14-Jun-22(CTTL, No.J22X04181)	Jun-23
Power sensor NRP-Z91	101547	14-Jun-22(CTTL, No.J22X04181)	Jun-23
Power sensor NRP-Z91	101548	14-Jun-22(CTTL, No.J22X04181)	Jun-23
Reference 10dBAttenuator	18N50W-10dB	19-Jan-23(CTTL, No.J23X00212)	Jan-25
Reference 20dBAttenuator	18N50W-20dB	19-Jan-23(CTTL, No.J23X00211)	Jan-25
OCP DAK-3.5	SN 1040	18-Jan-23(SPEAG, No.OCP-DAK3.5-1040_Jan23)	Jan-24
Reference Probe EX3DV4	SN 3846	20-May-22(SPEAG, No.EX3-3846_May22)	May-23
DAE4	SN 1555	25-Aug-22(SPEAG, No.DAE4-1555_Aug22)	Aug-23
Secondary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
SignalGenerator MG3700A	6201052605	14-Jun-22(CTTL, No.J22X04182)	Jun-23
Network Analyzer E5071C	MY46110673	10-Jan-23(CTTL, No.J23X00104)	Jan-24

	Name	Function	Signature
Calibrated by:	Yu Zongying	SAR Test Engineer	
Reviewed by:	Lin Hao	SAR Test Engineer	
Approved by:	Qi Dianyuan	SAR Project Leader	

Issued: May 01, 2023

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: J23Z60208

Page 1 of 9



In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.52 HuaYuanBei Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2117
E-mail: emf@caict.ac.cn http://www.caict.ac.cn

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A,B,C,D	modulation dependent linearization parameters
Polarization Φ	Φ rotation around probe axis
Polarization θ	θ rotation around an axis that is in the plane normal to probe axis (at measurement center), i $\theta=0$ is normal to probe axis

Connector Angle information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}: Assessed for E-field polarization $\theta=0$ ($f \leq 900\text{MHz}$ in TEM-cell; $f > 1800\text{MHz}$: waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not effect the E^2 -field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z} = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}: DCP are numerical linearization parameters assessed based on the data of power sweep (no uncertainty required). DCP does not depend on frequency nor media.
- PAR: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics.
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; VR_{x,y,z}; A,B,C are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800\text{MHz}$) and inside waveguide using analytical field distributions based on power measurements for $f > 800\text{MHz}$. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty valued are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from $\pm 50\text{MHz}$ to $\pm 100\text{MHz}$.
- Spherical isotropy (3D deviation from isotropy): in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).



In Collaboration with
s p e a g
CALIBRATION LABORATORY



Add: No.52 HuaYuanBei Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2117
E-mail: emf@caict.ac.cn <http://www.caict.ac.cn>

DASY/EASY – Parameters of Probe: EX3DV4 – SN:7633

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc ($k=2$)
Norm($\mu V/(V/m)^2$) ^A	0.66	0.64	0.68	$\pm 10.0\%$
DCP(mV) ^B	109.8	112.6	114.4	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB μV	C	D dB	VR mV	Unc ^E ($k=2$)
0	CW	X	0.0	0.0	1.0	0.00	210.8	$\pm 2.2\%$
		Y	0.0	0.0	1.0		210.6	
		Z	0.0	0.0	1.0		218.3	

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor $k=2$, which for a normal distribution Corresponds to a coverage probability of approximately 95%.

^A The uncertainties of Norm X, Y, Z do not affect the E²-field uncertainty inside TSL (see Page 4).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.



In Collaboration with
s p e a g
CALIBRATION LABORATORY



Add: No.52 HuaYuanBei Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2117
E-mail: emf@caict.ac.cn http://www.caict.ac.cn

DASY/EASY – Parameters of Probe: EX3DV4 – SN:7633

Calibration Parameter Determined in Head Tissue Simulating Media

f [MHz] ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unct. (k=2)
750	41.9	0.89	11.03	11.03	11.03	0.13	1.45	±12.7%
835	41.5	0.90	10.66	10.66	10.66	0.16	1.41	±12.7%
900	41.5	0.97	10.62	10.62	10.62	0.19	1.29	±12.7%
1750	40.1	1.37	8.96	8.96	8.96	0.21	1.17	±12.7%
1900	40.0	1.40	8.67	8.67	8.67	0.26	0.99	±12.7%
2000	40.0	1.40	8.72	8.72	8.72	0.27	0.99	±12.7%
2300	39.5	1.67	8.32	8.32	8.32	0.64	0.66	±12.7%
2450	39.2	1.80	8.07	8.07	8.07	0.64	0.66	±12.7%
2600	39.0	1.96	7.86	7.86	7.86	0.48	0.78	±12.7%
3300	38.2	2.71	7.45	7.45	7.45	0.41	1.03	±13.9%
3500	37.9	2.91	7.21	7.21	7.21	0.40	1.04	±13.9%
3700	37.7	3.12	7.00	7.00	7.00	0.43	1.03	±13.9%
3900	37.5	3.32	6.91	6.91	6.91	0.40	1.25	±13.9%
4100	37.2	3.53	6.85	6.85	6.85	0.40	1.15	±13.9%
4200	37.1	3.63	6.75	6.75	6.75	0.35	1.35	±13.9%
4400	36.9	3.84	6.65	6.65	6.65	0.35	1.35	±13.9%
4600	36.7	4.04	6.55	6.55	6.55	0.40	1.30	±13.9%
4800	36.4	4.25	6.50	6.50	6.50	0.40	1.35	±13.9%
4950	36.3	4.40	6.22	6.22	6.22	0.40	1.35	±13.9%
5250	35.9	4.71	5.72	5.72	5.72	0.40	1.50	±13.9%
5600	35.5	5.07	5.17	5.17	5.17	0.55	1.20	±13.9%
5750	35.4	5.22	5.22	5.22	5.22	0.50	1.30	±13.9%

^C Frequency validity above 300 MHz of ±100MHz only applies for DASY v4.4 and higher (Page 2), else it is restricted to ±50MHz. The uncertainty is the RSS of ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequency up to 6 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ±10% if liquid compensation formula is applied to measured SAR values. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for the frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

Certificate No:J23Z60208

Page 4 of 9




In Collaboration with
s p e a g
CALIBRATION LABORATORY



Add: No.52 HuaYuanBei Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2117
E-mail: emf@caict.ac.cn <http://www.caict.ac.cn>

Frequency Response of E-Field (TEM-Cell: ifi110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field: $\pm 7.4\%$ ($k=2$)



In Collaboration with
s p e a g
CALIBRATION LABORATORY






Add: No.52 HuaYuanBei Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2117
E-mail: emf@caict.ac.cn <http://www.caict.ac.cn>

Receiving Pattern (Φ), $\theta=0^\circ$

f=600 MHz, TEM

f=1800 MHz, R22



Uncertainty of Axial Isotropy Assessment: $\pm 1.2\%$ ($k=2$)





In Collaboration with
s p e a g
CALIBRATION LABORATORY



Add: No.52 HuaYuanBei Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2117
E-mail: emf@caict.ac.cn <http://www.caict.ac.cn>

Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell, $f = 900 \text{ MHz}$)



Uncertainty of Linearity Assessment: $\pm 0.9\%$ ($k=2$)

Certificate No: J23Z60208

Page 7 of 9



In Collaboration with
s p e a g
CALIBRATION LABORATORY





Add: No.52 HuaYuanBei Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2117
E-mail: emf@caict.ac.cn <http://www.caict.ac.cn>


Conversion Factor Assessment

f=750 MHz,WGLS R9(H_convF)

f=1750 MHz,WGLS R22(H_convF)



Deviation from Isotropy in Liquid



Uncertainty of Spherical Isotropy Assessment: $\pm 3.2\%$ ($k=2$)

Certificate No:J23Z60208

Page 8 of 9



In Collaboration with
s p e a g
CALIBRATION LABORATORY



Add: No.52 HuaYuanBei Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2117
E-mail: emf@caict.ac.cn <http://www.caict.ac.cn>

DASY/EASY – Parameters of Probe: EX3DV4 – SN:7633

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	24.2
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disable
Probe Overall Length	337mm
Probe Body Diameter	10mm
Tip Length	9mm
Tip Diameter	2.5mm
Probe Tip to Sensor X Calibration Point	1mm
Probe Tip to Sensor Y Calibration Point	1mm
Probe Tip to Sensor Z Calibration Point	1mm
Recommended Measurement Distance from Surface	1.4mm



Add: No.52 HuaYuanBei Road, Haidian District, Beijing, 100191
Tel: +86-10-62304633-2117
E-mail: emf@caict.ac.cn http://www.caict.ac.cn



中国认可
国际互认
校准
CALIBRATION
CNAS L0570



Client 3In

Certificate No: 23J02Z80032

CALIBRATION CERTIFICATE

Object D835V2 - SN: 4d112

Calibration Procedure(s) FF-Z11-003-01
Calibration Procedures for dipole validation kits


Calibration date: September 6, 2023

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRP2	106277	22-Sep-22 (CTTL, No.J22X09561)	Sep-23
Power sensor NRP8S	104291	22-Sep-22 (CTTL, No.J22X09561)	Sep-23
Reference Probe EX3DV4	SN 3617	31-Mar-23(CTTL-SPEAG,No.Z23-60161)	Mar-24
DAE4	SN 1556	11-Jan-23(CTTL-SPEAG,No.Z23-60034)	Jan-24
Secondary Standards	ID #	Cal Date (Calibrated by, Certificate No.)	Scheduled Calibration
Signal Generator E4438C	MY49071430	05-Jan-23 (CTTL, No. J23X00107)	Jan-24
NetworkAnalyzer E5071C	MY46110673	10-Jan-23 (CTTL, No. J23X00104)	Jan-24

	Name	Function	Signature
Calibrated by:	Zhao Jing	SAR Test Engineer	
Reviewed by:	Lin Hao	SAR Test Engineer	
Approved by:	Qi Dianyuan	SAR Project Leader	

Issued: September 16, 2023

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: 23J02Z80032

Page 1 of 6



Add: No.52 HuaYuanBei Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2117
E-mail: emf@caict.ac.cn <http://www.caict.ac.cn>

**Glossary:**

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM _{x,y,z}
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- a) IEC/IEEE 62209-1528, "Measurement Procedure for The Assessment of Specific Absorption Rate of Human Exposure to Radio Frequency Fields from Hand-held and Body-mounted Wireless Communication Devices- Part 1528: Human Models, Instrumentation and Procedures (Frequency range of 4 MHz to 10 GHz)", October 2020
- b) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- c) DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor $k=2$, which for a normal distribution Corresponds to a coverage probability of approximately 95%.



Add: No.52 HuaYuanBei Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2117
E-mail: emf@caict.ac.cn <http://www.caict.ac.cn>

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY52	V52.10.4
Extrapolation	Advanced Extrapolation	
Phantom	Triple Flat Phantom 5.1C	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	835 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.5	0.90 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	41.2 $\pm$ 6 %	0.88 mho/m $\pm$ 6 %
Head TSL temperature change during test	<1.0 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm^3 (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.38 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	9.67 W/kg $\pm$ 18.8 % ($k=2$)
SAR averaged over 10 cm^3 (10 g) of Head TSL	Condition	
SAR measured	250 mW input power	1.54 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	6.24 W/kg $\pm$ 18.7 % ($k=2$)



Add: No.52 HuaYuanBei Road, Haidian District, Beijing, 100191, China
 Tel: +86-10-62304633-2117
 E-mail: emf@caict.ac.cn <http://www.caict.ac.cn>



Appendix (Additional assessments outside the scope of CNAS L0570)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	51.4Ω- 0.55jΩ
Return Loss	- 36.5dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.303 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feed-point can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard. No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feed-point may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------



Add: No.52 HuaYuanBei Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2117
E-mail: emf@caict.ac.cn http://www.caict.ac.cn



DASY5 Validation Report for Head TSL

Date: 2023-09-06

Test Laboratory: CTTL, Beijing, China

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d112

Communication System: UID 0, CW; Frequency: 835 MHz

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.88 \text{ S/m}$; $\epsilon_r = 41.24$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3617; ConvF(10.1, 10.1, 10.1) @ 835 MHz; Calibrated: 2023-03-31
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1556; Calibrated: 2023-01-11
- Phantom: MFP_V5.1C (20deg probe tilt); Type: QD 000 P51 Cx; Serial: 1062
- DASY52 52.10.4(1535); SEMCAD X 14.6.14(7501)

Dipole Calibration/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 58.67 V/m; Power Drift = -0.02 dB


Peak SAR (extrapolated) = 3.85 W/kg

SAR(1 g) = 2.38 W/kg; SAR(10 g) = 1.54 W/kg

Smallest distance from peaks to all points 3 dB below = 17.1 mm

Ratio of SAR at M2 to SAR at M1 = 62.4%

Maximum value of SAR (measured) = 3.30 W/kg




0 dB = 3.30 W/kg = 5.19 dBW/kg



Add: No.52 HuaYuanBei Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2117
E-mail: emf@caict.ac.cn <http://www.caict.ac.cn>

Impedance Measurement Plot for Head TSL





Add: No.52 HuaYuanBei Road, Haidian District, Beijing, 100191
Tel: +86-10-62304633-2117
E-mail: emf@caict.ac.cn http://www.caict.ac.cn



中国认可
国际互认
校准
CALIBRATION
CNAS L0570



Client 3in

Certificate No: 23J02Z80034

CALIBRATION CERTIFICATE

Object D1750V2 - SN: 1044

Calibration Procedure(s) FF-Z11-003-01
Calibration Procedures for dipole validation kits

Calibration date: September 8, 2023

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRP2	106277	22-Sep-22 (CTTL, No.J22X09561)	Sep-23
Power sensor NRP8S	104291	22-Sep-22 (CTTL, No.J22X09561)	Sep-23
Reference Probe EX3DV4	SN 3617	31-Mar-23(CTTL-SPEAG,No.Z23-60161)	Mar-24
DAE4	SN 1556	11-Jan-23(CTTL-SPEAG,No.Z23-60034)	Jan-24
Secondary Standards	ID #	Cal Date (Calibrated by, Certificate No.)	Scheduled Calibration
Signal Generator E4438C	MY49071430	05-Jan-23 (CTTL, No. J23X00107)	Jan-24
Network Analyzer E5071C	MY46110673	10-Jan-23 (CTTL, No. J23X00104)	Jan-24

	Name	Function	Signature
Calibrated by:	Zhao Jing	SAR Test Engineer	
Reviewed by:	Lin Hao	SAR Test Engineer	
Approved by:	Qi Dianyuan	SAR Project Leader	

Issued: September 16, 2023

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: 23J02Z80034

Page 1 of 6



In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.52 HuaYuanBei Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2117
E-mail: emf@caict.ac.cn <http://www.caict.ac.cn>

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM _{x,y,z}
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEC/IEEE 62209-1528, "Measurement Procedure for The Assessment of Specific Absorption Rate of Human Exposure to Radio Frequency Fields from Hand-held and Body-mounted Wireless Communication Devices- Part 1528: Human Models, Instrumentation and Procedures (Frequency range of 4 MHz to 10 GHz)", October 2020
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor $k=2$, which for a normal distribution Corresponds to a coverage probability of approximately 95%.



Add: No.52 HuaYuanBei Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2117
E-mail: emf@caict.ac.cn http://www.caict.ac.cn

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY52	52.10.4
Extrapolation	Advanced Extrapolation	
Phantom	Triple Flat Phantom 5.1C	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	1750 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	40.1	1.37 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	40.4 $\pm$ 6 %	1.39 mho/m $\pm$ 6 %
Head TSL temperature change during test	<1.0 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	9.25 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	36.7 W/kg $\pm$ 18.8 % (k=2)
SAR averaged over 10 cm³ (10 g) of Head TSL	Condition	
SAR measured	250 mW input power	4.89 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	19.4 W/kg $\pm$ 18.7 % (k=2)



In Collaboration with
s p e a g
CALIBRATION LABORATORY



Add: No.52 HuaYuanBei Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2117
E-mail: emf@caict.ac.cn <http://www.caict.ac.cn>

Appendix (Additional assessments outside the scope of CNAS L0570)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	47.8Ω- 0.20jΩ
Return Loss	- 32.9dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.121 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feed-point can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard. No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feed-point may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------



Add: No.52 HuaYuanBei Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2117
E-mail: emf@caict.ac.cn http://www.caict.ac.cn



DASY5 Validation Report for Head TSL

Date: 2023-09-08

Test Laboratory: CTTL, Beijing, China

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: D1750V2 - SN: 1044

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1750$ MHz; $\sigma = 1.394$ S/m; $\epsilon_r = 40.43$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN3617; ConvF(8.4, 8.4, 8.4) @ 1750 MHz; Calibrated: 2023-03-31
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1556; Calibrated: 2023-01-11
- Phantom: MFP_V5.1C (20deg probe tilt); Type: QD 000 P51 Cx; Serial: 1062
- DASY52 52.10.4(1535); SEMCAD X 14.6.14(7501)

Dipole Calibration/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 96.76 V/m; Power Drift = -0.04 dB


Peak SAR (extrapolated) = 17.3 W/kg

SAR(1 g) = 9.25 W/kg; SAR(10 g) = 4.89 W/kg

Smallest distance from peaks to all points 3 dB below = 10 mm

Ratio of SAR at M2 to SAR at M1 = 54%

Maximum value of SAR (measured) = 14.4 W/kg





Add: No.52 HuaYuanBei Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2117
E-mail: cmf@caict.ac.cn <http://www.caict.ac.cn>



Impedance Measurement Plot for Head TSL

