TEST REPORT

No. I18D00236-SRD01

For

Client: Shanghai Sunmi Technology Co.,Ltd.

Production: Wireless data POS System

Model Name: T5930

Brand Name: SUNMI

FCC ID : 2AH25V2

Hardware Version: V3

Software Version: ZAP1522_769_DEV_dailybuild_20181205071714_userdebug_DCC

Issued date: 2019-01-28

NOTE

1. The test results in this test report relate only to the devices specified in this report.
2. This report shall not be reproduced except in full without the written approval of East China Institute of Telecommunications.
3. ANSI/TIA-603-E and KDB 971168 D01 has not been approved by A2LA.
4. For the test results, the uncertainty of measurement is not taken into account when judging the compliance with specification, and the results of measurement or the average value of measurement results are taken as the criterion of the compliance with specification directly.

Test Laboratory:
East China Institute of Telecommunications
Add: 7-8F, G Area, No.668, Beijing East Road, Huangpu District, Shanghai, P. R. China
Tel: +86 21 63843300
FAX: +86 21 63843301
E-Mail: welcome@ecit.org.cn

Revision Version

Report Number	Revision	Date	Memo
I18D00236-SRD01	00	2019-01-28	Initial creation of test report

CONTENTS

1. TEST LABORATORY 6
1.1. TESTING LOCATION 6
1.2. TESTING ENVIRONMENT 6
1.3. PROJECT DATA 6
1.4. SIGNATURE 6
2. CLIENT INFORMATION 7
2.1. APPLICANT INFORMATION 7
2.2. MANUFACTURER INFORMATION 7
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) 8
3.1. ABOUT EUT 8
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST 8
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST 8
4. REFERENCE DOCUMENTS 9
4.1. DOCUMENTS SUPPLIED BY APPLICANT 9
4.2. REFERENCE DOCUMENTS FOR TESTING 9
5. TEST RESULTS 10
5.1. SUMMARY OF TEST RESULTS 10
5.2. STATEMENTS 10
6. TEST EQUIPMENTS UTILIZED 11
6.1. CONDUCTED TEST SYSTEM 11
6.2. RADIATED EMISSION TEST SYSTEM 11
7. MEASUREMENT UNCERTAINTY 13
8. TEST ENVIRONMENT 14
ANNEX A. DETAILED TEST RESULTS 15
ANNEX A.1. OUTPUT POWER 15

ANNEX A.2. PEAK-TO-AVERAGE POWER RATIO 17

ANNEX A.3. OCCUPIED BANDWIDTH 19

ANNEX A.4. -26DB EMISSION BANDWIDTH 33

ANNEX A.5. BAND EDGE AT ANTENNA TERMINALS 47

ANNEX A.6. FREQUENCY STABILITY 54

ANNEX A.7. CONDUCTED SPURIOUS EMISSION 61

ANNEX A.8. RADIATED 79

ANNEX B. ACCREDITATION CERTIFICATE 102

1. Test Laboratory

1.1. Testing Location

Company Name	East China Institute of Telecommunications
Address	7-8/F., Area G, No.666, Beijing East Road, Shanghai, China
Postal Code	200001
Telephone	+86 21 63843300
Fax	+86 21 63843301
FCC registration No	958356

1.2. Testing Environment

Normal Temperature	15℃-35℃
Relative Humidity	20%-75%

1.3. Project Data

Project Leader	Zhou Yan
Testing Start Date	2018-12-25
Testing End Date	2019-01-25

1.4. Signature

Yang Dejun
(Prepared this test report)

Shi Hongqi
(Reviewed this test report)

Zheng Zhongbin
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name	Shanghai Sunmi Technology Co.,Ltd.
Address	Room 505, KIC Plaza, No.388 Song Hu Road, Yang Pu District, Shanghai, China
Telephone	86-18721763396
Postcode	200433

2.2. Manufacturer Information

Company Name	Shanghai Sunmi Technology Co.,Ltd.
Address	Room 505, KIC Plaza, No.388 Song Hu Road, Yang Pu District, Shanghai, China
Telephone	86-18721763396
Postcode	200433

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Production	Wireless data POS System
Model name	T5930
FCC ID	2AH25V2
GSM Frequency Band	GSM850/GSM900/GSM1800/GSM1900
UMTS Frequency Band	Band I/II/IV/V
CDMA Frequency Band	/
LTE Frequency Band	Band 2/3/4/7/17/28
Additional Communication Function	BT/BLE/2.4G WLAN 802.11 b/g/n20 /5G WLAN 802.11 a/n20/n40
Extreme Temperature	-15/+55℃
Nominal Voltage	7.6V
Extreme High Voltage	8.7V
Extreme Low Voltage	6.8V

Note: Photographs of EUT are shown in ANNEX A of this test report.

3.2. Internal Identification of EUT used during the test

EUT ID*	Model Name	SN or IMEI	HW Version	SW Version	Date of receipt
N02(main supply)	T5930	/	V3	ZAP1522_769_DEV_dailybuild_20181205071714_userdebug_DCC	2018-12-24
N08(secondary supply)	T5930	/	V3	ZAP1522_769_DEV_dailybuild_20181205071714_userdebug_DCC	2018-12-24
N09(secondary supply)	T5930	/	V3	ZAP1522_769_DEV_dailybuild_20181205071714_userdebug_DCC	2018-12-24

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	Type	Manufacturer
AE1	RF cable	---	AE1

*AE ID: is used to identify the test sample in the lab internally.

4. Reference Documents

4.1. Documents supplied by applicant

All technical documents are supplied by the client or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	2018/10/01
FCC Part 22	PUBLIC MOBILE SERVICES	2018/10/01
FCC Part 2	FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS	2018/10/01
ANSI-TIA-603-E	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2016
ANSI C63.26	American National Standard of Procedures for Compliance Testing of Licensed Transmitters Used in Licensed Radio	2015
KDB 971168 D01	Measurement Guidance for Certification of Licensed Digital Transmitters	v03r01

5. Test Results

5.1. Summary of Test Results

Measurement Items	Sub-clause of Part15C	Sub-clause of IC	Verdict
Output Power	2.1046/22.913(a)/24.232(c)	/	P
Peak-to-Average Ratio	24.232(d)	/	P
99%Occupied Bandwidth	2.1049(h)(i)/ 22.917(b)	/	P
-26dB Emission Bandwidth	22.917(b)/§24.238(b)	/	P
Band Edge at antenna terminals	22.917(a)/24.238(a)	/	P
Frequency stability	2.1055/24.235	/	P
Conducted Spurious mission	2.1053/22.917(a)/24.238(a)	/	P
Emission Limit	2.1051/22.917/24.238/ 22.913/24.232	/	P

Note: please refer to Annex A in this test report for the detailed test results.
The following terms are used in the above table.

P	Pass, the EUT complies with the essential requirements in the standard.
NP	Not Perform, the test was not performed by ECIT.
NA	Not Applicable, the test was not applicable.
F	Fail, the EUT does not comply with the essential requirements in the standard.

5.2. Statements

The T5930, supporting GPRS/EDGE/WCDMA/ LTE/BT/BLE/WLAN/NFC, manufactured by Shanghai Sunmi Technology Co.,Ltd., is an initial product for testing.

ECIT only performed test cases which identified with P/NP/NA/F results in Annex A.

ECIT has verified that the compliance of the tested device specified in section 3 of this test report is successfully evaluated according to the procedure and test methods as defined in type certification requirement listed in section 4 of this test report.

6. Test Equipments Utilized

6.1. Conducted Test System

No.	Name	Type	SN	Manufacture	Calibration date	Cal.interval
1	Spectrum Analyzer	FSQ26	101096	R&S	2018-05-11	1 Year
2	Universal Radio Communicatio	CMU200	123124	R&S	2018-05-11	1 Year
3	DC Power Supply	ZUP60-14	LOC-220Z006 -0007	TDL-Lambda	2018-05-11	1 Year

6.2. Radiated Emission Test System

The test equipment and ancillaries used are as follows.

No.	Equipment	Model	Serial Number	Manufacturer	Calibration date	Cal.interval
1	Universal Radio Communication Tester	CMU200	123123	R&S	2018-05-11	1 Year
2	EMI Test Receiver	ESU40	100307	R&S	2018-05-11	1 Year
3	TRILOG Broadband Antenna	VULB9163	VULB9163-515	Schwarzbeck	2017-02-25	3 Year
4	Double-ridged Waveguide Antenna	ETS-3117	00135890	ETS	2017-01-11	3 Year
5	2-Line V-Network	ENV216	101380	R&S	2018-05-11	1 Year
6	Substitution Antenna	ETS-3117	00135890	ETS	2017-01-11	3 Year

7	RF Signal Generator	SMF100A	102314	R&S	2018-05-11	1 Year
8	Substitution Antenna	VUBA9117	9117-266	Schwarzbeck	2017-11-18	3 Year
9	Amplifier	SCU08	10146	R&S	2018-05-11	1 Year

Climate chamber

No.	Equipment	Model	Serial Number	Manufacturer	Calibration date	Cal.interval
1	Climate chamber	SH-641	92012011	ESPEC	2017-12-25	2 Year

7. Measurement Uncertainty

Measurement uncertainty for all the testing in this report are within the limit specified in ECIT documents . The detailed measurement uncertainty is defined in ECIT documents.

Measurement Items	Range	Confidence Level	Calculated Uncertainty
Maximum Peak Output Power	30MHz-3600MHz	95%	±0.544dB
EBW and VBW	30MHz-3600MHz	95%	±62.04Hz
Transmitter Spurious Emission-Conducted	30MHz-2GHz	95%	±0.90dB
Transmitter Spurious Emission-Conducted	2GHz-3.6GHz	95%	±0.88dB
Transmitter Spurious Emission-Conducted	3.6GHz-8GHz	95%	±0.96dB
Transmitter Spurious Emission-Conducted	8GHz-20GHz	95%	±0.94dB
Transmitter Spurious Emission-Radiated	9KHz-30MHz	95%	±5.66dB
Transmitter Spurious Emission-Radiated	30MHz-1000MHz	95%	±4.98dB
Transmitter Spurious Emission-Radiated	1000MHz -18000MHz	95%	±5.06dB
Transmitter Spurious Emission-Radiated	18000MHz -40000MHz	95%	±5.20dB
Frequency stability	1MHz-16GHz	95%	±62.04Hz

8. Test Environment

Shielding Room1 (6.0 meters×3.0 meters×2.7 meters) did not exceed following limits along the conducted RF performance testing:

Temperature	Min. = 15 ℃, Max. = 35 ℃
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	> 100 dB
Ground system resistance	< 0.5 Ω

Control room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 ℃, Max. = 35 ℃
Relative humidity	Min. =25 %, Max. = 75 %
Shielding effectiveness	> 100 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Fully-anechoic chamber1 (6.9 meters×10.9 meters×5.4 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 ℃, Max. = 35 ℃
Relative humidity	Min. = 25 %, Max. = 75 %
Shielding effectiveness	> 100 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
VSWR	Between 0 and 6 dB, from 1GHz to 18GHz
Site Attenuation Deviation	Between -4 and 4 dB,30MHz to 1GHz
Uniformity of field strength	Between 0 and 6 dB, from 80MHz to 3000 MHz

ANNEX A. Detailed Test Results

ANNEX A.1. OUTPUT POWER

A.1.1. Summary

During the process of testing, the EUT was controlled Rhode & Schwarz Digital Radio. Communication tester (CMU-200) to ensure max power transmission and proper modulation.
This result contains peak output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

A.1.1. Summary

During the process of testing, the EUT was controlled Rhode & Schwarz Digital Radio. Communication tester (CMU-200) to ensure max power transmission and proper modulation.
This result contains peak output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

A.1.2. Conducted

A.1.2.1. Method of Measurements

Method of measurements please refer to KDB971168 D01 v03 clause 5.
The EUT was set up for the max output power with pseudo random data modulation.
The power was measured with Rhode & Schwarz Spectrum Analyzer FSQ(peak).
These measurements were done at 3 frequencies, 1850.2 MHz, 1880.0MHz and 1909.8MHz for PCS1900 band; 824.2MHz, 836.6MHz and 848.8MHz for GSM850 band. (bottom, middle and top of operational frequency range).
These measurements were done at 3 frequencies, 1852.4 MHz, 1880.0MHz and 1907.6MHz for WCDMA Band II; 1732.6 MHz, 1712.4MHz and 1752.6MHz for WCDMA Band IV, 826.4MHz, 836.6MHz and 846.6MHz for WCDMA Band V. (bottom, middle and top of operational frequency range).

A.1.2.2 Test procedures:

1. The transmitter output port was connected to base station.
2. Set the EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

A.1.2.3 Limit:

22.A13(a) Mobile stations are limited to 7watts.
24.232(c) Mobile and portable stations are limited to 2 watts.

A.1.2.4 Test Procedure:

The transmitter output power was connected to calibrated attenuator, the other end of which was connected to signal analyzer. Transmitter output power was read off the power in dBm. The power outputs at the transmitter antenna port was determined by adding the value of attenuator to the signal analyzer reading.

A.1.2.5 GSM Test Condition:

RBW	VBW	Sweep time	Span
3MHz	10MHz	Auto	50MHz

A.1.2.6 WCDMA Test Condition:

RBW	VBW	Sweep time	Span
10MHz	30MHz	Auto	50MHz

A.1.2.7 Measurement results:

GPRS 850 (GMSK 1 Slot)		
Channel/fc(MHz)	Peak power (dBm)	AV power (dBm)
Mid 189/836.4	32.09	31.88
Low 128/824.2	31.97	31.76
High 251/848.8	32.15	31.92
EDGE 850 (8PSK 1 Slot)		
Channel/fc(MHz)	Peak power (dBm)	AV power (dBm)
Mid 189/836.4	29.54	26.62
Low 128/824.2	29.78	26.74
High 251/848.8	29.44	26.59

GPRS 1900 (GMSK 1 Slot)		
Channel/fc(MHz)	Peak power (dBm)	AV power (dBm)
Mid 661/1880	29.02	28.89
Low 512/1850.2	28.95	28.74
High 810/1909.8	29.11	28.94
EDGE 1900 (8PSK 1 Slot)		
Channel/fc(MHz)	Peak power (dBm)	AV power (dBm)
Mid 661/1880	28.97	25.93
Low 512/1850.2	29.05	26.03

High 810/1909.8	28.93	25.9

WCDMA II		
Channel/fc(MHz)	Peak power (dBm)	AV power (dBm)
Mid 9400 /1880	25.52	22.41
Low 9262/1852.4	25.88	22.35
High 9538/1907.6	25.83	22.45
WCDMA BAND IV		
Channel/fc(MHz)	Peak power (dBm)	AV power (dBm)
Mid 1413 /1732.6	26.07	22.71
Low 1312/1712.4	25.82	22.56
High 1513/1752.6	25.89	22.65
WCDMA BAND V		
Channel/fc(MHz)	Peak power (dBm)	AV power (dBm)
Mid 4183/836.6	26.65	23.29
Low 4132/826.4	26.61	23.27
High 4233/846.6	26.63	23.28

Conclusion: PASS

ANNEX A.2. Peak-to-Average Power Ratio

Method of test measurements please refer to KDB971168 D01 v03 clause 5.7.

A.2.1 PAPR Limit

The peak-to-average power ratio (PAPR) of the transmission may not exceed 13dB

A.2.2 Test procedures

1. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
2.
   1) Select the spectrum analyzer CCDF function.
   2) Set RBW⩾signal's occupied bandwidth.
   3) Set the number of counts to a value that stabilizes the measured CCDF cure;
   4) Sweep time ⩾ 1s.
3. Record the maximum PAPR level associated with a probability of 0.1%.

A.2.3 Test results:

GPRS850			
Channel	128	189	251
Frequency (MHz)	824.2	836.4	848.8
PAPR(dB)	8.25	8.43	8.46
EDGE850			
Channel	128	189	251
Frequency (MHz)	824.2	836.4	848.8
PAPR(dB)	8.19	8.43	8.44

GPRS1900			
Channel	512	661	810
Frequency (MHz)	1850.2	1880	1909.8
PAPR(dB)	6.41	6.44	6.47
EDGE1900			
Channel	128	189	251
Frequency (MHz)	824.2	836.4	848.8
PAPR(dB)	6.53	6.41	6.61

WCDMA Band II			
Channel	9262	9400	9538
Frequency (MHz)	1852.4	1880	1907.6
PAPR(dB)	4.52	4.55	4.74
WCDMA Band IV			
Channel	1312	1413	1513
Frequency (MHz)	1712.4	1732.6	1752.6
PAPR(dB)	5.16	4.49	4.39

WCDMA Band V			
Channel	4132	4183	4233
Frequency (MHz)	826.4	836.4	846.6
PAPR(dB)	4.01	4.2	4.62

Conclusion: PASS

ANNEX A.3. Occupied Bandwidth

Method of test please refer to KDB971168 D01 v03 clause 4.0.

A.3.1. Occupied Bandwidth

Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of GSM850, PCS1900, WCDMA BANDII, WCDMA BANDIV and WCDMA BANDV.

A.3.2 Test Procedure:

1. The EUT output RF connector was connected with a short cable to the signal analyzer.
2. RBW was set to about 1% of emission BW, VBW >= 3 times RBW,.
3. 99% bandwidth were measured, the occupied bandwidth is delta frequency between the two points where the display line intersects the signal trace.

A.3.3 Test result:

GPRS850		
Test channel	Frequency (MHz)	99% Occupied Bandwidth(kHz)
Mid 189	836.4	240.385
Low 128	824.2	248.397
High 251	848.8	248.397
EDGE850		
Test channel	Frequency (MHz)	99% Occupied Bandwidth(kHz)
Mid 189	836.4	246.795
Low 128	824.2	253.205

High 251	848.8	251.603

Conclusion: PASS

GPRS 850



Channel 189-Occupied Bandwidth (99%)



Channel 128-Occupied Bandwidth (99%)



Channel 251-Occupied Bandwidth (99%)

EDGE 850



Channel 189-Occupied Bandwidth (99%)



Channel 128-Occupied Bandwidth (99%)



Channel 251-Occupied Bandwidth (99%)

GPRS1900		
Test channel	Frequency (MHz)	99% Occupied Bandwidth(KHz)
Mid 661	1880	245.192
Low 512	1850.2	245.192

High 810	1909.8	245.192
EDGE1900		
Test channel	Frequency (MHz)	99% Occupied Bandwidth(KHz)
Mid 661	1880	246.795
Low 512	1850.2	248.397
High 810	1909.8	291.603

Conclusion: PASS

GPRS 1900



Channel 661-Occupied Bandwidth



Channel 512-Occupied Bandwidth



Channel 810-Occupied Bandwidth

EDGE 1900



Date: 7.JAN.2019 04:05:01

Channel 661-Occupied Bandwidth



Date: 7.JAN.2019 04:07:09

Channel 512-Occupied Bandwidth



Channel 810-Occupied Bandwidth

WCDMA BAND II		
Test channel	Frequency (MHz)	99% Occupied Bandwidth(MHz)
Mid 9400	1880	4.167
Low 9262	1852.4	4.167
High 9538	1907.6	4.167

Conclusion: PASS

WCDMA BAND II



Channel 9400-Occupied Bandwidth



Channel 9262-Occupied Bandwidth



Channel 9538-Occupied Bandwidth

WCDMA BAND IV		
Test channel	Frequency (MHz)	99% Occupied Bandwidth(MHz)
Mid 1413	1732.6	4.183
Low 1312	1712.4	4.167
High 1513	1752.6	4.183

Conclusion: PASS

WCDMA BAND II



Channel 1413-Occupied Bandwidth



Channel 1312-Occupied Bandwidth



Channel 1513-Occupied Bandwidth

WCDMA BAND V		
Test channel	Frequency (MHz)	99% Occupied Bandwidth(MHz)
Mid 4183	836.6	4.167
Low 4132	826.4	4.167
High 4233	846.6	4.183

Conclusion: PASS

WCDMA BAND V



Channel 4183-Occupied Bandwidth



Channel 4132-Occupied Bandwidth



Channel 4233-Occupied Bandwidth

ANNEX A.4. -26dB Emission Bandwidth

Method of test please refer to KDB971168 D01 v03 clause 4.0.

A.4.1. -26dB Emission Bandwidth

Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of GSM850, PCS1900, WCDMA BANDII, WCDMA BANDIV and WCDMA BANDV.

A.4.2 Test Procedure:

1. The EUT output RF connector was connected with a short cable to the signal analyzer.
2. RBW was set to about 1% of emission BW, VBW >= 3 times RBW,.
3. 26dB bandwidth were measured, the occupied bandwidth is delta frequency between the two points where the display line intersects the signal trace.

A.4.3 Measurement methods:

For GSM: signal analyzer setting as: RBW=3KHz;VBW=10KHz;Span=1MHz.
For WCDMA: signal analyzer setting as: RBW=50KHz;VBW=200KHz;Span=10MHz.

A.4.4 Test results:

GPRS 850		
Test channel	Frequency (MHz)	–26dBc Emission Bandwidth(MHz)
Mid 189	836.4	312.5
Low 128	824.2	314.103
High 251	848.8	318.91
EDGE 850		
Test channel	Frequency (MHz)	–26dBc Emission Bandwidth(MHz)
Mid 189	836.4	317.308
Low 128	824.2	312.5
High 251	848.8	318.91

Conclusion: PASS

GPRS 850



Channel 189- Emission Bandwidth (-26dBc BW)



Channel 128- Emission Bandwidth (-26dBc BW)



Channel 251- Emission Bandwidth (-26dBc BW)

EDGE 850



Channel 189- Emission Bandwidth (-26dBc BW)



Channel 128- Emission Bandwidth (-26dBc BW)



Channel 251- Emission Bandwidth (-26dBc BW)

GPRS1900		
Test channel	Frequency (MHz)	–26dBc Emission Bandwidth(MHz)
Mid 661	1880	312.5
Low 512	1850.2	318.91
High 810	1909.8	314.103
EDGE1900		
Test channel	Frequency (MHz)	–26dBc Emission Bandwidth(MHz)
Mid 661	1880	312.5
Low 512	1850.2	301.282
High 810	1909.8	314.103

Conclusion: PASS

GPRS 1900



Channel 661- Emission Bandwidth (-26dBc BW)



Channel 512- Emission Bandwidth (-26dBc BW)



Channel 810- Emission Bandwidth (-26dBc BW)

EDGE 1900



Channel 661- Emission Bandwidth (-26dBc BW)



Channel512- Emission Bandwidth (-26dBc BW)



Channel 810- Emission Bandwidth (-26dBc BW)

WCDMA BAND II		
Test channel	Frequency (MHz)	–26dBc Emission Bandwidth(MHz)
Mid 9400	1880	4.712
Low 9262	1852.4	4.696
High 9538	1907.6	4.712

Conclusion: PASS

WCDMA BAND II



Channel 9400- Emission Bandwidth (-26dBc BW)



Channel 9262- Emission Bandwidth (-26dBc BW)



Channel 9538- Emission Bandwidth (-26dBc BW)

WCDMA BAND IV		
Test channel	Frequency (MHz)	–26dBc Emission Bandwidth(MHz)
Mid 1413	1732.6	4.728
Low 1312	1712.4	4.728
High 1513	1752.6	4.712

Conclusion: PASS

WCDMA BAND IV



Channel 1413- Emission Bandwidth (-26dBc BW)



Channel 1312- Emission Bandwidth (-26dBc BW)



Channel 1513- Emission Bandwidth (-26dBc BW)

WCDMA BAND V		
Test channel	Frequency (MHz)	–26dBc Emission Bandwidth(MHz)
Mid 4183	836.6	4.744
Low 4132	826.4	4.728
High 4233	846.6	4.744

Conclusion: PASS

WCDMA BAND V



Channel 4183- Emission Bandwidth (-26dBc BW)



Channel4132- Emission Bandwidth (-26dBc BW)



Channel 4233- Emission Bandwidth (-26dBc BW)

ANNEX A.5. Band Edge at antenna terminals

Method of test measurements please refer to KDB971168 D01 v03 clause 6.

A.5.1 Limit:

The magnitude of each spurious and harmonic emission that can be detected when the equipment is operated under the conditions specification in the instruction manual and/or alignment procedure, shall not be less than 43+10log (Mean power in watts) dBc below the mean power output outside a license's frequency block(-13dBm).

A.5.2 Test procedure:

1. The RF output of the transceiver was connected to a signal analyzer through appropriate attenuation.
2. In the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.
3. The RF fundamental frequency should be excluded against the limit line in the operating frequency band
4. The limit line is derived from 43+10log(P) Db below the transmitter power P(Watts)
   =P(W)-[43+10log(P)](Db)
   =[30+10log(P)](dBm)-[43+10log(P)](Db)
   =-13dBm

GPRS 850



Channel 128- LOW BAND EDGE BLOCK



Channel 251- HIGH BAND EDGE BLOCK

EDGE 850



Channel 128- LOW BAND EDGE BLOCK



Channel 251- HIGH BAND EDGE BLOCK

GPRS 1900



Channel 512- LOW BAND EDGE BLOCK



Channel 810- HIGH BAND EDGE BLOCK

EDGE 1900



Channel 512- LOW BAND EDGE BLOCK



Channel 810- HIGH BAND EDGE BLOCK

WCDMA BAND II



Channel 9262- LOW BAND EDGE BLOCK



Channel 9538- HIGH BAND EDGE BLOCK

Conclusion: PASS

WCDMA BAND IV



Channel 1312- LOW BAND EDGE BLOCK



Channel 1513- HIGH BAND EDGE BLOCK

Conclusion: PASS

WCDMA BAND V



Channel 4132- LOW BAND EDGE BLOCK



Channel 4233- HIGH BAND EDGE BLOCK

Conclusion: PASS

ANNEX A.6. FREQUENCY STABILITY

Method of test measurements please refer to KDB971168 D01 v03 clause 9.

A.5.1.Method of Measurement and test procedures

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a “call mode”. This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30℃.
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on mid channel of GSM850, PCS1900, WCDMA BANDII and WCDMA BANDV, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10℃ increments from -30℃ to +50℃. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
5. Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50℃.
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call

on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 C increments from +50℃ to -30℃. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5℃ during the measurement procedure.

A.5.2. Measurement Limit

A.5.2.1. For Hand carried battery powered equipment

According to the JTC standard the GSM frequency stability of the carrier shall be accurate to within 0.1ppm of the received frequency from the base station. And the WCDMA is 2.5ppm. This accuracy is sufficient to meet Sec.24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 6.8VDC and 8.7VDC, with a nominal voltage of 7.6VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages was varied from 85% to 115%.

A.5.2.2. For equipment powered by primary supply voltage

According to the JTC standard the GSM frequency stability of the carrier shall be accurate to within 0.1ppm of the received frequency from the base station. And the WCDMA is 2.5ppm. This accuracy is sufficient to meet Sec.24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

A.5.3 Test results

GSM850Mid Channel/fc(MHz) 189/836.4

Frequency Error VS Temperature

Power Supply (VDc)	Environment Temperature(℃)	Frequency error(Hz)	Limit (Hz)
7.6	-30	-2.37	2091
7.6	-20	-2.27	2091
7.6	-10	-2.65	2091
7.6	0	-2.14	2091
7.6	10	-2.27	2091
7.6	20	-1.99	2091
7.6	30	-1.86	2091

7.6	40	-2.25	2091
7.6	50	-2.69	2091

Frequency Error VS Voltage

Power Supply (VDc)	Environment Temperature(℃)	Frequency error(Hz)	Limit (Hz)
6.8	25	-2.17	2091
7.6	25	-2.57	2091
8.7	25	-2.54	2091

PCS1900 Mid Channel/fc(MHz) 661/1880

Frequency Error VS Temperature

Power Supply (VDc)	Environment Temperature(℃)	Frequency error(Hz)	Limit (Hz)
7.6	-30	-1.97	4700
7.6	-20	-1.55	4700
7.6	-10	-1.61	4700
7.6	0	-1.73	4700
7.6	10	-1.39	4700
7.6	20	-1.51	4700
7.6	30	-1.77	4700
7.6	40	-1.82	4700
7.6	50	-1.75	4700

Frequency Error VS Voltage

Power Supply (VDc)	Environment Temperature(℃)	Frequency error(Hz)	Limit (Hz)
6.8	25	-1.59	4700
7.6	25	-1.89	4700
8.7	25	-1.88	4700

WCDMA BAND II Mid Channel/fc(MHz) 9400 /1880

Frequency Error VS Temperature

Power Supply (VDc)	Environment Temperature(℃)	Frequency error(Hz)	Limit (Hz)
7.6	-30	10.88	4700
7.6	-20	13.05	4700
7.6	-10	-12.53	4700
7.6	0	-11.66	4700
7.6	10	-13.4	4700
7.6	20	-13.06	4700
7.6	30	-13.17	4700
7.6	40	-12.05	4700
7.6	50	-11.92	4700

Frequency Error VS Voltage

Power Supply (VDc)	Environment Temperature(℃)	Frequency error(Hz)	Limit (Hz)
6.8	25	-12.63	4700
7.6	25	-13.37	4700
8.7	25	-12.92	4700

WCDMA BAND IV Mid Channel/fc(MHz) 1413/1732.6

Frequency Error VS Temperature

Power Supply (VDc)	Environment Temperature(℃)	Frequency error(Hz)	Limit (Hz)
7.6	-30	-4.82	4331.5
7.6	-20	-4.12	4331.5
7.6	-10	-4.81	4331.5
7.6	0	--4.19	4331.5
7.6	10	-4.33	4331.5
7.6	20	-4.91	4331.5
7.6	30	-4.60	4331.5
7.6	40	-4.75	4331.5
7.6	50	-4.18	4331.5

Frequency Error VS Voltage

Power Supply (VDc)	Environment Temperature(℃)	Frequency error(Hz)	Limit (Hz)
6.8	25	-4.45	4331.5
7.6	25	-4.28	4331.5
8.7	25	-4.36	4331.5

WCDMA BAND V Mid Channel/fc(MHz) 4183/836.6

Frequency Error VS Temperature

Power Supply (VDc)	Environment Temperature(℃)	Frequency error(Hz)	Limit (Hz)
7.6	-30	-6.33	2091.5
7.6	-20	-6.3	2091.5
7.6	-10	-7.74	2091.5
7.6	0	-8.03	2091.5
7.6	10	-8.29	2091.5
7.6	20	-7.8	2091.5
7.6	30	-8.21	2091.5
7.6	40	-8.97	2091.5
7.6	50	-8.15	2091.5

Frequency Error VS Voltage

Power Supply (VDc)	Environment Temperature(℃)	Frequency error(Hz)	Limit (Hz)
6.8	25	-9.7	2091.5
7.6	25	-9.92	2091.5
8.7	25	-9.58	2091.5

Conclusion: PASS

ANNEX A.7. CONDUCTED SPURIOUS EMISSION

A.7.1. GSM Measurement Method and test procedures

Method of test measurements please refer to Part 2.1053/ Part 22.917/ Part 24.23.

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of PCS1900 band, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For GSM850, data taken from 30 MHz to 10 GHz.
2. The sweep time is set automatically by instrument itself. That should be the optimal sweep time for the span and the RBW. If the sweep time is too short, that is sweep is too fast, the sweep result is not accurate; If the sweep time is too long, that is sweep is too low, some frequency components may be lost. The instrument will give a optimal sweep time according the selected span and RBW.
3. The procedure to get the conducted spurious emission is as follows:
The trace mode is set to MaxHold to get the highest signal at each frequency;
Wait 25 seconds;Get the result.
4. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

GSM 850 Transmitter

Channel	Frequency(MHz)
128	824.2
189	836.4
251	848.8

PCS 1900 Transmitter

Channel	Frequency(MHz)
512	1850.2
661	1880.0
810	1909.8

A.7.1.1. Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A7.1.2. Measurement result

Spurious emission limit -13dBm.

Note: peak above the limit line is the carrier frequency.

A7.1.2.1. GSM 850



Channel 128: 30MHz~1GHz



Channel 128: 1GHz~10GHz



Channel 189: 30MHz~1GHz



Channel 189: 1GHz~10GHz



Channel 251: 30MHz~1GHz



Channel 251: 1GHz~10GHz

A7.1.2.2. PCS 1900



Channel 512: 30MHz~1GHz



Channel 512: 1GHz~20GHz



Channel 661: 30MHz~1GHz



Channel 661: 1GHz~20GHz



Channel 810: 30MHz~1GHz



Channel 810: 1GHz~20GHz

Conclusion: PASS

A7.2. WCDMA Measurement Method and test procedures

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of WCDMA Band II, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For WCDMA Band V, data taken from 30 MHz to 10GHz.

2. The sweep time is set automatically by instrument itself. That should be the optimal sweep time for the span and the RBW. If the sweep time is too short, that is sweep is too fast, the sweep result is not accurate; If the sweep time is too long, that is sweep is too low, some frequency components may be lost. The instrument will give a optimal sweep time according the selected span and RBW.

3. The procedure to get the conducted spurious emission is as follows:

The trace mode is set to MaxHold to get the highest signal at each frequency;

Wait 25 seconds;

Get the result.

4. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

WCDMA Band II Transmitter

Channel	Frequency (MHz)

9262	1852.40
9400	1880.00
9538	1907.60

WCDMA Band V Transmitter

Channel	Frequency (MHz)
4132	826.40
4183	836.60
4233	846.60

A 7.2.1. Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A 7.2.2. Measurement result

Spurious emission limit -13dBm.

Note: peak above the limit line is the carrier frequency.

A 7.2.2.1. WCDMA Band II



Channel 9262: 30MHz~1GHz



Channel 9262:1GHz~20GHz



Channel 9400: 30MHz~1GHz



Channel 9400:1GHz~20GHz



Channel 9538: 30MHz~1GHz



Channel 9538:1GHz~20GHz

Conclusion: PASS

A 7.2.2.2. WCDMA Band IV



Channel 1312: 30MHz~1GHz



Channel 1312:1GHz~20GHz



Channel 1413: 30MHz~1GHz



Channel 1413:1GHz~20GHz



Channel 1513: 30MHz~1GHz



Channel 1513:1GHz~20GHz

Conclusion: PASS

A 7.2.2.2. WCDMA Band V



Channel 4132: 30MHz~1GHz



Channel 4132:1GHz~20GHz



Channel 4183: 30MHz~1GHz



Channel 4183:1GHz~20GHz



Channel 4233: 30MHz~1GHz



Channel 4233:1GHz~20GHz

Conclusion: PASS

ANNEX A.8. RADIATED

A.8.1. ERP

A.8.1.1. GSM ERP

A.8.1.1.1. Description

This is the test for the maximum radiated power from the EUT.

Rule Part 24.232(c) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power"and 24.232(c) specifies that "Peak transmit power must be measured over any interval ofcontinuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."Rule Part 22.913(a) specifies ” The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.”

A.8.1.1.2. Method of Measurement

The measurements procedures in TIA-603E-2016 is used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from thereceive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUTfor emission measurements. The height of receiving antenna is 1.5m. The test setup refers tofigure below. Detected emissions were maximized at each frequency by rotating the EUTthrough 360° and adjusting the receiving antenna polarization. The radiated emissionmeasurements of all transmit frequencies in three channels (High, Middle, Low) weremeasured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level duringthe test. And the maximum value of the receiver should be recorded as (Pr).

3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at thereference point

of the chamber. An RF Signal source for the frequency band of interest isconnected to the substitution antenna with a cable that has been constructed to not interferewith the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of thesubstitution antenna, and adjust the level of the signal generator output until the value of thereceiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. Thetest should be performed by rotating the test item and adjusting the receiving antennapolarization.

4. A amplifier should be connected to the Signal Source output port. And the cable should beconnect between the Amplifier and the Substitution Antenna.

The cable loss (P_{cl}) ,the Substitution Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should berecorded after test.

The measurement results are obtained as described below:

Power(EIRP)=P_{Mea}+ P_{Ag}- P_{cl}+ G_a

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15dBi) and known input power.

6. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15dBi.

A.8.1.1.3 GSM 850-ERP 22.913(a)

A.8.1.1.3.1 Limits

	Power Step	Burst Peak ERP (dBm)
GPRS	3	≤38.45dBm (7W)
EDGE	6	≤38.45dBm (7W)

A.8.1.1.3.2 Measurement result

GPRS(GMSK)

Frequency (MHz)	P_{Mea}(dBm)	P_{cl}(dB)	P_{Ag}(dB)	G_aAntenna Gain(dBd)	PeakERP(dBm)	Polarization
824.2	-8.44	3.1	37	3.11	28.57	H
836.6	-8.03	3.1	37	3.11	28.98	H
848.8	-7.6	3.1	37	3.11	29.41	H

EDGE(8PSK)

Frequency (MHz)	P_{Mea}(dBm)	P_{cl}(dB)	P_{Ag}(dB)	G_aAntenna Gain(dBd)	PeakERP(dBm)	Polarization
824.2	-12.72	3.1	37	3.11	24.29	H
836.6	-12.01	3.1	37	3.11	25.00	H
848.8	-11.29	3.1	37	3.11	25.72	H

Frequency: 824.2MHz

Peak ERP(dBm)= P_{Mea}(-12.72dBm) - P_{cl}(3.1dB) +P_{Ag}(37dB) + G_a(3.11dBd)

= 24.29dBm

Note: ANALYZER SETTINGS: RBW = VBW = 3MHz

A.8.1.1.4 PCS 1900-EIRP 24.232(c)

A.8.1.1.4.1 Limits

	Power Step	Burst Peak EIRP (dBm)
GPRS	3	≤33dBm (2W)
EDGE	6	≤33dBm (2W)

A.8.1.1.4.2 Measurement result

GPRS(GMSK)

Frequency (MHz)	P_{Mea}(dBm)	P_{cl}(dB)	P_{Ag}(dB)	G_aAntenna Gain(dBi)	PeakEIRP(dBm)	Polarization
1850.2	-4.37	4.6	36	4.7	31.73	V
1880.0	-3.48	4.6	35.6	4.7	32.22	H
1909.8	-4.52	4.7	36	4.7	31.48	V

EDGE(8PSK)

Frequency (MHz)	P_{Mea}(dBm)	P_{cl}(dB)	P_{Ag}(dB)	G_aAntenna Gain(dBi)	PeakEIRP(dBm)	Polarization
1850.2	-7.75	4.6	36	4.7	28.35	V
1880.0	-6.53	4.6	35.6	4.7	29.17	H
1909.8	-7.41	4.7	36	4.7	28.59	V

Frequency: 1850.2MHz

Peak EIRP(dBm)= P_{Mea}(-7.75dBm) - P_{cl}(4.6dB)+ P_{Ag}(36dB) +G_a(4.7dB)=28.35dBm

ANALYZER SETTINGS: RBW = VBW = 3MHz

A.8.1.2. WCDMA ERP

A.8.1.2.1. Description

This is the test for the maximum radiated power from the EUT.

Rule Part 24.232(c) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power"and 24.232(c) specifies that "Peak transmit power must be measured over any interval ofcontinuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."Rule Part 22.913(a) specifies ” The ERP of mobile transmitters and auxiliary test transmitters mustnot exceed 7 Watts.”

A.8.1.2.2. Method of Measurement

The measurements procedures in TIA-603E-2016 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from thereceive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUTfor emission measurements. The height of receiving antenna is 1.5m. The test setup refers tofigure below. Detected emissions were maximized at each frequency by rotating the EUTthrough 360° and adjusting the receiving antenna polarization. The radiated emissionmeasurements of all transmit frequencies in three channels (High, Middle, Low) weremeasured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).

3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna.

The cable loss (P_{cl}) ,the Substitution Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test.

The measurement results are obtained as described below:

Power(EIRP)=P_{Mea}+ P_{Ag} -P_{cl}+ G_a

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15

dBi) and known input power.

6. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15dBi.

A.8.1.2.3 WCDMA Band II-ERP

	Burst Peak EIRP (dBm)
WCDMA Band II	≤33dBm (2W)

A.8.1.2.3.1 Measurement result

Frequency (MHz)	P_{Mea}(dBm)	P_{cl}(dB)	P_{Ag}(dB)	G_aAntenna Gain(dBi)	PeakEIRP(dBm)	Polarization
1852.4	-17.94	3.54	43.8	2.9	25.22	V
1880.0	-17.18	3.54	43.8	2.9	25.98	H
1907.6	-17.32	3.54	43.8	2.9	25.84	V

Frequency: 1852.40MHz

Peak EIRP(dBm)= P_{Mea}(-17.94dBm)- P_{cl}(3.54dB)+ P_{Ag}(43.8dB)+G_a(2.9dBi) =25.22dBm

ANALYZER SETTINGS: RBW = VBW = 5MHz

A.8.1.2.4 Limits

	Burst Peak EIRP (dBm)
WCDMA Band IV	≤33dBm (2W)

A.8.1.2.4.1 Measurement result

Frequency (MHz)	P_{Mea}(dBm)	P_{cl}(dB)	P_{Ag}(dB)	G_aAntenna Gain(dBd)	PeakERP(dBm)	Polarization
1712.4	-9.05	4.6	36	2.9	25.25	H
1732.6	-9.14	4.6	36	2.9	25.16	H
1752.6	-8.95	4.6	36	2.9	25.35	H

Frequency: 1712.4 MHz

Peak ERP(dBm)= P_{Mea}(-9.05dBm)- P_{cl}(4.6dB)+P_{Ag}(36dB)+G_a(2.9dBd)=25.25dBm

ANALYZER SETTINGS: RBW = VBW = 5MHz

A.8.1.2.5 Limits

	Burst Peak EIRP (dBm)
WCDMA Band V	≤38.45dBm (7W)

A.8.1.2.5.1 Measurement result

Frequency (MHz)	P_{Mea}(dBm)	P_{cl}(dB)	P_{Ag}(dB)	G_aAntenna Gain(dBd)	PeakERP(dBm)	Polarization
826.4	-16.91	3.1	37	2.9	19.89	H
836.6	-17	3.1	37	2.9	19.80	H
846.6	-16.25	3.1	37	2.9	20.55	H

Frequency: 826.4 MHz

Peak ERP(dBm)= P_{Mea}(-16.91dBm)- P_{cl}(3.1dB)+P_{Ag}(37dB)+G_a(2.9dBd)=19.89dBm

ANALYZER SETTINGS: RBW = VBW = 5MHz

Note: the EUT was displayed in several different direction, the worst cases were shown.

A.8.2 EMISSION LIMIT (§2.1051/§22.917§24.238)

A.8.2.1 GSM Measurement Method

The measurement procedures in TIA-603E-2016are used.

The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz. The resolution bandwidth is set as outlined in Part 24.238 and Part 22.917. The spectrum is scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of PCS1900 and GSM850.

A.8.2.2 The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10thharmonic were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).

3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss (P_{pl}) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain (G_a) should be recorded after test.

A amplifier should be connected in for the test.

The Path loss (P_{pl}) is the summation of the cable loss .

The measurement results are obtained as described below:

Power(EIRP)=P_{Mea}- P_{pl}+ G_a

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.

6. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15dBi

A.8.2.3 Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A.8.2.4 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the PCS1900 band (1850.2 MHz, 1880 MHz and 1909.8 MHz) and GSM850 band (824.2MHz, 836.6MHz, 848.8MHz) . It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the PCS1900 ,GSM850 into any of the other blocks. The equipment must

still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

A.8.2.5 Measurement Results

Measurements results:

Main supply

Frequency	Channel	Frequency Range	Result
GSM850	Low	30MHz~10GHz	P
	Middle	30MHz~10GHz	P
	High	30MHz~10GHz	P
GSM1900	Low	30MHz~20GHz	P
	Middle	30MHz~20GHz	P
	High	30MHz~20GHz	P

GSM850

GPRS Mode Channel 128

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit （dBm）	Polarization
1647.9	-24.11	4.3	2.9	-25.51	-13	H
2472.9	-32.52	5.3	3.7	-34.12	-13	H
3296.5	-44.21	6.2	4.7	-45.71	-13	V
4120.4	-45.67	7.0	7.7	-44.97	-13	V
4945.4	-43.72	7.7	9.0	-42.42	-13	H
5770.4	-49.55	8.5	10.5	-47.55	-13	V

Note:

GPRS 850, CH128

Power(ERP)= Pmea-Pcl+Ga=-49.55-8.5+10.5=-47.55dbm

This method Applicable to the following table.

GPRS Mode Channel 189

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit （dBm）	Polarization
1675.7	-29.42	4.4	2.9	-30.92	-13	H
2510.4	-28.92	5.4	3.7	-30.62	-13	V
3346.2	-44.37	6.2	4.7	-45.87	-13	V
4183.8	-42.19	7.0	7.7	-41.49	-13	V
5020.4	-44.43	7.8	9.0	-43.23	-13	V
5956.2	-48.46	8.5	10.4	-46.56	-13	V

GPRS Mode Channel 251

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit （dBm）	Polarization
1697.1	-26.35	4.4	2.9	-27.85	-13	H
2546.8	-31.8	5.4	3.7	-33.5	-13	H
3395.8	-42.57	6.3	4.7	-44.17	-13	V
4243.8	-42.41	7.1	7.7	-41.81	-13	H
5093.1	-47.13	7.9	9.0	-46.03	-13	V
5813.1	-49.89	8.4	10.5	-47.79	-13	V

EGPRS Mode Channel 128

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit （dBm）	Polarization

1650.0	-37.34	4.3	2.9	-38.74	-13	H
2514.6	-36.49	5.4	3.7	-38.19	-13	H
3573.5	-46.81	6.4	4.7	-48.51	-13	V
4539.2	-46.78	7.4	7.3	-46.88	-13	H
4945.4	-47.43	7.7	9.0	-46.13	-13	H
6196.9	-49.23	8.7	10.8	-47.13	-13	V

EGPRS Mode Channel 189

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit（dBm）	Polarization
1670.4	-37.14	4.3	2.9	-38.54	-13	H
2510.4	-34.58	5.4	3.7	-36.28	-13	V
3345.0	-46.54	6.2	4.7	-48.04	-13	V
4502.3	-47.74	7.3	7.3	-47.74	-13	H
5516.5	-49.34	8.2	9.5	-48.04	-13	V
6403.1	-49.33	8.9	11.5	-46.73	-13	H

EGPRS Mode Channel 251

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit（dBm）	Polarization
1697.1	-30.95	4.4	2.9	-32.45	-13	H
2442.9	-36.5	5.3	3.7	-38.1	-13	H

3395.8	-46.13	6.3	4.7	-47.73	-13	V
4243.8	-48.24	7.1	7.7	-47.64	-13	H
5058.5	-48.74	7.8	9.0	-47.54	-13	H
6410.8	-49.56	8.9	11.5	-46.96	-13	V

PCS1900

GPRS Mode Channel 512

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit （dBm）	Polarization
3700.8	-46.73	6.6	7.7	-45.63	-13	H
5551.2	-51.98	8.2	9.5	-50.68	-13	V
7400.4	-50.61	9.7	14.6	-45.71	-13	V
9711.6	-53.56	10.9	18.3	-46.16	-13	H
11157.6	-49.44	12.1	18.5	-43.04	-13	V
12781.2	-47.31	12.5	19.2	-40.61	-13	V

GPRS Mode Channel 661

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit （dBm）	Polarization
3760.2	-47.61	6.6	7.7	-46.51	-13	H
5362.8	-51	8.1	8.7	-50.4	-13	H
7519.2	-49.69	9.7	14.6	-44.79	-13	V

9469.2	-54.03	10.7	18.6	-46.13	-13	V
10399.2	-49.73	11.6	17.1	-44.23	-13	H
12727.2	-48.08	12.7	19.2	-41.58	-13	V

GPRS Mode Channel 810

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit （dBm）	Polarization
3819.6	-48.04	6.7	7.7	-47.04	-13	H
5730.0	-50.5	8.5	10.5	-48.5	-13	H
7639.2	-46.58	9.7	15.3	-40.98	-13	V
9186.0	-54.57	10.5	18.5	-46.57	-13	V
10806.0	-48.28	11.7	17.3	-42.68	-13	H
12885.6	-47.68	13.0	20.2	-40.48	-13	V

Conclusion: PASS

Note: the EUT was displayed in several different direction, the worst cases were shown.

EGPRS Mode Channel 512

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit （dBm）	Polarization
3700.2	-49.3	6.6	7.7	-48.2	-13	H
4487.4	-50.72	7.3	7.3	-50.72	-13	V
5265.6	-51.65	8.0	8.7	-50.95	-13	V
7400.4	-51.63	9.7	14.6	-46.73	-13	H
10796.4	-49.07	11.7	17.3	-43.47	-13	H

14331.6	-48.57	13.6	23.5	-38.67	-13	H

EGPRS Mode Channel 661

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit （dBm）	Polarization
3759.0	-49.93	6.6	7.7	-48.83	-13	H
5640.6	-51.32	8.3	10.5	-49.12	-13	H
6396.0	-52.09	8.9	11.5	-49.49	-13	H
7520.4	-53.29	9.7	14.6	-48.39	-13	H
10014.0	-51.2	11.2	17.6	-44.8	-13	V
12792.0	-47.04	12.5	19.2	-40.34	-13	V

EGPRS Mode Channel 810

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit （dBm）	Polarization
3819.6	-49	6.7	7.7	-48	-13	H
4496.4	-50.39	7.3	7.3	-50.39	-13	V
5729.4	-51.2	8.5	10.5	-49.2	-13	H
7638.0	-48.04	9.7	15.3	-42.44	-13	V
11248.8	-49.03	12.1	18.5	-42.63	-13	V
14295.6	-47.3	13.6	23.5	-37.4	-13	H

Conclusion: PASS

Note: the EUT was displayed in several different direction, the worst cases were shown.

Secondary supply

Frequency	Channel	Frequency Range	Result
GSM850	Low	30MHz~10GHz	P
	Middle	30MHz~10GHz	P
	High	30MHz~10GHz	P

GSM850

GPRS Mode Channel 128

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit（dBm）	Polarization
1646.8	-29.86	4.3	2.9	-31.26	-13	V
2471.8	-32.64	5.3	3.7	-34.24	-13	V
3296.5	-38.1	6.2	4.7	-39.6	-13	H
4120.4	-47.1	7.0	7.7	-46.4	-13	H
4946.5	-44.73	7.7	9.0	-43.43	-13	H
6130.8	-49.37	8.7	10.8	-47.27	-13	H

Note:

GPRS 850, CH128

Power(ERP)= Pmea-Pcl+Ga=-49.37-8.7+10.8=-47.27dbm

This method Applicable to the following table.

GPRS Mode Channel 189

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit（dBm）	Polarization
1672.5	-23.32	4.3	2.9	-24.72	-13	V
2509.3	-31.26	5.4	3.7	-32.96	-13	H
3346.2	-42.69	6.2	4.7	-44.19	-13	V

4183.8	-45.7	7.0	7.7	-45	-13	H
5019.2	-47.14	7.8	9.0	-45.94	-13	H
6321.5	-49.36	8.8	10.8	-47.36	-13	H

GPRS Mode Channel 251

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit （dBm）	Polarization
1697.1	-28.37	4.4	2.9	-29.87	-13	H
2546.8	-29.07	5.4	3.7	-30.77	-13	V
3394.6	-44.34	6.3	4.7	-45.94	-13	V
4242.7	-45.18	7.1	7.7	-44.58	-13	V
5091.9	-47.9	7.9	9.0	-46.8	-13	H
6444.6	-48.68	8.9	11.5	-46.08	-13	H

EGPRS Mode Channel 128

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit （dBm）	Polarization
1646.8	-29.29	4.3	2.9	-30.69	-13	H
2471.8	-33.53	5.3	3.7	-35.13	-13	H
3294.2	-43.6	6.2	4.7	-45.1	-13	H
4121.5	-45.23	7.0	7.7	-44.53	-13	H
4945.4	-46.46	7.7	9.0	-45.16	-13	H

6424.6	-48.97	8.9	11.5	-46.37	-13	H

EGPRS Mode Channel 189

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit（dBm）	Polarization
1673.6	-37.41	4.3	2.9	-38.81	-13	V
2510.4	-35.21	5.4	3.7	-36.91	-13	V
3345.0	-46.64	6.2	4.7	-48.14	-13	V
4182.7	-49.23	7.0	7.7	-48.53	-13	V
5020.4	-49.16	7.8	9.0	-47.96	-13	V
6050.8	-49.63	8.6	10.4	-47.83	-13	V

EGPRS Mode Channel 251

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit（dBm）	Polarization
1697.1	-35.24	4.4	2.9	-36.74	-13	V
2546.8	-34.36	5.4	3.7	-36.06	-13	V
3394.6	-46.54	6.3	4.7	-48.14	-13	V
4575.0	-47.82	7.4	7.3	-47.92	-13	H
6401.5	-49.49	8.9	11.5	-46.89	-13	V
7613.8	-51.08	9.7	14.6	-46.18	-13	V

A.7.2.2. WCDMA Measurement Method

The measurements procedures in TIA-603E-2016 are used.

The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set as outlined in Part 24.238 and Part 24.917.

The spectrum is scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of WCDMA Band V.

The procedure of radiated spurious emissions is the same like GSM.

A.7.2.2.1. Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A.7.2.2.2. Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the WCDMA Band V (826.4MHz, 836.6MHz and 846.6MHz) . It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the WCDMA Band V into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

A.7.2.2.3. Measurement Results Table

Main supply

Frequency	Channel	Frequency Range	Result
WCDMA Band II	Low	30MHz~20GHz	P
	Middle	30MHz~20GHz	P
	High	30MHz~20GHz	P
WCDMA Band IV	Low	30MHz~20GHz	P
	Middle	30MHz~20GHz	P
	High	30MHz~20GHz	P
WCDMA Band V	Low	30MHz~20GHz	P
	Middle	30MHz~20GHz	P
	High	30MHz~20GHz	P

WCDMA BAND II Mode Channel 9262

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit （dBm）	Polarization
3701.6	-59.89	6.6	7.7	-58.79	-13	H
5338.8	-59.84	8.1	8.7	-59.24	-13	V
7221.2	-60.95	9.5	13.7	-56.75	-13	H
8900.4	-62.26	10.4	18.3	-54.36	-13	H
10430.4	-57.93	11.6	17.1	-52.43	-13	V
11907.9	-55.57	12.5	17.1	-50.97	-13	V

WCDMA BAND II Mode Channel 9400

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit （dBm）	Polarization
3757.6	-60.86	6.6	7.7	-59.76	-13	H
5452.8	-59.02	8.1	9.5	-57.62	-13	V
7593.6	-60.12	9.7	14.6	-55.22	-13	V
9675.6	-60.69	10.9	18.3	-53.29	-13	V
11147.4	-57.75	12.1	18.5	-51.35	-13	H
12102.5	-54.06	12.6	17.1	-49.56	-13	H

WCDMA BAND II Mode Channel 9538

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit （dBm）	Polarization

3813.2	-59.72	6.7	7.7	-58.72	-13	H
5534.4	-59.37	8.2	9.5	-58.07	-13	V
7418.0	-61.95	9.7	14.6	-57.05	-13	H
9583.6	-61.08	10.8	18.6	-53.28	-13	V
10739.6	-57.53	11.7	17.3	-51.93	-13	H
12019.2	-54.38	12.6	17.1	-49.88	-13	V

WCDMA BAND IV Mode Channel 1312

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit （dBm）	Polarization
3422.8	-60.96	6.3	4.7	-62.56	-13	H
5140.8	-50.03	7.9	8.7	-49.23	-13	V
6399.2	-58.24	8.9	11.5	-55.64	-13	V
8250.8	-62.87	10.1	17.3	-55.67	-13	V
9228.8	-61.64	10.6	18.5	-53.74	-13	V
10335.6	-58.74	11.5	17.4	-52.84	-13	V

WCDMA BAND IV Mode Channel 1413

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit （dBm）	Polarization
3458.8	-62.42	6.4	4.7	-64.12	-13	H

5200.8	-52.46	8.0	8.7	-51.76	-13	V
6873.6	-59.95	9.2	12.3	-56.85	-13	H
8251.2	-62.02	10.1	17.3	-54.82	-13	H
9700.0	-61.47	10.9	18.3	-54.07	-13	V
10795.6	-56.7	11.7	17.3	-51.1	-13	V

WCDMA BAND IV Mode Channel 1513

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit（dBm）	Polarization
3503.6	-61.54	6.4	4.7	-63.24	-13	H
5260.4	-51.65	8.0	8.7	-50.95	-13	V
7196.4	-61.77	9.5	13.7	-57.57	-13	H
8799.2	-64.49	10.4	18.5	-56.39	-13	V
9910.0	-60.93	11.0	17.6	-54.33	-13	H
10787.6	-55.84	11.7	17.3	-50.24	-13	H

WCDMA BAND V Mode Channel 4132

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit（dBm）	Polarization
1651.1	-45.16	4.3	2.9	-46.56	-13	H
2427.3	-51.39	5.3	3.7	-52.99	-13	H

3289.2	-62.83	6.2	4.7	-64.33	-13	H
4241.6	-60.11	7.1	7.7	-59.51	-13	V
4963.6	-57.24	7.7	9.0	-55.94	-13	H
6362.4	-59.33	8.8	10.8	-57.33	-13	V

WCDMA BAND V Mode Channel 4183

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit（dBm）	Polarization
1671.1	-45.58	4.3	2.9	-46.98	-13	H
2481.5	-50.86	5.3	3.7	-52.46	-13	H
3177.6	-60.34	6.1	4.7	-61.74	-13	H
3998.4	-61.65	6.9	7.7	-60.85	-13	H
4477.2	-58.61	7.3	7.3	-58.61	-13	H
5490.4	-60.79	8.2	9.5	-59.49	-13	V

WCDMA BAND V Mode Channel 4233

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit（dBm）	Polarization
1695.0	-46.37	4.4	2.9	-47.87	-13	H
2480.0	-51.15	5.3	3.7	-52.75	-13	V
3329.2	-63.12	6.2	4.7	-64.62	-13	V

4596.4	-58.53	7.4	7.3	-58.63	-13	H
5452.8	-59.48	8.1	9.5	-58.08	-13	V
6317.2	-60.23	8.8	10.8	-58.23	-13	V

Conclusion: PASS

Note: the EUT was displayed in several different direction, the worst cases were shown.

Secondary supply

Frequency	Channel	Frequency Range	Result
WCDMA Band IV	Low	30MHz~20GHz	P
	Middle	30MHz~20GHz	P
	High	30MHz~20GHz	P

WCDMA BAND IV Mode Channel 1312

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit （dBm）	Polarization
5134.4	-50.46	7.9	8.7	-49.66	-13	V
6374.4	-59.33	8.8	10.8	-57.33	-13	V
7612.4	-60.71	9.7	14.6	-55.81	-13	V
9396.0	-62.26	10.7	18.6	-54.36	-13	H
10732.4	-55.8	11.7	17.3	-50.2	-13	V
11630.0	-56.91	12.2	17.6	-51.51	-13	V

WCDMA BAND IV Mode Channel 1413

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit （dBm）	Polarization

5198.4	-51.1	8.0	8.7	-50.4	-13	V
6371.2	-59.44	8.8	10.8	-57.44	-13	H
7330.8	-61.41	9.6	13.7	-57.31	-13	H
8868.8	-62.79	10.4	18.5	-54.69	-13	V
10383.6	-57.84	11.6	17.1	-52.34	-13	H
11661.2	-57.29	12.4	17.6	-52.09	-13	V

WCDMA BAND IV Mode Channel 1513

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit（dBm）	Polarization
5254.8	-49.22	8.0	8.7	-48.52	-13	H
6368.0	-58.17	8.8	10.8	-56.17	-13	H
7865.2	-62.17	9.9	15.3	-56.77	-13	V
9605.2	-61.68	10.8	18.6	-53.88	-13	V
11210.7	-58.41	12.1	18.5	-52.01	-13	H
12453.2	-56.68	12.7	18.7	-50.68	-13	V

ANNEX B. Accreditation Certificate

ilac-MRA a2LA

Accredited Laboratory

A2LA has accredited

EAST CHINA INSTITUTE OF TELECOMMUNICATIONS

Shanghai, People's Republic of China

for technical competence in the field of

Electrical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 *General requirements for the competence of testing and calibration laboratories*. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (*refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009*).

Presented this 15th day of March 2017.

President and CEO
For the Accreditation Council
Certificate Number 3682.01
Valid to February 28, 2019

For the tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.

************End of the Report************