

RF Exposure evaluation

FCC ID	2AH3J-HS86-MINI-14
Product Name	TV-BOX
Model/Type reference	HS86 MINI 14
Listed Model(s)	HS86 PRO 13, HS86 MINI 13, HS86 PRO 14, HS86 PRO 16, HS86 MINI 16, HS86 PRO 18, HS86 MINI 18, HS86 PRO 19, HS86 MINI 19, HS86 PRO 26, HS86 MINI 26, HS86 PRO 28, HS86 MINI 28, HS86 PRO 10, HS86 MINI 10, HS86 PRO 20, HS86 MINI 20, HS86 PRO 50, HS86 MINI 50, HS86 PRO 80, HS86 MINI 80, HS86 T1, HS86 T2, HS86 T6, HS86 T8, HS86 T9, HS86 T10, HS86 T12, HS86 T16, HS86 T20, HS86 X20, HS86 X30, HS86 X50, HS86 X70, HS86 X80, HS86 T18

1. Reference

ANSI C95.1–1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

FCC CFR 47 part1 1.1310: Radio frequency radiation exposure limits.

FCC CFR 47 part2 2.1091: Radio frequency radiation exposure evaluation: mobile devices

2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f2)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500–100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f2)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

4. Antenna Information

The module can only use antennas certificated as follows provided by manufacturer;

Antenna No.	Type of antenna:	Gain of the antenna (Max.)	Frequency range:
2.4GWIFI	PCB Antenna	1.47dBi	2400-2500MHz

5. Conducted Peak Output Power
2.4GWIFI

Mode	Channel	Output Power (dBm)	Output Power (mW)
IEEE 802.11b	1	7.44	5.55
	6	7.00	5.01
	11	7.36	5.45
IEEE 802.11g	1	7.32	5.40
	6	6.77	4.75
	11	6.98	4.99
IEEE 802.11n_20	1	7.14	5.18
	6	6.96	4.97
	11	7.01	5.02
IEEE 802.11n_40	3	7.33	5.41
	6	7.45	5.56
	9	7.15	5.19
IEEE 802.11ax_20	1	7.21	5.26
	6	6.96	4.97
	11	7.00	5.01
IEEE 802.11ax_40	3	7.34	5.42
	6	7.44	5.55
	9	7.11	5.14
IEEE 802.11ac_20	1	7.24	5.30
	6	6.99	5.00
	11	6.74	4.72
IEEE 802.11ac_40	3	7.30	5.37
	6	7.44	5.55
	9	7.05	5.07

6. Manufacturing Tolerance

2.4GWIFI

IEEE 802.11b			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	7	7	7
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11g			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	7	6	6
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n_20			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	7	6	7
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n_40			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	7	7	7
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ax_20			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	6	7	7
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ax_40			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	7	7	7
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac_20			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	7	6	6

Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac_40			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	7	7	7
Tolerance $\pm$ (dB)	1.0	1.0	1.0

7. Standalone MPE Result

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20\text{cm}$, as well as the gain of the used antenna is 1.47dBi, the RF power density can be obtained.

Mode	Output power		Antenna Gain (dBi)	Antenna Gain(linear)	MPE (mW/cm^2)	MPE Limits (mW/cm^2)
	dBm	mW				
2.4GWIFI	8	6.31	1.47	1.47	0.00176	1.0000

Remark:

1. Output power (Peak) including turn-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer.

8. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----End of the report-----