

FCC IC TEST REPORT

FCC ID:2AH3J-ITALKBB

IC:29322-ITALKBB

Product : iTalkBB Karaoke Set-top Box
Model Name : iTalkBB TV Box 5, iTalkBB TV Box
Brand : iTalkBB
Report No. : NCT24021466E

Prepared for

Shenzhen Hugsun Technology Co., Ltd.

413-415 Room, 4/F, No.6 Bldg., Tongfuyu Industrial Park, Dalang Street, Shenzhen, China

5th Floor, Building 1, Guole Science Park, No.1 Lirong Road Dalang Street, Longhua District, Shenzhen, China

Prepared by

Shenzhen NCT Testing Technology Co., Ltd.

A101&2F B2, Fuqiao 6th Area, Xintian Community, Fuhai Street, Baoan District, Shenzhen, People's Republic of China

TEL: 400-8868-419

FAX: 86-755-27790922

1 TEST RESULT CERTIFICATION

Applicant : Shenzhen Hugsun Technology Co., Ltd.
413-415 Room, 4/F, No.6 Bldg., Tongfuyu Industrial Park, Dalang Street, Shenzhen, China
Address : 5th Floor, Building 1, Guole Science Park, No.1 Lirong Road Dalang Street, Longhua District, Shenzhen, China
Manufacturer : Shenzhen Hugsun Technology Co., Ltd.
413-415 Room, 4/F, No.6 Bldg., Tongfuyu Industrial Park, Dalang Street, Shenzhen, China
Address : 5th Floor, Building 1, Guole Science Park, No.1 Lirong Road Dalang Street, Longhua District, Shenzhen, China
Product name : iTalkBB Karaoke Set-top Box
Model name : iTalkBB TV Box 5, iTalkBB TV Box
Standards : FCC CFR47 Part 15 Section 15.247
RSS-247 Issue 3, August 2023
RSS-GEN Issue 5 April 2018 Amendment 2(February 2021)
Test procedure : ANSI C63.10:2013
Date of test : May 21, 2024- Jun. 05, 2024
Date of Issue : Jun. 05, 2024

This device described above has been tested by NCT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NCT, this document may be altered or revised by NCT, personal only, and shall be noted in the revision of the document.

Test Engineer:



Keven Wu / Engineer

Technical Manager:


Henry Wang / Manager


Contents

Page

1 TEST RESULT CERTIFICATION	2
2 TEST SUMMARY	5
3 GENERAL INFORMATION	6
3.1 GENERAL DESCRIPTION OF E.U.T.....	6
3.2 CHANNEL LIST	8
3.3 TEST SITE	9
3.4 TEST SETUP CONFIGURATION	10
3.5 TEST MODE	10
4 EQUIPMENT DURING TEST	11
4.1 EQUIPMENTS LIST	11
4.2 MEASUREMENT UNCERTAINTY.....	13
4.3 DESCRIPTION OF SUPPORT UNITS.....	13
5 CONDUCTED EMISSION	14
5.1 E.U.T. OPERATION.....	14
5.2 EUT SETUP	14
5.3 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	15
5.4 MEASUREMENT PROCEDURE	15
5.5 CONDUCTED EMISSION LIMIT	15
5.6 MEASUREMENT DESCRIPTION.....	15
5.7 CONDUCTED EMISSION TEST RESULT	15
6 RADIATED SPURIOUS EMISSIONS	18
6.1 EUT OPERATION	18
6.2 TEST SETUP	19
6.3 SPECTRUM ANALYZER SETUP.....	20
6.4 TEST PROCEDURE	21
6.5 SUMMARY OF TEST RESULTS	22
7 CONDUCT BAND EDGE AND SPURIOUS EMISSIONS MEASUREMENT	31
7.1 TEST PROCEDURE.....	31
7.2 TEST RESULT	32

8 6DB&99% BANDWIDTH MEASUREMENT	44
8.1 TEST PROCEDURE.....	44
8.2 TEST RESULT	44
9 MAXIMUM PEAK OUTPUT POWER.....	62
9.1 TEST PROCEDURE.....	62
9.2 TEST RESULT	62
10 POWER SPECTRAL DENSITY.....	64
10.1 TEST PROCEDURE.....	64
10.2 TEST RESULT	64
11 ANTENNA APPLICATION	73
11.1 ANTENNA REQUIREMENT	73
11.2 RESULT	73
12 TEST SETUP AND EUT PHOTOS	74

2 Test Summary

Test Items	Test Requirement	Result
Conduct Emission	FCC part 15.207 RSS-Gen § 8.8 RSS-247 § 3.1	PASS
Radiated Spurious Emissions	FCC part 15.205/15.209 RSS-Gen § 8.9&8.10	PASS
Conducted Spurious Emission	FCC part 15.205/15.209 RSS-247 § 5.5	PASS
Band edge	FCC part 15.247(d) RSS-247 § 5.5	PASS
6dB&99% Bandwidth	FCC part 15.247 (a)(2) RSS-GEN § 6.7 RSS-247 § 5.2	PASS
Maximum Peak Output Power	FCC part 15.247 (b)(3) RSS-247 § 5.4	PASS
Power Spectral Density	FCC part 15.247 (e) RSS-247 § 5.2	PASS
Antenna Requirement	FCC part 15.203/15.247 (c) RSS-GEN § 6.8	PASS

Remark:

"N/A" denotes test is not applicable in this Test Report.

3 General Information

3.1 General Description of E.U.T.

Manufacturer	:	Shenzhen Hugsun Technology Co., Ltd.
Address	:	413-415 Room, 4/F, No.6 Bldg., Tongfuyu Industrial Park, Dalang Street, Shenzhen, China 5th Floor, Building 1, Guole Science Park, No.1 Lirong Road Dalang Street, Longhua District, Shenzhen, China
Product Name	:	iTalkBB Karaoke Set-top Box
Model Name	:	iTalkBB TV Box 5
Sample ID	:	NCT24021466-001#
Sample(s) Status:	:	Engineer sample
Series Model	:	iTalkBB TV Box
Model Different.:	:	All the same except the model number.
Specification	:	802.11b/g/n HT20/n HT40
Operation Frequency	:	2412-2462MHz for 802.11b/g/n20; 2422-2452MHz for 802.11n40;
Number of Channel	:	11 channels for 802.11b/g/n20; 7 channels for 802.11n40;
Type of Modulation	:	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
Antenna installation	:	PCB Antenna
Antenna Gain	:	2.06dBi
Power supply	:	DC 5V/2A From adapter input AC 120V/60Hz
Adapter Information	:	Model:KA12H-0502000US Input:AC100-240V 50/60Hz 0.4A Max Output: DC 5V 2000mA
Product Marketing Name	:	iTalkBB TV Box 5, iTalkBB TV Box
Hardware Version Identification Number	:	iTalkBB TV Box 5
Hardware Version	:	KTV-RK3528-D4-V10

Software Version	:	09010030
Remark : the Antenna gain is provided by customer from Antenna spec. and the laboratory will not be responsible for the accumulated calculation results which covers the information provided by the applicant.		



3.2 Channel List

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (802.11b: 1 Mbps; 802.11g: 6 Mbps; 802.11n (HT20): MCS0; 802.11n (HT40): MCS0; were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for 802.11 b/g/n (HT20)/n (HT40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447		

Test Frequency and Channel for 802.11 b/g/n (HT20/HT40):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	6	2437	11	2462
3	2422	6	2437	9	2452

3.3 Test Site

Site Description

EMC Lab. : Accredited by CNAS, 2022-09-27

The certificate is valid until 2028.01.07

The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2017)

The Certificate Registration Number is L8251

Designation Number: CN1347

Test Firm Registration Number: 894804

Accredited by A2LA, June 14, 2023

The Certificate Registration Number is 6837.01

Accredited by Industry Canada, November 09, 2018


The Conformity Assessment Body Identifier is CN0150

Company Number: 30806

Name of Firm : Shenzhen NCT Testing Technology Co., Ltd.

Site Location : A101&2F B2, Fuqiao 6th Area, Xintian Community, Fuhai Street, Baoan District, Shenzhen, People's Republic of China

3.4 Test Setup Configuration



3.5 Test Mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

Test Software	RFTester
Power level setup	default

4 Equipment During Test

4.1 Equipments List

Conducted emission Test Equipment

Name	Model No.	Serial No.	Manufacturer	Date of Cal.	Due Date
944 Shielded Room	944 Room	/	EMToni	2022/5/31	2025/5/30
EMI Test Receiver	ESPI	101604	Rohde & Schwarz	2023/6/21	2024/6/20
LISN	ENV 216	102796	Rohde & Schwarz	2023/6/21	2024/6/20
LISN	VN1-13S	004023	CRANAGE	2023/6/21	2024/6/20
Cable	RG223-1500MM	NA	RG	2023/6/21	2024/6/20

Radiated emission & Radio Frequency Test Equipment

Name	Model No.	Serial No.	Manufacturer	Date of Cal.	Due Date
966 Shielded Room	966 Room	/	EMToni	2022/5/31	2025/5/30
EMI Test Receiver	ESCI	101178	Rohde & Schwarz	2023/6/21	2024/6/20
Amplifier (30MHz-1GHz)	BBV 9743 B	00374	SCHNWARZBECK	2023/6/21	2024/6/20
Bilog Antenna (30MHz-1GHz)	VULB9162	00473	SCHNWARZBECK	2023/3/19	2025/3/18
Horn antenna (1GHz-18GHz)	BBHA 9120 D	02622	SCHNWARZBECK	2023/3/19	2025/3/18
Preamplifier (1GHz-18GHz)	BBV 9718D	0024	SCHNWARZBECK	2023/6/21	2024/6/20
Spectrum Analyzer (10Hz-40GHz)	FSV 40	100952	Rohde & Schwarz	2023/6/21	2024/6/20
Preamplifier (18GHz-40GHz)	BBV 9721	0056	SCHNWARZBECK	2023/6/21	2024/6/20
Double Ridge Guide Horn Antenna (18GHz-40GHz)	SAS-574	588	A.H.System	2023/3/19	2025/3/18
Loop Antenna (9KHz-30MHz)	FMZB 1513-60	00115	SCHNWARZBECK	2023/6/21	2024/6/20

Amplifier (9KHz-30MHz)	BBV 9745	00109	CHNWARZBECK	2023/6/21	2024/6/20
MXG Signal Analyzer	N9020A	MY50510202	Agilent	2023/6/21	2024/6/20
MXG Vector Signal Generator	N5182A	MY50140020	Agilent	2023/6/21	2024/6/20
MXG Analog Signal Generator	N5181A	MY47420919	Agilent	2023/6/21	2024/6/20
Power Sensor	TR1029-2	512364	Techoy	2023/6/21	2024/6/20
RF Swith	TR1029-1	512364	Techoy	2023/6/21	2024/6/20
Cable	DA800- 4000MM	NA	DA	2023/6/21	2024/6/20
Cable	DA800- 11000MM	NA	DA	2023/6/21	2024/6/20

Other

Item	Name	Manufacturer	Model	Software version
1	EMC Conduction Test System	AUDIX	e3	6.120718
2	EMC radiation test system	AUDIX	e3	6.120718
3	RF test system	TACHOY	RFTest	V1.0.0
4	RF communication test system	TACHOY	RFTest	V1.0.0

4.2 Measurement Uncertainty

Parameter	Uncertainty
RF output power, conducted	±1.0dB
Power Spectral Density, conducted	±2.2dB
Radio Frequency	± 1 x 10 ⁻⁶
Bandwidth	± 1.5 x 10 ⁻⁶
Time	±2%
Duty Cycle	±2%
Temperature	±1°C
Humidity	±5%
DC and low frequency voltages	±3%
Conducted Emissions (150kHz~30MHz)	±3.64dB
Radiated Emission(9KHz~30MHz)	±4.51dB
Radiated Emission(30MHz~1GHz)	±5.03dB
Radiated Emission(1GHz~25GHz)	±4.74dB
Radiated Emission(25GHz~40GHz)	±3.38dB
Remark: The coverage Factor (k=2), and measurement Uncertainty for a level of Confidence of 95%	

4.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	iTalkBB Karaoke Set-top Box	N/A	iTalkBB TV Box 5	N/A	EUT
E-2	Adapter	Keyu	KA12H-0502000US	N/A	EUT
E-3	Display	TGD	ME221	T22D07	Auxiliary
E-4	USB flash disk	Kingston	DTXON/64GB	10291016	Auxiliary

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

5 Conducted Emission

Test Requirement: : FCC CFR 47 Part 15 Section 15.207, RSS-Gen§8.8, RSS-247§ 3.1
Test Method : ANSI C63.10: 2013
Test Result : PASS
Frequency Range : 150kHz to 30MHz
Class/Severity : Class B


5.1 E.U.T. Operation

Operating Environment :


Temperature : 24.5 °C
Humidity : 51.3 % RH
Atmospheric Pressure : 101.11kPa

5.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10:2013.



5.3 Test SET-UP (Block Diagram of Configuration)



5.4 Measurement Procedure

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

5.5 Conducted Emission Limit

Conducted Emission

Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

5.6 Measurement Description


The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

5.7 Conducted Emission Test Result

Pass.

Please refer to the following pages.

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Phase :	L
Test Voltage :	AC 120V/60Hz		




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1617	46.59	9.78	56.37	65.38	-9.01	peak	P
2	0.1617	34.76	9.78	44.54	55.38	-10.84	AVG	P
3 *	0.1695	46.56	9.77	56.33	64.98	-8.65	peak	P
4	0.1695	34.24	9.77	44.01	54.98	-10.97	AVG	P
5	0.1773	44.07	9.77	53.84	64.61	-10.77	peak	P
6	0.1773	30.64	9.77	40.41	54.61	-14.20	AVG	P
7	0.2240	37.24	9.75	46.99	62.67	-15.68	peak	P
8	0.2240	25.52	9.75	35.27	52.67	-17.40	AVG	P
9	0.2436	34.94	9.75	44.69	61.97	-17.28	peak	P
10	0.2474	21.05	9.75	30.80	51.84	-21.04	AVG	P
11	0.2787	30.03	9.76	39.79	60.85	-21.06	peak	P
12	0.2787	11.50	9.76	21.26	50.85	-29.59	AVG	P

Notes: 1.An initial pre-scan was performed on the line and neutral lines with peak detector.

2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.

3.Measurement Level = Reading level + Correct Factor

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Phase :	N
Test Voltage :	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1773	42.13	9.77	51.90	64.61	-12.71	peak	P
2	0.1773	28.43	9.77	38.20	54.61	-16.41	AVG	P
3 *	0.1890	43.68	9.76	53.44	64.08	-10.64	peak	P
4	0.1890	23.29	9.76	33.05	54.08	-21.03	AVG	P
5	0.2162	39.38	9.75	49.13	62.96	-13.83	peak	P
6	0.2162	29.75	9.75	39.50	52.96	-13.46	AVG	P
7	0.2358	34.50	9.75	44.25	62.24	-17.99	peak	P
8	0.2358	20.81	9.75	30.56	52.24	-21.68	AVG	P
9	0.3331	21.29	9.76	31.05	49.37	-18.32	AVG	P
10	0.3487	32.63	9.76	42.39	58.99	-16.60	peak	P
11	9.7936	28.93	10.15	39.08	60.00	-20.92	peak	P
12	9.9966	19.90	10.16	30.06	50.00	-19.94	AVG	P

Notes: 1.An initial pre-scan was performed on the line and neutral lines with peak detector.

2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.

3.Measurement Level = Reading level + Correct Factor

6 Radiated Spurious Emissions

Test Requirement : FCC CFR47 Part 15 Section 15.209 & 15.247,
RSS-Gen §8.9, RSS-Gen §8.10

Test Method : ANSI C63.10:2013

Test Result : PASS

Measurement Distance : 3m

Limit : See the follow table

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log^{(2400/F(\text{kHz}))} + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log^{(24000/F(\text{kHz}))} + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

6.1 EUT Operation

Operating Environment :

Temperature: : 24.5°C

Humidity: : 52 % RH


Atmospheric Pressure: : 101.11kPa

Test Voltage : DC 5V


6.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site


The test setup for emission measurement below 30MHz



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz



6.3 Spectrum Analyzer Setup

Below 30MHz			
IF Bandwidth	:	10kHz	
Resolution Bandwidth	:	10kHz	
Video Bandwidth	:	10kHz	
30MHz ~ 1GHz			
Detector	:	PK	QP
Resolution Bandwidth	:	100kHz	120kHz
Video Bandwidth	:	300kHz	300kHz
Above 1GHz			
Detector	:	PK	AV
Resolution Bandwidth	:	1MHz	1MHz
Video Bandwidth	:	3MHz	10Hz

6.4 Test Procedure

1. Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane, And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions. The spectrum was investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.
8. The test above 1GHz must be use the fully anechoic room, and the test below 1GHz use the half anechoic room

6.5 Summary of Test Results

Test Frequency: 9KHz-30MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	>20

Note:

The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.


Distance extrapolation factor = $40 \log(\text{Specific distance} / \text{test distance})$ (dB);
Limit line = Specific limits (dBuV) + distance extrapolation factor.

Test Frequency: 30MHz ~ 1GHz

All the modulation modes were tested the data of the worst mode (TX 802.11b Low Channel) are recorded in the following pages and the others modulation methods do not exceed the limits.


Please refer to the following test plots:

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	DC 5V from Adapter input AC 120V/60Hz	Mode:	TX 802.11b Low Channel



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna	Verdict
1	148.310	37.35	-17.16	43.5	6.15	Peak	Horizontal	Pass
2	296.683	41.23	-11.04	46.0	4.77	Peak	Horizontal	Pass
3	445.056	41.78	-7.99	46.0	4.22	Peak	Horizontal	Pass
4	494.514	41.42	-7.12	46.0	4.58	Peak	Horizontal	Pass
5	593.429	42.03	-5.22	46.0	3.97	Peak	Horizontal	Pass
6	742.529	41.36	-3.47	46.0	4.64	Peak	Horizontal	Pass

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	DC 5V from Adapter input AC 120V/60Hz	Mode:	TX 802.11b Low Channel



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna	Verdict
1	30.000	34.56	-14.19	40.0	5.44	QP	Vertical	Pass
2	148.310	40.92	-17.16	43.5	2.58	Peak	Vertical	Pass
3	197.768	37.16	-13.50	43.5	6.34	Peak	Vertical	Pass
4	445.299	43.48	-8.00	46.0	2.52	Peak	Vertical	Pass
5	593.429	41.66	-5.22	46.0	4.34	Peak	Vertical	Pass
6	741.802	41.41	-3.43	46.0	4.59	Peak	Vertical	Pass

Remark: Emission Level = Reading + Cable Loss + ANT Factor

Test Frequency: From 1GHz to 25GHz

Mode: TX 802.11b

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/ m)	Margin (dB)	Detect or Type
Low Channel:2412MHz									
V	4824.00	52.85	34.12	5.03	32.39	56.15	74.00	-17.85	PK
V	4824.00	40.34	34.12	5.03	32.39	43.64	54.00	-10.36	AV
V	7236.00	49.81	32.54	6.29	35.86	59.42	74.00	-14.58	PK
V	7236.00	35.12	32.54	6.29	35.86	44.73	54.00	-9.27	AV
V	9648.00	41.49	32.98	7.55	38.4	54.46	74.00	-19.54	PK
V	9648.00	30.11	32.98	7.55	38.4	43.08	54.00	-10.92	AV
V	12060.00	40.7	32.09	8.93	39	56.54	74.00	-17.46	PK
V	12060.00	27.16	32.09	8.93	39	43	54.00	-11	AV
H	4824.00	50.48	34.12	5.03	32.39	53.78	74.00	-20.22	PK
H	4824.00	35.41	34.12	5.03	32.39	38.71	54.00	-15.29	AV
H	7236.00	46.23	32.54	6.29	35.86	55.84	74.00	-18.16	PK
H	7236.00	32.84	32.54	6.29	35.86	42.45	54.00	-11.55	AV
H	9648.00	46.11	32.98	7.55	38.4	59.08	74.00	-14.92	PK
H	9648.00	30.28	32.98	7.55	38.4	43.25	54.00	-10.75	AV
H	12060.00	41.16	32.09	8.93	39	57	74.00	-17	PK
H	12060.00	26.59	32.09	8.93	39	42.43	54.00	-11.57	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/ m)	Margin (dB)	Detect or Type
Middle Channel:2437MHz									
V	4874.00	52.41	34.07	5.09	32.59	56.02	74.00	-17.98	PK
V	4874.00	39.25	34.07	5.09	32.59	42.86	54.00	-11.14	AV
V	7311.00	49.56	32.63	6.34	35.96	59.23	74.00	-14.77	PK
V	7311.00	33.88	32.63	6.34	35.96	43.55	54.00	-10.45	AV
V	9748.00	42.06	32.92	7.59	38.4	55.13	74.00	-18.87	PK
V	9748.00	30.95	32.92	7.59	38.4	44.02	54.00	-9.98	AV
V	12185.00	41.84	31.96	8.88	39.04	57.8	74.00	-16.2	PK
V	12185.00	28.11	31.96	8.88	39.04	44.07	54.00	-9.93	AV
H	4874.00	50.89	34.07	5.09	32.59	54.5	74.00	-19.5	PK
H	4874.00	35.16	34.07	5.09	32.59	38.77	54.00	-15.23	AV
H	7311.00	45.87	32.63	6.34	35.96	55.54	74.00	-18.46	PK
H	7311.00	32.84	32.63	6.34	35.96	42.51	54.00	-11.49	AV
H	9748.00	42.19	32.92	7.59	38.4	55.26	74.00	-18.74	PK
H	9748.00	28.79	32.92	7.59	38.4	41.86	54.00	-12.14	AV
H	12185.00	39.88	31.96	8.88	39.04	55.84	74.00	-18.16	PK
H	12185.00	25.16	31.96	8.88	39.04	41.12	54.00	-12.88	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/ m)	Margin (dB)	Detect or Type
High Channel:2462MHz									
V	4924.00	51.59	34.02	5.15	32.8	55.52	74.00	-18.48	PK
V	4924.00	40.23	34.02	5.15	32.8	44.16	54.00	-9.84	AV
V	7386.00	43.89	32.71	6.4	36.05	53.63	74.00	-20.37	PK
V	7386.00	33.74	32.71	6.4	36.05	43.48	54.00	-10.52	AV
V	9848.00	42.84	32.86	7.62	38.4	56	74.00	-18	PK
V	9848.00	29.98	32.86	7.62	38.4	43.14	54.00	-10.86	AV
V	12310.00	40.16	31.82	8.84	39.08	56.26	74.00	-17.74	PK
V	12310.00	29.06	31.82	8.84	39.08	45.16	54.00	-8.84	AV
H	4924.00	49.79	34.02	5.15	32.8	53.72	74.00	-20.28	PK
H	4924.00	37.51	34.02	5.15	32.8	41.44	54.00	-12.56	AV
H	7386.00	46.23	32.71	6.4	36.05	55.97	74.00	-18.03	PK
H	7386.00	34.08	32.71	6.4	36.05	43.82	54.00	-10.18	AV
H	9848.00	39.84	32.86	7.62	38.4	53	74.00	-21	PK
H	9848.00	28.93	32.86	7.62	38.4	42.09	54.00	-11.91	AV
H	12310.00	38.74	31.82	8.84	39.08	54.84	74.00	-19.16	PK
H	12310.00	20.03	31.82	8.84	39.08	36.13	54.00	-17.87	AV

Note:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
4. We test all the mode and recorded the worst mode (TX 802.11b) in the report.

Radiated Band Emission Measurement:

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Detector Type	Result
802.11b	Low Channel 2412MHz									
	H	2390.00	58.13	35.17	3.48	27.49	53.93	74.00	PK	PASS
	H	2390.00	52.11	35.17	3.48	27.49	47.91	54.00	AV	PASS
	H	2400.00	60.51	35.16	3.49	27.52	56.36	74.00	PK	PASS
	H	2400.00	51.06	35.16	3.49	27.52	46.91	54.00	AV	PASS
	V	2390.00	58.77	35.17	3.48	27.49	54.57	74.00	PK	PASS
	V	2390.00	50.89	35.17	3.48	27.49	46.69	54.00	AV	PASS
	V	2400.00	60.93	35.16	3.49	27.52	56.78	74.00	PK	PASS
	V	2400.00	48.82	35.16	3.49	27.52	44.67	54.00	AV	PASS
	High Channel 2462MHz									
	H	2483.50	59.16	35.11	3.56	27.75	55.36	74.00	PK	PASS
	H	2483.50	47.58	35.11	3.56	27.75	43.78	54.00	AV	PASS
	H	2500.00	60.84	35.1	3.57	27.8	57.11	74.00	PK	PASS
	H	2500.00	50.77	35.1	3.57	27.8	47.04	54.00	AV	PASS
	V	2483.50	61.03	35.11	3.56	27.75	57.23	74.00	PK	PASS
	V	2483.50	49.76	35.11	3.56	27.75	45.96	54.00	AV	PASS
	V	2500.00	59.81	35.1	3.57	27.8	56.08	74.00	PK	PASS
	V	2500.00	50.84	35.1	3.57	27.8	47.11	54.00	AV	PASS
802.11g	Low Channel 2412MHz									
	H	2390.00	58.24	35.17	3.48	27.49	54.04	74.00	PK	PASS
	H	2390.00	50.94	35.17	3.48	27.49	46.74	54.00	AV	PASS
	H	2400.00	60.21	35.16	3.49	27.52	56.06	74.00	PK	PASS
	H	2400.00	50.39	35.16	3.49	27.52	46.24	54.00	AV	PASS

802.11 n20	V	2390.00	57.89	35.17	3.48	27.49	53.69	74.00	PK	PASS
	V	2390.00	51.02	35.17	3.48	27.49	46.82	54.00	AV	PASS
	V	2400.00	60.16	35.16	3.49	27.52	56.01	74.00	PK	PASS
	V	2400.00	50.21	35.16	3.49	27.52	46.06	54.00	AV	PASS
	High Channel 2462MHz									
	H	2483.50	59.91	35.11	3.56	27.75	56.11	74.00	PK	PASS
	H	2483.50	51.21	35.11	3.56	27.75	47.41	54.00	AV	PASS
	H	2500.00	63.09	35.1	3.57	27.8	59.36	74.00	PK	PASS
	H	2500.00	53.45	35.1	3.57	27.8	49.72	54.00	AV	PASS
	V	2483.50	61.61	35.11	3.56	27.75	57.81	74.00	PK	PASS
	V	2483.50	52.06	35.11	3.56	27.75	48.26	54.00	AV	PASS
	V	2500.00	61.17	35.1	3.57	27.8	57.44	74.00	PK	PASS
	V	2500.00	51.37	35.1	3.57	27.8	47.64	54.00	AV	PASS
	Low Channel 2412MHz									
	H	2390.00	58.22	35.17	3.48	27.49	54.02	74.00	PK	PASS
	H	2390.00	51.09	35.17	3.48	27.49	46.89	54.00	AV	PASS
	H	2400.00	59.63	35.16	3.49	27.52	55.48	74.00	PK	PASS
	H	2400.00	50.02	35.16	3.49	27.52	45.87	54.00	AV	PASS
	V	2390.00	59.13	35.17	3.48	27.49	54.93	74.00	PK	PASS
	V	2390.00	52.09	35.17	3.48	27.49	47.89	54.00	AV	PASS
	V	2400.00	60.27	35.16	3.49	27.52	56.12	74.00	PK	PASS
	V	2400.00	51.44	35.16	3.49	27.52	47.29	54.00	AV	PASS
	High Channel 2462MHz									
	H	2483.50	59.16	35.11	3.56	27.75	55.36	74.00	PK	PASS
	H	2483.50	49.06	35.11	3.56	27.75	45.26	54.00	AV	PASS
	H	2500.00	60.19	35.1	3.57	27.8	56.46	74.00	PK	PASS

	H	2500.00	50.01	35.1	3.57	27.8	46.28	54.00	AV	PASS
	V	2483.50	57.52	35.11	3.56	27.75	53.72	74.00	PK	PASS
	V	2483.50	50.88	35.11	3.56	27.75	47.08	54.00	AV	PASS
	V	2500.00	59.68	35.1	3.57	27.8	55.95	74.00	PK	PASS
	V	2500.00	51.26	35.1	3.57	27.8	47.53	54.00	AV	PASS
802.11 n40	Low Channel 2422MHz									
	H	2390.00	58.04	35.17	3.48	27.49	53.84	74.00	PK	PASS
	H	2390.00	51.11	35.17	3.48	27.49	46.91	54.00	AV	PASS
	H	2400.00	62.09	35.16	3.49	27.52	57.94	74.00	PK	PASS
	H	2400.00	50.41	35.16	3.49	27.52	46.26	54.00	AV	PASS
	V	2390.00	58.74	35.17	3.48	27.49	54.54	74.00	PK	PASS
	V	2390.00	52.13	35.17	3.48	27.49	47.93	54.00	AV	PASS
	V	2400.00	61.27	35.16	3.49	27.52	57.12	74.00	PK	PASS
	V	2400.00	50.85	35.16	3.49	27.52	46.7	54.00	AV	PASS
	High Channel 2452MHz									
	H	2483.50	59.81	35.11	3.56	27.75	56.01	74.00	PK	PASS
	H	2483.50	52.07	35.11	3.56	27.75	48.27	54.00	AV	PASS
	H	2500.00	60.27	35.1	3.57	27.8	56.54	74.00	PK	PASS
	H	2500.00	50.71	35.1	3.57	27.8	46.98	54.00	AV	PASS
	V	2483.50	59.63	35.11	3.56	27.75	55.83	74.00	PK	PASS
	V	2483.50	50.72	35.11	3.56	27.75	46.92	54.00	AV	PASS
	V	2500.00	58.05	35.1	3.57	27.8	54.32	74.00	PK	PASS
	V	2500.00	51.19	35.1	3.57	27.8	47.46	54.00	AV	PASS
Remark:										
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit										
2. We test all the mode and recorded the worst mode in the report.										

7 Conduct Band Edge And Spurious Emissions Measurement

Test Requirement	: Section 15.247(d) In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)). RSS-247 § 5.5
Test Method	: ANSI C63.10:2013
Test Limit	: Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)). RSS-247 § 5.5: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.


7.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto
Detector function = peak, Trace = max hold

7.2 Test Result

802.11b


CH01 (Lower)




CH 11(Upper)




CH01



CH06




CH11



802.11g


CH01 (Lower)




CH 11(Upper)




CH01



CH06




CH11




802.11n20


CH01 (Lower)




CH 11(Upper)




CH01



CH06




CH11




802.11n40


CH03 (Lower)




CH 09(Upper)




CH03



CH06



CH09



8 6dB&99% Bandwidth Measurement

Test Requirement : FCC CFR47 Part 15 Section 15.247, RSS-GEN §6.7& RSS-247 §5.2

Test Method : ANSI C63.10:2013

Test Limit : Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

8.1 Test Procedure

For 6dB Bandwidth Measurement

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz

For 99% Bandwidth Measurement

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 1%-5% OBW, VBW $\geq$ 3RBW

8.2 Test Result


Test CH	-6dB Occupy Bandwidth (MHz)					Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)	Limit(KHz)	
Lowest	7.601	15.72	16.58	35.22	>500	Pass
Middle	8.607	15.17	15.17	35.15		
Highest	7.089	15.34	15.16	36.33		

Test CH	99% Occupy Bandwidth (MHz)					Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)	Limit(KHz)	
Lowest	11.842	16.855	18.029	36.150	/	Pass
Middle	13.502	16.510	17.727	35.950		
Highest	11.272	16.609	17.787	36.304		


802.11b

-6dB Occupy Bandwidth


CH01



CH06




CH11




99% Occupy Bandwidth


CH01



CH06




CH11




802.11g

-6dB Occupy Bandwidth


CH01



CH06




CH11




99% Occupy Bandwidth


CH01



CH06




CH11




802.11n20

-6dB Occupy Bandwidth


CH01



CH06




CH11




99% Occupancy Bandwidth


CH01



CH06




CH11




802.11n40

-6dB Occupancy Bandwidth


CH03



CH06




CH09



99% Occupy Bandwidth


CH03



CH06



CH09



9 Maximum Peak Output Power

Test Requirement	: FCC CFR47 Part 15 Section 15.247, RSS-247 § 5.4
Test Method	: ANSI C63.10:2013
Test Limit	: Regulation 15.247 (b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. RSS-247 § 5.4 (d) For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

9.1 Test Procedure

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

9.2 Test Result

	Maximum Peak Output Power (dBm)				Limit
	802.11b	802.11g	802.11n20	802.11n40	
Low Channel	15.72	14.25	14.07	13.11	1W(30dBm)
Middle Channel	15.16	14.59	14.23	12.89	1W(30dBm)
High Channel	15.96	15.21	15.16	13.05	1W(30dBm)
	EIRP (dBm)				Limit
Low Channel	17.78	16.31	16.13	15.17	4W(36dBm)
Middle Channel	17.22	16.65	16.29	14.95	4W(36dBm)
High Channel	18.02	17.27	17.22	15.11	4W(36dBm)

10 Power Spectral density

Test Requirement	: FCC CFR47 Part 15 Section 15.247,RSS-247 §5.2 (b)
Test Method	: ANSI C63.10:2013
Test Limit	: Regulation 15.247(f) The power spectral density conducted from the intentional radiator to the antenna due to the digital modulation operation of the hybrid system, with the frequency hopping operation turned off, shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. RSS-247 §5.2 (b) The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of section 5.4(d), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

10.1 Test Procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3kHz. VBW = 10kHz, Span = 1.5 times the DTS channel bandwidth(6 dB bandwidth). Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.

10.2 Test Result

	Power Spectral density (dBm/3kHz)				Limit
	802.11b	802.11g	802.11n20	802.11n40	
Low Channel	-11.660	-12.290	-12.340	-13.885	8dBm/3kHz
Middle Channel	-13.202	-11.243	-11.348	-13.947	8dBm/3kHz
High Channel	-10.820	-9.347	-9.592	-13.089	8dBm/3kHz

802.11b


CH01



CH06




CH11




802.11g


CH01



CH06




CH11




802.11n20


CH01



CH06




CH11




802.11n40


CH03



CH06



CH09



11 Antenna Application

11.1 Antenna Requirement

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(c) (1)(i) requirement:

Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

According to RSS-GEN section 6.8

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

11.2 Result

The EUT'S antenna, permanent attached antenna, is PCB Antenna . The antenna's gain is 2.06dBi and meets the requirement.

12 Test Setup and EUT Photos

Reference to the attachment for details.

*****THE END REPORT*****

