



RF EXPOSURE REPORT

Report No.: SET2016-06125

Product Name: GPS Tracker

FCC ID: 2AH3LSVR2

Model No. : SVR-2

Applicant: ITrax, Inc.

Address: 2201 Francisco Drive Suite 140-257 El Dorado Hills, CA 95762

Dates of Testing: 04/12/2016 — 04/21/2016

Issued by: CCIC-SET

Lab Location: Electronic Testing Building, Shahe Road, Xili, Nanshan District, Shenzhen, 518055, P. R. China

Tel: 86 755 26627338 **Fax:** 86 755 26627238

This test report consists of 8 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CCIC-SET. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CCIC-SET within 20 days since the date when the report is received. It will not be taken into consideration beyond this limit.



Test Report

Product Name : GPS Tracker

Brand Name : ITRAX

Trade Name : ITRAX

Applicant : ITrax, Inc.

Applicant Address : 2201 Francisco Drive Suite 140-257 El Dorado Hills, CA
95762

Manufacturer : SHENZHEN EELINK COMMUNICATION TECHNOLOGY
CO., LTD.

Manufacturer Address : 3 Floor ,Yu yang mansion, 2nd Road of Langshan,
Science and Technology Park, Nanshan District ,
ShenZhen ,CHINA

Test Standards : FCC Part 2 (Section 2.1091)
IEEE C95.1

Test Result : PASS

Tested by :

2016.04.21

Lu Lei, Test Engineer

Reviewed by :

2016.04.21

Zhu Qi, Senior Engineer

Approved by :

2016.04.21

Wu Li'an, Manager

TABLE OF CONTENTS

1. GENERAL INFORMATION	4
1.1. EUT Description	4
1.2. Test Facilities	5
2. RF EXPOSURE	6
2.1. Limits for maximum permissible exposure (MPE)	6
2.2. MPE calculation Formula	7
2.3. Classification.....	7
2.4. Classification results of maximum conducted power	8
2.5. Result	8

Change History		
Issue	Date	Reason for change
1.0	2016-04-21	First edition

1. General Information

1.1. EUT Description

EUT Type	GPS Tracker
Hardware Version	GPT09_V13
Software Version	M6100_V1.9.8
EUT supports Radios application	GPRS
Frequency Range	GPRS 850MHz: Tx: 824.2 - 848.8MHz (at intervals of 200kHz); Rx: 869.2 - 893.8MHz (at intervals of 200kHz) GPRS 1900MHz: Tx: 1850.2 - 1909.8MHz (at intervals of 200kHz); Rx: 1930.2 - 1989.8MHz (at intervals of 200kHz)
Antenna Type	PIFA Antenna
Antenna Gain	-1dBi

1.2. Test Facilities

CNAS-Lab Code: L1659

CCIC Southern Electronic Product Testing (Shenzhen) Co., Ltd. CCIC is a third party testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L1659. A 12.8*6.8*6.4 (m) fully anechoic chamber was used for the radiated spurious emissions test.

FCC-Registration No.: 406086

CCIC Southern Electronic Product Testing (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 406086, valid time is until October 28, 2017.

IC-Registration No.: 11185A-1

CCIC Southern Electronic Product Testing (Shenzhen) Co., Ltd. EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 11185A-1 on July. 15, 2013, valid time is until July. 15, 2016.

2. RF Exposure

2.1. Limits for maximum permissible exposure (MPE)

An estimation of MPE in this application for product is used to ensure if it complies to the rules of the standard in the regulation list above.

Maximum permissible exposure (MPE) refers to the RF energy that is acceptable for human exposure. It is broken down into two categories, Occupational/controlled and General population/uncontrolled.

Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

We analysis if it comply with the limits for General population/uncontrolled exposure. The FCC's MPE limits for field strength and power density are given in 47CFR 1.1310(Table below).These limits are generally based on recommended exposure guidelines published by the National Council on Radiation Protection and Measurements (NCRP), and also partly based on guidelines recommended by the American National Standards Institute (ANSI) in Section 4.1 of ANSI/IEEE C95.1.

(B) Limits for General Population/uncontrolled Exposure				
Frequency Range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Average time (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30
f=frequency in MHz		*Plane-wave equivalent power density		

A rough estimation of the expected exposure in power flux density on a given point can be made with the following equation:

2.2. MPE calculation Formula

$$S = \frac{PG}{4\pi R^2}$$

where

S = power density in mW/cm²

P = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm (20cm)

The antenna of the product, under normal use condition is at least 20 cm away from the body of the user. Warning statement to the user for keeping at least 20cm separation distance and the prohibition of operating to a person has been printed on the user's manual. Therefore, the S of the device is calculated with R=20cm, and if it is below the limit S, then we can conclude the device complies with the rules.

2.3. Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4. Classification results of maximum conducted power

Test Mode	Maximum Conducted Power (dBm)	Maximum Tune up power(dBm)	Max Tune up Average Power (dBm)
GPRS 850	32.21	33	23.97
GPRS 1900	28.98	30	20.97

Note: For GSM, Duty cycle=1/8.

Test Mode	Maximum E.I.R.P. (dBm)	Maximum E.I.R.P. (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)	Result
GPRS 850	22.97	198.15	0.039	0.55	PASS
GPRS 1900	19.97	99.31	0.020	1.0	PASS

Note: antenna Gain= -1dBi

2.5. Result

This is a Mobile Device and the maximum Power Density is 0.039(mW/cm²), which is lower than the exclusion threshold 0.55(mW/cm²).

The SAR measurement is not required.