

# FCC Radio Test Report

## FCC ID: 2AH4HMT4201

This report concerns: Original Grant

**Project No.** : 2104C020  
**Equipment** : LTE Cat-M1 Tracker  
**Brand Name** : Mobilogix  
**Test Model** : MT4201E  
**Series Model** : MT4201C  
**Applicant** : Mobilogix, Inc.  
**Address** : 5500 Trabuco Rd Suite 150 Irvine, CA, USA  
**Manufacturer** : Mobilogix, Inc.  
**Address** : 5500 Trabuco Rd Suite 150 Irvine, CA, USA  
**Factory** : Suga Electronics (Dongguan) Co., Ltd.  
**Address** : No.8 Fulong Road, Qingxi Town, Dongguan City  
**Date of Receipt** : Apr. 28, 2021  
**Date of Test** : Apr. 29, 2021 ~ May 18, 2021  
**Issued Date** : Jun. 07, 2021  
**Report Version** : R00  
**Test Sample** : Engineering Sample No.: DG2021042934 for radiated, DG2021042934 for conducted.  
**Standard(s)** : FCC CFR Title 47, Part 15, Subpart C  
FCC KDB 558074 D01 15.247 Meas Guidance v05r02  
ANSI C63.10-2013

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Treey Chen

Prepared by : Treey Chen

Steven Lu

Approved by : Steven Lu



Certificate #5123.02

Add: No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China.

Tel: +86-769-8318-3000

Web: [www.newbtl.com](http://www.newbtl.com)

**Declaration**

**BTL** represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

**BTL's** reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, A2LA, or any agency of the U.S. Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

**BTL's** laboratory quality assurance procedures are in compliance with the **ISO/IEC 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

**BTL** is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

**Limitation**

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Please note that the measurement uncertainty is provided for informational purpose only and are not use in determining the Pass/Fail results.

| <b>Table of Contents</b>                                     | <b>Page</b> |
|--------------------------------------------------------------|-------------|
| <b>REPORT ISSUED HISTORY</b>                                 | <b>5</b>    |
| <b>1 . SUMMARY OF TEST RESULTS</b>                           | <b>6</b>    |
| 1.1 TEST FACILITY                                            | 7           |
| 1.2 MEASUREMENT UNCERTAINTY                                  | 7           |
| 1.3 TEST ENVIRONMENT CONDITIONS                              | 8           |
| <b>2 . GENERAL INFORMATION</b>                               | <b>9</b>    |
| 2.1 GENERAL DESCRIPTION OF EUT                               | 9           |
| 2.2 DESCRIPTION OF TEST MODES                                | 10          |
| 2.3 PARAMETERS OF TEST SOFTWARE                              | 10          |
| 2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED | 11          |
| 2.5 SUPPORT UNITS                                            | 11          |
| <b>3 . RADIATED EMISSIONS</b>                                | <b>12</b>   |
| 3.1 LIMIT                                                    | 12          |
| 3.2 TEST PROCEDURE                                           | 13          |
| 3.3 DEVIATION FROM TEST STANDARD                             | 14          |
| 3.4 TEST SETUP                                               | 14          |
| 3.5 EUT OPERATING CONDITIONS                                 | 15          |
| 3.6 TEST RESULT - 9 KHZ TO 30 MHZ                            | 15          |
| 3.7 TEST RESULT - 30 MHZ TO 1000 MHZ                         | 15          |
| 3.8 TEST RESULT - ABOVE 1000 MHZ                             | 15          |
| <b>4 . BANDWIDTH</b>                                         | <b>16</b>   |
| 4.1 LIMIT                                                    | 16          |
| 4.2 TEST PROCEDURE                                           | 16          |
| 4.3 DEVIATION FROM STANDARD                                  | 16          |
| 4.4 TEST SETUP                                               | 16          |
| 4.5 EUT OPERATION CONDITIONS                                 | 16          |
| 4.6 TEST RESULTS                                             | 16          |
| <b>5 . MAXIMUM OUTPUT POWER</b>                              | <b>17</b>   |
| 5.1 LIMIT                                                    | 17          |
| 5.2 TEST PROCEDURE                                           | 17          |
| 5.3 DEVIATION FROM STANDARD                                  | 17          |
| 5.4 TEST SETUP                                               | 17          |

| <b>Table of Contents</b>                            | <b>Page</b> |
|-----------------------------------------------------|-------------|
| 5.5 EUT OPERATION CONDITIONS                        | 17          |
| 5.6 TEST RESULTS                                    | 17          |
| <b>6 . CONDUCTED SPURIOUS EMISSION</b>              | <b>18</b>   |
| 6.1 LIMIT                                           | 18          |
| 6.2 TEST PROCEDURE                                  | 18          |
| 6.3 DEVIATION FROM STANDARD                         | 18          |
| 6.4 TEST SETUP                                      | 18          |
| 6.5 EUT OPERATION CONDITIONS                        | 18          |
| 6.6 TEST RESULTS                                    | 18          |
| <b>7 . POWER SPECTRAL DENSITY</b>                   | <b>19</b>   |
| 7.1 LIMIT                                           | 19          |
| 7.2 TEST PROCEDURE                                  | 19          |
| 7.3 DEVIATION FROM STANDARD                         | 19          |
| 7.4 TEST SETUP                                      | 19          |
| 7.5 EUT OPERATION CONDITIONS                        | 19          |
| 7.6 TEST RESULTS                                    | 19          |
| <b>8 . MEASUREMENT INSTRUMENTS LIST</b>             | <b>20</b>   |
| APPENDIX A - RADIATED EMISSION - 9 KHZ TO 30 MHZ    | 22          |
| APPENDIX B - RADIATED EMISSION - 30 MHZ TO 1000 MHZ | 27          |
| APPENDIX C - RADIATED EMISSION - ABOVE 1000 MHZ     | 30          |
| APPENDIX D - BANDWIDTH                              | 55          |
| APPENDIX E - MAXIMUM OUTPUT POWER                   | 58          |
| APPENDIX F - CONDUCTED SPURIOUS EMISSION            | 60          |
| APPENDIX G - POWER SPECTRAL DENSITY                 | 63          |

**REPORT ISSUED HISTORY**

| Report Version | Description     | Issued Date   |
|----------------|-----------------|---------------|
| R00            | Original Issue. | Jun. 07, 2021 |

## 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

| FCC CFR Title 47, Part 15, Subpart C |                             |                                        |          |         |
|--------------------------------------|-----------------------------|----------------------------------------|----------|---------|
| Standard(s) Section                  | Test Item                   | Test Result                            | Judgment | Remark  |
| 15.247(d)<br>15.205(a)<br>15.209(a)  | Radiated Emissions          | APPENDIX A<br>APPENDIX B<br>APPENDIX C | PASS     | -----   |
| 15.247(a)(2)                         | Bandwidth                   | APPENDIX D                             | PASS     | -----   |
| 15.247(b)(3)                         | Maximum Output Power        | APPENDIX E                             | PASS     | -----   |
| 15.247(d)                            | Conducted Spurious Emission | APPENDIX F                             | PASS     | -----   |
| 15.247(e)                            | Power Spectral Density      | APPENDIX G                             | PASS     | -----   |
| 15.203                               | Antenna Requirement         | -----                                  | PASS     | Note(2) |

Note:

- (1) "N/A" denotes test is not applicable to this device.
- (2) The device what use a permanently attached antenna were considered sufficient to comply with the provisions of 15.203.

## 1.1 TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China  
 BTL's Test Firm Registration Number for FCC: 357015  
 BTL's Designation Number for FCC: CN1240

## 1.2 MEASUREMENT UNCERTAINTY

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))  
 The BTL measurement uncertainty as below table:

### A. Radiated emissions Measurement:

| Test Site | Method | Measurement Frequency Range | Ant.<br>H / V | U, (dB) |
|-----------|--------|-----------------------------|---------------|---------|
| DG-CB03   | CISPR  | 9kHz ~ 30MHz                | -             | 3.02    |
|           |        | 30MHz ~ 200MHz              | V             | 4.26    |
|           |        | 30MHz ~ 200MHz              | H             | 3.38    |
|           |        | 200MHz ~ 1,000MHz           | V             | 3.98    |
|           |        | 200MHz ~ 1,000MHz           | H             | 3.94    |
|           |        | 1GHz ~ 6GHz                 | -             | 3.96    |
|           |        | 6GHz ~ 18GHz                | -             | 5.24    |
|           |        | 18GHz ~ 26.5GHz             | -             | 3.62    |
|           |        | 26.5GHz ~ 40GHz             | -             | 4.00    |

### B. Other Measurement:

| Test Item                   | Uncertainty |
|-----------------------------|-------------|
| Bandwidth                   | ±3.8 %      |
| Maximum Output Power        | ±0.95 dB    |
| Conducted Spurious Emission | ±2.71 dB    |
| Power Spectral Density      | ±0.86 dB    |
| Temperature                 | ±0.08 °C    |
| Humidity                    | ±1.5%       |

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

### 1.3 TEST ENVIRONMENT CONDITIONS

| Test Item                             | Temperature | Humidity | Test Voltage | Tested By  |
|---------------------------------------|-------------|----------|--------------|------------|
| Radiated Emissions-9 kHz to 30 MHz    | 25°C        | 60%      | DC 48V       | Grani Zhou |
| Radiated Emissions-30 MHz to 1000 MHz | 26°C        | 52%      | DC 48V       | Grani Zhou |
| Radiated Emissions-Above 1000 MHz     | 26°C        | 52%      | DC 48V       | Grani Zhou |
| Bandwidth                             | 21.9°C      | 52%      | DC 48V       | Jesse Wang |
| Maximum Output Power                  | 21.9°C      | 52%      | DC 48V       | Jesse Wang |
| Conducted Spurious Emission           | 21.9°C      | 52%      | DC 48V       | Jesse Wang |
| Power Spectral Density                | 21.9°C      | 52%      | DC 48V       | Jesse Wang |

## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

|                         |                                                                                 |
|-------------------------|---------------------------------------------------------------------------------|
| Equipment               | LTE Cat-M1 Tracker                                                              |
| Brand Name              | Mobilogix                                                                       |
| Test Model              | MT4201E                                                                         |
| Series Model            | MT4201C                                                                         |
| Model Difference(s)     | Only differ in model name and Harness.                                          |
| Hardware Version        | 1.2                                                                             |
| Software Version        | 1.5.0.1                                                                         |
| Power Source            | 1# DC voltage supplied from external power supply.<br>2# Supplied from battery. |
| Power Rating            | 1# DC 48V<br>2# DC 3.7V                                                         |
| Operation Frequency     | 2402 MHz ~ 2480 MHz                                                             |
| Modulation Type         | GFSK                                                                            |
| Bit Rate of Transmitter | 1Mbps, 2Mbps                                                                    |
| Max. Output Power       | 2Mbps: -0.07 dBm (0.0010 W)                                                     |

Note:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

#### 2. Channel List:

| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|
| 00      | 2402            | 20      | 2442            |
| 01      | 2404            | 21      | 2444            |
| 02      | 2406            | 22      | 2446            |
| 03      | 2408            | 23      | 2448            |
| 04      | 2410            | 24      | 2450            |
| 05      | 2412            | 25      | 2452            |
| 06      | 2414            | 26      | 2454            |
| 07      | 2416            | 27      | 2456            |
| 08      | 2418            | 28      | 2458            |
| 09      | 2420            | 29      | 2460            |
| 10      | 2422            | 30      | 2462            |
| 11      | 2424            | 31      | 2464            |
| 12      | 2426            | 32      | 2466            |
| 13      | 2428            | 33      | 2468            |
| 14      | 2430            | 34      | 2470            |
| 15      | 2432            | 35      | 2472            |
| 16      | 2434            | 36      | 2474            |
| 17      | 2436            | 37      | 2476            |
| 18      | 2438            | 38      | 2478            |
| 19      | 2440            | 39      | 2480            |

#### 3. Table for Filed Antenna:

| Ant. | Brand | Model Name | Antenna Type | Connector | Gain (dBi) |
|------|-------|------------|--------------|-----------|------------|
| 1    | N/A   | N/A        | Chip         | N/A       | 0.5        |

Note:

The antenna gain is provided by the manufacturer.

## 2.2 DESCRIPTION OF TEST MODES

The test system was pre-tested based on the consideration of all possible combinations of EUT operation mode.

| Pretest Mode | Description                    |
|--------------|--------------------------------|
| Mode 1       | TX Mode_1Mbps Channel 00/19/39 |
| Mode 2       | TX Mode_2Mbps Channel 00/19/39 |
| Mode 3       | TX Mode_2Mbps Channel 00       |

Following mode(s) was (were) found to be the worst case(s) and selected for the final test.

| Radiated emissions test - Below 1GHz |                          |
|--------------------------------------|--------------------------|
| Final Test Mode                      | Description              |
| Mode 3                               | TX Mode_2Mbps Channel 00 |

| Radiated emissions test - Above 1GHz |                                |
|--------------------------------------|--------------------------------|
| Final Test Mode                      | Description                    |
| Mode 1                               | TX Mode_1Mbps Channel 00/19/39 |
| Mode 2                               | TX Mode_2Mbps Channel 00/19/39 |

| Conducted test  |                                |
|-----------------|--------------------------------|
| Final Test Mode | Description                    |
| Mode 1          | TX Mode_1Mbps Channel 00/19/39 |
| Mode 2          | TX Mode_2Mbps Channel 00/19/39 |

Note:


- (1) For radiated emission above 1 GHz test, the spurious points of 1GHz~26.5GHz have been pre-tested and in this report only recorded the worst case. The remaining spurious points are all below the limit value of 20dB.
- (2) For AC power line conducted emissions and radiated emissions below 1 GHz test, the 2Mbps channel 00 is found to be the worst case and recorded.

## 2.3 PARAMETERS OF TEST SOFTWARE

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.

| Test Software Version | QCOM_V1.6 |      |      |
|-----------------------|-----------|------|------|
| Frequency (MHz)       | 2402      | 2440 | 2480 |
| 1Mbps                 | -5        | -5   | -5   |
| 2Mbps                 | -5        | -5   | -5   |

## 2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



## 2.5 SUPPORT UNITS

| Item | Equipment | Brand | Model No.  | Series No. |
|------|-----------|-------|------------|------------|
| A    | Notebook  | HONOR | NBLK-WAX9X | N/A        |

| Item | Cable Type | Shielded Type | Ferrite Core | Length |
|------|------------|---------------|--------------|--------|
| 1    | USB Cable  | NO            | NO           | 0.1m   |
| 2    | DC Cable   | NO            | NO           | 1.5m   |

### 3. RADIATED EMISSIONS

#### 3.1 LIMIT

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

##### LIMITS OF RADIATED EMISSION MEASUREMENT (9 kHz-1000 MHz)

| Frequency<br>(MHz) | Field Strength<br>(microvolts/meter) | Measurement Distance<br>(meters) |
|--------------------|--------------------------------------|----------------------------------|
| 0.009-0.490        | 2400/F(kHz)                          | 300                              |
| 0.490-1.705        | 24000/F(kHz)                         | 30                               |
| 1.705-30.0         | 30                                   | 30                               |
| 30-88              | 100                                  | 3                                |
| 88-216             | 150                                  | 3                                |
| 216-960            | 200                                  | 3                                |
| Above 960          | 500                                  | 3                                |

##### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000 MHz)

| Frequency (MHz) | (dBuV/m at 3 m) |         |
|-----------------|-----------------|---------|
|                 | Peak            | Average |
| Above 1000      | 74              | 54      |

Note:

- (1) The limit for radiated test was performed according to FCC CFR Title 47, Part 15, Subpart C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

### 3.2 TEST PROCEDURE

- a. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1 GHz)
- b. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1 GHz)
- c. The height of the equipment or of the substitution antenna shall be 0.8m or 1.5m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- e. The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- f. The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.  
(below 1 GHz)
- h. All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1 GHz)
- i. For the actual test configuration, please refer to the related Item –EUT Test Photos.

The following table is the setting of the receiver:

| Spectrum Parameters    | Setting                         |
|------------------------|---------------------------------|
| Start ~ Stop Frequency | 9 kHz~150 kHz for RBW 200 Hz    |
| Start ~ Stop Frequency | 0.15 MHz~30 MHz for RBW 9 kHz   |
| Start ~ Stop Frequency | 30 MHz~1000 MHz for RBW 100 kHz |

| Spectrum Parameters                        | Setting                                                    |
|--------------------------------------------|------------------------------------------------------------|
| Start Frequency                            | 1000 MHz                                                   |
| Stop Frequency                             | 10th carrier harmonic                                      |
| RBW / VBW<br>(Emission in restricted band) | 1 MHz / 3 MHz for PK value<br>1 MHz / 1/T Hz for AVG value |


| Spectrum Parameters    | Setting                             |
|------------------------|-------------------------------------|
| Start ~ Stop Frequency | 9 kHz~90 kHz for PK/AVG detector    |
| Start ~ Stop Frequency | 90 kHz~110 kHz for QP detector      |
| Start ~ Stop Frequency | 110 kHz~490 kHz for PK/AVG detector |
| Start ~ Stop Frequency | 490 kHz~30 MHz for QP detector      |
| Start ~ Stop Frequency | 30 MHz~1000 MHz for QP detector     |
| Start ~ Stop Frequency | 1 GHz~26.5 GHz for PK/AVG detector  |

### 3.3 DEVIATION FROM TEST STANDARD


No deviation.


### 3.4 TEST SETUP

9 kHz to 30 MHz



30 MHz to 1 GHz





### 3.5 EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

### 3.6 TEST RESULT - 9 kHz TO 30 MHz

Please refer to the APPENDIX A.

Remark:

- (1) Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB).
- (2) Limit line = specific limits (dBuV) + distance extrapolation factor.

### 3.7 TEST RESULT - 30 MHz TO 1000 MHz

Please refer to the APPENDIX B.

### 3.8 TEST RESULT - ABOVE 1000 MHz

Please refer to the APPENDIX C.

Remark:

- (1) No limit: This is fundamental signal, the judgment is not applicable.  
For fundamental signal judgment was referred to Peak output test.

## 4. BANDWIDTH

### 4.1 LIMIT

| Section          | Test Item              | Limit          |
|------------------|------------------------|----------------|
| FCC 15.247(a)(2) | 6 dB Bandwidth         | $\geq 500$ kHz |
|                  | 99% Emission Bandwidth | -              |

### 4.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- The following table is the setting of the spectrum analyzer:

For 6 dB Bandwidth:

| Spectrum Parameters | Setting                 |
|---------------------|-------------------------|
| Span Frequency      | > Measurement Bandwidth |
| RBW                 | 100 kHz                 |
| VBW                 | 300 kHz                 |
| Detector            | Peak                    |
| Trace               | Max Hold                |
| Sweep Time          | Auto                    |


For 99% Emission Bandwidth:

| Spectrum Parameters | Setting                                 |
|---------------------|-----------------------------------------|
| Span Frequency      | Between 1.5 times and 5.0 times the OBW |
| RBW                 | 30 kHz                                  |
| VBW                 | 100 kHz                                 |
| Detector            | Peak                                    |
| Trace               | Max Hold                                |
| Sweep Time          | Auto                                    |

### 4.3 DEVIATION FROM STANDARD

No deviation.

### 4.4 TEST SETUP



### 4.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

### 4.6 TEST RESULTS

Please refer to the APPENDIX D.

## 5. MAXIMUM OUTPUT POWER

### 5.1 LIMIT

| Section          | Test Item            | Limit                    |
|------------------|----------------------|--------------------------|
| FCC 15.247(b)(3) | Maximum Output Power | 1.0000 watt or 30.00 dBm |

### 5.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- The following table is the setting of the spectrum analyzer:

| Spectrum Parameters | Setting                    |
|---------------------|----------------------------|
| Span Frequency      | $\geq 3 \times \text{RBW}$ |
| RBW                 | 3 MHz                      |
| VBW                 | 3 MHz                      |
| Detector            | Peak                       |
| Trace               | Max Hold                   |
| Sweep Time          | Auto                       |

### 5.3 DEVIATION FROM STANDARD

No deviation.

### 5.4 TEST SETUP



### 5.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

### 5.6 TEST RESULTS

Please refer to the APPENDIX E.

## 6. CONDUCTED SPURIOUS EMISSION

### 6.1 LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak Output Power limits. If the transmitter complies with the Output Power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required.

### 6.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- The following table is the setting of the spectrum analyzer:

| Spectrum Parameters | Setting  |
|---------------------|----------|
| Start Frequency     | 30 MHz   |
| Stop Frequency      | 26.5 GHz |
| RBW                 | 100 kHz  |
| VBW                 | 300 kHz  |
| Detector            | Peak     |
| Trace               | Max Hold |
| Sweep Time          | Auto     |

### 6.3 DEVIATION FROM STANDARD

No deviation.

### 6.4 TEST SETUP



### 6.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

### 6.6 TEST RESULTS

Please refer to the APPENDIX F.

## 7. POWER SPECTRAL DENSITY

### 7.1 LIMIT

| Section       | Test Item              | Limit                   |
|---------------|------------------------|-------------------------|
| FCC 15.247(e) | Power Spectral Density | 8 dBm<br>(in any 3 kHz) |

### 7.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- The following table is the setting of the spectrum analyzer:

| Spectrum Parameters | Setting                         |
|---------------------|---------------------------------|
| Span Frequency      | 2 MHz (1 Mbps) / 4 MHz (2 Mbps) |
| RBW                 | 3 kHz                           |
| VBW                 | 10 kHz                          |
| Detector            | Peak                            |
| Trace               | Max Hold                        |
| Sweep Time          | Auto                            |

### 7.3 DEVIATION FROM STANDARD

No deviation.

### 7.4 TEST SETUP



### 7.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

### 7.6 TEST RESULTS

Please refer to the APPENDIX G.

## 8. MEASUREMENT INSTRUMENTS LIST

| Radiated Emissions - 9 kHz to 30 MHz |                      |              |                          |            |                  |
|--------------------------------------|----------------------|--------------|--------------------------|------------|------------------|
| Item                                 | Kind of Equipment    | Manufacturer | Type No.                 | Serial No. | Calibrated until |
| 1                                    | Loop Antenna         | EM           | EM-6876-1                | 230        | Apr. 28, 2022    |
| 2                                    | Cable                | N/A          | RG 213/U                 | N/A        | May 29, 2021     |
| 3                                    | EMI Test Receiver    | R&S          | ESCI                     | 100895     | Feb. 27, 2022    |
| 4                                    | Measurement Software | Farad        | EZ-EMC<br>Ver.NB-03A1-01 | N/A        | N/A              |
| 5                                    | 966 Chambe Room      | RM           | 9*6*6m                   | N/A        | Jul. 25, 2021    |

| Radiated Emissions - 30 MHz to 1 GHz |                      |              |                                |             |                  |
|--------------------------------------|----------------------|--------------|--------------------------------|-------------|------------------|
| Item                                 | Kind of Equipment    | Manufacturer | Type No.                       | Serial No.  | Calibrated until |
| 1                                    | Antenna              | Schwarzbeck  | VULB9160                       | 9160-3232   | Mar. 15, 2022    |
| 2                                    | Amplifier            | HP           | 8447D                          | 2944A08742  | Feb. 28, 2022    |
| 3                                    | Receiver             | Agilent      | N9038A                         | MY52130039  | Jul. 25, 2021    |
| 4                                    | Cable                | emci         | LMR-400(30MHz-1<br>GHz)(8m+5m) | N/A         | May 22, 2021     |
| 5                                    | Controller           | CT           | SC100                          | N/A         | N/A              |
| 6                                    | Controller           | MF           | MF-7802                        | MF780208416 | N/A              |
| 7                                    | Measurement Software | Farad        | EZ-EMC<br>Ver.NB-03A1-01       | N/A         | N/A              |
| 8                                    | 966 Chambe Room      | RM           | 9*6*6m                         | N/A         | Jul. 25, 2021    |


| Radiated Emissions - Above 1 GHz |                                     |                |                          |               |                  |
|----------------------------------|-------------------------------------|----------------|--------------------------|---------------|------------------|
| Item                             | Kind of Equipment                   | Manufacturer   | Type No.                 | Serial No.    | Calibrated until |
| 1                                | Double Ridged Guide Antenna         | ETS            | 3115                     | 75789         | May 10, 2022     |
| 2                                | Broad-Band Horn Antenna             | Schwarzbeck    | BBHA 9170                | 9170319       | Jul. 07, 2021    |
| 3                                | Amplifier                           | Agilent        | 8449B                    | 3008A02584    | Jul. 25, 2021    |
| 4                                | Microwave Preamplifier With Adaptor | EMC INSTRUMENT | EMC2654045               | 980039 & HA01 | Feb. 28, 2022    |
| 5                                | Receiver                            | Agilent        | N9038A                   | MY52130039    | Jul. 25, 2021    |
| 6                                | Controller                          | CT             | SC100                    | N/A           | N/A              |
| 7                                | Controller                          | MF             | MF-7802                  | MF780208416   | N/A              |
| 8                                | Cable                               | N/A            | EMC104-SM-SM-6<br>000    | N/A           | Oct. 16, 2021    |
| 9                                | Measurement Software                | Farad          | EZ-EMC<br>Ver.NB-03A1-01 | N/A           | N/A              |
| 10                               | Filter                              | STI            | STI15-9912               | N/A           | Jul. 25, 2021    |
| 11                               | 966 Chambe Room                     | RM             | 9*6*6m                   | N/A           | Jul. 25, 2021    |

| <b>Bandwidth &amp;<br/>Maximum Output Power &amp;<br/>Power Spectral Density &amp;<br/>Conducted Spurious Emission</b> |                   |              |          |            |                  |
|------------------------------------------------------------------------------------------------------------------------|-------------------|--------------|----------|------------|------------------|
| Item                                                                                                                   | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
| 1                                                                                                                      | Spectrum Analyzer | R&S          | FSP40    | 100185     | Jul. 25, 2021    |
| 2                                                                                                                      | Attenuator        | WOKEN        | 6SM3502  | VAS1214NL  | Feb. 07, 2022    |
| 3                                                                                                                      | RF Cable          | Tongkaichuan | N/A      | N/A        | N/A              |
| 4                                                                                                                      | DC Block          | Mini         | N/A      | N/A        | N/A              |

Remark: "N/A" denotes no model name, serial no. or calibration specified.  
All calibration period of equipment list is one year.

## **APPENDIX A - RADIATED EMISSION - 9 KHZ TO 30 MHZ**

|           |                          |              |        |
|-----------|--------------------------|--------------|--------|
| Test Mode | TX Mode Channel 00_2Mbps | Polarization | Ant 0° |
|-----------|--------------------------|--------------|--------|




| No. | Mk. | Freq.  | Reading Level | Correct Factor | Measurement | Limit  | Margin |          |         |
|-----|-----|--------|---------------|----------------|-------------|--------|--------|----------|---------|
|     |     | MHz    | dBuV          | dB             | dBuV/m      | dBuV/m | dB     | Detector | Comment |
| 1   |     | 0.0185 | 40.88         | 13.68          | 54.56       | 122.26 | -67.70 | AVG      |         |
| 2   |     | 0.0300 | 35.19         | 12.95          | 48.14       | 118.06 | -69.92 | AVG      |         |
| 3   | *   | 0.0420 | 36.24         | 12.63          | 48.87       | 115.14 | -66.27 | AVG      |         |

## REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

|           |                          |              |        |
|-----------|--------------------------|--------------|--------|
| Test Mode | TX Mode Channel 00_2Mbps | Polarization | Ant 0° |
|-----------|--------------------------|--------------|--------|




| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1   |     | 0.8350       | 28.98                    | 11.87                   | 40.85                      | 69.17           | -28.32       | QP       |         |
| 2   |     | 1.5355       | 30.24                    | 11.53                   | 41.77                      | 63.88           | -22.11       | QP       |         |
| 3   | *   | 2.1552       | 37.65                    | 11.23                   | 48.88                      | 69.54           | -20.66       | QP       |         |

## REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.  
(2) Margin Level = Measurement Value - Limit Value.

|           |                          |              |         |
|-----------|--------------------------|--------------|---------|
| Test Mode | TX Mode Channel 00_2Mbps | Polarization | Ant 90° |
|-----------|--------------------------|--------------|---------|




| No. | Mk. | Freq.  | Reading Level | Correct Factor | Measurement | Limit  | Margin |          |         |
|-----|-----|--------|---------------|----------------|-------------|--------|--------|----------|---------|
|     |     | MHz    | dBuV          | dB             | dBuV/m      | dBuV/m | dB     | Detector | Comment |
| 1   | *   | 0.0186 | 45.18         | 13.65          | 58.83       | 122.21 | -63.38 | AVG      |         |
| 2   |     | 0.0343 | 35.27         | 12.84          | 48.11       | 116.90 | -68.79 | AVG      |         |
| 3   |     | 0.0603 | 30.06         | 12.48          | 42.54       | 112.00 | -69.46 | AVG      |         |

## REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

|           |                          |              |         |
|-----------|--------------------------|--------------|---------|
| Test Mode | TX Mode Channel 00_2Mbps | Polarization | Ant 90° |
|-----------|--------------------------|--------------|---------|



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1   |     | 0.7876       | 38.41                    | 11.88                   | 50.29                      | 69.68           | -19.39       | QP       |         |
| 2   | *   | 1.0374       | 36.74                    | 11.78                   | 48.52                      | 67.29           | -18.77       | QP       |         |
| 3   |     | 2.2250       | 29.25                    | 11.20                   | 40.45                      | 69.54           | -29.09       | QP       |         |


## REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

## **APPENDIX B - RADIATED EMISSION - 30 MHZ TO 1000 MHZ**

|           |                          |              |          |
|-----------|--------------------------|--------------|----------|
| Test Mode | TX Mode Channel 00_2Mbps | Polarization | Vertical |
|-----------|--------------------------|--------------|----------|

80 dBuV/m




| No. | Freq.<br>MHz | Reading<br>Level<br>dBuV/m | Correct<br>Factor<br>dB | Measure<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment |
|-----|--------------|----------------------------|-------------------------|---------------------------|-----------------|--------------|----------|---------|
| 1   | 112.4500     | 38.02                      | -14.82                  | 23.20                     | 43.50           | -20.30       | Peak     |         |
| 2   | 181.3200     | 35.87                      | -13.81                  | 22.06                     | 43.50           | -21.44       | Peak     |         |
| 3   | 254.0700     | 32.45                      | -12.78                  | 19.67                     | 46.00           | -26.33       | Peak     |         |
| 4   | 500.4500     | 35.06                      | -6.54                   | 28.52                     | 46.00           | -17.48       | Peak     |         |
| 5   | 675.0500     | 30.63                      | -3.40                   | 27.23                     | 46.00           | -18.77       | Peak     |         |
| 6 * | 825.4000     | 31.48                      | -0.66                   | 30.82                     | 46.00           | -15.18       | Peak     |         |

## REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

|           |                          |              |            |
|-----------|--------------------------|--------------|------------|
| Test Mode | TX Mode Channel 00_2Mbps | Polarization | Horizontal |
|-----------|--------------------------|--------------|------------|

80 dBuV/m



| No. | Freq.<br>MHz | Reading<br>Level<br>dBuV/m | Correct<br>Factor<br>dB | Measure<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment |
|-----|--------------|----------------------------|-------------------------|---------------------------|-----------------|--------------|----------|---------|
| 1   | 123.1200     | 33.49                      | -13.92                  | 19.57                     | 43.50           | -23.93       | Peak     |         |
| 2   | 240.4900     | 38.10                      | -13.36                  | 24.74                     | 46.00           | -21.26       | Peak     |         |
| 3   | 335.5500     | 33.98                      | -10.23                  | 23.75                     | 46.00           | -22.25       | Peak     |         |
| 4   | 480.0800     | 34.62                      | -6.89                   | 27.73                     | 46.00           | -18.27       | Peak     |         |
| 5   | 650.8000     | 30.58                      | -3.72                   | 26.86                     | 46.00           | -19.14       | Peak     |         |
| 6 * | 822.4900     | 30.82                      | -0.66                   | 30.16                     | 46.00           | -15.84       | Peak     |         |


## REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

## **APPENDIX C - RADIATED EMISSION - ABOVE 1000 MHZ**

|           |                         |              |          |
|-----------|-------------------------|--------------|----------|
| Test Mode | TX 2402 MHz _CH00_1Mbps | Polarization | Vertical |
|-----------|-------------------------|--------------|----------|



| No. | Freq.<br>MHz | Reading<br>Level<br>dBuV/m | Correct<br>Factor<br>dB | Measure<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment  |
|-----|--------------|----------------------------|-------------------------|---------------------------|-----------------|--------------|----------|----------|
| 1   | 2390.0000    | 39.58                      | 7.26                    | 46.84                     | 74.00           | -27.16       | Peak     |          |
| 2   | 2390.0000    | 30.12                      | 7.26                    | 37.38                     | 54.00           | -16.62       | AVG      |          |
| 3   | 2401.9500    | 67.02                      | 7.26                    | 74.28                     | 74.00           | 0.28         | Peak     | No Limit |
| 4 * | 2402.2000    | 66.10                      | 7.26                    | 73.36                     | 54.00           | 19.36        | AVG      | No Limit |


## REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

|           |                         |              |          |
|-----------|-------------------------|--------------|----------|
| Test Mode | TX 2402 MHz _CH00_1Mbps | Polarization | Vertical |
|-----------|-------------------------|--------------|----------|

80 dBuV/m




| No. | Freq.<br>MHz | Reading<br>Level<br>dBuV/m | Correct<br>Factor<br>dB | Measure<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment |
|-----|--------------|----------------------------|-------------------------|---------------------------|-----------------|--------------|----------|---------|
| 1 * | 4803.6850    | 27.66                      | 4.40                    | 32.06                     | 54.00           | -21.94       | AVG      |         |
| 2   | 4804.3900    | 38.99                      | 4.40                    | 43.39                     | 74.00           | -30.61       | Peak     |         |

## REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

|           |                         |              |            |
|-----------|-------------------------|--------------|------------|
| Test Mode | TX 2402 MHz _CH00_1Mbps | Polarization | Horizontal |
|-----------|-------------------------|--------------|------------|

130 dBuV/m



| No. | Freq.<br>MHz | Reading<br>Level<br>dBuV/m | Correct<br>Factor<br>dB | Measure<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment  |
|-----|--------------|----------------------------|-------------------------|---------------------------|-----------------|--------------|----------|----------|
| 1   | 2390.0000    | 39.17                      | 7.26                    | 46.43                     | 74.00           | -27.57       | Peak     |          |
| 2   | 2390.0000    | 29.92                      | 7.26                    | 37.18                     | 54.00           | -16.82       | AVG      |          |
| 3 * | 2402.2000    | 70.56                      | 7.26                    | 77.82                     | 54.00           | 23.82        | AVG      | No Limit |
| 4   | 2402.4000    | 71.55                      | 7.26                    | 78.81                     | 74.00           | 4.81         | Peak     | No Limit |


## REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

|           |                         |              |            |
|-----------|-------------------------|--------------|------------|
| Test Mode | TX 2402 MHz _CH00_1Mbps | Polarization | Horizontal |
|-----------|-------------------------|--------------|------------|

80 dBuV/m



| No. | Freq.<br>MHz | Reading<br>Level<br>dBuV/m | Correct<br>Factor<br>dB | Measure<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment |
|-----|--------------|----------------------------|-------------------------|---------------------------|-----------------|--------------|----------|---------|
| 1 * | 4803.6530    | 27.65                      | 4.40                    | 32.05                     | 54.00           | -21.95       | AVG      |         |
| 2   | 4804.5950    | 39.12                      | 4.40                    | 43.52                     | 74.00           | -30.48       | Peak     |         |


## REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

|           |                         |              |          |
|-----------|-------------------------|--------------|----------|
| Test Mode | TX 2440 MHz _CH19_1Mbps | Polarization | Vertical |
|-----------|-------------------------|--------------|----------|

130 dBuV/m




| No. | Freq.<br>MHz | Reading<br>Level<br>dBuV/m | Correct<br>Factor<br>dB | Measure<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment  |
|-----|--------------|----------------------------|-------------------------|---------------------------|-----------------|--------------|----------|----------|
| 1   | 2440.1000    | 68.27                      | 7.25                    | 75.52                     | 74.00           | 1.52         | Peak     | No Limit |
| 2 * | 2440.2000    | 67.36                      | 7.25                    | 74.61                     | 54.00           | 20.61        | AVG      | No Limit |

## REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

|           |                         |              |          |
|-----------|-------------------------|--------------|----------|
| Test Mode | TX 2440 MHz _CH19_1Mbps | Polarization | Vertical |
|-----------|-------------------------|--------------|----------|

80 dBuV/m




| No. | Freq.     | Reading Level | Correct Factor | Measurement | Limit  | Margin |          |         |
|-----|-----------|---------------|----------------|-------------|--------|--------|----------|---------|
|     | MHz       | dBuV/m        | dB             | dBuV/m      | dBuV/m | dB     | Detector | Comment |
| 1   | 4879.4650 | 39.42         | 4.60           | 44.02       | 74.00  | -29.98 | Peak     |         |
| 2 * | 4880.3310 | 27.70         | 4.60           | 32.30       | 54.00  | -21.70 | AVG      |         |

## REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

|           |                         |              |            |
|-----------|-------------------------|--------------|------------|
| Test Mode | TX 2440 MHz _CH19_1Mbps | Polarization | Horizontal |
|-----------|-------------------------|--------------|------------|

130 dBuV/m




| No. | Freq.<br>MHz | Reading<br>Level<br>dBuV/m | Correct<br>Factor<br>dB | Measure<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment  |
|-----|--------------|----------------------------|-------------------------|---------------------------|-----------------|--------------|----------|----------|
| 1 * | 2440.2000    | 76.19                      | 7.25                    | 83.44                     | 54.00           | 29.44        | AVG      | No Limit |
| 2   | 2440.4500    | 77.00                      | 7.25                    | 84.25                     | 74.00           | 10.25        | Peak     | No Limit |

## REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

|           |                         |              |            |
|-----------|-------------------------|--------------|------------|
| Test Mode | TX 2440 MHz _CH19_1Mbps | Polarization | Horizontal |
|-----------|-------------------------|--------------|------------|

80 dBuV/m




| No. | Freq.<br>MHz | Reading<br>Level<br>dBuV/m | Correct<br>Factor<br>dB | Measure<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment |
|-----|--------------|----------------------------|-------------------------|---------------------------|-----------------|--------------|----------|---------|
| 1 * | 4880.2719    | 27.70                      | 4.60                    | 32.30                     | 54.00           | -21.70       | AVG      |         |
| 2   | 4880.3290    | 39.57                      | 4.60                    | 44.17                     | 74.00           | -29.83       | Peak     |         |

## REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

|           |                         |              |          |
|-----------|-------------------------|--------------|----------|
| Test Mode | TX 2480 MHz _CH39_1Mbps | Polarization | Vertical |
|-----------|-------------------------|--------------|----------|

130 dBuV/m



| No. | Freq.<br>MHz | Reading<br>Level<br>dBuV/m | Correct<br>Factor<br>dB | Measure<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment  |
|-----|--------------|----------------------------|-------------------------|---------------------------|-----------------|--------------|----------|----------|
| 1   | 2479.9000    | 65.82                      | 7.25                    | 73.07                     | 74.00           | -0.93        | Peak     | No Limit |
| 2 * | 2480.2000    | 65.08                      | 7.25                    | 72.33                     | 54.00           | 18.33        | AVG      | No Limit |
| 3   | 2483.5000    | 39.23                      | 7.25                    | 46.48                     | 74.00           | -27.52       | Peak     |          |
| 4   | 2483.5000    | 30.03                      | 7.25                    | 37.28                     | 54.00           | -16.72       | AVG      |          |


## REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

|           |                         |              |          |
|-----------|-------------------------|--------------|----------|
| Test Mode | TX 2480 MHz _CH39_1Mbps | Polarization | Vertical |
|-----------|-------------------------|--------------|----------|

80 dBuV/m




| No. | Freq.<br>MHz | Reading<br>Level<br>dBuV/m | Correct<br>Factor<br>dB | Measure<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment |
|-----|--------------|----------------------------|-------------------------|---------------------------|-----------------|--------------|----------|---------|
| 1 * | 4960.2230    | 27.77                      | 4.81                    | 32.58                     | 54.00           | -21.42       | AVG      |         |
| 2   | 4960.9460    | 39.54                      | 4.82                    | 44.36                     | 74.00           | -29.64       | Peak     |         |

#### REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

|           |                         |              |            |
|-----------|-------------------------|--------------|------------|
| Test Mode | TX 2480 MHz _CH39_1Mbps | Polarization | Horizontal |
|-----------|-------------------------|--------------|------------|

130 dBuV/m



| No. | Freq.<br>MHz | Reading<br>Level<br>dBuV/m | Correct<br>Factor<br>dB | Measure<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment  |
|-----|--------------|----------------------------|-------------------------|---------------------------|-----------------|--------------|----------|----------|
| 1   | 2479.6500    | 73.21                      | 7.25                    | 80.46                     | 74.00           | 6.46         | Peak     | No Limit |
| 2 * | 2479.9500    | 72.40                      | 7.25                    | 79.65                     | 54.00           | 25.65        | AVG      | No Limit |
| 3   | 2483.5000    | 38.88                      | 7.25                    | 46.13                     | 74.00           | -27.87       | Peak     |          |
| 4   | 2483.5000    | 30.17                      | 7.25                    | 37.42                     | 54.00           | -16.58       | AVG      |          |


## REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

|           |                         |              |            |
|-----------|-------------------------|--------------|------------|
| Test Mode | TX 2480 MHz _CH39_1Mbps | Polarization | Horizontal |
|-----------|-------------------------|--------------|------------|

80 dBuV/m




| No. | Freq.<br>MHz | Reading<br>Level<br>dBuV/m | Correct<br>Factor<br>dB | Measure<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment |
|-----|--------------|----------------------------|-------------------------|---------------------------|-----------------|--------------|----------|---------|
| 1 * | 4959.6349    | 27.84                      | 4.81                    | 32.65                     | 54.00           | -21.35       | AVG      |         |
| 2   | 4960.4440    | 39.40                      | 4.81                    | 44.21                     | 74.00           | -29.79       | Peak     |         |

## REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.  
(2) Margin Level = Measurement Value - Limit Value.

|           |                         |              |          |
|-----------|-------------------------|--------------|----------|
| Test Mode | TX 2402 MHz _CH00_2Mbps | Polarization | Vertical |
|-----------|-------------------------|--------------|----------|




| No. | Freq.<br>MHz | Reading<br>Level<br>dBuV/m | Correct<br>Factor<br>dB | Measure<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment  |
|-----|--------------|----------------------------|-------------------------|---------------------------|-----------------|--------------|----------|----------|
| 1   | 2390.0000    | 40.33                      | 7.26                    | 47.59                     | 74.00           | -26.41       | Peak     |          |
| 2   | 2390.0000    | 30.27                      | 7.26                    | 37.53                     | 54.00           | -16.47       | AVG      |          |
| 3 * | 2402.2000    | 63.22                      | 7.26                    | 70.48                     | 54.00           | 16.48        | AVG      | No Limit |
| 4   | 2402.4500    | 64.36                      | 7.26                    | 71.62                     | 74.00           | -2.38        | Peak     | No Limit |

## REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.  
(2) Margin Level = Measurement Value - Limit Value.

|           |                         |              |          |
|-----------|-------------------------|--------------|----------|
| Test Mode | TX 2402 MHz _CH00_2Mbps | Polarization | Vertical |
|-----------|-------------------------|--------------|----------|

80 dBuV/m




| No. | Freq.     | Reading Level | Correct Factor | Measurement | Limit  | Margin |          |         |
|-----|-----------|---------------|----------------|-------------|--------|--------|----------|---------|
|     | MHz       | dBuV/m        | dB             | dBuV/m      | dBuV/m | dB     | Detector | Comment |
| 1 * | 4804.1820 | 27.67         | 4.40           | 32.07       | 54.00  | -21.93 | AVG      |         |
| 2   | 4804.6920 | 39.51         | 4.40           | 43.91       | 74.00  | -30.09 | Peak     |         |

## REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

|           |                         |              |            |
|-----------|-------------------------|--------------|------------|
| Test Mode | TX 2402 MHz _CH00_2Mbps | Polarization | Horizontal |
|-----------|-------------------------|--------------|------------|




| No. | Freq.<br>MHz | Reading<br>Level<br>dBuV/m | Correct<br>Factor<br>dB | Measure<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment  |
|-----|--------------|----------------------------|-------------------------|---------------------------|-----------------|--------------|----------|----------|
| 1   | 2390.0000    | 39.25                      | 7.26                    | 46.51                     | 74.00           | -27.49       | Peak     |          |
| 2   | 2390.0000    | 30.14                      | 7.26                    | 37.40                     | 54.00           | -16.60       | AVG      |          |
| 3 * | 2401.9500    | 68.68                      | 7.26                    | 75.94                     | 54.00           | 21.94        | AVG      | No Limit |
| 4   | 2402.4500    | 72.27                      | 7.26                    | 79.53                     | 74.00           | 5.53         | Peak     | No Limit |

## REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.  
(2) Margin Level = Measurement Value - Limit Value.

|           |                         |              |            |
|-----------|-------------------------|--------------|------------|
| Test Mode | TX 2402 MHz _CH00_2Mbps | Polarization | Horizontal |
|-----------|-------------------------|--------------|------------|

80 dBuV/m




| No. | Freq.<br>MHz | Reading<br>Level<br>dBuV/m | Correct<br>Factor<br>dB | Measure<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment |
|-----|--------------|----------------------------|-------------------------|---------------------------|-----------------|--------------|----------|---------|
| 1 * | 4804.3270    | 27.92                      | 4.40                    | 32.32                     | 54.00           | -21.68       | AVG      |         |
| 2   | 4804.8929    | 39.01                      | 4.40                    | 43.41                     | 74.00           | -30.59       | Peak     |         |

## REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

|           |                         |              |          |
|-----------|-------------------------|--------------|----------|
| Test Mode | TX 2440 MHz _CH19_2Mbps | Polarization | Vertical |
|-----------|-------------------------|--------------|----------|

130 dBuV/m




| No. | Freq.<br>MHz | Reading<br>Level<br>dBuV/m | Correct<br>Factor<br>dB | Measure<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment  |
|-----|--------------|----------------------------|-------------------------|---------------------------|-----------------|--------------|----------|----------|
| 1   | 2439.9000    | 68.74                      | 7.25                    | 75.99                     | 74.00           | 1.99         | Peak     | No Limit |
| 2 * | 2440.2000    | 67.76                      | 7.25                    | 75.01                     | 54.00           | 21.01        | AVG      | No Limit |

## REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

|           |                         |              |          |
|-----------|-------------------------|--------------|----------|
| Test Mode | TX 2440 MHz _CH19_2Mbps | Polarization | Vertical |
|-----------|-------------------------|--------------|----------|

80 dBuV/m




| No. | Freq.<br>MHz | Reading<br>Level<br>dBuV/m | Correct<br>Factor<br>dB | Measure<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment |
|-----|--------------|----------------------------|-------------------------|---------------------------|-----------------|--------------|----------|---------|
| 1 * | 4879.3480    | 27.62                      | 4.60                    | 32.22                     | 54.00           | -21.78       | AVG      |         |
| 2   | 4880.8260    | 39.45                      | 4.60                    | 44.05                     | 74.00           | -29.95       | Peak     |         |

## REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

|           |                         |              |            |
|-----------|-------------------------|--------------|------------|
| Test Mode | TX 2440 MHz _CH19_2Mbps | Polarization | Horizontal |
|-----------|-------------------------|--------------|------------|

130 dBuV/m




| No. | Freq.<br>MHz | Reading<br>Level<br>dBuV/m | Correct<br>Factor<br>dB | Measure<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment  |
|-----|--------------|----------------------------|-------------------------|---------------------------|-----------------|--------------|----------|----------|
| 1 * | 2439.9500    | 73.94                      | 7.25                    | 81.19                     | 54.00           | 27.19        | AVG      | No Limit |
| 2   | 2440.4000    | 77.58                      | 7.25                    | 84.83                     | 74.00           | 10.83        | Peak     | No Limit |

## REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.  
(2) Margin Level = Measurement Value - Limit Value.

|           |                         |              |            |
|-----------|-------------------------|--------------|------------|
| Test Mode | TX 2440 MHz _CH19_2Mbps | Polarization | Horizontal |
|-----------|-------------------------|--------------|------------|

80 dBuV/m




| No. | Freq.<br>MHz | Reading<br>Level<br>dBuV/m | Correct<br>Factor<br>dB | Measure<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment |
|-----|--------------|----------------------------|-------------------------|---------------------------|-----------------|--------------|----------|---------|
| 1 * | 4879.3470    | 27.84                      | 4.60                    | 32.44                     | 54.00           | -21.56       | AVG      |         |
| 2   | 4879.6240    | 39.01                      | 4.60                    | 43.61                     | 74.00           | -30.39       | Peak     |         |

## REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

|           |                         |              |          |
|-----------|-------------------------|--------------|----------|
| Test Mode | TX 2480 MHz _CH39_2Mbps | Polarization | Vertical |
|-----------|-------------------------|--------------|----------|

130 dBuV/m



| No. | Freq.<br>MHz | Reading<br>Level<br>dBuV/m | Correct<br>Factor<br>dB | Measure<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment  |
|-----|--------------|----------------------------|-------------------------|---------------------------|-----------------|--------------|----------|----------|
| 1   | 2479.9500    | 65.92                      | 7.25                    | 73.17                     | 74.00           | -0.83        | Peak     | No Limit |
| 2 * | 2480.1500    | 64.89                      | 7.25                    | 72.14                     | 54.00           | 18.14        | AVG      | No Limit |
| 3   | 2483.5000    | 38.02                      | 7.25                    | 45.27                     | 74.00           | -28.73       | Peak     |          |
| 4   | 2483.5000    | 29.83                      | 7.25                    | 37.08                     | 54.00           | -16.92       | AVG      |          |


## REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

|           |                         |              |          |
|-----------|-------------------------|--------------|----------|
| Test Mode | TX 2480 MHz _CH39_2Mbps | Polarization | Vertical |
|-----------|-------------------------|--------------|----------|

80 dBuV/m




| No. | Freq.<br>MHz | Reading<br>Level<br>dBuV/m | Correct<br>Factor<br>dB | Measure<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment |
|-----|--------------|----------------------------|-------------------------|---------------------------|-----------------|--------------|----------|---------|
| 1 * | 4959.5400    | 28.01                      | 4.81                    | 32.82                     | 54.00           | -21.18       | AVG      |         |
| 2   | 4959.7080    | 39.32                      | 4.81                    | 44.13                     | 74.00           | -29.87       | Peak     |         |

## REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

|           |                         |              |            |
|-----------|-------------------------|--------------|------------|
| Test Mode | TX 2480 MHz _CH39_2Mbps | Polarization | Horizontal |
|-----------|-------------------------|--------------|------------|



| No. | Freq.<br>MHz | Reading<br>Level<br>dBuV/m | Correct<br>Factor<br>dB | Measure<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment  |
|-----|--------------|----------------------------|-------------------------|---------------------------|-----------------|--------------|----------|----------|
| 1   | 2479.4000    | 73.22                      | 7.25                    | 80.47                     | 74.00           | 6.47         | Peak     | No Limit |
| 2 * | 2479.9500    | 69.60                      | 7.25                    | 76.85                     | 54.00           | 22.85        | AVG      | No Limit |
| 3   | 2483.5000    | 38.64                      | 7.25                    | 45.89                     | 74.00           | -28.11       | Peak     |          |
| 4   | 2483.5000    | 30.84                      | 7.25                    | 38.09                     | 54.00           | -15.91       | AVG      |          |


## REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

|           |                         |              |            |
|-----------|-------------------------|--------------|------------|
| Test Mode | TX 2480 MHz _CH39_2Mbps | Polarization | Horizontal |
|-----------|-------------------------|--------------|------------|

80 dBuV/m



| No. | Freq.<br>MHz | Reading<br>Level<br>dBuV/m | Correct<br>Factor<br>dB | Measure<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment |
|-----|--------------|----------------------------|-------------------------|---------------------------|-----------------|--------------|----------|---------|
| 1 * | 4959.6660    | 27.82                      | 4.81                    | 32.63                     | 54.00           | -21.37       | AVG      |         |
| 2   | 4959.9800    | 39.27                      | 4.81                    | 44.08                     | 74.00           | -29.92       | Peak     |         |

## REMARKS:


- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

## APPENDIX D - BANDWIDTH


|           |                |
|-----------|----------------|
| Test Mode | TX Mode _1Mbps |
|-----------|----------------|

| Channel | Frequency (MHz) | 6 dB Bandwidth (MHz) | 99 % Occupied Bandwidth (MHz) | 6 dB Bandwidth Min. Limit (MHz) | Test Result |
|---------|-----------------|----------------------|-------------------------------|---------------------------------|-------------|
| 00      | 2402            | 0.714                | 1.040                         | 0.5                             | Pass        |
| 19      | 2440            | 0.712                | 1.044                         | 0.5                             | Pass        |
| 39      | 2480            | 0.718                | 1.044                         | 0.5                             | Pass        |

CH00




Date: 13.MAY.2021 16:00:33

CH19  
6 dB Bandwidth



Date: 13.MAY.2021 16:02:06

CH39




Date: 13.MAY.2021 16:03:44


99 % Occupied Bandwidth



Date: 13.MAY.2021 16:00:08



Date: 13.MAY.2021 16:02:12




Date: 13.MAY.2021 16:03:50

|           |                |
|-----------|----------------|
| Test Mode | TX Mode _2Mbps |
|-----------|----------------|


| Channel | Frequency (MHz) | 6 dB Bandwidth (MHz) | 99 % Occupied Bandwidth (MHz) | 6 dB Bandwidth Min. Limit (MHz) | Test Result |
|---------|-----------------|----------------------|-------------------------------|---------------------------------|-------------|
| 00      | 2402            | 1.384                | 2.088                         | 0.5                             | Pass        |
| 19      | 2440            | 1.368                | 2.104                         | 0.5                             | Pass        |
| 39      | 2480            | 1.368                | 2.104                         | 0.5                             | Pass        |

CH00




Date: 13.MAY.2021 16:05:39

CH19  
6 dB Bandwidth




Date: 13.MAY.2021 16:07:38

CH39




Date: 13.MAY.2021 16:09:16


99 % Occupied Bandwidth



Date: 13.MAY.2021 16:05:12



Date: 13.MAY.2021 16:07:44




Date: 13.MAY.2021 16:09:23


## APPENDIX E - MAXIMUM OUTPUT POWER

|           |                |
|-----------|----------------|
| Test Mode | TX Mode _1Mbps |
|-----------|----------------|


| Frequency (MHz) | Output Power (dBm) | Output Power (W) | Max. Limit (dBm) | Max. Limit (W) | Test Result |
|-----------------|--------------------|------------------|------------------|----------------|-------------|
| 2402            | -0.08              | 0.0010           | 30.00            | 1.0000         | Pass        |
| 2440            | -0.25              | 0.0009           | 30.00            | 1.0000         | Pass        |
| 2480            | -0.50              | 0.0009           | 30.00            | 1.0000         | Pass        |



Date: 13.MAY.2021 16:01:22




Date: 13.MAY.2021 16:03:01




Date: 13.MAY.2021 16:04:39

|           |                |
|-----------|----------------|
| Test Mode | TX Mode _2Mbps |
|-----------|----------------|


| Frequency (MHz) | Output Power (dBm) | Output Power (W) | Max. Limit (dBm) | Max. Limit (W) | Test Result |
|-----------------|--------------------|------------------|------------------|----------------|-------------|
| 2402            | -0.07              | 0.0010           | 30.00            | 1.0000         | Pass        |
| 2440            | -0.19              | 0.0009           | 30.00            | 1.0000         | Pass        |
| 2480            | -0.45              | 0.0009           | 30.00            | 1.0000         | Pass        |



Date: 13.MAY.2021 16:06:28



Date: 13.MAY.2021 16:08:33




Date: 13.MAY.2021 16:10:11


## **APPENDIX F - CONDUCTED SPURIOUS EMISSION**

Test Mode TX Mode \_1Mbps

## Bandedge CH00 (Lower)






## Bandedge CH39 (Upper)



Date: 13.MAY.2021 16:00:41

Date: 13.MAY.2021 16:03:58

## CH00 – 10th Harmonic of the fundamental frequency






Date: 13.MAY.2021 16:00:154

Date: 13.MAY.2021 16:01:02

Date: 13.MAY.2021 16:01:09

## CH19 – 10th Harmonic of the fundamental frequency






Date: 13.MAY.2021 16:02:33

Date: 13.MAY.2021 16:02:42

Date: 13.MAY.2021 16:02:49

## CH39 – 10th Harmonic of the fundamental frequency




Date: 13.MAY.2021 16:04:11

Date: 13.MAY.2021 16:04:19

Date: 13.MAY.2021 16:04:26


Test Mode TX Mode \_2Mbps

## Bandedge CH00 (Lower)




Date: 13.MAY.2021 16:05:47

## Bandedge CH39 (Upper)




Date: 13.MAY.2021 16:09:30


## CH00 – 10th Harmonic of the fundamental frequency



Date: 13.MAY.2021 16:06:00




Date: 13.MAY.2021 16:06:08




Date: 13.MAY.2021 16:06:16


## CH19 – 10th Harmonic of the fundamental frequency



Date: 13.MAY.2021 16:08:05




Date: 13.MAY.2021 16:08:13




Date: 13.MAY.2021 16:08:20


## CH39 – 10th Harmonic of the fundamental frequency



Date: 13.MAY.2021 16:09:14



Date: 13.MAY.2021 16:09:51




Date: 13.MAY.2021 16:09:59


## **APPENDIX G - POWER SPECTRAL DENSITY**

|           |                |
|-----------|----------------|
| Test Mode | TX Mode _1Mbps |
|-----------|----------------|


| Channel | Frequency (MHz) | Power Spectral Density (dBm/3 kHz) | Max. Limit (dBm/3 kHz) | Test Result |
|---------|-----------------|------------------------------------|------------------------|-------------|
| 00      | 2402            | -16.59                             | 8.00                   | Pass        |
| 19      | 2440            | -16.65                             | 8.00                   | Pass        |
| 39      | 2480            | -16.94                             | 8.00                   | Pass        |



Date: 13.MAY.2021 16:01:16




Date: 13.MAY.2021 16:02:55




Date: 13.MAY.2021 16:04:33

|           |                |
|-----------|----------------|
| Test Mode | TX Mode _2Mbps |
|-----------|----------------|


| Channel | Frequency (MHz) | Power Spectral Density (dBm/3 kHz) | Max. Limit (dBm/3 kHz) | Test Result |
|---------|-----------------|------------------------------------|------------------------|-------------|
| 00      | 2402            | -19.96                             | 8.00                   | Pass        |
| 19      | 2440            | -20.26                             | 8.00                   | Pass        |
| 39      | 2480            | -20.31                             | 8.00                   | Pass        |



Date: 13.MAY.2021 16:06:22



Date: 13.MAY.2021 16:08:27



Date: 13.MAY.2021 16:10:05

End of Test Report