

RF Exposure Evaluation

According to KDB 447498 D01 General RF Exposure Guidance v06 and part 2.1091, Unless specifically required by the *published RF exposure KDB procedures*, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding *SAR Test Exclusion Threshold* condition(s), listed below, is (are) satisfied.

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula: **$P_d = (P_{out} * G) / (4 * \pi * r^2)$**

Where

P_d = power density in mW/cm², **P_{out}** = output power to antenna in mW;

G = gain of antenna in linear scale, **π** = 3.1416;

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

Test Result of RF Exposure Evaluation

Mode	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
BLE	3.46	2.22	0.0009	1.0	PASS
2.4GWIFI	15.31	33.96	0.0134	1.0	PASS
5GWIFI	10.56	11.38	0.0050	1.0	PASS
2.4G	3.36	2.17	0.0012	1.0	PASS
Z-WAVE	-27.37	0.01	0.0001	1.0	PASS
LTE	/	273	0.0543	1.0	PASS

The device could support transmission with BLE and 2.4GWIFI and 5GWIFI and Z-WAVE and LTE simultaneously

Power Density at R=20cm (mW/cm²)

EIRP=67.83-95.2=-27.37dBm

WIFI and BT: $0.0009/1+0.0134/1+0.0050+0.0012/1+0.0001/1+0.0543/1+0.5431/1=0.0749$
 < 1.0 Limit (mW/cm²),

Antenna gain:

2.4GWIFI&BLE: 2.98dBi

5GWIFI: 3.41dBi

Z-WAVE: 0.79dBi

2.4G: 4.34dBi

No RF Exposure Evaluation/SAR test is required.