

**Shenzhen Global Test Service Co.,Ltd.**

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

RF Exposure evaluation**Report Reference No.....: GTS20190918014-1-7****FCC ID.....: 2AH68-PIVOT3SAT**

Compiled by

(position+printed name+signature)..: File administrators Tracy Hu

Supervised by

(position+printed name+signature)..: Test Engineer Moon Tan



Approved by

(position+printed name+signature)..: Manager Simon Hu

Date of issue.....: Dec. 26, 2019

Representative Laboratory Name .: Shenzhen Global Test Service Co.,Ltd.

Address.....: No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

Applicant's name: TuringSense, Inc

Address: 4675 Stevens Creek Blvd,Santa Clara, CA 95051

Test specification

Standard: **47CFR §1.1310**
47CFR §2.1093
KDB447498 v06

TRF Originator: Shenzhen Global Test Service Co.,Ltd.

Master TRF.....: Dated 2014-12

Shenzhen Global Test Service Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: Pivot Yoga

Trade Mark: N/A

Manufacturer: **Sceiba Intelligent Fashin Co Ltd.**

Model/Type reference.....: PIVOT Yoga Pant1.0" for the pants

Listed Models: N/A

Exposure category.....: General population/uncontrolled environment

EUT Type: Production Unit

Hardware Version: 2.0

Software Version: FW 9.12.22.94.42.1

Rating: DC 3.7V by Battery
Recharged by DC 5V

Result.....: **PASS**

TEST REPORT

Test Report No. :	GTS20190918014-1-7	Nov. 22, 2019
		Date of issue

Equipment under Test : Pivot Yoga

Model /Type : PIVOT Yoga Pant1.0" for the pants

Listed Models : N/A

Applicant : **TuringSense, Inc**

Address : 4675 Stevens Creek Blvd,Santa Clara, CA 95051

Manufacturer : **Sceiba Inteligent Fashin Co Ltd.**

Address : A301, DongXin Science & Technology Park, 2nd St. ChenWu Village, Houjie Town , Donguan, China

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1. SUMMARY4

 1.1. EUT configuration.....4

 1.2. Product Description4

2. TEST ENVIRONMENT5

 2.1. Address of the test laboratory5

 2.2. Test Facility5

 2.3. Environmental conditions5

 2.4. Statement of the measurement uncertainty5

3. METHOD OF MEASUREMENT6

 3.1. Applicable Standard6

 3.2. Requirement.....6

4. EVALUATION RESULT6

 4.1. Standalone MPE6

5. CONCLUSION6

1. SUMMARY

1.1. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

○ - supplied by the manufacturer

● - supplied by the lab

●	adapter	Length (m) :	/
		Shield :	/
		Detachable :	/

1.2. Product Description

Name of EUT	Pivot Yoga
Trade Mark:	N/A
Model Number	PIVOT Yoga Pant1.0" for the pants
Listed Models	N/A
FCC ID	2AH68-PIVOT3SAT
Power Supply	DC 3.7V from battery Recharged by DC 5V
Adapter information:	N/A
ESB	
Modulation Type	GFSK
Operation frequency	2402-2480MHz
Antenna Type	Internal antenna
Antenna gain	2.11 dBi
Remark:	

2. TEST ENVIRONMENT

2.1. Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

2.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L8169)

Shenzhen Global Test Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA (Certificate No. 4758.01)

Shenzhen Global Test Service Co., Ltd. has been assessed by the American Association for Laboratory Accreditation (A2LA). Certificate No. 4758.01.

2.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

2.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the Shenzhen Global Test Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3. METHOD OF MEASUREMENT

3.1. Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1093 RF exposure requirement

KDB447498 v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

3.2. Requirement

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.

2. Power and distance are rounded to the nearest mW and mm before calculation.

3. The result is rounded to one decimal place for comparison.

4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

4. EVALUATION RESULT

4.1. Standalone MPE

MODE	Frequency (MHz)	Minimum Separation Distance (mm)	Output Power (Turn-up Procedure)		Calculated value	Threshold (1-g SAR)	SAR Test Exclusion
			dBm	mW			
ESB	2480	5	1.0	1.2589	0.3965	3	YES

5. CONCLUSION

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06, No SAR is required.

.....End of Report.....