

## RF Exposure Report

**Report No.:** MFCCOG-WTW-P22060455

**FCC ID:** 2AH7L-UPSA

**Test Model:** PAS800, PAS800L, PAS800P

**Received Date:** Jun. 15, 2022

**Date of Evaluation:** Sep. 15, 2022

**Issued Date:** Oct. 26, 2023

**Applicant:** Schneider Electric Industries SAS

**Address:** Electropole Site - 38EQ1, 31 rue Pierre Mendes France, Eybens - 38050  
Grenoble cedex 9

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Lin Kou Laboratories

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

**Test Location:** No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City  
33383, TAIWAN

**FCC Registration / Designation Number:** 788550 / TW0003



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

## Table of Contents

|                                               |          |
|-----------------------------------------------|----------|
| <b>Release Control Record</b> .....           | <b>3</b> |
| <b>1 Certificate of Conformity</b> .....      | <b>4</b> |
| <b>2 Applicable RF Exposure Limit</b> .....   | <b>5</b> |
| <b>3 Applicable Evaluation Criteria</b> ..... | <b>6</b> |
| <b>4 Test Result</b> .....                    | <b>8</b> |
| <b>5 Conclusion</b> .....                     | <b>8</b> |

### Release Control Record

| Issue No.            | Description      | Date Issued   |
|----------------------|------------------|---------------|
| MFCCOG-WTW-P22060455 | Original Release | Oct. 26, 2023 |

## 1 Certificate of Conformity

**Product:** EcoStruxure™ Panel Server Advanced

**Brand:** Schneider Electric

**Test Model:** PAS800, PAS800L, PAS800P

**Sample Status:** Engineering Sample

**Applicant:** Schneider Electric Industries SAS

**Date of Evaluation:** Sep. 15, 2022

**FCC Rule Part:** FCC Part 2 (Section 2.1091)

**Standards:** KDB 447498 D04 Interim General RF Exposure Guidance v01

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :** Vera Huang , **Date:** Oct. 26, 2023  
Vera Huang / Specialist

**Approved by :** Jeremy Lin , **Date:** Oct. 26, 2023  
Jeremy Lin / Project Engineer

## 2 Applicable RF Exposure Limit

### § 1.1310 Radiofrequency radiation exposure limits.

(a) Specific absorption rate (SAR) shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in § 1.1307(b) of this part within the frequency range of 100 kHz to 6 GHz (inclusive).

(b) The SAR limits for occupational/controlled exposure are 0.4 W/kg, as averaged over the whole body, and a peak spatial-average SAR of 8 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit for occupational/controlled exposure is 20 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 6 minutes to determine compliance with occupational/controlled SAR limits.

(c) The SAR limits for general population/uncontrolled exposure are 0.08 W/kg, as averaged over the whole body, and a peak spatial-average SAR of 1.6 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit is 4 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 30 minutes to determine compliance with general population/uncontrolled SAR limits.

### (e) Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields

#### ➤ Limits for General Population/Uncontrolled Exposure

| Frequency Range (MHz)                                 | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm <sup>2</sup> ) | Average Time (minutes) |
|-------------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|------------------------|
| Limits For General Population / Uncontrolled Exposure |                               |                               |                                     |                        |
| 0.3-1.34                                              | 614                           | 1.63                          | (100)*                              | 30                     |
| 1.34-30                                               | 824/f                         | 2.19/f                        | (180/f <sup>2</sup> )*              | 30                     |
| 30-300                                                | 27.5                          | 0.073                         | 0.2                                 | 30                     |
| 300-1500                                              | ...                           | ...                           | f/1500                              | 30                     |
| 1500-100,000                                          | ...                           | ...                           | 1.0                                 | 30                     |

#### ➤ Limits for Occupational/Controlled Exposure

| Frequency Range (MHz)                                 | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm <sup>2</sup> ) | Average Time (minutes) |
|-------------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|------------------------|
| Limits For General Population / Uncontrolled Exposure |                               |                               |                                     |                        |
| 0.3-3.0                                               | 614                           | 1.63                          | *(100)                              | ≤6                     |
| 3.0-30                                                | 1842/f                        | 4.89/f                        | *(900/f <sup>2</sup> )              | <6                     |
| 30-300                                                | 61.4                          | 0.163                         | 1.0                                 | <6                     |
| 300-1,500                                             |                               |                               | f/300                               | <6                     |
| 1,500-100,000                                         |                               |                               | 5                                   | <6                     |

### 3 Applicable Evaluation Criteria

#### ☐ 1 mW Blanket Exemption – §1.1307(b)(3)(i)(A)

- The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A).

#### ☒ MPE-based Exemption – §1.1307(b)(3)(i)(C)

- The minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. Table applies to any RF source (i.e. single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits.

| RF Source frequency (MHz)                                                                             | Threshold ERP (watts) |
|-------------------------------------------------------------------------------------------------------|-----------------------|
| 0.3-1.34                                                                                              | $1,920 R^2$ .         |
| 1.34-30                                                                                               | $3,450 R^2/f^2$ .     |
| 30-300                                                                                                | $3.83 R^2$ .          |
| 300-1,500                                                                                             | $0.0128 R^2f$ .       |
| 1,500-100,000                                                                                         | $19.2R^2$ .           |
| R must be at least $\lambda/2\pi$ , where $\lambda$ is the free-space operating wavelength in meters. |                       |

#### ☐ MPE-based Exemption – §1.1307(b)(3)(i)(B)

- For mobile devices that are not exempt per Table 1 of §1.1307(b)(1)(i)(C) and device at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz.

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

#### ☐ SAR-based Exemption - §1.1307(b)(3)(i)(B)

- The SAR-based exemption formula of §1.1307(b)(3)(i)(B), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold  $P_{th}$  (mW). This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and  $f$  is in GHz,  $d$  is the separation distance (cm)

When 10-g extremity SAR applies, SAR test exemption may be considered by applying a factor of 2.5 to the SAR-based exemption thresholds.

## Multiple RF Sources

□ Sum of multiple sources is less than 1 mW during the time-averaging period – §1.1307(b)(3)(ii)(A)

- The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).

□ Fixed RF sources operating in the same time-averaging period – §1.1307(b)(3)(ii)(B)

- Either SAR-based or MPE-based exemption may be considered for test exemption for fixed, mobile, or portable device exposure conditions; therefore, the contributions from each exemption in conjunction with the measured SAR (Evaluated<sub>k</sub> term) should be used to determine exemption for simultaneous transmission according to Formula below,

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

The sum of the ratios of the applicable terms for SAR-based, MPE-based and measured SAR or MPE should be less than 1, to determine simultaneous transmission exposure compliance.

Where:

$a$  = number of fixed, mobile, or portable RF sources claiming exemption using [paragraph \(b\)\(3\)\(i\)\(B\)](#) of this section for  $P_{th}$ , including existing exempt transmitters and those being added.

$c$  = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

$P_{th,i}$  = the exemption threshold power ( $P_{th}$ ) according to [paragraph \(b\)\(3\)\(i\)\(B\)](#) of this section for fixed, mobile, or portable RF source  $i$ .

$ERP_{th,j}$  = exemption threshold ERP for fixed, mobile, or portable RF source  $j$ , at a distance of at least  $\lambda/2\pi$  according to the applicable formula of [paragraph \(b\)\(3\)\(i\)\(C\)](#) of this section.

$Exposure Limit_k$  = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source  $k$ , as applicable from [§ 1.1310 of this chapter](#).

$b$  = number of fixed, mobile, or portable RF sources claiming exemption using [paragraph \(b\)\(3\)\(i\)\(C\)](#) of this section for Threshold ERP, including existing exempt transmitters and those being added.

$P_i$  = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source  $i$  at a distance between 0.5 cm and 40 cm (inclusive).

$ERP_j$  = the ERP of fixed, mobile, or portable RF source  $j$ .

$Evaluated_k$  = the maximum reported SAR or MPE of fixed, mobile, or portable RF source  $k$  either in the device or at the transmitter site from an existing evaluation at the location of exposure.

#### 4 Test Result

| MPE-based Exemption §1.1307(b)(3)(i)(C) |                      |                    |                    |                  |               |                      |             |
|-----------------------------------------|----------------------|--------------------|--------------------|------------------|---------------|----------------------|-------------|
| Operation Mode                          | Frequency Band (MHz) | Average Power (mW) | Antenna Gain (dBi) | Maximum ERP (mW) | Distance (cm) | Limit Threshold (mW) | Test Result |
| Bluetooth                               | 2402-2480            | 0.02312            | 2.54               | 0.025            | 20            | 768                  | Pass        |
| Zigbee                                  | 2405-2480            | 0.1637             | 2.54               | 0.179            | 20            | 768                  | Pass        |
| WLAN 2.4GHz                             | 2412-2462            | 0.811              | 2.54               | 0.887            | 20            | 768                  | Pass        |
| WLAN 5GHz                               | 5180-5825            | 0.1038             | 3.88               | 0.155            | 20            | 768                  | Pass        |

Note:

- This report is prepared for FCC class II permissive change. The difference compared with the original report (BV CPS report no.: SABHBQ-WTW-P21080521) are listed as below. The output power is lowered via firmware/software settings only (and cannot be changed by end-user / any other third parties).
  - Reducing power setting
  - Changing internal antenna gain
  - Changing 5G antenna gain of external antenna
- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
- Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.
- The WLAN 2.4GHz, 5GHz, Zigbee and BT of the device can transmit simultaneously but not WLAN 2.4GHz and 5GHz at the same time.

| Multiple RF Sources (Simultaneous Operations) |                      |                  |                      |          |               |                 |             |
|-----------------------------------------------|----------------------|------------------|----------------------|----------|---------------|-----------------|-------------|
| Exemption Evaluation                          |                      |                  |                      |          | Sum of Ratios | Limit of Ratios | Test Result |
| Operation Mode                                | Frequency Band (MHz) | Maximum ERP (mW) | Limit Threshold (mW) | Ratio    |               |                 |             |
| Bluetooth                                     | 2402-2480            | 0.025            | 768                  | 0.000033 | 0.001266      | 1               | Pass        |
| Zigbee                                        | 2405-2480            | 0.179            | 768                  | 0.000233 |               |                 |             |
| WLAN 2.4GHz                                   | 2412-2462            | 0.887            | 768                  | 0.001    |               |                 |             |

| Multiple RF Sources (Simultaneous Operations) |                      |                  |                      |          |               |                 |             |
|-----------------------------------------------|----------------------|------------------|----------------------|----------|---------------|-----------------|-------------|
| Exemption Evaluation                          |                      |                  |                      |          | Sum of Ratios | Limit of Ratios | Test Result |
| Operation Mode                                | Frequency Band (MHz) | Maximum ERP (mW) | Limit Threshold (mW) | Ratio    |               |                 |             |
| Bluetooth                                     | 2402-2480            | 0.025            | 768                  | 0.000033 | 0.000468      | 1               | Pass        |
| Zigbee                                        | 2405-2480            | 0.179            | 768                  | 0.000233 |               |                 |             |
| WLAN 5GHz                                     | 5180-5825            | 0.155            | 768                  | 0.000202 |               |                 |             |

#### 5 Conclusion

Source-base time average power is below Exemption Criteria and/or MPE thresholds, therefore the device is compliant FCC RF exposure requirement.

--- END ---