

FCC Test Report

Report No.: RFCCOG-WTW-P22060455-3

FCC ID: 2AH7L-UPSA

Test Model: PAS800, PAS800L, PAS800P (Refer to item 3.1 for more details)

Received Date: Jun. 15, 2022

Test Date: Sep. 08, 2022

Issued Date: Oct. 26, 2023

Applicant: Schneider Electric Industries SAS

Address: Electropole Site - 38EQ1, 31 rue Pierre Mendes France, Eybens - 38050
Grenoble cedex 9

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, TAIWAN

FCC Registration / 788550 / TW0003
Designation Number:



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 Summary of Test Results	5
2.1 Modification Record	5
3 General Information	6
3.1 General Description of EUT	6
3.2 Description of Test Modes	8
3.2.1 Test Mode Applicability and Tested Channel Detail	8
3.3 Duty Cycle of Test Signal	8
3.4 Description of Support Units	9
3.4.1 Configuration of System under Test	9
3.5 General Description of Applied Standards and References	9
4 Test Types and Results	10
4.1 6dB Bandwidth Measurement	10
4.1.1 Limits of 6dB Bandwidth Measurement	10
4.1.2 Test Setup	10
4.1.3 Test Instruments	10
4.1.4 Test Procedure	10
4.1.5 Deviation from Test Standard	10
4.1.6 EUT Operating Conditions	10
4.1.7 Test Result	11
4.2 Conducted Output Power Measurement	12
4.2.1 Limits of Conducted Output Power Measurement	12
4.2.2 Test Setup	12
4.2.3 Test Instruments	12
4.2.4 Test Procedures	12
4.2.5 Deviation from Test Standard	12
4.2.6 EUT Operating Conditions	12
4.2.7 Test Results	12
4.3 Power Spectral Density Measurement	13
4.3.1 Limits of Power Spectral Density Measurement	13
4.3.2 Test Setup	13
4.3.3 Test Instruments	13
4.3.4 Test Procedure	13
4.3.5 Deviation from Test Standard	13
4.3.6 EUT Operating Condition	13
4.3.7 Test Results	14
4.4 Conducted Out of Band Emission Measurement	15
4.4.1 Limits of Conducted Out of Band Emission Measurement	15
4.4.2 Test Setup	15
4.4.3 Test Instruments	15
4.4.4 Test Procedure	15
4.4.5 Deviation from Test Standard	15
4.4.6 EUT Operating Condition	15
4.4.7 Test Results	15
Appendix – Information of the Testing Laboratories	18

Release Control Record

Issue No.	Description	Date Issued
RFCCOG-WTW-P22060455-3	Original Release	Oct. 26, 2023

1 Certificate of Conformity

Product: EcoStruxure™ Panel Server Advanced

Brand: Schneider Electric

Test Model: PAS800, PAS800L, PAS800P (Refer to item 3.1 for more details)

Sample Status: Engineering sample

Applicant: Schneider Electric Industries SAS

Test Date: Sep. 08, 2022

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10-2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Vera Huang , Date: Oct. 26, 2023
Vera Huang / Specialist

Approved by : Jeremy Lin , Date: Oct. 26, 2023
Jeremy Lin / Project Engineer

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	N/A	Refer to Note 1
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	N/A	Refer to Note 1
15.247(d)	Antenna Port Emission	Pass	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	Pass	Meet the requirement of limit.
15.247(b)	Conducted power	Pass	Meet the requirement of limit.
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	Internal Antenna: No antenna connector is used. External Antenna: Antenna connector is RP-SMA not a standard connector.

Note:

1. Only antenna port conducted measurement tests were performed for this addendum. Refer to original report for other test data.
2. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	EcoStruxure™ Panel Server Advanced
Brand	Schneider Electric
Test Model	PAS800, PAS800L, PAS800P
Model Difference	Refer to note
Sample Status	Engineering sample
Power Supply rating	PAS800: 110 to 277Vac/dc +/-10%, 50-60Hz(+/-5Hz) < 3.5W/12VA , -25°C to 70°C PAS800L: 24Vdc +/-10% , 145 mA , < 3.5W, -25°C to 70°C PAS800P: POE(PD) - Class 0, 37Vdc to 57Vdc, < 3.5 W, 48Vdc (Typical), 72 mA, -25°C to 70°C
Modulation Type	O-QPSK
Modulation Technology	DSSS
Transfer Rate	250 kbps
Operating Frequency	2405 ~ 2480MHz
Number of Channel	16
Output Power	1.318mW
Antenna Type	Refer to note
Antenna Connector	Refer to note
Accessory Device	External Antenna (Brand: Schneider Electric, Model: PASA-ANT1)
Cable Supplied	NA

Note:

- This report is prepared for FCC class II permissive change. The difference compared with the original report (BV CPS report no.: RFBHBQ-WTW-P21080521-3) are listed as below. The output power is lowered via firmware/software settings only (and cannot be changed by end-user / any other third parties. Therefore, only antenna port conducted measurement tests were verified and recorded in this report.
 - Reducing power setting
 - Changing internal antenna gain
- All models are listed as below.

Brand	Model	Difference
Schneider Electric	PAS800	All three models are similar in construction and functioning except the mode of powering. PAS800: powered by 110V-277Vac/dc PAS800L: powered by 24Vdc source PAS800P: Powered Over Ethernet.
	PAS800L	
	PAS800P	

3. The following antennas were provided to the EUT.

Internal Antenna

No.	Brand	Model	Antenna Type	Connector	Gain(dBi)	Remark
1	Schneider Electric	U7_1	PCB	NA	2.31	long cable
2	Schneider Electric	U8_1	PCB	NA	0.91	short cable

External Antenna

No.	Brand	Model	Antenna Type	Connector	Gain(dBi)	Remark
1	Schneider Electric	PASA-ANT1	Dipole	RP-SMA	2.54	-

* Detail antenna specification please refer to antenna datasheet or an antenna gain measurement report.

4. The WLAN 2.4GHz, 5GHz, Zigbee and BT of the device can transmit simultaneously but not WLAN 2.4GHz and 5GHz at the same time.
5. Spurious emission of the simultaneous operation (WLAN 2.4GHz, 5GHz, Zigbee and BT) has been evaluated and no non-compliance was found.

3.2 Description of Test Modes

16 channels are provided to this EUT:

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
11	2405	15	2425	19	2445	23	2465
12	2410	16	2430	20	2450	24	2470
13	2415	17	2435	21	2455	25	2475
14	2420	18	2440	22	2460	26	2480

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT Configure Mode	Applicable to				Antenna	Description
	RE $\geq$ 1G	RE<1G	PLC	APCM		
-	-	-	-	√	Internal	EUT (PAS800) + AC power

Where RE $\geq$ 1G: Radiated Emission above 1GHz & Bandedge Measurement

RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

Note:

1. "-" means no effect.

2. The internal and external antenna had been pre-tested for reduced power conducted power. The worst case scenario is the internal antenna.

Antenna Port Conducted Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.


EUT Configure Mode	Available Channel	Tested Channel	Modulation Type
-	11 to 26	11, 18, 26	O-QPSK

Test Condition:

Applicable to	Environmental Conditions	Input Power (System)	Tested by
APCM	25 deg. C, 60% RH	120Vac, 60Hz	Wayne Lin

3.3 Duty Cycle of Test Signal

Duty cycle of test signal is 100%.




3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Load	NA	NA	NA	NA	Provided by Lab

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	LAN	2	1.5	N	0	RJ45, Cat5e
2.	AC cable	1	30	Y	0	Provided by client

3.4.1 Configuration of System under Test



3.5 General Description of Applied Standards and References

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and references:

Test standard:

FCC Part 15, Subpart C (15.247)

ANSI C63.10-2013

ANSI C63.10-2020

All test items have been performed and recorded as per the above standards.

References Test Guidance:

KDB 558074 D01 15.247 Meas Guidance v05r02

All test items have been performed as a reference to the above KDB test guidance.


4 Test Types and Results

4.1 6dB Bandwidth Measurement

4.1.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.1.2 Test Setup



4.1.3 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer ROHDE & SCHWARZ	FSV40	100980	Apr. 20, 2022	Apr. 19, 2023
Peak Power Analyzer KEYSIGHT	8990B	MY51000485	Jan. 18, 2022	Jan. 17, 2023
Wideband Power Sensor KEYSIGHT	N1923A	MY58020002	Jan. 17, 2022	Jan. 16, 2023

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Oven room.

4.1.4 Test Procedure

- Set resolution bandwidth (RBW) = 100kHz.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

4.1.5 Deviation from Test Standard


No deviation.

4.1.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.1.7 Test Result

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
11	2405	1.66	0.5	Pass
18	2440	1.67	0.5	Pass
26	2480	1.68	0.5	Pass




4.2 Conducted Output Power Measurement

4.2.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

4.2.2 Test Setup



4.2.3 Test Instruments

Refer to section 4.1.3 to get information of above instrument.

4.2.4 Test Procedures

For Peak Power

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

For Average Power

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

4.2.5 Deviation from Test Standard

No deviation.

4.2.6 EUT Operating Conditions

Same as item 4.1.6.

4.2.7 Test Results

For Peak Power

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass/Fail
11	2405	0.6442	-1.91	30.00	Pass
18	2440	1.318	1.20	30.00	Pass
26	2480	1.306	1.16	30.00	Pass

For Average Power


Channel	Frequency (MHz)	Average Power (mW)	Average Power (dBm)
11	2405	0.15	-8.24
18	2440	0.1637	-7.86
26	2480	0.1633	-7.87

4.3 Power Spectral Density Measurement

4.3.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm per 3kHz.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.3 to get information of above instrument.

4.3.4 Test Procedure

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq 3 \times \text{RBW}$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.

4.3.5 Deviation from Test Standard


No deviation.

4.3.6 EUT Operating Condition

Same as item 4.1.6

4.3.7 Test Results

Channel	Freq. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass / Fail
11	2405	-26.01	8.00	Pass
18	2440	-25.58	8.00	Pass
26	2480	-25.59	8.00	Pass




4.4 Conducted Out of Band Emission Measurement

4.4.1 Limits of Conducted Out of Band Emission Measurement

Below 20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.3 to get information of above instrument.

4.4.4 Test Procedure

MEASUREMENT PROCEDURE REF

- Set the RBW = 100 kHz.
- Set the VBW $\geq$ 300 kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOBE

- Set RBW = 100 kHz.
- Set VBW $\geq$ 300 kHz.
- Detector = peak.
- Sweep = auto couple.
- Trace Mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 EUT Operating Condition



Same as item 4.1.6

4.4.7 Test Results



The conducted emission test is performed on each TX port of operating mode without summing or adding $10\log(N)$ since the limit is relative emission limit.

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.



CH 11




CH 18




CH 26



CH 11 Band edge



CH 26 Band edge



Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@bureauveritas.com

Web Site: <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---