

Test Report

No. 1-2265-26-01-03_TR1-R01

February 10. 2026

Applicant	OneSpan
Product	Digipass authenticator
Model	FX2 - A
Tested Technology	Bluetooth LE
Test Standard	FCC 47 CFR Part 2
Verdict	TEST EXEMPTION FULFILLED
The test results apply only to the equipment specified in this document.	

This test report is electronically signed and valid without handwritten signature.
Public keys for verification of the electronic signatures can be requested at the testing laboratory.



Digitally signed by
Alexander.Hnatovskiy@cetec
omadvanced.com
Date: 2026.02.10 12:00:54

authorized by

Alexander Hnatovskiy
Coordinator Area
Regulatory Services Radio



Digitally signed by
Eric.Tuettmann@cetecomadv
anced.com
Date: 2026.02.10 10:40:51

created by

Eric Tuettmann
Testing Manager
Regulatory Services Radio

Table of Contents

1. Disclaimer	3
2. Document history.....	4
2.1. Current release	4
2.2. Previous releases	4
3. Test laboratory.....	5
3.1. Contact information	5
3.2. Involved test locations.....	5
3.3. Subcontracted laboratories.....	5
3.4. Laboratory listings and recognitions	5
4. Client information	6
4.1. Applicant.....	6
4.2. Manufacturer.....	6
5. Test sample information	7
5.1. General Information	7
5.1.1. General Data of Main EUT as Declared by Applicant.....	7
6. Measurement details	8
6.1. Test methodology.....	8
7. 1.1 General Information	9
7.1. Notes and Disclaimer	9
7.2. References	9
7.3. General RF Exposure Test Exemptions	10
8. SAR Based Test Exemption	12
8.1. KDB 447498 D04 Interim General RF Exposure Guidance v01, section 2.1.3:.....	12
8.1.1. Results.....	14

1. Disclaimer

The test results of this test report relate exclusively to the test item specified in chapter "Test sample information". cetecom advanced does not assume responsibility for any conclusions and generalizations drawn from the test results regarding other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of cetecom advanced.

The testing service provided by cetecom advanced has been rendered under the current "General Terms and Conditions for cetecom advanced".

cetecom advanced will not be liable for any loss or damage resulting from false, inaccurate, inappropriate, or incomplete product information provided by the customer.

Under no circumstances does the cetecom advanced test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the cetecom advanced test report include or imply any product or service warranties from cetecom advanced, including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by cetecom advanced.

All rights and remedies regarding vendor's products and services for which cetecom advanced has prepared this test report shall be provided by the party offering such products or services and not by cetecom advanced. In no case this test report can be considered as a Letter of Approval.

This test report is electronically signed and valid without handwritten signature. Public keys for verification of the electronic signatures can be requested at the testing laboratory.

The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 10 years at cetecom advanced.

2. Document history

2.1. Current release

Release No.: R01
Date of release: February 10. 2026
Applied changes: Initial release

2.2. Previous releases

Version	Applied change	Date of release
n/a		

3. Test laboratory

3.1. Contact information

cetecom advanced GmbH
Untertuerkheimer Str. 6-10
66117 Saarbruecken
Germany

3.2. Involved test locations

Saarbrücken Lab

Untertürkheimer Strasse 6 – 10
66117 Saarbrücken
Germany

3.3. Subcontracted laboratories

None.

3.4. Laboratory listings and recognitions

	Saarbrücken	Essen
FCC	DE0002	DE0003
ISED	DE0001 3462C	DE0001 3462D

4. Client information

4.1. Applicant

Name: OneSpan
Address: BELGIUM, 1831 Machelen, De Kleetlaan 12A
Contact Person: Erik Van Bever
Contact Person's Email: Erik.Van.bever@onespan.com

4.2. Manufacturer

Name: OneSpan
Address: BELGIUM, 1831 Machelen, De Kleetlaan 12A
Contact Person: Erik Van Bever
Contact Person's Email: Erik.Van.bever@onespan.com

5. Test sample information

The data about the test samples is given/supplied by the customer and not under control by cetecom advanced GmbH.

5.1. General Information

5.1.1. General Data of Main EUT as Declared by Applicant

FCC ID	2AH88-FX2B
--------	------------

Antenna	Integrated Antenna
---------	--------------------

6. Measurement details

6.1. Test methodology

Test method, standard, rule	Description
FCC 47 CFR Part 2	Federal Communications Commission, 47 code of federal regulations, Part 2: General Rules & Regulations for Equipment Authorisation

7. 1.1 General Information

7.1. Notes and Disclaimer

The test results of this test report relate exclusively to the test item specified in this test report. cetecom advanced GmbH does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of cetecom advanced GmbH.

The testing service provided by cetecom advanced GmbH has been rendered under the current "General Terms and Conditions for cetecom advanced GmbH".

cetecom advanced GmbH will not be liable for any loss or damage resulting from false, inaccurate, inappropriate or incomplete product information provided by the customer.

Under no circumstances does the cetecom advanced GmbH test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the cetecom advanced GmbH test report include or imply any product or service warranties from cetecom advanced GmbH, including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by cetecom advanced GmbH.

All rights and remedies regarding vendor's products and services for which cetecom advanced GmbH has prepared this test report shall be provided by the party offering such products or services and not by cetecom advanced GmbH.

In no case this test report can be considered as a Letter of Approval.

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

7.2. References

Guidance	Version	Description
----------	---------	-------------

47 CFR 1.1307		Actions that may have a significant environmental effect, for which Environmental Assessments (EAs) must be prepared.
47 CFR 2.1091		Radiofrequency radiation exposure evaluation: mobile devices.
47 CFR 2.1093		Radiofrequency radiation exposure evaluation: portable devices.

7.3. General RF Exposure Test Exemptions

KDB 447498 D04 Interim General RF Exposure Guidance v01, section 2.1.1:

RF exposure test exemptions provide means to obtain certification without the need of showing data (measurements, or analytical/numerical modeling) to demonstrate compliance. Hereafter, in this context, an RF source is referred to as “exempt RF device” in the sense that it is not required to show data demonstrating compliance to RF exposure limits.

Test exemptions apply for devices used in general population/uncontrolled exposure environments, according to the SAR-based, or MPE-based exemption thresholds. However, it is always possible, especially when the potential for exposure cannot be easily determined, that an RF exposure evaluation may become required according §§ 1.1307(c) and (d).

As detailed in Section 3.1 (see KDB 447498 D04, Section 2.1.2), the 1-mW and SAR-based test exemption conditions are in terms of source-based available maximum time-averaged (matched conducted) output power for all operating configurations, adjusted for tune-up tolerance, and at the minimum test separation distance required for the particular RF exposure scenario under consideration. This minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander. To qualify for SAR test exemption, the test separation distances applied must be fully explained and justified (typically in the SAR measurement, or SAR analysis report, according to KDB Pub. 865664) by showing the actual operating configurations and exposure conditions of the transmitter, and applicable host platform requirements (e.g., KDB Pubs. 648474, 616217, 941225)

When no other RF exposure testing or reporting is required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for SAR test exemption.

If RF exposure testing requirements for a specific device are covered in a KDB publication, those requirements must be satisfied before applying any SAR test exemption provisions. For example, this is the case for handheld PTT two-way radios, handsets, laptops, and tablets, etc. Finally, when 10-g extremity SAR applies, SAR test exemption may be considered by applying a factor of 2.5 to the SAR-based exemption thresholds.

KDB 447498 D04 Interim General RF Exposure Guidance v01, Appendix A:

Frequency-dependent and distance-dependent power thresholds were adopted in Report and Order FCC 19-126. Appendix D of NPRM FCC 13-39 has the derivation of the frequency- dependent and distance-dependent time-averaged power thresholds, below which single portable RF sources operating in the frequency range of 300 MHz (0.3 GHz) to 6 GHz may be exempt from RF evaluation.

The previous power exclusion thresholds for mobile devices in § 2.1091(c) were 1.5 W ERP for transmitters operating at frequencies at or below 1.5 GHz, and 3 W ERP for transmitters operating at frequencies above 1.5 GHz. The new exemption criteria are similar to the previous power exclusion thresholds above 1.5 GHz between 20 cm and 40 cm but consider the potential for whole body resonance at frequencies below 1.5 GHz. The new exemption criteria are less restrictive than the previous power exclusion thresholds between 0.8 GHz and 1.5 GHz, and additionally support extension of these exclusion thresholds down to 0.3 GHz. The new exemption criteria can be used out to a separation distance of 40 cm for mobile and fixed RF sources operating between 300 MHz and 6 GHz. At 40 cm, the MPE-based exemption criteria and the SAR-based exemption criteria are equal.

Generally, the sequence to apply for single portable RF sources includes the following steps: Generally, the sequence to apply for single portable RF sources includes the following steps:

determination of 1 mW blanket exemption under § 1.1307(b)(3)(i)(A)

determination of exemption under the MPE-based § 1.1307(b)(3)(i)(C) if 1) is not met

determination of exemption under the SAR-based § 1.1307(b)(3)(i)(B) if both 1) and 2) are not met.

8. SAR Based Test Exemption

8.1. KDB 447498 D04 Interim General RF Exposure Guidance v01, section 2.1.3:

A more comprehensive exemption, considering a variable power threshold that depends on both the separation distance and power, is provided in § 1.1307(b)(3)(i)(B). This exemption is applicable to the frequency range between 300 MHz and 6 GHz, with test separation distances between 0.5 cm and 40 cm, and for all RF sources in fixed, mobile, and portable device exposure conditions.

Accordingly, a RF source is considered an RF exempt device if its available maximum time- averaged (matched conducted) power or its effective radiated power (ERP), whichever is greater, are below a specified threshold. This exemption threshold was derived based on general population 1-g SAR requirements.

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum time- averaged power or maximum time- averaged ERP, whichever is greater.

If the ERP of a device is not easily determined, such as for a portable device with a small form factor, the applicant may use the available maximum time-averaged power exclusively if the device antenna or radiating structure does not exceed an electrical length of $\lambda/4$.

As for devices with antennas of length greater than $\lambda/4$ where the gain is not well defined, but always less than that of a half-wave dipole (length $\lambda/2$), the available maximum time-averaged power generated by the device may be used in place of the maximum time-averaged ERP, where that value is not known.

The separation distance is the smallest distance from any part of the antenna or radiating structure for all persons, during operation at the applicable ERP. In the case of mobile or portable devices, the separation distance is from the outer housing of the device where it is closest to the antenna.

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula (2).

$$P_{th}(mW) = \begin{cases} ERP_{20cm} \left(\frac{d}{20\text{ cm}} \right)^x, & d \leq 20\text{ cm} \\ ERP_{20cm}, & 20\text{ cm} \leq d \leq 40\text{ cm} \end{cases} \quad (2)$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20cm} \sqrt{f}} \right) \quad (3)$$

and f is in GHz, d is the separation distance (cm), and ERP_{20cm} is per Formula (1). The example values shown in Table 2 are for illustration only.

Table 2: Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)										
		5	10	15	20	25	30	35	40	45	50
	300	39	65	88	110	129	148	166	184	201	217
	450	22	44	67	89	112	135	158	180	203	226
	835	9	25	44	66	90	116	145	175	207	240
	1900	3	12	26	44	66	92	122	157	195	236
	2450	3	10	22	38	59	83	111	143	179	219
	3600	2	8	18	32	49	71	96	125	158	195
	5800	1	6	14	25	40	58	80	106	136	169

8.1.1. Results

customer declared minimum safety distance: 5mm

Technology	Frequency [MHz]		Ref.	Note	Output Power [dBm]		Output Power [mW]		Share of Limit
	f _{min}	f _{max}	#	#	P _{cond.}	ERP	P _{max}	Threshold	%
Bluetooth LE	2402	2480	A	1	3.7	1.6	2	3	86.1%

Values:

Value	Explanation
P _{Cond.}	Maximum conducted output power for the applicable frequency band
P _{Max}	Highest of ERP and P _{Cond.} , in mW
Threshold	SAR-based threshold in mW.
Share of Threshold	P _{max} / Threshold

Value	Explanantion
P _{cond}	Maximum conducted output power for the applicable frequency band
P _{max}	Highest of ERP and P _{cond} in mW
Threshold	SAR based Limit in mW
Share of Limit	P _{max} / Threshold

Referenced Documents:

#	Document	Document type	Additional Information
A		cetecom advanced report	pg 20 , 4.4 dBm EIRP

Notes:

#	Description
1	A band specific duty cycle of 85% has been considered

End of document