

TEST REPORT

Applicant Name: JEM ACCESSORIES INC.
Address: 32 Brunswick Avenue, Edison, New Jersey, United States, 08817
Report Number: 2501P30700E-RF-00
FCC ID: 2AHAS-AHF91014M

Test Standard (s)

FCC PART 15.247

Sample Description

Product Type: Bluetooth FM transmitter with 30W PD USB-C+USB-A
Model No.: AHF9-1014
Multiple Model(s) No.: N/A
Trade Mark: 
Date Received: 2025-01-20
Issue Date: 2025-06-04

Test Result:

Pass▲

▲ In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Allen Bai

Allen Bai
RF Engineer

Approved By:

Jimmy Xiao

Jimmy Xiao
EMC Manager

Note: The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.

This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

Bay Area Compliance Laboratories Corp. (Shenzhen)

5F(B-West), 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, Futian Free Trade Zone, Shenzhen, China

Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	3
GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY.....	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
SUMMARY OF TEST RESULTS.....	8
TEST EQUIPMENT LIST	9
REQUIREMENTS AND TEST PROCEDURES	10
RADIATED EMISSIONS.....	10
20 dB EMISSION BANDWIDTH.....	13
CHANNEL SEPARATION TEST	15
QUANTITY OF HOPPING CHANNEL TEST	16
TIME OF OCCUPANCY (DWELL TIME)	17
PEAK OUTPUT POWER MEASUREMENT	18
BAND EDGES.....	19
ANTENNA REQUIREMENT	20
TEST DATA AND RESULTS.....	21
RADIATED EMISSIONS.....	21
20 dB EMISSION BANDWIDTH.....	41
CHANNEL SEPARATION.....	44
NUMBER OF HOPPING FREQUENCY	46
MAXIMUM CONDUCTED OUTPUT POWER	48
100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	51
TIME OF OCCUPANCY (DWELL TIME)	54
RF EXPOSURE EVALUATION	57
EUT PHOTOGRAPHS.....	58
TEST SETUP PHOTOGRAPHS	59

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	2501P30700E-RF-00	Original Report	2025-06-04

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Frequency Range	2402~2480MHz
Transmit Peak Power	-0.13dBm
Modulation Technique	Bluetooth: GFSK, $\pi/4$ -DQPSK, 8DPSK
Antenna Specification [#]	-3dBi (provided by the applicant)
Input Voltage Range	DC 12-24V
Sample serial number	2XNA-1 for Radiated Emissions Test 2XNA-2 for RF Conducted Test (Assigned by BACL, Shenzhen)
Sample/EUT Status	Good condition
Adapter Information	N/A

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		109.2kHz(k=2, 95% level of confidence)
RF output power, conducted		0.86dB(k=2, 95% level of confidence)
Dwell Time		±1%(k=2, 95% level of confidence)
AC Power Lines Conducted Emissions	9kHz-150kHz	3.63dB(k=2, 95% level of confidence)
	150kHz-30MHz	3.66dB(k=2, 95% level of confidence)
Radiated Emissions	0.009MHz~30MHz	3.60dB(k=2, 95% level of confidence)
	30MHz~200MHz (Horizontal)	5.32dB(k=2, 95% level of confidence)
	30MHz~200MHz (Vertical)	5.43dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Horizontal)	5.77dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Vertical)	5.73dB(k=2, 95% level of confidence)
	1GHz - 6GHz	5.34dB(k=2, 95% level of confidence)
	6GHz - 18GHz	5.40dB(k=2, 95% level of confidence)
	18GHz - 40GHz	5.64dB(k=2, 95% level of confidence)
Temperature		±1°C
Humidity		±1%
Supply voltages		±0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 715558, the FCC Designation No. : CN5045.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	40	2442
1	2403	41	2443
2	2404	42	2444
...	...	...	...
...	...	...	...
36	2438	75	2477
37	2439	76	2478
38	2440	77	2479
39	2441	78	2480

EUT was tested with Channel 0, 39 and 78.

EUT Exercise Software

Exercise Software [#]	Fcc_assist 1.0.2.2.exe
Power Level [#]	10

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
instek	DC Power Supply	GPS-3030DD	EM832096
MIUI	Mobile Phone	Redmi Note 12T Pro	48257/S3T100576
Honor	Mobilephone	CHL-AL00	A6CB023915001290

External I/O Cable


Cable Description	Length (m)	From Port	To
Un-shielded Detachable DC Cable	2.0	EUT	DC Power Supply
Un-shielded Detachable USB Cable	1.0	Mobile Phone	EUT
Un-shielded Detachable USB Cable	1.5	Mobile Phone	EUT

Block Diagram of Test Setup

For Radiated Emissions below 1GHz:



For Radiated Emissions above 1GHz:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.203	Antenna Requirement	Compliant
FCC §15.207(a)	AC Line Conducted Emissions	Not Applicable
FCC §15.205, §15.209, §15.247(d)	Radiated Spurious Emission	Compliant
FCC §15.247(a)(1)	20 dB Emission Bandwidth	Compliant
FCC §15.247(a)(1)	Channel Separation	Compliant
FCC §15.247(a)(1)(iii)	Number of Hopping Frequency	Compliant
FCC §15.247(a)(1)(iii)	Time of Occupancy (dwell time)	Compliant
FCC §15.247(b)(1)	Maximum Conducted Output Power	Compliant
FCC §15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
C63.10 §11.6	Duty Cycle	/
§2.1091	MPE-Based Exemption	Compliant

Not Applicable: The EUT is used in the vehicle condition.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR3	102455	2024/12/04	2025/12/03
Sonoma instrument	Pre-amplifier	310N	186238	2024/05/21	2025/05/20
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2023/07/20	2026/07/19
Unknown	Cable	XH500C	J-10M-A	2024/06/18	2025/06/17
BACL	Active Loop Antenna	1313-1A	4031911	2024/05/14	2027/05/13
Unknown	Cable	2Y194	0735	2024/12/04	2025/12/03
Unknown	Cable	PNG214	1354	2024/12/04	2025/12/03
Audix	EMI Test software	E3	19821b(V9)	NCR	NCR
Rohde&Schwarz	Spectrum Analyzer	FSV40	101605	2025/03/26	2026/03/25
A.H.System	Preamplifier	PAM-0118P	489	2024/11/15	2025/11/14
Schwarzbeck	Horn Antenna	BBHA9120D(1201)	1143	2023/07/26	2026/07/25
Unknown	RF Cable	KMSE	0735	2024/12/06	2025/12/05
Unknown	RF Cable	UFA147	219661	2024/12/06	2025/12/05
Unknown	RF Cable	XH750A-N	J-10M	2024/12/06	2025/12/05
JD	Multiplex Switch Test Control Set	DT7220FSU	DQ77926	2024/06/18	2025/06/17
JD	Multiplex Switch Test Control Set	DT7220SCU	DS79903	2024/09/09	2025/09/08
A.H.System	Pre-amplifier	PAM-1840VH	190	2024/06/18	2025/06/17
Electro-Mechanics Co	Horn Antenna	3116	9510-2270	2023/09/18	2026/09/17
UTIFLEX	RF Cable	NO. 13	232308-001	2024/12/18	2025/12/17
Audix	EMI Test software	E3	191218(V9)	NCR	NCR
RF Conducted Test					
R&S	Spectrum Analyzer	FSU26	200120	2024/12/04	2025/12/03
Unknown	10dB Attenuator	Unknown	F-03-EM190	2024/06/27	2025/06/26

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

REQUIREMENTS AND TEST PROCEDURES


Radiated Emissions

Applicable Standard


FCC §15.205; §15.209; §15.247(d)


EUT Setup

9 kHz-30MHz:



30MHz-1GHz:



Above 1GHz:

The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2020. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement	Detector
9 kHz – 150 kHz	/	/	200 Hz	QP	QP
	300 Hz	1 kHz	/	PK	Peak
150 kHz – 30 MHz	/	/	9 kHz	QP	QP
	10 kHz	30 kHz	/	PK	Peak
30 MHz – 1000 MHz	/	/	120 kHz	QP	QP
	100 kHz	300 kHz	/	PK	Peak
Above 1 GHz	Harmonics				
	1MHz	3 MHz	/	PK	Peak
	Average Emission Level=Peak Emission Level+20*log(Duty cycle)				
	Band Edge & Other Emissions				
	1MHz	3 MHz	/	PK	Peak
	1MHz	≥10 Hz	/	Average	Peak

For Duty cycle measurement:

Use the duty cycle factor correction factor method per 15.35(c).

Duty cycle=On time/100milliseconds, On time= $N_1 \cdot L_1 + N_2 \cdot L_2 + \dots + N_{n-1} \cdot L_{n-1} + N_n \cdot L_n$,

Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulse, etc.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, average detection modes for frequency bands 9–90 kHz and 110–490 kHz, peak and average detection modes for frequencies above 1 GHz.

For 9 kHz-30MHz, the report shall list the six emissions with the smallest margin relative to the limit, for each of the three antenna orientations (parallel, perpendicular, and ground-parallel) unless the margin is greater than 20 dB.

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

All emissions under the average limit and under the noise floor have not recorded in the report.

Factor & Over Limit/Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit/Margin} &= \text{Level/Corrected Amplitude} - \text{Limit} \\ \text{Level / Corrected Amplitude} &= \text{Read Level} + \text{Factor}\end{aligned}$$

20 dB Emission Bandwidth

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.


Test Procedure

Test Method: ANSI C63.10-2020 Clause 6.9.2

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be at least three times RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level. Specific guidance is given in 4.1.6.2.
- d) Steps a) through c) might require iteration to adjust within the specified tolerances.
- e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
- f) Set detection mode to peak and trace mode to max-hold.
- g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
- h) Determine the “-xx dB down amplitude” using $[(\text{reference value}) - \text{xx}]$. Alternatively, this calculation may be made by using the marker-delta function of the instrument.
- i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).

j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The dBc bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.

k) The dBc bandwidth shall be reported by providing spectral plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).



Channel Separation Test

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Test Procedure


Test Method: ANSI C63.10-2020 Clause 7.8.2

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: Wide enough to capture the peaks of two adjacent channels.
- b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c) Video (or average) bandwidth (VBW) $\geq$ RBW.
- d) Sweep: No faster than coupled (auto) time.
- e) Detector function: Peak.
- f) Trace: Max-hold.
- g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Compliance of an EUT with the appropriate regulatory limit shall be determined. A spectral plot of the data shall be included in the test report.

Where the device shares the same channel plan (carrier frequencies and number of channels) across multiple data rates or modulation schemes then the carrier separation need only be measured for one of those modulation schemes or data rates.



Note: The limit is $\frac{2}{3} \times 20$ dB bandwidth

Quantity of Hopping Channel Test

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure


Test Method: ANSI C63.10-2020 Clause 7.8.3

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: The frequency band of operation. Depending on the number of channels the device supports, it could be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c) VBW $\geq$ RBW.
- d) Sweep: No faster than coupled (auto) time.
- e) Detector function: Peak.
- f) Trace: Max-hold.
- g) Allow the trace to stabilize.

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A spectral plot of the data shall be included in the test report.

Where the device shares the same channel plan (carrier frequencies and number of channels) across multiple data rates or modulation schemes then the number of channels need only be measured for one of those modulation schemes or data rates.



Time of Occupancy (Dwell Time)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

Test Method: ANSI C63.10-2020 Clause 7.8.4


Use the following spectrum analyzer settings to determine the dwell time per hop:

- a) Span: Zero span, centered on a hopping channel.
- b) RBW shall be $\leq$ channel spacing and where possible RBW should be set $\gg 1 / T$, where T is the expected transmission time per hop.
- c) Sweep time: Set so that the start of the first transmission and end of the last transmission for the hop are clearly captured. Setting the sweep time to be slightly longer than the hopping period per channel (hopping period = $1/\text{hopping rate}$) should achieve this.
- d) Use a video trigger, where possible with a trigger delay, so that the start of the transmission is clearly observed. The trigger level might need adjustment to reduce the chance of triggering when the system hops on an adjacent channel.
- e) Detector function: Peak.
- f) Trace: Clear-write, single sweep.
- g) Place markers at the start of the first transmission on the channel and at the end of the last transmission. The dwell time per hop is the time between these two markers.

To determine the number of hops on a channel in the regulatory observation period repeat the measurement using a longer sweep time. When the device uses a single hopping sequence the period of measurement should be sufficient to capture at least 2 hops. When the device uses a dynamic hopping sequence, or the sequence varies, the period of measurement may need to capture multiple hops to better determine the average time of occupancy. Count the number of hops on the channel across the sweep time.

The average number of hops on the same channel within the regulatory observation period is calculated from the number of hops on the channel divided by the spectrum analyzer sweep time multiplied by the regulatory observation period. For example, if three hops are counted with an analyzer sweep time of 500 ms and the regulatory observation period is 10 s, then the number of hops in that ten seconds is $3 / 0.5 \times 10$, or 60 hops.

The average time of occupancy is calculated by multiplying the dwell time per hop by the number of hops in the observation period.



Peak Output Power Measurement

Applicable Standard


According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

Test Method: ANSI C63.10-2020 Clause 7.8.5

This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. Frequency hopping shall be disabled for this test. Use the following spectrum analyzer settings:

- a) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
- b) RBW > 20 dB bandwidth of the emission being measured.
- c) VBW $\geq$ RBW.
- d) Sweep: No faster than coupled (auto) time.
- e) Detector function: Peak.
- f) Trace: Max-hold.
- g) Allow trace to stabilize.
- h) Use the marker-to-peak function to set the marker to the peak of the emission.
- i) The indicated level is the peak output power, after any corrections for external attenuators and cables.
- j) A spectral plot of the test results and setup description shall be included in the test report.



Note: A short RF cable with low cable loss connected to the EUT antenna port, which was provided by client or lab, the cable loss was added with offset into test equipment, the total offset consists of attenuator and/or RF cable loss

Band Edges


Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

Test Method: ANSI C63.10-2020 Clause 7.8.7.2 & Clause 6.10

- 1) Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band-edge, as well as any modulation products that fall outside of the authorized band of operation.
- 2) Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW/RBW})]$ below the reference level. Specific guidance is given in 4.1.6.2.
- 3) Attenuation: Auto (at least 10 dB preferred).
- 4) Sweep time: No faster than coupled (auto) time.
- 5) Resolution bandwidth: 100 kHz.
- 6) Video bandwidth: 300 kHz.
- 7) Detector: Peak.
- 8) Trace: Max-hold.



ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

Antenna Connector Construction

The EUT has an internal antenna arrangement, which was permanently attached, the antenna gain[#] is -3dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliant

TEST DATA AND RESULTS


Radiated Emissions

Environmental Conditions

Temperature (°C)	23.7~25.6	Relative Humidity (%)	41~54
ATM Pressure (kPa):	101.3	Test engineer:	Anson Su &Visen Wu
Test date:	2025/02/20~2025/04/17		
EUT operation mode:	Below 1GHz: Transmitting(Maximum output power mode, EDR (8DPSK) High Channel) Above 1GHz: Transmitting(Maximum output power mode, EDR (8DPSK))		
Note:	1. For the radiated spurious emission below 30MHz, only the worst case (parallel) was recorded. 2. For the radiated spurious emission below 1GHz, When the test result of peak was less than the limit of QP/Average more than 6dB, just peak value were recorded. 3. After pre-scan in the X, Y and Z axes of orientation, the worst case z-axis of orientation were recorded.		

Below 1GHz:


9kHz-150kHz



Site : Chamber A
Condition : 3m
Project Number : 2501P30700E-RF
Test Mode : BT Transmitting
Detector: Peak RBW/VBW: 0.3/1kHz
Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.01	32.29	22.73	55.02	127.55	-72.53	Peak
2	0.02	30.72	19.47	50.19	122.34	-72.15	Peak
3	0.04	27.80	19.55	47.35	116.33	-68.98	Peak
4	0.07	24.84	19.56	44.40	111.27	-66.87	Peak
5	0.09	22.45	18.02	40.47	108.18	-67.71	Peak
6	0.13	19.98	16.06	36.04	105.05	-69.01	Peak


150kHz-30MHz



Site : Chamber A
Condition : 3m
Project Number : 2501P30700E-RF
Test Mode : BT Transmitting
Detector: Peak RBW/VBW: 10/30kHz
Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.59	5.27	49.99	55.26	72.13	-16.87	Peak
2	1.18	0.69	49.42	50.11	65.98	-15.87	Peak
3	1.76	-0.92	45.69	44.77	69.54	-24.77	Peak
4	2.36	-1.80	42.85	41.05	69.54	-28.49	Peak
5	2.91	-2.10	40.65	38.55	69.54	-30.99	Peak
6	3.49	-2.42	37.74	35.32	69.54	-34.22	Peak

30MHz-1GHz_Horizontal




Site : Chamber A
 Condition : 3m Horizontal
 Project Number : 2501P30700E-RF
 Test Mode : BT Transmitting
 Detector: Peak RBW/VBW: 100/300kHz
 Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	167.97	-13.00	53.80	40.80	43.50	-2.70	QP
2	180.02	-13.65	50.30	36.65	43.50	-6.85	QP
3	192.00	-14.01	52.99	38.98	43.50	-4.52	QP
4	203.97	-13.36	54.10	40.74	43.50	-2.76	QP
5	216.02	-14.20	55.09	40.89	46.00	-5.11	QP
6	227.99	-13.94	56.79	42.85	46.00	-3.15	QP
7	239.99	-13.32	53.30	39.98	46.00	-6.02	QP
8	251.95	-13.08	55.09	42.01	46.00	-3.99	QP
9	264.05	-12.35	56.79	44.44	46.00	-1.56	QP
10	276.00	-11.32	52.10	40.78	46.00	-5.22	QP
11	287.99	-11.22	55.50	44.28	46.00	-1.72	QP
12	299.97	-11.20	52.40	41.20	46.00	-4.80	QP
13	312.04	-11.00	55.50	44.50	46.00	-1.50	QP
14	324.03	-10.70	53.40	42.70	46.00	-3.30	QP
15	336.04	-10.50	54.09	43.59	46.00	-2.41	QP

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
16	348.03	-10.21	52.40	42.19	46.00	-3.81	QP
17	359.97	-9.89	54.40	44.51	46.00	-1.49	QP
18	359.97	-9.89	54.70	44.81	46.00	-1.19	QP
19	372.00	-9.43	53.00	43.57	46.00	-2.43	QP
20	384.10	-9.04	53.70	44.66	46.00	-1.34	QP
21	396.07	-8.60	51.71	43.11	46.00	-2.89	QP
22	408.05	-8.20	52.10	43.90	46.00	-2.10	QP
23	431.98	-7.78	50.40	42.62	46.00	-3.38	QP

30MHz-1GHz_Vertical



Site : Chamber A
 Condition : 3m Vertical
 Project Number : 2501P30700E-RF
 Test Mode : BT Transmitting
 Detector: Peak RBW/VBW: 100/300kHz
 Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	167.97	-13.00	54.50	41.50	43.50	-2.00	QP
2	180.02	-13.65	50.40	36.75	43.50	-6.75	QP
3	192.00	-14.01	52.69	38.68	43.50	-4.82	QP
4	203.97	-13.36	54.00	40.64	43.50	-2.86	QP
5	216.02	-14.20	55.69	41.49	46.00	-4.51	QP
6	227.99	-13.94	56.59	42.65	46.00	-3.35	QP
7	239.99	-13.32	53.70	40.38	46.00	-5.62	QP
8	251.95	-13.08	53.39	40.31	46.00	-5.69	QP
9	264.05	-12.35	53.69	41.34	46.00	-4.66	QP
10	276.00	-11.32	51.70	40.38	46.00	-5.62	QP
11	287.99	-11.22	52.40	41.18	46.00	-4.82	QP
12	312.04	-11.00	52.78	41.78	46.00	-4.22	QP
13	336.04	-10.50	53.86	43.36	46.00	-2.64	QP
14	359.97	-9.89	52.00	42.11	46.00	-3.89	QP
15	384.10	-9.04	52.80	43.76	46.00	-2.24	QP

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
16	408.05	-8.20	51.00	42.80	46.00	-3.20	QP
17	431.98	-7.78	47.50	39.72	46.00	-6.28	QP
18	456.11	-7.24	46.60	39.36	46.00	-6.64	QP
19	480.11	-6.34	46.81	40.47	46.00	-5.53	QP
20	504.04	-5.77	45.50	39.73	46.00	-6.27	QP
21	600.11	-5.28	45.40	40.12	46.00	-5.88	QP
22	623.98	-4.70	43.80	39.10	46.00	-6.90	QP

Above 1GHz:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave					
8DPSK							
Low Channel							
4804	55.01	PK	H	-7.79	47.22	74	-26.78
4804	52.70	PK	V	-7.79	44.91	74	-29.09
Middle Channel							
4882	54.25	PK	H	-7.58	46.67	74	-27.33
4882	53.85	PK	V	-7.58	46.27	74	-27.73
High Channel							
4960	54.23	PK	H	-7.56	46.67	74	-27.33
4960	52.68	PK	V	-7.56	45.12	74	-28.88

Note:

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor


Corrected Amplitude = Factor + Reading

Margin = Corrected. Amplitude - Limit

The other spurious emission which is in the noise floor level was not recorded. The test result of peak was less than the limit of average, so just peak values were recorded.

Test plots


Left Band edge_Horizontal



Condition : Horizontal
 Project No. : 2501P30700E-RF
 Tester : Visen Wu
 Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
 Note : BT_3DH5_2402

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2379.084	-10.96	62.47	51.51	74.00	-22.49	Peak
2	2390.000	-10.98	60.03	49.05	74.00	-24.95	Peak


Left Band edge_Vertical



Condition : Vertical
Project No. : 2501P30700E-RF
Tester : Visen Wu
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : BT_3DH5_2402

		Read		Limit	Over	Remark
Freq Factor		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2360.571	-10.91	62.24	51.33	74.00	-22.67 Peak
2	2390.000	-10.98	60.38	49.40	74.00	-24.60 Peak


Right Band edge_Horizontal



Condition : Horizontal
Project No. : 2501P30700E-RF
Tester : Visen Wu
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : BT_3DH5_2480

		Read		Limit	Over	Remark
Freq		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 2483.500	-10.97	61.20	50.23	74.00	-23.77	Peak
2 2494.329	-10.99	63.20	52.21	74.00	-21.79	Peak

Right Band edge_Vertical




Condition : Vertical
Project No. : 2501P30700E-RF
Tester : Visen Wu
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : BT_3DH5_2480

		Read		Limit	Over	Remark
Freq Factor		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	60.39	49.42	74.00	-24.58 Peak
2	2487.196	-10.97	63.14	52.17	74.00	-21.83 Peak

1-25GHz (Listed with the worst harmonic margin test plot)


1-4GHz_Horizontal



Condition : Horizontal
Project No. : 2501P30700E-RF
Tester : Visen Wu
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : BT_3DH5_2402

Freq		Read		Limit	Over	Remark
Factor		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	3902.488	-9.81	56.58	46.77	74.00	-27.23 Peak


1-4GHz_Vertical



Condition : Vertical
Project No. : 2501P30700E-RF
Tester : Visen Wu
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : BT_3DH5_2402

Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	3638.455	-9.87	56.43	46.56	74.00	-27.44	Peak


4-18GHz_Horizontal_Peak



Condition : Horizontal
Project No. : 2501P30700E-RF
Tester : Visen Wu
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : BT_3DH5_2402

Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4804.000	-7.79	55.01	47.22	74.00	-26.78	Peak
2	17984.250	13.12	48.42	61.54	74.00	-12.46	Peak


4-18GHz_Horizontal_Average



Condition : Horizontal
 Project No. : 2501P30700E-RF
 Tester : Visen Wu
 Spectrum setting: Average reading: RBW:1MHz VBW:1kHz Detector:Peak
 Note : BT_3DH5_2402

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	18000.000	13.20	34.60	47.80	54.00	-6.20	Average


4-18GHz_Vertical_Peak



Condition : Vertical
Project No. : 2501P30700E-RF
Tester : Visen Wu
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : BT_3DH5_2402

Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4804.000	-7.79	52.70	44.91	74.00	-29.09	Peak
2	17957.990	13.00	48.12	61.12	74.00	-12.88	Peak


4-18GHz_Vertical_Average



Condition : Vertical
Project No. : 2501P30700E-RF
Tester : Visen Wu
Spectrum setting: Average reading: RBW:1MHz VBW:1kHz Detector:Peak
Note : BT_3DH5_2402

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	17998.250	13.19	34.70	47.89	54.00	-6.11	Average


18-25GHz_Horizontal



Condition : Horizontal
Project No. : 2501P30700E-RF
Tester : Visen Wu
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : BT_3DH5_2402

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 19242.150	15.28	36.52	51.80	74.00	-22.20	Peak

18-25GHz_Vertical



Condition : Vertical
Project No. : 2501P30700E-RF
Tester : Visen Wu
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : BT_3DH5_2402

Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 19233.150		15.29	36.99	52.28	74.00	-21.72	Peak

20 dB Emission Bandwidth

Test Information:


Sample No.:	2XNA-2	Test Date:	2025/02/15
Test Site:	RF	Test Mode:	Transmitting
Tester:	Rainbow Zhu	Test Result:	N/A

Environmental Conditions:


Temperature: (°C)	25.6	Relative Humidity: (%)	58	ATM Pressure: (kPa)	101.1
----------------------	------	------------------------------	----	------------------------	-------

Test Data:


Mode	Channel	Result (MHz)
DH1	Low Channel	0.893
	Middle Channel	0.889
	High Channel	0.889
2DH1	Low Channel	1.256
	Middle Channel	1.256
	High Channel	1.256
3DH1	Low Channel	1.249
	Middle Channel	1.245
	High Channel	1.249




ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 15:14:55




ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 15:17:30




ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 15:18:49




ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 15:22:21




ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 15:24:55




ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 15:26:31



ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 15:31:06



ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 15:34:42



ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 15:36:46

Channel Separation**Test Information:**

Sample No.:	2XNA-2	Test Date:	2025/02/15
Test Site:	RF	Test Mode:	Transmitting
Tester:	Rainbow Zhu	Test Result:	Pass


Environmental Conditions:

Temperature: (°C)	25.6	Relative Humidity: (%)	58	ATM Pressure: (kPa)	101.1
-----------------------------	------	----------------------------------	----	-------------------------------	-------

Test Data:

Mode	Channel	Result (MHz)	Limit (MHz)	Verdict
DH1	Middle Channel	1.003	0.837	Pass

Note: Only the BDR (GFSK) mode result is reported since EDR ($\pi/4$ -DQPSK) and EDR (8DPSK) modes have the exact same channel plan, and the limit is the maximum 20dB bandwidth *2/3.



ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 17:23:27

Number of Hopping Frequency

Test Information:


Sample No.:	2XNA-2	Test Date:	2025/02/15
Test Site:	RF	Test Mode:	Transmitting
Tester:	Rainbow Zhu	Test Result:	Pass

Environmental Conditions:


Temperature: (°C)	25.6	Relative Humidity: (%)	58	ATM Pressure: (kPa)	101.1
----------------------	------	------------------------------	----	------------------------	-------

Test Data:


Mode	Channel	Result	Limit	Verdict
DH1	Hopping Channel	79	15	Pass
2DH1	Hopping Channel	79	15	Pass
3DH1	Hopping Channel	79	15	Pass



ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 16:47:23



ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 16:58:33



ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 17:12:35

Maximum Conducted Output Power

Test Information:


Sample No.:	2XNA-2	Test Date:	2025/02/15
Test Site:	RF	Test Mode:	Transmitting
Tester:	Rainbow Zhu	Test Result:	Pass

Environmental Conditions:


Temperature: (°C)	25.6	Relative Humidity: (%)	58	ATM Pressure: (kPa)	101.1
----------------------	------	------------------------------	----	------------------------	-------

Test Data:


Mode	Test Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)	Verdict
DH1	2402	-1.79	21.00	Pass
	2441	-1.53	21.00	Pass
	2480	-1.35	21.00	Pass
2DH1	2402	-1.06	21.00	Pass
	2441	-0.86	21.00	Pass
	2480	-0.61	21.00	Pass
3DH1	2402	-0.56	21.00	Pass
	2441	-0.30	21.00	Pass
	2480	-0.13	21.00	Pass




ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 15:16:34




ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 15:17:57




ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 15:21:12




ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 15:24:00




ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 15:25:22




ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 15:29:04



ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 15:32:45



ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 15:35:26



ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 15:39:12


100 kHz Bandwidth of Frequency Band Edge

Test Information:


Sample No.:	2XNA-2	Test Date:	2025/06/04
Test Site:	RF	Test Mode:	Transmitting
Tester:	Rainbow Zhu	Test Result:	Pass

Environmental Conditions:


Temperature: (°C)	24.6	Relative Humidity: (%)	52	ATM Pressure: (kPa)	101.1
----------------------	------	------------------------------	----	------------------------	-------




ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 4.JUN.2025 20:29:34




ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 4.JUN.2025 20:31:57




ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 4.JUN.2025 17:58:33




ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 4.JUN.2025 18:00:28




ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 4.JUN.2025 20:34:16




ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 4.JUN.2025 20:40:58




ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 4.JUN.2025 18:02:54




ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 4.JUN.2025 18:05:20




ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 4.JUN.2025 20:44:26



ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 4.JUN.2025 20:46:42



ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 4.JUN.2025 18:14:50



ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 4.JUN.2025 18:18:30

Time of Occupancy (dwell time)**Test Information:**

Sample No.:	2XNA-2	Test Date:	2025/02/15
Test Site:	RF	Test Mode:	Transmitting
Tester:	Rainbow Zhu	Test Result:	Pass

Environmental Conditions:


Temperature: (°C)	25.6	Relative Humidity: (%)	58	ATM Pressure: (kPa)	101.1
-----------------------------	------	----------------------------------	----	-------------------------------	-------

Test Data:

Mode	Channel	Pulse width (ms)	Dwell time (s)	Limit (s)	Verdict
DH1	Hopping Channel	0.383	0.123	0.400	Pass
DH3	Hopping Channel	1.646	0.263	0.400	Pass
DH5	Hopping Channel	2.913	0.311	0.400	Pass
2DH1	Hopping Channel	0.391	0.125	0.400	Pass
2DH3	Hopping Channel	1.654	0.265	0.400	Pass
2DH5	Hopping Channel	2.919	0.311	0.400	Pass
3DH1	Hopping Channel	0.393	0.126	0.400	Pass
3DH3	Hopping Channel	1.650	0.264	0.400	Pass
3DH5	Hopping Channel	2.925	0.312	0.400	Pass


Note:**DH1:Dwell time=Pulse width (ms) × (1600/2/79) ×31.6 s****DH3:Dwell time=Pulse width (ms) × (1600/4/79) ×31.6 s****DH5:Dwell time=Pulse width (ms) × (1600/6/79) ×31.6 s****2DH1: Dwell time=Pulse width (ms) × (1600/2/79) ×31.6 s****2DH3: Dwell time=Pulse width (ms) × (1600/4/79) ×31.6 s****2DH5: Dwell time=Pulse width (ms) × (1600/6/79) ×31.6 s****3DH1: Dwell time=Pulse width (ms) × (1600/2/79) ×31.6 s****3DH3: Dwell time=Pulse width (ms) × (1600/4/79) ×31.6 s****3DH5: Dwell time=Pulse width (ms) × (1600/6/79) ×31.6 s**

DH1_Hopping




ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 15:49:19

DH3_Hopping




ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 15:50:36

DH5_Hopping




ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 15:53:26

2DH1_Hopping




ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 15:54:53

2DH3_Hopping




ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 15:57:11

2DH5_Hopping




ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 15:58:23

3DH1_Hopping




ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 16:00:09

3DH3_Hopping



ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 16:01:41

3DH5_Hopping



ProjectNo.:2501P30700E-RF Tester:Rainbow Zhu
Date: 15.FEB.2025 16:02:58

RF EXPOSURE EVALUATION

MPE-Based Exemption

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 v01 Interim General RF Exposure Guidance

MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power(ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(3)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.

R is the minimum separation distance in meters

f = frequency in MHz

Result

Mode	Frequency (MHz)	Tune up conducted power [#] (dBm)	Antenna Gain [#]		ERP		Evaluation Distance (m)	ERP Limit (W)
			(dBi)	(dBd)	(dBm)	(mW)		
Bluetooth	2402-2480	0.5	-3	-5.15	-4.65	0.34	0.2	0.768

Note: The tune up conducted power and antenna gain was declared by the applicant.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant

EUT PHOTOGRAPHS

Please refer to the attachment 2501P30700E-RF External photo and 2501P30700E-RF Internal photo.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2501P30700E-RF Test Setup photo.

******* END OF REPORT *******