

TEST REPORT

Applicant Name: JEM ACCESSORIES INC.
Address: 32 Brunswick Avenue, Edison, New Jersey, United States, 08817
Report Number: 2601R26613E-RF-00B
FCC ID: 2AHAS-EOP11005J

Test Standard (s)

FCC PART 15.407

Sample Description

Product Type: Smart RGB-MWT Light Socket Cam
Model No.: EOP1-1005-WHT
Multiple Model(s) No.: EOP1-1005, EOP1-1005-BLK
Trade Mark: Energizer **Energizer**[®]
Date Received: 2026-04-01
Issue Date: 2026-05-21

Test Result:	Pass▲
--------------	-------

▲ In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

GaLa Liu

GaLa Liu
RF Engineer

Approved By:

Nancy Wang

Nancy Wang
RF Supervisor

Note: The information marked * is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.
This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.
This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.
This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

Bay Area Compliance Laboratories Corp. (Shenzhen)

5F(B-West), 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China
Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	3
GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION	6
SUMMARY OF TEST RESULTS	10
TEST EQUIPMENT LIST	11
REQUIREMENTS AND TEST PROCEDURES	13
AC LINE CONDUCTED EMISSIONS	13
UNDESIRABLE EMISSION	15
EMISSION BANDWIDTH & 99% OCCUPIED BANDWIDTH	19
CONDUCTED TRANSMITTER OUTPUT POWER	21
POWER SPECTRAL DENSITY	22
DUTY CYCLE	23
RF EXPOSURE EVALUATION	24
ANTENNA REQUIREMENT	26
TEST DATA AND RESULTS	27
AC LINE CONDUCTED EMISSIONS	27
UNDESIRABLE EMISSION	30
RF CONDUCTED DATA	142
Emission Bandwidth	143
99% Occupied Bandwidth	150
Maximum Conducted Output Power	157
Power Spectral Density	159
Duty Cycle	166
EUT PHOTOGRAPHS	167
TEST SETUP PHOTOGRAPHS	168

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	2601R26613E-RF-00B	Original Report	2026-05-21

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	Smart RGB-MWT Light Socket Cam
Test Model	EOP1-1005-WHT
Multiple Model(s)	EOP1-1005, EOP1-1005-BLK
Frequency Range	5150-5250MHz; 5250-5350MHz; 5470-5725MHz; 5725-5850MHz
Mode	802.11a/n20
Maximum Conducted Average Output Power	5150-5250MHz: 17.05dBm; 5250-5350MHz: 16.17dBm 5470-5725MHz: 15.55dBm; 5725-5850MHz: 15.36dBm
Modulation Technique	OFDM
Antenna Specification[#]	5150-5250MHz: 1.45dBi; 5250-5350MHz: 1.51dBi 5470-5725MHz: 1.45dBi; 5725-5850MHz: 1.49dBi (provided by the applicant)
Voltage Range	AC120V
Sample serial number	3JBW-1 for AC Line Conducted Emissions and Radiated Emissions Test 3JBW-2 for RF Conducted Test (Assigned by BACL, Shenzhen)
Sample/EUT Status	Good condition
Adapter Information	N/A
Note: The Multiple models are electrically identical with the test model except for model number, sales channels and color. Please refer to the declaration letter [#] for more detail, which was provided by manufacturer.	

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and E of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart E, section 15.203, 15.205, 15.207, 15.209 and 15.407 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB789033 D02 General U-NII Test Procedures New Rules v02r01.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		52.29kHz(k=1.96, 95% level of confidence)
RF Frequency		81.235Hz(k=1.96, 95% level of confidence)
RF output power, conducted		1.57dB(k=1.96, 95% level of confidence)
Power Spectral Density		2.09dB(k=1.96, 95% level of confidence)
Conducted Spurious Emission		2.48dB(k=1.96, 95% level of confidence)
AC Power Lines Conducted Emissions	9kHz~150 kHz	3.46dB(k=2, 95% level of confidence)
	150 kHz ~30MHz	3.72dB(k=2, 95% level of confidence)
Radiated Emissions	0.009MHz~30MHz	3.66dB(k=2, 95% level of confidence)
	30MHz~1000MHz (Horizontal)	5.10dB(k=2, 95% level of confidence)
	30MHz~1000MHz (Vertical)	6.28dB(k=2, 95% level of confidence)
	1GHz - 6GHz	6.18dB(k=2, 95% level of confidence)
	6GHz - 18GHz	6.62dB(k=2, 95% level of confidence)
	18GHz - 40GHz	6.66dB(k=2, 95% level of confidence)
Temperature		$\pm 0.4^{\circ}\text{C}$
Humidity		$\pm 2\%$
Supply voltages		DC $\pm 0.4\%$; AC $\pm 1\%$

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West), 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, test firm registration No.: 715558, the FCC Designation No. : CN5045.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode, which was provided by manufacturer.

For 5150-5250MHz Band, 4 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220
40	5200	48	5240

For 802.11a/n20 mode: channel 36, 40, 48 were tested;

For 5250-5350MHz Band, 4 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
52	5260	60	5300
56	5280	64	5320

For 802.11a, 802.11n20 mode: channel 52, 60, 64 were tested;

For 5470-5725MHz Band, 12 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
100	5500	124	5620
104	5520	128	5640
108	5540	132	5660
112	5560	136	5680
116	5580	140	5700
120	5600	144	5720

For 802.11a, 802.11n20 mode: channel 100, 120, 140, 144 were tested;

For 5725-5850MHz Band, 5 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	161	5805
153	5765	165	5825
157	5785	/	/

For 802.11a/n20 mode: channel 149, 157, 165 were tested;

EUT Exercise Software

Exercise Software [#]		Secure LRT		
5150-5250 MHz Band				
Mode	Test Channels	Test Frequency (MHz)	Data rate	Power Level [#]
802.11a	Low	5180	6Mbps	18
	Middle	5200	6Mbps	18
	High	5240	6Mbps	18
802.11n ht20	Low	5180	MCS0	18
	Middle	5200	MCS0	18
	High	5240	MCS0	18
5250-5350 MHz Band				
Mode	Test Channels	Test Frequency (MHz)	Data rate	Power Level [#]
802.11a	Low	5260	6Mbps	18
	Middle	5300	6Mbps	18
	High	5320	6Mbps	18
802.11n ht20	Low	5260	MCS0	18
	Middle	5300	MCS0	18
	High	5320	MCS0	18
5470-5725 MHz Band				
Mode	Test Channels	Test Frequency (MHz)	Data rate	Power Level [#]
802.11a	Low	5500	6Mbps	17
	Middle	5600	6Mbps	17
	High	5700	6Mbps	17
	Cross	5720	6Mbps	17
802.11n ht20	Low	5500	MCS0	17
	Middle	5600	MCS0	17
	High	5700	MCS0	17
	Cross	5720	MCS0	17
5725-5850 MHz Band				
Mode	Test Channels	Test Frequency (MHz)	Data rate	Power Level [#]
802.11a	Low	5745	6Mbps	17
	Middle	5785	6Mbps	17
	High	5825	6Mbps	17
802.11n ht20	Low	5745	MCS0	17

	Middle	5785	MCS0	17
	High	5825	MCS0	17

Note: The worst-case data rates are determined to be as above for each mode based upon investigation by measuring the power and PSD across all data rates bandwidths, and modulations.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Unknown	Receptacle	Unknown	Unknown
Unknown	Socket	Unknown	Unknown
Unknown	TF Card	Unknown	Unknown

External I/O Cable


Cable Description	Length (m)	From Port	To
Un-shielding Un-detachable AC Cable	1.2	Receptacle	AC Mains
Un-shielding Un-detachable AC Cable	1.2	Socket	Receptacle/LISN

Block Diagram of Test Setup


For AC Line Conducted Emissions:



For Radiated Emissions below 1GHz:



For Radiated Emissions above 1GHz:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307 (b) & §2.1091	MPE-Based Exemption	Compliant
§15.203	Antenna Requirement	Compliant
§15.207(a)	AC Line Conducted Emissions	Compliant
§15.205& §15.209 &§15.407(b)	Undesirable Emission& Restricted Bands	Compliant
§15.407(a) (e)	Emission Bandwidth & 99% Occupied Bandwidth	Compliant
§15.407(a)	Conducted Transmitter Output Power	Compliant
§15.407 (a)	Power Spectral Density	Compliant
§15.407 (h)	Transmit Power Control (TPC)	Not Applicable
§15.407 (h)	Dynamic Frequency Selection (DFS)	Compliant*
C63.10 §11.6	Duty Cycle	/

Compliant*: Please refer to the DFS report 2601R26613E-RF-00C.

Not Applicable: For 5250-5350MHz/5470-5725MHz, the maximum EIRP is 17.68 dBm $\leq$ 27dBm (500mW).

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted emission Test					
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2025/09/01	2026/08/31
Rohde & Schwarz	LISN	ENV216	101613	2025/09/18	2026/09/17
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2025/09/18	2026/09/17
Unknown	CE Cable	Unknown	UF A210B-1-0720-504504	2025/09/18	2026/09/17
Audix	EMI Test software	E3	191218 V9(c)	NCR	NCR
Radiated Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR3	102455	2025/09/01	2026/08/31
Sonoma instrument	Pre-amplifier	310 N	186238	2025/09/08	2026/09/07
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2023/07/20	2026/07/19
Unknown	Chamber A Cable	Cable A1	Cable A1	2025/09/08	2026/09/07
Unknown	Chamber A Cable	Cable A2	Cable A2	2025/09/08	2026/09/07
BACL	Active Loop Antenna	1313-1A	4031911	2024/05/14	2027/05/13
Unknown	Chamber A Cable	Cable A3	Cable A3	2025/09/08	2026/09/07
Unknown	Chamber A Cable	Cable A4	Cable A4	2025/09/08	2026/09/07
Audix	EMI Test software	E3	19821b(V9)	NCR	NCR
TDK	Chamber	Chamber A	2#	2023/07/12	2026/07/11
Rohde & Schwarz	Spectrum Analyzer	FSV40	101605	2025/09/01	2026/08/31
A.H.System	Preamplifier	PAM-0118P	489	2025/09/08	2026/09/07
Schwarzbeck	Horn Antenna	BBHA9120D (1201)	1143	2023/07/26	2026/07/25
Unknown	Chamber B Cable	Cable B1	Cable B1	2025/09/08	2026/09/07
Unknown	Chamber B Cable	Cable B2	Cable B2	2025/09/08	2026/09/07
Unknown	Chamber B Cable	Cable B3	Cable B3	2025/09/08	2026/09/07
JD	Filter Switch Unit	DT7220FSU	DS79906	2025/08/12	2026/08/11
JD	Multiplex Switch Test Control Set	DT7220SCU	DS79903	2025/08/12	2026/08/11
A.H.System	Pre-amplifier	PAM-1840VH	190	2025/09/08	2026/09/07
Electro-Mechanics Co	Horn Antenna	3116	9510-2270	2023/09/18	2026/09/17

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Unknown	Chamber B Cable	Cable B4	Cable B4	2025/09/17	2026/09/16
Unknown	Chamber B Cable	Cable B5	Cable B5	2025/09/17	2026/09/16
Audix	EMI Test software	E3	191218 V9(c)	NCR	NCR
TDK	Chamber	Chamber B	1#	2023/07/14	2026/07/13
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSV40	101942	2025/09/01	2026/08/31
JD	JD Auto Test software	NA	1.0.0.3769	NCR	NCR
ANRITSU	Microwave peak power sensor	MA24418A	12622	2025/09/01	2026/08/31
Unknown	10dB Attenuator	Unknown	F-03-EM224	2025/06/26	2026/06/25

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).


REQUIREMENTS AND TEST PROCEDURES

AC Line Conducted Emissions

Applicable Standard

FCC §15.207

EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and Average detection mode.

Factor & Over Limit Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$

Note: The term "cable loss" refers to the combination of a cable and a 10dB transient limiter (attenuator).

Undesirable Emission

Applicable Standard

FCC §15.407 (b); §15.209; §15.205;


(b) Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:



- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209.

EUT Setup

9 kHz-30MHz:



30MHz-1GHz:**Above 1 GHz:**

The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC 15.209 and FCC 15.407 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9 kHz-1GHz:

Frequency Range	RBW	Video B/W	IF B/W	Measurement	Detector
9 kHz – 150 kHz	/	/	200 Hz	QP	QP
	300 Hz	1 kHz	/	PK	Peak
150 kHz – 30 MHz	/	/	9 kHz	QP	QP
	10 kHz	30 kHz	/	PK	Peak
30 MHz – 1000 MHz	/	/	120 kHz	QP	QP
	120 kHz	500 kHz	/	PK	Peak

1-40GHz:

Pre-scan

Measurement	Duty cycle	RBW	Video B/W	Detector
PK	Any	1MHz	3 MHz	Peak
AV	>98%	1MHz	1 kHz	Peak
	<98%	1MHz	>1/Ton, not less than 1kHz	Peak

Final measurement for emission identified during pre-scan

Measurement	Duty cycle	RBW	Video B/W	Detector
PK	Any	1MHz	3 MHz	Peak
AV	>98%	1MHz	10 Hz	Peak
	<98%	1MHz	$\geq 1/Ton$	Peak

Note: Ton is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

Radiated Spurious Emission

During the radiated emission test, the adapter was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all the installation combinations.

All final data was recorded in Quasi-peak detection mode except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, average detection modes for frequency bands 9–90 kHz and 110–490 kHz, peak and average detection modes for frequencies above 1 GHz.

For 9 kHz-30MHz, the report shall list the six emissions with the smallest margin relative to the limit, for each of the three antenna orientations (parallel, perpendicular, and ground-parallel) unless the margin is greater than 20 dB.

According to ANSI C63.10-2020,9.2.1: For field strength measurements made at other than the distance specified by the limit, extrapolate the measured field strength to the field strength at the distance specified by the limit using an inverse distance correction factor (20 dB/decade of distance)

$$E_{\text{SpecLimit}} = E_{\text{Meas}} + 20 \log \left(\frac{d_{\text{Meas}}}{d_{\text{SpecLimit}}} \right)$$

where

$E_{\text{SpecLimit}}$	is the field strength of the emission at the distance specified by the limit, in dBμV/m
E_{Meas}	is the field strength of the emission at the measurement distance, in dBμV/m
d_{Meas}	is the measurement distance, in m
$d_{\text{SpecLimit}}$	is the distance specified by the limit, in m

So the extrapolation factor of 1m is $20 \cdot \log(1/3) = -9.5$ dB, for 18-40GHz range, the limit of 1m distance was added by 9.5dB from limit of 3m to compared with the result measurement at 1m distance.

Factor & Over Limit/Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit} &= \text{Level} - \text{Limit}; \text{Margin} = \text{Limit} - \text{Corrected Amplitude} \\ \text{Level / Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

Emission Bandwidth & 99% Occupied Bandwidth

Applicable Standard

The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Test Procedure

According to ANSI C63.10-2020 Section 12.5.1 & 12.5.2 & 12.5.3

12.5.1 Emission bandwidth for the band 5.725 GHz to 5.85 GHz

The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max-hold.
- e) Sweep = No faster than coupled (auto) time.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

12.5.2 Emission bandwidth for all other bands

The procedure for this method is as follows:


- a) Set RBW = shall be in the range of 1% to 5% of the emission bandwidth.
- b) Set the VBW $>$ RBW.
- c) Detector = peak.
- d) Trace mode = max-hold.
- e) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is in the range of 1% to 5%.

12.5.3 Occupied bandwidth

See 6.9.3 for the measurement procedure for OBW.

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be at least three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.6.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max-hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h) The occupied bandwidth shall be reported by providing spectral plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).



Note: Offset (10.5dB) = Attenuator (10dB) + Cable loss (0.5dB)

Conducted Transmitter Output Power

Applicable Standard

For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple colocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure

According to ANSI C63.10-2020 Section 12.4.3.2 Method PM-G

- a. Place the EUT on a bench and set it in transmitting mode.
- b. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.



Note 1: A short RF cable with low cable loss connected to the EUT antenna port, which was provided by client or lab, the cable loss was add with offset into test equipment, the total offset consists of attenuator and/or RF cable and/or power splitter loss

Note 2: Offset (10.5dB) = Attenuator (10dB) + Cable loss (0.5dB)

Power Spectral Density


For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple colocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure

According to ANSI C63.10-2020 Clause 12.6 Method SA-2 should be applied



Note 1: A short RF cable with low cable loss connected to the EUT antenna port, which was provided by client or lab, the cable loss was add with offset into test equipment, the total offset consists of attenuator and/or RF cable and/or power splitter loss

Note 2: Offset (10.5dB) = Attenuator (10dB) + Cable loss (0.5dB)


Duty Cycle

Test Procedure

According to ANSI C63.10-2020 Section 12.2

Measurements of duty cycle and transmission duration shall be performed using one of the following techniques:

- a) A diode detector and an oscilloscope that together have a sufficiently short response time to permit accurate measurements of the ON and OFF times of the transmitted signal.
- b) The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:
 - 1) Set the center frequency of the instrument to the center frequency of the transmission.
 - 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
 - 3) Set $VBW \geq RBW$. Set detector = peak or average.
 - 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)



Note: Offset (10.5dB) = Attenuator (10dB) + Cable loss (0.5dB)

RF EXPOSURE EVALUATION

MPE-Based Exemption

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 v01 Interim General RF Exposure Guidance

MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power(ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(3)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.

R is the minimum separation distance in meters

f = frequency in MHz

For multiple RF sources: Multiple RF sources are exempt if:

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation:

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Result

Mode	Frequency (MHz)	Tune up conducted power [#] (dBm)	Antenna Gain#		ERP		Evaluation Distance (m)	ERP Limit (W)
			(dBi)	(dBd)	(dBm)	(W)		
2.4G Wi-Fi	2412-2462	25	2.97	0.82	25.82	0.382	0.2	0.768
5G Wi-Fi	5180-5240	18	1.45	-0.70	17.30	0.054	0.2	0.768
	5260-5320	17	1.51	-0.64	16.36	0.043	0.2	0.768
	5500-5720	16	1.45	-0.70	15.30	0.034	0.2	0.768
	5745-5825	16	1.49	-0.66	15.34	0.034	0.2	0.768

Note: The tune up conducted power and antenna gain was declared by the applicant.

Note: 2.4G and 5G WiFi cannot synchronize transmission.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant

ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

Antenna Connector Construction

The EUT has a PIFA antenna arrangement which was permanently attached, fulfill the requirement of this section. Please refer to EUT photos. Please refer to the EUT photos.

Frequency Range	Antenna Type	Antenna Gain [#]	Impedance
5150-5250MH	PIFA	1.45dBi	50Ω
5250-5350MHz	PIFA	1.51dBi	50Ω
5470-5725MHz	PIFA	1.45dBi	50Ω
5725-5850MHz	PIFA	1.49dBi	50Ω

Result: Compliant


TEST DATA AND RESULTS

AC Line Conducted Emissions

Environmental Conditions

Temperature (°C)	25.2	Relative Humidity (%)	48
ATM Pressure (kPa)	100.5	Test engineer	Macy.shi
Test date	2026.4.24		
EUT operation mode	Transmitting (Maximum output power mode, Band 1 802.11a Low Channel)		

AC 120V 60 Hz, Line



Condition: Line


Project : 2601R26613E-RF

tester : Macy.shi Note:5G WIFI Transmitting

Setting : RBW:9kHz

	Freq	Read Level	Level	LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.154	1.54	21.16	9.60	10.02	55.79	-34.63	Average
2	0.154	20.21	39.83	9.60	10.02	65.79	-25.96	QP
3	0.175	-1.96	17.67	9.60	10.03	54.74	-37.07	Average
4	0.175	16.39	36.02	9.60	10.03	64.74	-28.72	QP
5	0.247	-1.36	18.27	9.60	10.03	51.87	-33.60	Average
6	0.247	15.56	35.19	9.60	10.03	61.87	-26.68	QP
7	0.439	13.44	33.07	9.60	10.03	47.09	-14.02	Average
8	0.439	25.37	45.00	9.60	10.03	57.09	-12.09	QP
9	0.739	-2.45	17.19	9.60	10.04	46.00	-28.81	Average
10	0.739	11.37	31.01	9.60	10.04	56.00	-24.99	QP
11	1.008	-3.67	16.15	9.60	10.22	46.00	-29.85	Average
12	1.008	8.28	28.10	9.60	10.22	56.00	-27.90	QP

AC 120V 60 Hz, Neutral



Condition: neutral

Project : 2601R26613E-RF

tester : Macy.shi Note: 5G WIFI Transmitting

Setting : RBW:9kHz


	Freq	Read Level	LISN Level	Cable Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.154	3.43	23.05	9.60	10.02	55.78	-32.73	Average
2	0.154	20.70	40.32	9.60	10.02	65.78	-25.46	QP
3	0.219	-2.15	17.48	9.60	10.03	52.87	-35.39	Average
4	0.219	15.93	35.56	9.60	10.03	62.87	-27.31	QP
5	0.410	5.63	25.26	9.60	10.03	47.64	-22.38	Average
6	0.410	18.31	37.94	9.60	10.03	57.64	-19.70	QP
7	0.441	14.92	34.55	9.60	10.03	47.04	-12.49	Average
8	0.441	25.39	45.02	9.60	10.03	57.04	-12.02	QP
9	0.621	-6.48	13.16	9.60	10.04	46.00	-32.84	Average
10	0.621	4.68	24.32	9.60	10.04	56.00	-31.68	QP
11	0.762	-2.83	16.81	9.60	10.04	46.00	-29.19	Average
12	0.762	8.84	28.48	9.60	10.04	56.00	-27.52	QP

Undesirable Emission**Environmental Conditions**

Temperature (°C)	24.1-24.6	Relative Humidity (%)	47-50
ATM Pressure (kPa):	100.5-101.4	Test engineer:	Anson Su & Zenos Qiao
Test date:	2026.04.24-2026.04.26		
EUT operation mode:	Below 1GHz: Transmitting (Maximum output power mode, Band 1 802.11a Low Channel) Above 1GHz: Transmitting		
Note:	1. For the radiated spurious emission below 30MHz, only the worst case (parallel) was recorded. 2. For the radiated spurious emission below 1GHz, When the test result of peak was less than the limit of QP/Average more than 6dB, just peak value were recorded. 3. The orientation of the EUT has been pre adjusted to allow for measuring the maximum emission of the EUT.		

Below 1GHz:


9kHz-150kHz



Site : Chamber A
Condition : 3m
Project Number : 2601R26613E-RF
Test Mode : 5G WIFI Transmitting
Detector: Peak RBW/VBW: 0.3/1kHz
Tester : Anson Su

	Freq Factor		Read		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	Limit	
1	0.010	32.28	23.49	55.77	127.53	-71.76	Peak
2	0.018	30.69	22.04	52.73	122.28	-69.55	Peak
3	0.029	28.71	21.04	49.75	118.39	-68.64	Peak
4	0.041	27.33	21.01	48.34	115.31	-66.97	Peak
5	0.066	24.84	20.28	45.12	111.27	-66.15	Peak
6	0.117	20.99	18.66	39.65	106.23	-66.58	Peak


150kHz-30MHz



Site : Chamber A
Condition : 3m
Project Number : 2601R26613E-RF
Test Mode : 5G WIFI Transmitting
Detector: Peak RBW/VBW: 10/30kHz
Tester : Anson Su

	Freq	Factor	Read		Limit	Over	Remark
			Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.494	6.51	33.70	40.21	73.72	-33.51	Peak
2	0.718	3.71	33.70	37.41	70.41	-33.00	Peak
3	0.848	2.34	33.86	36.20	68.93	-32.73	Peak
4	0.981	1.35	32.91	34.26	67.65	-33.39	Peak
5	1.349	0.22	32.72	32.94	64.82	-31.88	Peak
6	1.612	-0.51	32.09	31.58	63.24	-31.66	Peak


30MHz-1GHz_Horizontal



Site : Chamber A
Condition : 3m Horizontal
Project Number : 2601R26613E-RF
Test Mode : 5G WIFI Transmitting
Detector: Peak RBW/VBW: 120/500kHz
Tester : Anson Su

	Freq Factor		Read Level		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	Line	Limit	
1	148.25	-12.70	42.97	30.27	43.50	-13.23	Peak
2	225.01	-14.44	46.45	32.01	46.00	-13.99	Peak
3	275.04	-11.76	48.28	36.52	46.00	-9.48	Peak
4	325.03	-11.08	48.63	37.55	46.00	-8.45	Peak
5	375.12	-9.75	49.67	39.92	46.00	-6.08	Peak
6	725.21	-3.61	43.53	39.92	46.00	-6.08	Peak

30MHz-1GHz_Vertical



Site : Chamber A
Condition : 3m Vertical
Project Number : 2601R26613E-RF
Test Mode : 5G WIFI Transmitting
Detector: Peak RBW/VBW: 120/500kHz
Tester : Anson Su

	Freq Factor		Read		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	Line	Limit	
1	74.98	-17.97	42.35	24.38	40.00	-15.62	Peak
2	125.01	-11.50	40.64	29.14	43.50	-14.36	Peak
3	148.25	-12.70	42.85	30.15	43.50	-13.35	Peak
4	375.12	-9.75	43.92	34.17	46.00	-11.83	Peak
5	575.13	-5.79	44.67	38.88	46.00	-7.12	Peak
6	725.21	-3.61	39.11	35.50	46.00	-10.50	Peak

Above 1GHz:**5150-5250 MHz**

Frequency (MHz)	Reading (dBμV)	PK/Ave	Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
802.11a							
Low Channel							
10360	53.39	PK	H	2.48	55.87	68.2	-12.33
10360	53.05	PK	V	2.48	55.53	68.2	-12.67
Middle Channel							
10400	53.76	PK	H	2.47	56.23	68.2	-11.97
10400	53.43	PK	V	2.47	55.9	68.2	-12.3
High Channel							
10480	54.12	PK	H	2.19	56.31	68.2	-11.89
10480	53.81	PK	V	2.19	56	68.2	-12.2
802.11n20							
Low Channel							
10360	53.17	PK	H	2.48	55.65	68.2	-12.55
10360	52.84	PK	V	2.48	55.32	68.2	-12.88
Middle Channel							
10400	53.55	PK	H	2.47	56.02	68.2	-12.18
10400	53.21	PK	V	2.47	55.68	68.2	-12.52
High Channel							
10480	53.9	PK	H	2.19	56.09	68.2	-12.11
10480	53.58	PK	V	2.19	55.77	68.2	-12.43

5250-5350MHz

Frequency (MHz)	Reading (dB μ V)	PK/Ave	Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
802.11a							
Low Channel							
10520	53.25	PK	H	2.13	55.38	68.2	-12.82
10520	52.93	PK	V	2.13	55.06	68.2	-13.14
Middle Channel							
10600	53.61	PK	H	2.2	55.81	68.2	-12.39
10600	53.28	PK	V	2.2	55.48	68.2	-12.72
High Channel							
10640	54.08	PK	H	2.57	56.65	74	-17.35
10640	41.35	AV	H	2.57	43.92	54	-10.08
10640	53.73	PK	V	2.57	56.3	74	-17.7
10640	41.12	AV	V	2.57	43.69	54	-10.31
802.11n20							
Low Channel							
10520	53.13	PK	H	2.13	55.26	68.2	-12.94
10520	52.79	PK	V	2.13	54.92	68.2	-13.28
Middle Channel							
10600	53.48	PK	H	2.2	55.68	68.2	-12.52
10600	53.15	PK	V	2.2	55.35	68.2	-12.85
High Channel							
10640	53.94	PK	H	2.57	56.51	74	-17.49
10640	41.19	AV	H	2.57	43.76	54	-10.24
10640	53.6	PK	V	2.57	56.17	74	-17.83
10640	40.98	AV	V	2.57	43.55	54	-10.45

5470-5725MHz

Frequency (MHz)	Reading (dB μ V)	PK/Ave	Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
802.11a							
Low Channel							
11000	53.65	PK	H	4.26	57.91	74	-16.09
11000	40.58	AV	H	4.26	44.84	54	-9.16
11000	53.29	PK	V	4.26	57.55	74	-16.45
11000	40.36	AV	V	4.26	44.62	54	-9.38
Middle Channel							
11200	53.86	PK	H	3.61	57.47	74	-16.53
11200	40.65	AV	H	3.61	44.26	54	-9.74
11200	53.53	PK	V	3.61	57.14	74	-16.86
11200	40.42	AV	V	3.61	44.03	54	-9.97
High Channel							
11400	54.47	PK	H	3.31	57.78	74	-16.22
11400	41.05	AV	H	3.31	44.36	54	-9.64
11400	54.12	PK	V	3.31	57.43	74	-16.57
11400	40.83	AV	V	3.31	44.14	54	-9.86
Cross Channel							
11440	54.23	PK	H	3.46	57.69	74	-16.31
11440	40.87	AV	H	3.46	44.33	54	-9.67
11440	53.9	PK	V	3.46	57.36	74	-16.64
11440	40.64	AV	V	3.46	44.1	54	-9.9

Frequency (MHz)	Reading (dB μ V)	PK/Ave	Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
802.11n20							
Low Channel							
11000	53.54	PK	H	4.26	57.8	74	-16.2
11000	40.39	AV	H	4.26	44.65	54	-9.35
11000	53.22	PK	V	4.26	57.48	74	-16.52
11000	40.18	AV	V	4.26	44.44	54	-9.56
Middle Channel							
11200	53.73	PK	H	3.61	57.34	74	-16.66
11200	40.46	AV	H	3.61	44.07	54	-9.93
11200	53.39	PK	V	3.61	57	74	-17
11200	40.24	AV	V	3.61	43.85	54	-10.15
High Channel							
11400	54.24	PK	H	3.31	57.55	74	-16.45
11400	40.93	AV	H	3.31	44.24	54	-9.76
11400	53.89	PK	V	3.31	57.2	74	-16.8
11400	40.72	AV	V	3.31	44.03	54	-9.97
Cross Channel							
11440	54.05	PK	H	3.46	57.51	74	-16.49
11440	40.68	AV	H	3.46	44.14	54	-9.86
11440	54.71	PK	V	3.46	58.17	74	-15.83
11440	40.47	AV	V	3.46	43.93	54	-10.07

5725-5850MHz

Frequency (MHz)	Reading (dBμV)	PK/Ave	Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
802.11a							
Low Channel							
11490	53.21	PK	H	3.64	56.85	74	-17.15
11490	40.19	AV	H	3.64	43.83	54	-10.17
11490	52.87	PK	V	3.64	56.51	74	-17.49
11490	39.98	AV	V	3.64	43.62	54	-10.38
Middle Channel							
11570	53.72	PK	H	3.34	57.06	74	-16.94
11570	40.66	AV	H	3.34	44	54	-10
11570	53.39	PK	V	3.34	56.73	74	-17.27
11570	40.43	AV	V	3.34	43.77	54	-10.23
High Channel							
11650	54.36	PK	H	3.46	57.82	74	-16.18
11650	40.91	AV	H	3.46	44.37	54	-9.63
11650	54.02	PK	V	3.46	57.48	74	-16.52
11650	40.69	AV	V	3.46	44.15	54	-9.85
802.11n20							
Low Channel							
11490	53.08	PK	H	3.64	56.72	74	-17.28
11490	40.05	AV	H	3.64	43.69	54	-10.31
11490	52.73	PK	V	3.64	56.37	74	-17.63
11490	39.82	AV	V	3.64	43.46	54	-10.54
Middle Channel							
11570	53.59	PK	H	3.34	56.93	74	-17.07
11570	40.52	AV	H	3.34	43.86	54	-10.14
11570	53.25	PK	V	3.34	56.59	74	-17.41
11570	40.31	AV	V	3.34	43.65	54	-10.35
High Channel							
11650	54.17	PK	H	3.46	57.63	74	-16.37
11650	40.8	AV	H	3.46	44.26	54	-9.74
11650	53.84	PK	V	3.46	57.3	74	-16.7
11650	40.58	AV	V	3.46	44.04	54	-9.96

Note:

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor


Corrected Amplitude = Factor + Reading

Margin = Corrected. Amplitude - Limit

The other spurious emission which is in the noise floor level was not recorded.

Test plots:**1-18GHz (Listed with the worst case test plot)**


1-7GHz_Horizontal_802.11a_5240MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-A-5240

	Freq	Factor	Read		Limit	Over	Remark
			Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6446.500	-1.16	49.47	48.31	68.20	-19.89	Peak


1-7GHz_Vertical_802.11a_5240MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-A-5240

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6578.500	-1.30	49.30	48.00	68.20	-20.20	Peak


7-18GHz_Horizontal_Peak_802.11a_5240MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-A-5240

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 10480.000	2.19	54.12	56.31	68.20	-11.89 Peak
2 17990.380	13.21	48.88	62.09	74.00	-11.91 Peak


7-18GHz_Horizontal_Average_802.11a_5240MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band1-A-5240

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 17972.500	13.13	34.39	47.52	54.00	-6.48 Average


7-18GHz_Vertical_Peak_802.11a_5240MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-A-5240

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	10480.000	2.19	53.81	56.00	68.20	-12.20	Peak
2	17925.750	12.89	48.78	61.67	74.00	-12.33	Peak


7-18GHz_Vertical_Average_802.11a_5240MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band1-A-5240

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17998.630	13.25	34.41	47.66	54.00	-6.34	Average


1-7GHz_Horizontal_802.11n20_5240MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-N20-5240

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 6390.250	-1.31	49.05	47.74	68.20	-20.46 Peak


1-7GHz_Vertical_802.11n20_5240MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-N20-5240

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6443.500	-1.18	49.48	48.30	68.20	-19.90	Peak


7-18GHz_Horizontal_Peak_802.11n20_5240MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-N20-5240

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 10480.000	2.19	53.90	56.09	68.20	-12.11 Peak
2 17945.000	12.97	48.55	61.52	74.00	-12.48 Peak


7-18GHz_Horizontal_Average_802.11n20_5240MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band1-N20-5240

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 17991.750	13.22	34.23	47.45	54.00	-6.55 Average


7-18GHz_Vertical_Peak_802.11n20_5240MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-N20-5240

Freq	Factor	Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 10480.000	2.19	53.58	55.77	68.20	-12.43	Peak
2 17980.750	13.17	48.52	61.69	74.00	-12.31	Peak


7-18GHz_Vertical_Average_802.11n20_5240MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band1-N20-5240

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 17998.630	13.26	34.23	47.49	54.00	-6.51 Peak


1-7GHz_Horizontal_802.11a_5320MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-A-5320

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 6549.250	-1.24	49.91	48.67	68.20	-19.53 Peak


1-7GHz_Vertical_802.11a_5320MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-A-5320

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 6484.750	-1.20	49.04	47.84	68.20	-20.36 Peak


7-18GHz_Horizontal_Peak_802.11a_5320MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-A-5320

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 10640.000	2.57	54.08	56.65	74.00	-17.35 Peak
2 17995.880	13.24	49.19	62.43	74.00	-11.57 Peak


7-18GHz_Horizontal_Average_802.11a_5320MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band2-A-5320

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 10640.000	2.57	41.35	43.92	54.00	-10.08 Average
2 17967.000	13.09	34.35	47.44	54.00	-6.56 Average


7-18GHz_Vertical_Peak_802.11a_5320MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-A-5320

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 10640.000	2.57	53.73	56.30	74.00	-17.70 Peak
2 17896.880	12.69	49.36	62.05	74.00	-11.95 Peak


7-18GHz_Vertical_Average_802.11a_5320MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band2-A-5320

Freq	Factor	Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 10640.000	2.57	41.12	43.69	54.00	-10.31	Average
2 17989.000	13.20	34.68	47.88	54.00	-6.12	Average


1-7GHz_Horizontal_802.11n20_5320MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-N20-5320

	Freq	Factor	Read		Limit	Over	Remark
			Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6516.250	-1.22	49.60	48.38	68.20	-19.82	Peak


1-7GHz_Vertical_802.11n20_5320MHz



Condition : Vertical
 Project No. : 2601R26613E-RF
 Tester : Zenos Qiao
 Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
 Note : 5GWiFi-Band2-N20-5320

	Freq	Factor	Read		Limit	Over	Remark
			Level	Level			
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6505.750	-1.21	50.10	48.89	68.20	-19.31	Peak


7-18GHz_Horizontal_Peak_802.11n20_5320MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-N20-5320

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 10640.000	2.57	53.94	56.51	74.00	-17.49	Peak
2 17982.130	13.16	48.95	62.11	74.00	-11.89	Peak


7-18GHz_Horizontal_Average_802.11n20_5320MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band2-N20-5320

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 10640.000	2.57	41.19	43.76	54.00	-10.24	Average
2 17995.880	13.24	34.58	47.82	54.00	-6.18	Average


7-18GHz_Vertical_Peak_802.11n20_5320MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-N20-5320

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	10640.000	2.57	53.60	56.17	74.00	-17.83	Peak
2	17962.880	13.07	48.85	61.92	74.00	-12.08	Peak


7-18GHz_Vertical_Average_802.11n20_5320MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band2-N20-5320

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 10640.000	2.57	40.98	43.55	54.00	-10.45	Average
2 17987.630	13.19	34.37	47.56	54.00	-6.44	Average


1-7GHz_Horizontal_802.11a_5500MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-A-5500

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 6459.250	-1.18	49.87	48.69	68.20	-19.51 Peak


1-7GHz_Vertical_802.11a_5500MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-A-5500

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6484.000	-1.20	49.20	48.00	68.20	-20.20	Peak


7-18GHz_Horizontal_Peak_802.11a_5500MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-A-5500

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 11000.000	4.26	53.65	57.91	74.00	-16.09 Peak
2 17916.130	12.83	49.40	62.23	74.00	-11.77 Peak


7-18GHz_Horizontal_Average_802.11a_5500MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band3-A-5500

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 11000.000	4.26	40.58	44.84	54.00	-9.16	Average
2 17989.000	13.20	34.23	47.43	54.00	-6.57	Average


7-18GHz_Vertical_Peak_802.11a_5500MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-A-5500

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 11000.000	4.26	53.29	57.55	74.00	-16.45 Peak
2 17956.000	13.04	48.30	61.34	74.00	-12.66 Peak


7-18GHz_Vertical_Average_802.11a_5500MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band3-A-5500

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 11000.000	4.26	40.36	44.62	54.00	-9.38 Average
2 17993.130	13.23	34.29	47.52	54.00	-6.48 Average


1-7GHz_Horizontal_802.11n20_5500MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-N20-5500

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6745.750	-1.44	49.99	48.55	68.20	-19.65	Peak


1-7GHz_Vertical_802.11n20_5500MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-N20-5500

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 6478.000	-1.18	49.13	47.95	68.20	-20.25 Peak


7-18GHz_Horizontal_Peak_802.11n20_5500MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-N20-5500

Freq Factor		Read		Limit	Over	Remark
MHz	dB/m	Level	Level	Line	Limit	
		dBuV	dBuV/m	dBuV/m	dB	
1 11000.000	4.26	53.54	57.80	74.00	-16.20	Peak
2 17980.750	13.17	48.74	61.91	74.00	-12.09	Peak


7-18GHz_Horizontal_Average_802.11n20_5500MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band3-N20-5500

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 11000.000	4.26	40.39	44.65	54.00	-9.35 Average
2 17989.000	13.20	34.18	47.38	54.00	-6.62 Average


7-18GHz_Vertical_Peak_802.11n20_5500MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-N20-5500

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 11000.000	4.26	53.22	57.48	74.00	-16.52 Peak
2 17920.250	12.85	48.89	61.74	74.00	-12.26 Peak


7-18GHz_Vertical_Average_802.11n20_5500MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band3-N20-5500

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 11000.000	4.26	40.18	44.44	54.00	-9.56	Average
2 17998.630	13.25	34.19	47.44	54.00	-6.56	Average


1-7GHz_Horizontal_802.11a_5825MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-A-5825

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 6445.000	-1.17	49.09	47.92	68.20	-20.28 Peak


1-7GHz_Vertical_802.11a_5825MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-A-5825

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	6871.000	-1.33	49.13	47.80	68.20	-20.40	Peak


7-18GHz_Horizontal_Peak_802.11a_5825MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-A-5825

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	11650.000	3.46	54.36	57.82	74.00	-16.18	Peak
2	17925.750	12.89	48.03	60.92	74.00	-13.08	Peak


7-18GHz_Horizontal_Average_802.11a_5825MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band4-A-5825

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 11650.000	3.46	40.91	44.37	54.00	-9.63 Average
2 17984.880	13.18	34.25	47.43	54.00	-6.57 Average


7-18GHz_Vertical_Peak_802.11a_5825MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-A-5825

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	
1	11650.000	3.46	54.02	57.48	74.00 -16.52 Peak
2	17927.130	12.89	48.61	61.50	74.00 -12.50 Peak


7-18GHz_Vertical_Average_802.11a_5825MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band4-A-5825

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 11650.000	3.46	40.69	44.15	54.00	-9.85	Average
2 17989.000	13.20	34.37	47.57	54.00	-6.43	Average


1-7GHz_Horizontal_802.11n20_5825MHz



Condition : Horizontal
 Project No. : 2601R26613E-RF
 Tester : Zenos Qiao
 Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
 Note : 5GWiFi-Band4-N20-5825

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 6462.250	-1.18	50.41	49.23	68.20	-18.97	Peak


1-7GHz_Vertical_802.11n20_5825MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-N20-5825

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 6489.250	-1.20	49.17	47.97	68.20	-20.23 Peak


7-18GHz_Horizontal_Peak_802.11n20_5825MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-N20-5825

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 11650.000	3.46	54.17	57.63	74.00	-16.37 Peak
2 17907.880	12.80	48.99	61.79	74.00	-12.21 Peak


7-18GHz_Horizontal_Average_802.11n20_5825MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band4-N20-5825

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 11650.000	3.46	40.80	44.26	54.00	-9.74	Average
2 17991.750	13.22	34.37	47.59	54.00	-6.41	Average


7-18GHz_Vertical_Peak_802.11n20_5825MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-N20-5825

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1 11650.000	3.46	53.84	57.30	74.00	-16.70 Peak
2 17951.880	13.02	49.01	62.03	74.00	-11.97 Peak

7-18GHz_Vertical_Average_802.11n20_5825MHz




Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band4-N20-5825

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 11650.000	3.46	40.58	44.04	54.00	-9.96	Average
2 17990.380	13.21	34.31	47.52	54.00	-6.48	Average

18-40GHz (Only Listed with the worst harmonic margin test plot)


18-40GHz_Horizontal_802.11a_5500MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-A-5500

Freq Factor		Read Level		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 39298.750	23.90	37.80	61.70	83.50	-21.80	Peak

18-40GHz_Vertical_802.11a_5500MHz




Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-A-5500

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 39323.500	23.90	37.52	61.42	83.50	-22.08	Peak

Band Edge


Left Band edge Horizontal Peak 802.11a 5180MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-A-5180

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5149.442	-7.45	73.09	65.64	74.00	-8.36 Peak
2	5150.000	-7.45	69.69	62.24	74.00	-11.76 Peak


Left Band edge_Horizontal_Average_802.11a_5180MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band1-A-5180

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 5149.813	-7.45	57.85	50.40	54.00	-3.60	Average
2 5150.000	-7.45	57.59	50.14	54.00	-3.86	Average


Left Band edge_Vertical_Peak_802.11a_5180MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-A-5180

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 5149.998	-7.45	70.27	62.82	74.00	-11.18	Peak
2 5150.000	-7.45	69.86	62.41	74.00	-11.59	Peak


Left Band edge_Vertical_Average_802.11a_5180MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band1-A-5180

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5149.720	-7.45	56.38	48.93	54.00	-5.07 Average
2	5150.000	-7.45	55.05	47.60	54.00	-6.40 Average


Right Band edge_Horizontal_Peak_802.11a_5240MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-A-5240

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5350.000	-6.76	63.23	56.47	74.00	-17.53 Peak
2	5458.538	-6.28	66.52	60.24	74.00	-13.76 Peak


Right Band edge_Horizontal_Average_802.11a_5240MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band1-A-5240

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 5350.000	-6.76	53.25	46.49	54.00	-7.51	Average
2 5456.620	-6.28	54.20	47.92	54.00	-6.08	Average


Right Band edge_Vertical_Peak_802.11a_5240MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-A-5240

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	-6.76	64.35	57.59	74.00	-16.41 Peak
2	5457.140	-6.28	67.24	60.96	74.00	-13.04 Peak


Right Band edge_Vertical_Average_802.11a_5240MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band1-A-5240

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	-6.76	53.03	46.27	54.00	-7.73 Average
2	5456.652	-6.28	54.12	47.84	54.00	-6.16 Average


Left Band edge_Horizontal_Peak_802.11n20_5180MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-N20-5180

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5149.998	-7.45	72.25	64.80	74.00	-9.20 Peak
2	5150.000	-7.45	71.81	64.36	74.00	-9.64 Peak


Left Band edge_Horizontal_Average_802.11n20_5180MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band1-N20-5180

Freq Factor		Read		Limit	Over	Remark
MHz	dB/m	Level	Level	Line	Limit	
		dBuV	dBuV/m	dBuV/m	dB	
1	5149.905	-7.45	58.44	50.99	54.00	-3.01 Average
2	5150.000	-7.45	58.29	50.84	54.00	-3.16 Average


Left Band edge_Vertical_Peak_802.11n20_5180MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-N20-5180

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 5149.905	-7.45	68.83	61.38	74.00	-12.62	Peak
2 5150.000	-7.45	63.66	56.21	74.00	-17.79	Peak


Left Band edge_Vertical_Average_802.11n20_5180MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band1-N20-5180

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5149.998	-7.45	56.15	48.70	54.00	-5.30 Average
2	5150.000	-7.45	56.09	48.64	54.00	-5.36 Average


Right Band edge_Horizontal_Peak_802.11n20_5240MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-N20-5240

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 5350.000	-6.76	63.09	56.33	74.00	-17.67	Peak
2 5420.025	-6.49	66.38	59.89	74.00	-14.11	Peak


Right Band edge_Horizontal_Average_802.11n20_5240MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band1-N20-5240

			Read	Limit	Over	Remark	
	Freq	Factor	Level	Level	Line		Limit
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5350.000	-6.76	53.31	46.55	54.00	-7.45	Average
2	5445.505	-6.33	53.91	47.58	54.00	-6.42	Average


Right Band edge_Vertical_Peak_802.11n20_5240MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band1-N20-5240

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5350.000	-6.76	63.63	56.87	74.00	-17.13 Peak
2	5435.592	-6.40	66.12	59.72	74.00	-14.28 Peak


Right Band edge_Vertical_Average_802.11n20_5240MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band1-N20-5240

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	-6.76	53.15	46.39	54.00	-7.61 Average
2	5453.013	-6.29	54.02	47.73	54.00	-6.27 Average


Left Band edge_Horizontal_Peak_802.11a_5260MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-A-5260

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 5048.375	-7.29	65.25	57.96	74.00	-16.04	Peak
2 5150.000	-7.45	63.16	55.71	74.00	-18.29	Peak


Left Band edge_Horizontal_Average_802.11a_5260MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band2-A-5260

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5055.857	-7.31	53.74	46.43	54.00	-7.57 Average
2	5150.000	-7.45	53.87	46.42	54.00	-7.58 Average


Left Band edge_Vertical_Peak_802.11a_5260MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-A-5260

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5051.348	-7.29	65.60	58.31	74.00	-15.69 Peak
2	5150.000	-7.45	64.37	56.92	74.00	-17.08 Peak


Left Band edge_Vertical_Average_802.11a_5260MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band2-A-5260

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	4894.728	-7.61	53.94	46.33	54.00	-7.67 Average
2	5150.000	-7.45	52.97	45.52	54.00	-8.48 Average


Right Band edge_Horizontal_Peak_802.11a_5320MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-A-5320

Freq Factor		Read		Limit	Over	Remark
MHz	dB/m	Level	Level	Line	Limit	
		dBuV	dBuV/m	dBuV/m	dB	
1	5350.000	-6.76	64.55	57.79	74.00	-16.21 Peak
2	5350.942	-6.76	67.56	60.80	74.00	-13.20 Peak


Right Band edge_Horizontal_Average_802.11a_5320MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band2-A-5320

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 5350.000	-6.76	54.02	47.26	54.00	-6.74	Average
2 5353.462	-6.75	54.62	47.87	54.00	-6.13	Average


Right Band edge_Vertical_Peak_802.11a_5320MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-A-5320

Freq Factor		Read		Limit	Over	Remark
MHz	dB/m	Level	Level	Line	Limit	
		dBuV	dBuV/m	dBuV/m	dB	
1	5350.000	-6.76	64.80	58.04	74.00	-15.96 Peak
2	5434.710	-6.40	66.23	59.83	74.00	-14.17 Peak


Right Band edge_Vertical_Average_802.11a_5320MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band2-A-5320

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	-6.76	53.14	46.38	54.00	-7.62 Average
2	5454.083	-6.29	54.26	47.97	54.00	-6.03 Average


Left Band edge_Horizontal_Peak_802.11n20_5260MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-N20-5260

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5131.810	-7.46	65.29	57.83	74.00	-16.17 Peak
2	5150.000	-7.45	64.84	57.39	74.00	-16.61 Peak


Left Band edge_Horizontal_Average_802.11n20_5260MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band2-N20-5260

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5038.740	-7.29	53.85	46.56	54.00	-7.44 Average
2	5150.000	-7.45	52.95	45.50	54.00	-8.50 Average


Left Band edge_Vertical_Peak_802.11n20_5260MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-N20-5260

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 4890.627	-7.63	65.54	57.91	74.00	-16.09	Peak
2 5150.000	-7.45	63.40	55.95	74.00	-18.05	Peak


Left Band edge_Vertical_Average_802.11n20_5260MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band2-N20-5260

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5037.408	-7.28	53.43	46.15	54.00	-7.85 Average
2	5150.000	-7.45	53.26	45.81	54.00	-8.19 Average


Right Band edge_Horizontal_Peak_802.11n20_5320MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-N20-5320

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	-6.76	69.37	62.61	74.00	-11.39 Peak
2	5350.065	-6.76	69.87	63.11	74.00	-10.89 Peak


Right Band edge_Horizontal_Average_802.11n20_532MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band2-N20-5320

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5350.000	-6.76	54.29	47.53	54.00	-6.47	Average
2	5457.930	-6.28	54.19	47.91	54.00	-6.09	Average


Right Band edge_Vertical_Peak_802.11n20_5320MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band2-N20-5320

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 5350.000	-6.76	63.56	56.80	74.00	-17.20 Peak
2 5456.018	-6.28	66.19	59.91	74.00	-14.09 Peak


Right Band edge_Vertical_Average_802.11n20_5320MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band2-N20-5320

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5350.000	-6.76	53.20	46.44	54.00	-7.56 Average
2	5455.748	-6.28	54.00	47.72	54.00	-6.28 Average


Left Band edge_Horizontal_Peak_802.11a_5500MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-A-5500

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 5460.000	-6.26	64.24	57.98	74.00	-16.02	Peak
2 5469.756	-6.22	70.16	63.94	68.20	-4.26	Peak
3 5470.000	-6.22	65.95	59.73	68.20	-8.47	Peak


Left Band edge_Horizontal_Average_802.11a_5500MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band3-A-5500

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 5460.000	-6.26	53.77	47.51	54.00	-6.49 Average


Left Band edge_Vertical_Peak_802.11a_5500MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-A-5500

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 5460.000	-6.26	64.08	57.82	74.00	-16.18 Peak
2 5469.006	-6.23	67.03	60.80	68.20	-7.40 Peak
3 5470.000	-6.22	64.74	58.52	68.20	-9.68 Peak


Left Band edge_Vertical_Average_802.11a_5500MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band3-A-5500

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 5460.000	-6.26	53.56	47.30	54.00	-6.70	Average


Right Band edge_Horizontal_Peak_802.11a_5700MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-A-5700

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5725.000	-5.54	68.02	62.48	68.20	-5.72 Peak
2	5725.219	-5.53	70.41	64.88	68.20	-3.32 Peak


Right Band edge_Vertical_Peak_802.11a_5700MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-A-5700

	Freq Factor		Read		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5725.000	-5.54	64.87	59.33	68.20	-8.87	Peak
2	5739.431	-5.39	66.17	60.78	68.20	-7.42	Peak


Left Band edge_Horizontal_Peak_802.11n20_5500MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-N20-5500

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 5460.000	-6.26	63.59	57.33	74.00	-16.67	Peak
2 5469.897	-6.22	70.90	64.68	68.20	-3.52	Peak
3 5470.000	-6.22	65.86	59.64	68.20	-8.56	Peak


Left Band edge_Horizontal_Average_802.11n20_5500MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
Note : 5GWiFi-Band3-N20-5500

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 5460.000	-6.26	53.92	47.66	54.00	-6.34 Average


Left Band edge_Vertical_Peak_802.11n20_5500MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-N20-5500

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5460.000	-6.26	64.11	57.85	74.00	-16.15	Peak
2	5469.203	-6.23	66.31	60.08	68.20	-8.12	Peak
3	5470.000	-6.22	63.62	57.40	68.20	-10.80	Peak


Left Band edge_Vertical_Average_802.11n20_5500MHz



Condition : Vertical
 Project No. : 2601R26613E-RF
 Tester : Zenos Qiao
 Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak
 Note : 5GWiFi-Band3-N20-5500

	Freq	Factor	Read		Limit	Over	Remark
			Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5460.000	-6.26	53.62	47.36	54.00	-6.64	Average


Right Band edge_Horizontal_Peak_802.11n20_5700MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-N20-5700

	Freq Factor		Read Level		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5725.000	-5.54	69.39	63.85	68.20	-4.35	Peak
2	5725.378	-5.53	70.19	64.66	68.20	-3.54	Peak


Right Band edge_Vertical_Peak_802.11n20_5700MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band3-N20-5700

Freq Factor		Read Level		Limit	Over	Remark
				Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	5725.000	-5.54	64.49	58.95	68.20	-9.25 Peak
2	5740.612	-5.38	66.47	61.09	68.20	-7.11 Peak


Left Band edge_Horizontal_Peak_802.11a_5745MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-A-5745

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5649.566	-5.89	67.66	61.77	68.20	-6.43	Peak
2	5669.469	-5.85	68.06	62.21	82.65	-20.44	Peak
3	5719.938	-5.58	73.08	67.50	110.78	-43.28	Peak
4	5724.925	-5.54	79.14	73.60	122.03	-48.43	Peak


Left Band edge_Vertical_Peak_802.11a_5745MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-A-5745

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5612.683	-6.13	67.42	61.29	68.20	-6.91	Peak
2	5699.465	-5.78	66.23	60.45	104.81	-44.36	Peak
3	5716.993	-5.62	66.97	61.35	109.96	-48.61	Peak
4	5724.402	-5.54	69.73	64.19	120.84	-56.65	Peak


Right Band edge_Horizontal_Peak_802.11a_5825MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-A-5825

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 5850.083	-4.70	72.12	67.42	122.01	-54.59	Peak
2 5864.299	-4.64	69.40	64.76	108.19	-43.43	Peak
3 5890.967	-4.55	69.55	65.00	93.35	-28.35	Peak
4 5945.006	-4.49	66.64	62.15	68.20	-6.05	Peak


Right Band edge_Vertical_Peak_802.11a_5825MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-A-5825

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 5851.400	-4.69	68.02	63.33	119.01	-55.68 Peak
2 5858.264	-4.67	67.76	63.09	109.88	-46.79 Peak
3 5913.917	-4.50	67.89	63.39	76.37	-12.98 Peak
4 5927.879	-4.50	66.67	62.17	68.20	-6.03 Peak


Left Band edge_Horizontal_Peak_802.11n20_5745MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-N20-5745

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 5621.850	-6.08	68.20	62.12	68.20	-6.08 Peak
2 5666.215	-5.86	68.83	62.97	80.23	-17.26 Peak
3 5719.961	-5.58	74.68	69.10	110.79	-41.69 Peak
4 5724.925	-5.54	80.32	74.78	122.03	-47.25 Peak


Left Band edge_Vertical_Peak_802.11n20_5745MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-N20-5745

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 5616.934	-6.09	67.26	61.17	68.20	-7.03 Peak
2 5667.521	-5.85	66.75	60.90	81.20	-20.30 Peak
3 5719.819	-5.58	67.05	61.47	110.75	-49.28 Peak
4 5724.830	-5.54	71.75	66.21	121.81	-55.60 Peak


Right Band edge_Horizontal_Peak_802.11n20_5825MHz



Condition : Horizontal
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-N20-5825

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5850.486	-4.70	74.28	69.58	121.09	-51.51	Peak
2	5855.884	-4.68	71.91	67.23	110.55	-43.32	Peak
3	5887.865	-4.55	69.35	64.80	95.65	-30.85	Peak
4	5944.411	-4.49	66.67	62.18	68.20	-6.02	Peak

Right Band edge_Vertical_Peak_802.11n20_5825MHz



Condition : Vertical
Project No. : 2601R26613E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : 5GWiFi-Band4-N20-5825

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 5850.465	-4.70	69.37	64.67	121.14	-56.47 Peak
2 5855.607	-4.68	67.51	62.83	110.63	-47.80 Peak
3 5890.054	-4.55	67.40	62.85	94.03	-31.18 Peak
4 5928.368	-4.50	66.60	62.10	68.20	-6.10 Peak

RF Conducted data**Test Information:**

Sample No.:	3JBW-2	Test Date:	2026/04/25
Test Site:	RF	Test Mode:	Transmitting
Tester:	Ethan Bu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.5	Relative Humidity: (%)	43	ATM Pressure: (kPa)	101.3
----------------------	------	------------------------------	----	------------------------	-------

Emission Bandwidth**26dB Emission Bandwidth****5150-5250MHz**

Mode	Test Frequency (MHz)	Result (MHz)
802.11a	5180	33.561
	5200	33.483
	5240	31.472
802.11n20	5180	34.668
	5200	34.390
	5240	29.517

5250-5350MHz

Mode	Test Frequency (MHz)	Result (MHz)
802.11a	5260	28.190
	5300	28.081
	5320	28.181
802.11n20	5260	27.080
	5300	28.764
	5320	28.938

5470-5725MHz


Mode	Test Frequency (MHz)	Result (MHz)
802.11a	5500	24.963
	5600	23.760
	5700	22.934
	5720	22.931
802.11n20	5500	24.629
	5600	23.369
	5700	23.481
	5720	23.480

6dB Emission Bandwidth
5725-5850MHz

Mode	Test Frequency (MHz)	Result (MHz)	Limit (MHz)	Verdict
802.11a	5745	15.215	0.5	Pass
	5785	15.566	0.5	Pass
	5825	15.265	0.5	Pass
802.11n20	5745	15.566	0.5	Pass
	5785	15.616	0.5	Pass
	5825	15.616	0.5	Pass


5150-5250MHz

802.11a_5180MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
 Date: 25.APR.2026 21:01:47

802.11a_5200MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
 Date: 25.APR.2026 21:05:36

802.11a_5240MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
 Date: 25.APR.2026 21:08:16

802.11n20_5180MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
 Date: 25.APR.2026 21:11:45

802.11n20_5200MHz



ProjectNo.:2601R26613E-RF Tester:Ethan Bu
 Date: 25.APR.2026 21:15:09


802.11n20_5240MHz



ProjectNo.:2601R26613E-RF Tester:Ethan Bu
 Date: 25.APR.2026 21:18:25


5250-5350MHz

802.11a_5260MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 21:23:18

802.11a_5300MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 21:27:19

802.11a_5320MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 21:30:03

802.11n20_5260MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 21:33:11

802.11n20_5300MHz



ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 21:36:14


802.11n20_5320MHz



ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 21:39:10


5470-5725MHz

802.11a_5500MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 22:07:35

802.11a_5600MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 22:11:16

802.11a_5700MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 21:50:23

802.11a_5720MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 21:53:01

802.11n20_5500MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 21:56:02

802.11n20_5600MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 21:58:41

802.11n20_5700MHz



ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 22:01:24


802.11n20_5720MHz



ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 22:04:28


5725-5850MHz

802.11a_5745MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 22:13:55

802.11a_5785MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 22:16:41

802.11a_5825MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 22:19:23

802.11n20_5745MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 22:21:44

802.11n20_5785MHz



ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 22:32:56

802.11n20_5825MHz



ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 22:36:15

99% Occupied Bandwidth**5150-5250MHz**

Mode	Test Frequency (MHz)	99% OBW (MHz)
802.11a	5180	17.600
	5200	17.450
	5240	16.750
802.11n20	5180	18.950
	5200	18.700
	5240	18.050

Note:

The 99% Occupied Bandwidth have not fall into the band 5250-5350MHz, please refer to the test plots of 99% Occupied Bandwidth.

5250-5350MHz

Mode	Test Frequency (MHz)	99% OBW (MHz)
802.11a	5260	16.650
	5300	16.700
	5320	16.650
802.11n20	5260	17.900
	5300	17.900
	5320	17.900

5470-5725MHz

Mode	Test Frequency (MHz)	99% OBW (MHz)
802.11a	5500	16.550
	5600	16.550
	5700	16.550
	5720	16.550
802.11n20	5500	17.700
	5600	17.700
	5700	17.750
	5720	17.700

5725-5850MHz


Mode	Test Frequency (MHz)	99% OBW (MHz)
802.11a	5745	16.550
	5785	16.600
	5825	16.650
802.11n20	5745	17.750
	5785	17.800
	5825	17.800

Note:

The 99% Occupied Bandwidth have not fall into the band 5470-5725MHz, please refer to the test plots of 99% Occupied Bandwidth.


5150-5250MHz

802.11a_5180MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 21:02:32

802.11a_5200MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 21:06:13

802.11a_5240MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 21:09:16

802.11n20_5180MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 21:12:30

802.11n20_5200MHz



ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 21:15:46


802.11n20_5240MHz



ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 21:19:06


5250-5350MHz

802.11a_5260MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
 Date: 25.APR.2026 21:23:58

802.11a_5300MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
 Date: 25.APR.2026 21:27:56

802.11a_5320MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
 Date: 25.APR.2026 21:30:47

802.11n20_5260MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
 Date: 25.APR.2026 21:33:51

802.11n20_5300MHz



ProjectNo.:2601R26613E-RF Tester:Ethan Bu
 Date: 25.APR.2026 21:36:50


802.11n20_5320MHz



ProjectNo.:2601R26613E-RF Tester:Ethan Bu
 Date: 25.APR.2026 21:39:51


5470-5725MHz

802.11a_5500MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 22:08:24

802.11a_5600MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 22:11:57

802.11a_5700MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 21:51:17

802.11a_5720MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 21:53:46

802.11n20_5500MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 21:56:51

802.11n20_5600MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 21:59:22

802.11n20_5700MHz



ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 22:02:19


802.11n20_5720MHz



ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 22:05:13


5725-5850MHz

802.11a_5745MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 22:14:46

802.11a_5785MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 22:17:37

802.11a_5825MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 22:20:00

802.11n20_5745MHz




ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 22:22:33

802.11n20_5785MHz



ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 22:33:52

802.11n20_5825MHz



ProjectNo.:2601R26613E-RF Tester:Ethan Bu
Date: 25.APR.2026 22:36:51

Maximum Conducted Output Power**5150-5250MHz**

Mode	Test Frequency (MHz)	Average Output Power(dBm)	Limit (dBm)	Verdict
802.11a	5180	17.05	24	Pass
	5200	16.74	24	Pass
	5240	15.78	24	Pass
802.11n20	5180	16.93	24	Pass
	5200	16.7	24	Pass
	5240	15.83	24	Pass

5250-5350MHz

Mode	Test Frequency (MHz)	Average Output Power(dBm)	Limit (dBm)	Verdict
802.11a	5260	15.58	24	Pass
	5300	16.17	24	Pass
	5320	16.1	24	Pass
802.11n20	5260	15.44	24	Pass
	5300	16.05	24	Pass
	5320	15.98	24	Pass

5470-5725MHz

Mode	Test Frequency (MHz)	Average Output Power(dBm)	Limit (dBm)	Verdict
802.11a	5500	15.5	24	Pass
	5600	14.42	24	Pass
	5700	14.37	24	Pass
	5720	13.8	24	Pass
802.11n20	5500	15.55	24	Pass
	5600	14.36	24	Pass
	5700	14.27	24	Pass
	5720	13.65	24	Pass

5725-5850MHz

Mode	Test Frequency (MHz)	Average Output Power(dBm)	Limit (dBm)	Verdict
802.11a	5745	14.48	30	Pass
	5785	14.88	30	Pass
	5825	15.36	30	Pass
802.11n20	5745	14.53	30	Pass
	5785	14.65	30	Pass
	5825	15.18	30	Pass

Power Spectral Density**5150-5250MHz**

Mode	Test Frequency (MHz)	Reading (dBm/MHz)	Duty Cycle Factor(dB)	Result (dBm/MHz)	Limit (dBm/MHz)	Verdict
802.11a	5180	6.24	0.89	7.13	11	Pass
	5200	5.60	0.89	6.49	11	Pass
	5240	4.69	0.89	5.58	11	Pass
802.11n20	5180	5.59	0.85	6.44	11	Pass
	5200	5.65	0.85	6.50	11	Pass
	5240	4.44	0.85	5.29	11	Pass

5250-5350MHz

Mode	Test Frequency (MHz)	Reading (dBm/MHz)	Duty Cycle Factor(dB)	Result (dBm/MHz)	Limit (dBm/MHz)	Verdict
802.11a	5260	4.33	0.89	5.22	11	Pass
	5300	5.35	0.89	6.24	11	Pass
	5320	5.02	0.89	5.91	11	Pass
802.11n20	5260	3.93	0.85	4.78	11	Pass
	5300	4.51	0.85	5.36	11	Pass
	5320	4.78	0.85	5.63	11	Pass

5470-5725MHz

Mode	Test Frequency (MHz)	Reading (dBm/MHz)	Duty Cycle Factor(dB)	Result (dBm/MHz)	Limit (dBm/MHz)	Verdict
802.11a	5500	4.40	0.89	5.29	11	Pass
	5600	3.52	0.89	4.41	11	Pass
	5700	3.39	0.89	4.28	11	Pass
	5720	3.32	0.89	4.21	11	Pass
802.11n20	5500	4.27	0.85	5.12	11	Pass
	5600	3.11	0.85	3.96	11	Pass
	5700	2.74	0.85	3.59	11	Pass
	5720	3.66	0.85	4.51	11	Pass

5725-5850MHz

Mode	Test Frequency (MHz)	Reading (dBm/500kHz)	Duty Cycle Factor(dB)	Result (dBm/500kHz)	Limit (dBm/500kHz)	Verdict
802.11a	5745	0.69	0.89	1.58	30	Pass
	5785	0.63	0.89	1.52	30	Pass
	5825	1.35	0.89	2.24	30	Pass
802.11n20	5745	0.55	0.85	1.40	30	Pass
	5785	0.93	0.85	1.78	30	Pass
	5825	1.57	0.85	2.42	30	Pass

Result = Reading + Duty Cycle Factor