

MPE TEST REPORT

Applicant	AoFrio Ltd.
FCC ID	2AHCE-GW2
Product	Gateway
Brand	AoFrio
Model	Gateway (Cat 1 bis)
Report No.	EFTA25070355-IE-06-M1V1
Issue Date	November 27, 2025

Eurofins TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC 47 CFR Part 1 §1.1310, §2.1091**. The test results show that the equipment tested can demonstrate the compliance with the requirements as documented in this report.



Prepared by: Wei Fangying



Approved by: Xu Kai

Eurofins TA Technology (Shanghai) Co., Ltd.

Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

Version	Revision Description	Issue Date
Rev.0	Initial issue of report.	November 27, 2025
Rev.1	Updated information.	November 27, 2025
Note: This revised report (Report No.: EFTA25070355-IE-06-M1V1) supersedes and replaces the previously issued report (Report No.: EFTA25070355-IE-06-M1). Please discard or destroy the previously issued report and dispose of it accordingly.		

Table of Contents

1	Test Laboratory	4
1.1	Notes of the Test Report.....	4
1.2	Test Facility.....	4
1.3	Testing Location.....	4
1.4	Laboratory Environment	4
2	Description of Equipment Under Test	5
3	Maximum Tune up and Antenna Gain	6
4	MPE Limit.....	7
5	RF Exposure Evaluation Result.....	9
	ANNEX A: The EUT Appearance	10

1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **Eurofins TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Test Facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

1.3 Testing Location

Company: Eurofins TA Technology (Shanghai) Co., Ltd.
Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <https://www.eurofins.com/electrical-and-electronics>
E-mail: Kain.Xu@cpt.eurofinscn.com

1.4 Laboratory Environment

Temperature	Min. = 18°C, Max. = 25°C
Relative humidity	Min. = 20%, Max. = 80%
Ground system resistance	< 0.5 Ω
Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

2 Description of Equipment Under Test

Client Information

Applicant	AoFrio Ltd.
Applicant address	78 Apollo Drive, Rosedale, Auckland 0632, New Zealand
Manufacturer	AoFrio Ltd.
Manufacturer address	78 Apollo Drive, Rosedale, Auckland 0632, New Zealand

General Technologies

EUT Description			
Model	Gateway (Cat 1 bis)		
SN	Conducted	MPY25CV0H004090	
	Radiated	P126F00053	
Hardware Version	i1.0		
Software Version	1.1.6+5472		
Frequency	Band	TX (MHz)	RX (MHz)
	LTE Band 2	1850 ~ 1910	1930 ~ 1990
	LTE Band 4	1710 ~ 1755	2110 ~ 2155
	LTE Band 5	824 ~ 849	869 ~ 894
	LTE Band 7	2500 ~ 2570	2620 ~ 2690
	LTE Band 12	699 ~ 716	729 ~ 746
	LTE Band 13	777 ~ 787	746 ~ 756
	LTE Band 25	1850 ~ 1915	1930 ~ 1995
	LTE Band 26	814 ~ 849	859 ~ 894
	LTE Band 38	2570 ~ 2620	2570 ~ 2620
	LTE Band 41	2496 ~ 2690	2496 ~ 2690
	LTE Band 66	1710 ~ 1780	2110 ~ 2180
	Wi-Fi 2.4GHz	2400 ~ 2483.5	2400 ~ 2483.5
	Bluetooth (Low Energy)	2400 ~ 2483.5	2400 ~ 2483.5
Date of Testing	July 28, 2025 ~ September 15, 2025		
Date of Sample Received	July 28, 2025		
Note: 1. The EUT is sent from the applicant to Eurofins TA and the information of the EUT is declared by the applicant. 2. All indications of Pass/Fail in this report are opinions expressed by Eurofins TA Technology			

(Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.

3 Maximum Tune up and Antenna Gain

The numeric gain (G) of the antenna with a gain specified in dB is determined by
 Numeric gain (G)=10^(antenna gain/10)

Band	Maximum Tune up Tolerance		Antenna Gain (dBi)	Numeric Gain
	(dBm)	(mW)		
LTE Band 2	25.00	316.23	3.31	2.14
LTE Band 4	25.00	316.23	3.31	2.14
LTE Band 5	25.00	316.23	2.80	1.91
LTE Band 7	25.00	316.23	1.90	1.55
LTE Band 12	25.00	316.23	2.24	1.67
LTE Band 13	25.00	316.23	2.24	1.67
LTE Band 25	25.00	316.23	3.31	2.14
LTE Band 26	25.00	316.23	2.80	1.91
LTE Band 38	25.00	316.23	1.90	1.55
LTE Band 41	25.00	316.23	1.90	1.55
LTE Band 66	25.00	316.23	3.31	2.14
Wi-Fi 2.4GHz	23.50	223.87	2.00	1.58
Bluetooth LE	5.00	3.16	3.18	2.08

4 MPE Limit

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) LIMITS FOR OCCUPATIONAL/CONTROLLED EXPOSURE				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
(ii) LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

*f = frequency in MHz. * = Plane-wave equivalent power density.*

Note1. Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.

Note2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

The maximum permissible exposure for 300~1500 MHz is f/1500, for 1500~100,000MHz is 1.0. So

Band	The Maximum Permissible Exposure (mW/cm ²)
LTE Band 2	1.000
LTE Band 4	1.000
LTE Band 5	0.549
LTE Band 7	1.000
LTE Band 12	0.466
LTE Band 13	0.518
LTE Band 25	1.000
LTE Band 26	0.543
LTE Band 38	1.000
LTE Band 41	1.000
LTE Band 66	1.000
Wi-Fi 2.4GHz	1.000
Bluetooth LE	1.000

5 RF Exposure Evaluation Result

RF exposure evaluation method is based on KDB 447498 D01, this calculation is based on the conducted power, maximum power and antenna gain with provides the minimum separation distance. The formula shown below is from OET Bulletin 65 Edition 97-01 Per KDB 447498 D01:

$$S = PG / 4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = Time-average maximum tune up procedure (in appropriate units, e.g., mW)

G = the numeric gain of the antenna

R = distance to the center of radiation of the antenna (20 cm = limit for MPE)

Band	Maximum Tune up (dBm)	Antenna Gain (dBi)	Maximum EIRP (dBm)	PG (mW)	Result (mW/cm ²)	Limit Value (mW/cm ²)	The MPE Ratio
LTE Band 2	25.000	3.310	28.310	677.642	0.135	1.000	0.135
LTE Band 4	25.000	3.310	28.310	677.642	0.135	1.000	0.135
LTE Band 5	25.000	2.800	27.800	602.560	0.120	0.549	0.218
LTE Band 7	25.000	1.900	26.900	489.779	0.097	1.000	0.097
LTE Band 12	25.000	2.240	27.240	529.663	0.105	0.466	0.226
LTE Band 13	25.000	2.240	27.240	529.663	0.105	0.518	0.203
LTE Band 25	25.000	3.310	28.310	677.642	0.135	1.000	0.135
LTE Band 26	25.000	2.800	27.800	602.560	0.120	0.543	0.221
LTE Band 38	25.000	1.900	26.900	489.779	0.097	1.000	0.097
LTE Band 41	25.000	1.900	26.900	489.779	0.097	1.000	0.097
LTE Band 66	25.000	3.310	28.310	677.642	0.135	1.000	0.135
Wi-Fi 2.4GHz	23.500	2.000	25.500	354.813	0.071	1.000	0.071
Bluetooth LE	5.000	3.180	8.180	6.577	0.001	1.000	0.001
Note: R = 20cm $\pi = 3.1416$ The MPE Ratio = Mac Result÷Limit Value							

This device only supports simultaneous transmission via Wi-Fi 2.4GHz and WWAN and Bluetooth.

So, the simultaneous transmitting antenna pairs as below:

TER = WWAN Antenna MPE Ratio + Wi-Fi 2.4GHz Antenna MPE Ratio + Bluetooth Antenna MPE Ratio = 0.226 + 0.071 + 0.001 = 0.298<1

So, the limit is kept.

Note: For this device, minimum separation distance is 20cm, even if calculations indicate MPE distance is less.

ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.

*****END OF REPORT *****