

# DONGGUAN ARUN INDUSTRIAL.CO.LTD

## Cover Letter-Wireless Charger Approval

FCC ID: 2AHCLWX0001 (填ID 号码)

Data: 2016-2-15

Gentlemen:

There's an Wireless Charger that would like to have your authorization as an Inductive wireless power transfer applications approval.

The specific product as below, Wireless Charger, with its designed features and specified description, meets special requirements for KDB 680106 D01 section 5.2 requirements.

|                |                                 |
|----------------|---------------------------------|
| Company:       | DONGGUAN ARUN INDUSTRIAL.CO.LTD |
| Product Name : | Wireless Charger                |
| Model Number:  | WX0001                          |
| FCC ID :       | 2AHCLWX0001                     |

| KDB 680106 D01 Section 5.2 Requirements:                                                                                                                                                                                                   | Product Technical Specification:        | Result:      |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------|--------------|
| a) Power transfer frequency is less than 1 MHz                                                                                                                                                                                             | 110-205KHz                              | Complied     |
| b) Output power from each primary coil is less than 5 Watts                                                                                                                                                                                | 3.5Watts                                | Complied     |
| c) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils | only single primary                     | Complied     |
| d) Client device is inserted in or placed directly in contact with the transmitter                                                                                                                                                         | placed directly                         | Complied     |
| e) The maximum coupling surface area of the transmit (charging) device is between 60 cm2 and 400 cm2.                                                                                                                                      | 10 cm2                                  | Non-complied |
| f) Aggregate leakage fields at 10 cm surrounding the device from all simultaneous transmitting coils are demonstrated to be less than 30% of the MPE limit.                                                                                | Please reference RF exposure report.pdf | Complied     |

Sincerely,

By: Li Deshi  
(Signature)

Li Deshi  
(Print name)

Title: Manger

On behalf of: DONGGUAN ARUN INDUSTRIAL.CO.LTD

Telephone: 0769-83622930

(Company Name)

