

FCC RF EXPOSURE REPORT

FCC ID: 2AHCR-E12WF6

Project No. : 2602C080
Equipment : Door Phone
Brand Name : AKUVOX
Test Model : E12W
Model Name : E12W
Hardware Version : V1.00
Software Version : 312.30.2.9
Applicant : AKUVOX (XIAMEN) NETWORKS CO., LTD.
Address : 10/F, No.56 Guanri Road, Software Park II, Xiamen 361009, China
Manufacturer : AKUVOX (XIAMEN) NETWORKS CO., LTD.
Address : 10/F, No.56 Guanri Road, Software Park II, Xiamen 361009, China
Date of Receipt : Mar. 16, 2026
Date of Test : Mar. 16, 2026 ~ Apr. 28, 2026
Issued Date : Jul. 13, 2026
Test Sample : Engineering Sample No.: DG920260316222
Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091
 FCC Title 47 Part 2.1091 & KDB 447498 D01 v06

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc. (Dongguan)

Prepared by : Laughing Zhang
 Laughing Zhang

Approved by : Chay Cai
 Chay Cai

No.3, Jinshagang 1st Road, Dalang, Dongguan, Guangdong People's Republic of China.
 Tel: +86-769-8318-3000 Web: www.newbtl.com Service mail: btl_qa@newbtl.com

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacturer's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. BTL assumes no responsibility for the data provided by the customer, any statements, inferences or generalizations drawn by the customer or others from the reports issued by BTL.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

BTL is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Please note that the measurement uncertainty is provided for informational purpose only and are not use in determining the Pass/Fail results.

REVISION HISTORY

Report No.	Version	Description	Issued Date	Note
BTL-FCCP-5-2502C080	R00	Original Report.	Jul. 13, 2026	Valid

1. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

2. ANTENNA SPECIFICATION

For LE:

Ant.	Manufacturer	Model Name	Antenna Type	Connector	Gain (dBi)
1	Earda Technologies Co., Ltd	EWN-8253FET1AA	PCB	N/A	-2

For 2.4GHz:

Ant.	Manufacturer	Model Name	Antenna Type	Connector	Gain (dBi)
1	Word Easy Electronics Co., Ltd	WE007N.F0204.V01	PCB	N/A	3.5

For 5GHz:

Ant.	Manufacturer	Model Name	Antenna Type	Connector	Gain (dBi)
1	Word Easy Electronics Co., Ltd	WE007N.F0204.V01	PCB	N/A	2.2

Note: The antenna gain is provided by the manufacturer.

3. CALCULATED RESULT

For LE:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Max. Tune-up (dB)	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
-2.00	0.6310	3.84	0.5	4.34	2.7164	0.0003	1	Complies

For 2.4GHz:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Max. Tune-up (dB)	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3.50	2.2387	20.39	0.5	20.89	122.7439	0.0547	1	Complies

For 5GHz:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Max. Tune-up (dB)	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
2.20	1.6596	22.33	0.5	22.83	191.8669	0.0633	1	Complies

For the max simultaneous transmission MPE:

Ratio		Total	Limit of Ratio	Test Result
LE	5GHz			
0.0003	0.0633	0.0636	1	Complies

Note:

- (1) The calculated distance is 20 cm.
- (2) Ratio=Power Density (S) (mW/cm²)/Limit of Power Density (S) (mW/cm²)
- (3) Output power including tune up tolerance (±0.5dB).

End of Test Report