

FCC PART 15C

TEST REPORT

For

AKUVOX (XIAMEN) NETWORKS CO., LTD.

10/F, No.56, Software Park II, Xiamen, China

FCC ID: 2AHCR-R27XV2

Report Type: Original Report	Product Type: Door Phone
Test Engineer:	Stone Zhang <i>Stone Zhang</i>
Report Number:	RXM190816050-00B
Report Date:	2019-11-30
Reviewed By:	Oscar Ye EMC Manager <i>Oscar Ye</i>
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road,Kunshan,Jiangsu province,China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
JUSTIFICATION	5
EUT EXERCISE SOFTWARE	5
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
EXTERNAL I/O CABLE.....	5
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	8
TEST EQUIPMENT LIST	9
FCC§15.203 - ANTENNA REQUIREMENT.....	10
APPLICABLE STANDARD	10
ANTENNA CONNECTED CONSTRUCTION	10
FCC §15.207 (A) – AC LINE CONDUCTED EMISSIONS	11
APPLICABLE STANDARD	11
EUT SETUP	11
EMI TEST RECEIVER SETUP.....	11
TEST PROCEDURE	11
FACTOR & OVER LIMIT CALCULATION.....	12
TEST RESULTS SUMMARY	12
TEST DATA	12
FCC§15.225, §15.205 & §15.209 - RADIATED EMISSIONS TEST	17
APPLICABLE STANDARD	17
EUT SETUP	17
EMI TEST RECEIVER SETUP.....	18
CORRECTED AMPLITUDE & MARGIN CALCULATION	18
TEST RESULTS SUMMARY	18
TEST DATA	18
FCC§15.225(E) - FREQUENCY STABILITY.....	32
APPLICABLE STANDARD	32
TEST PROCEDURE	32
TEST DATA	33
§15.215(C) - 20DB EMISSION BANDWIDTH TESTING	35
REQUIREMENT	35
TEST PROCEDURE	35
TEST DATA	35

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant	AKUVOX (XIAMEN) NETWORKS CO., LTD.
Tested Model	R27A
Series Model	R27V
Operation Frequency:	125kHz,13.56MHz
Model Difference	Model names
Product Type	Door Phone
Dimension	280mm(L)*130mm(W)*32mm(H)
Power Supply	DC 12V power by External power supply or DC 48V power by POE

**All measurement and test data in this report was gathered from production sample serial number: 20190816050.
(Assigned by the BACL. The EUT supplied by the applicant was received on 2019-08-16)*

Objective

This Type approval report is prepared on behalf of *AKUVOX (XIAMEN) NETWORKS CO., LTD.* in accordance with Part 2- Subpart J, and Part 15-Subparts A and C of the Federal Communication Commission's rules.

The objective is to determine the Compliance of the EUT with FCC rules, sec 15.203, 15.205, 15.207, 15.209 ,15.215 and 15.225.

Related Submittal(s)/Grant(s)

N/A

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Lab Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19 dB
RF conducted test with spectrum		0.9dB
Radiated emission	9kHz~30MHz	6.07dB
	30MHz~1GHz	6.11dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01), the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Justification

The system was configured for testing in a typical fashion (as normally used by a typical user).
The device operates in 125 kHz and 13.56 MHz simultaneously for RFID detection

EUT Exercise Software

The EUT is tested in the engineering mode.

Equipment Modifications

No modification on the EUT.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
RUCKUS	Adapter	PA1024-4HUB	/
/	POE	NPE-5818	136287121
MCH	DC Power Supply	MCH-303D-II	14070562
DELL	Notebook	E6410	3094742521
Schneider Electric	Relay	RXM2LB2BD	N/A
WeiShi	Entrance guard	Q3	N/A
AnYong	Load	RXLG	N/A
FuShi	Switch	AR22PR-310B	N/A


External I/O Cable

Cable Description	Length (m)	From/Port	To
Power Cable	5.0	EUT	DC Power Supply
RJ45 Cable	5.0	EUT	POE
Power Cable	1.2	POE	POE Adapter
RJ45 cable	5.0	EUT	Notebook
Signal Cable	5.0	EUT	Switch
Signal Cable	5.0	EUT	Relay
Signal Cable	5.0	EUT	Entrance Guard
Power supply cable	5.0	EUT	Load


Block Diagram of Test Setup

For Conducted Emissions:

DC 12V power by External power supply:




DC 48V power by POE:




For Radiated Emissions (Below 30 MHz & Above 30 MHz):

DC 12V power by External power supply:



DC 48V power by POE:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.225 §15.209 §15.205	Radiated Emission Test	Compliant
§15.225(e)	Frequency Stability	Compliant
§15.215(c)	20dB Emission Bandwidth Testing	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2018-11-30	2019-11-29
Sunol Sciences	Broadband Antenna	JB3	A040914-2	2016-01-09	2022-01-08
Sonoma Instrument	Pre-amplifier	310N	171205	2019-08-15	2020-08-14
ETS-LINDGREN	Loop Antenna	6512	00108100	2019-04-25	2022-04-24
Rohde & Schwarz	Auto Test Software	EMC32	100361	/	/
Audix	Test Software	e3	V9	/	/
MICRO-COAX	Coaxial Cable	Cable-8	008	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2019-08-15	2020-08-14
BEST	DC Power Supply	PS-1502D+	DC001	2018-10-10	2019-10-09
BEST	DC Power Supply	PS-1502D+	DC001	2019-10-10	2020-10-09
BACL	Temperature & Humidity Chamber	BTH-150	30023	2018-10-10	2019-10-09
BACL	Temperature & Humidity Chamber	BTH-150	30023	2019-10-10	2020-10-09
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2019-07-11	2020-07-10
Rohde & Schwarz	LISN	ENV216	3560655016	2018-11-30	2019-11-29
Audix	Test Software	e3	V9	/	/
Narda	Attenuator/6dB	10690812-2	26850-6	2019-01-10	2020-01-09
MICRO-COAX	Coaxial Cable	Cable-15	015	2019-08-15	2020-08-14

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.203 - ANTENNA REQUIREMENT

Applicable Standard

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.


Antenna Connected Construction

The EUT has two integral antenna arrangement, one for 13.56MHz, one for 125kHz and antenna gain are 0.00dBi, which was permanently attached, fulfill the requirement of this section, please refer to the EUT photos.

Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS**Applicable Standard**

FCC§15.207(a)

EUT Setup

Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Factor & Over Limit Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over Limit of 7 dB means the emission is 7 dB above the limit. The equation for over limit calculation is as follows:

$$\text{Over Limit (dB)} = \text{Read level (dB}\mu\text{V)} + \text{Factor (dB)} - \text{Limit (dB}\mu\text{V)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data

Environmental Conditions


Temperature:	23.2~24.2 °C
Relative Humidity:	48~50 %
ATM Pressure:	101.3~102.0 kPa

The testing was performed by Stone Zhang from 2019-08-23 to 2019-11-21.


EUT operation mode: Transmitting

DC 12V power by External power supply:

AC 120V/60 Hz, Line



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.217	-5.70	19.82	14.12	52.92	-38.80	Average
2	0.217	0.80	19.82	20.62	62.92	-42.30	QP
3	0.400	-6.80	19.74	12.94	47.86	-34.92	Average
4	0.400	-0.80	19.74	18.94	57.86	-38.92	QP
5	0.497	-6.90	19.76	12.86	46.05	-33.19	Average
6	0.497	-2.00	19.76	17.76	56.05	-38.29	QP
7	0.661	-7.10	19.75	12.65	46.00	-33.35	Average
8	0.661	-4.00	19.75	15.75	56.00	-40.25	QP
9	14.750	3.20	19.63	22.83	50.00	-27.17	Average
10	14.750	9.20	19.63	28.83	60.00	-31.17	QP
11	21.830	6.20	19.85	26.05	50.00	-23.95	Average
12	21.830	10.90	19.85	30.75	60.00	-29.25	QP

AC 120V/60 Hz, Neutral


	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.185	-5.49	19.82	14.33	54.24	-39.91	Average
2	0.185	1.31	19.82	21.13	64.24	-43.11	QP
3	0.310	-6.51	19.83	13.32	49.97	-36.65	Average
4	0.310	0.39	19.83	20.22	59.97	-39.75	QP
5	0.426	-6.90	19.75	12.85	47.33	-34.48	Average
6	0.426	-1.90	19.75	17.85	57.33	-39.48	QP
7	0.914	-6.80	19.74	12.94	46.00	-33.06	Average
8	0.914	-5.00	19.74	14.74	56.00	-41.26	QP
9	14.907	3.40	19.63	23.03	50.00	-26.97	Average
10	14.907	8.50	19.63	28.13	60.00	-31.87	QP
11	22.655	6.30	19.81	26.11	50.00	-23.89	Average
12	22.655	10.90	19.81	30.71	60.00	-29.29	QP

Note:

- 1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)
 2) Over Limit (dB) = Read level (dBμV) + Factor (dB) - Limit (dBμV)


DC 48V power by POE:

AC 120V/60 Hz, Line



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.162	19.10	19.83	38.93	55.38	-16.45	Average
2	0.162	34.20	19.83	54.03	65.38	-11.35	QP
3	0.481	17.20	19.76	36.96	46.32	-9.36	Average
4	0.481	23.80	19.76	43.56	56.32	-12.76	QP
5	1.441	10.21	19.83	30.04	46.00	-15.96	Average
6	1.441	16.71	19.83	36.54	56.00	-19.46	QP
7	1.991	12.20	19.83	32.03	46.00	-13.97	Average
8	1.991	17.00	19.83	36.83	56.00	-19.17	QP
9	10.288	21.60	19.56	41.16	50.00	-8.84	Average
10	10.288	26.20	19.56	45.76	60.00	-14.24	QP
11	23.387	10.50	19.77	30.27	50.00	-19.73	Average
12	23.387	15.20	19.77	34.97	60.00	-25.03	QP

AC 120V/60 Hz, Neutral



	Freq	Read		Limit	Over	
	MHz	Level	Factor	Line	Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB
1	0.158	18.60	19.82	38.42	55.56	-17.14 Average
2	0.158	34.50	19.82	54.32	65.56	-11.24 QP
3	0.238	13.40	19.82	33.22	52.17	-18.95 Average
4	0.238	25.70	19.82	45.52	62.17	-16.65 QP
5	0.492	18.80	19.76	38.56	46.14	-7.58 Average
6	0.492	25.50	19.76	45.26	56.14	-10.88 QP
7	4.315	7.01	19.47	26.48	46.00	-19.52 Average
8	4.315	13.21	19.47	32.68	56.00	-23.32 QP
9	5.774	9.20	19.50	28.70	50.00	-21.30 Average
10	5.774	14.90	19.50	34.40	60.00	-25.60 QP
11	10.508	15.80	19.56	35.36	50.00	-14.64 Average
12	10.508	20.80	19.56	40.36	60.00	-19.64 QP

Note:

- 1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)
 2) Over Limit (dB) = Read level (dBUV) + Factor (dB) - Limit (dBUV)


FCC§15.225, §15.205 & §15.209 - RADIATED EMISSIONS TEST

Applicable Standard

FCC Part 15.205, 15.209, 15.225

- (a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.
- (b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.
- (c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.
- (d) The field strength of any emissions appearing outside of the 13.110–14.010 MHz band shall not exceed the general radiated emission limits in §15.209.

EUT Setup



The radiated emission tests were performed in the 3-meter chamber a test site, using the setup accordance with the ANSI C63.10. The specification used was the FCC Part Subpart C limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

According to FCC Rules, 47 CFR 15.33, the EUT emissions were investigated up to 1000 MHz.

During the radiated emission test, the EMI test Receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
9 kHz – 150 kHz	200 Hz	1 kHz	/	QP/Average
150 kHz – 30 MHz	9 kHz	30 kHz	/	QP/Average
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain

Corrected Amplitude = Meter Reading + Corrected Factor

The “**Margin**” column of the following data tables indicates the degree of Compliant with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.209, 15.205, 15.225.

Test Data

Environmental Conditions


Temperature:	24.2~25.1 °C
Relative Humidity:	48~50 %
ATM Pressure:	101.1~101.3 kPa

The testing was performed by Stone Zhang from 2019-09-17 to 2019-11-21.

Test mode: Transmitting

DC 12V power by External power supply:

1) Spurious Emissions (9 kHz~150 kHz):




Date: 18.SEP.2019 00:53:32

Indicated		PK/QP/Ave.	Corrected Factor (dB/m)	FCC Part 15.225/15.209	
Frequency (kHz)	Corrected Amplitude (dBμV/m) @3m			Limit (dBμV/m) @3m	Margin (dB)
35.21	57.38	PK	45.85	116.67	59.29
125.00	92.63	PK	50.51	105.66	13.03
136.89	85.91	PK	49.62	104.88	18.97
142.77	67.54	PK	50.81	104.51	36.97

Note:

1. The average emissions which fall into frequencies 9-90 kHz, 110-490 kHz was not recorded, because the peak emissions are below the average limit.

2) Spurious Emissions (150 kHz~30 MHz):




Date: 17.SEP.2019 23:14:19

Frequency (MHz)	Corrected Amplitude (dBμV/m)@3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	FCC Part 15.225/15.209	
				Limit (dBμV/m)@3m	Margin (dB)
0.20	78.22	PK	51.60	101.58	23.36
2.06	73.45	PK	14.15	89.54	16.09
4.02	52.51	PK	18.79	69.54	17.03
13.56	82.48	PK	15.15	124.00	41.52
15.42	32.68	PK	5.77	69.54	36.86
20.38	32.69	PK	5.25	69.54	36.85

Note:


1. The average emissions which fall into frequencies 9-90 kHz, 110-490 kHz was not recorded, because the peak emissions are below the average limit.
2. The EMI Test Receiver only can mark 4 points, and there are 2 points recorded by manual.

3) Spurious Emissions (13.11MHz~13.41 MHz):




Date: 17.SEP.2019 23:19:08

Spurious Emissions (13.41MHz~13.553 MHz):




Date: 17.SEP.2019 23:20:23

Spurious Emissions (13.567MHz~13.710 MHz):



Date: 17.SEP.2019 23:22:01


Spurious Emissions (13.710MHz~14.010 MHz):



Date: 17.SEP.2019 23:24:15

Frequency (MHz)	Corrected Amplitude (dBμV/m)@3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	FCC Part 15.225/15.209	
				Limit (dBμV/m)@3m	Margin (dB)
13.350	58.80	PK	6.14	80.50	21.70
13.553	70.15	PK	6.12	90.50	20.35
13.567	75.78	PK	6.12	90.50	14.72
13.773	59.00	PK	6.09	80.50	21.50

4) Spurious Emissions (30 MHz ~1 GHz):



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	Quasi Peak (dBμV/m)	Height (cm)	Polar (H/V)				
40.688600	29.86	100.0	V	92.0	-11.2	40.00	10.14
72.838100	16.37	100.0	V	252.0	-17.4	40.00	23.63
120.043700	25.91	200.0	H	209.0	-11.2	43.50	17.59
360.044900	31.13	100.0	H	336.0	-9.1	46.00	14.87
600.045800	33.15	200.0	H	117.0	-5.2	46.00	12.85
744.034650	33.46	100.0	H	44.0	-2.6	46.00	12.54

Note:


Corrected Amplitude = Corrected Factor + Reading

Corrected Factor = Antenna factor (Rx) + cable loss – amplifier factor

Margin = Limit - Corrected Amplitude

DC 48V power by POE:

1) Spurious Emissions (9 kHz~150 kHz):




Date: 21.NOV.2019 08:38:14

Frequency (MHz)	Corrected Amplitude (dBμV/m)@3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	FCC Part 15.225/15.209	
				Limit (dBμV/m)@3m	Margin (dB)
35.21	60.16	PK	45.85	116.67	56.51
125.00	93.30	PK	50.51	105.66	12.36
136.89	88.62	PK	49.62	104.88	16.26
143.45	70.88	PK	50.81	104.47	33.59

Note:

1. The average emissions which fall into frequencies 9-90 kHz, 110-490 kHz was not recorded, because the peak emissions are below the average limit.
2. The EMI Test Receiver only can mark 4 points.

2) Spurious Emissions (150 kHz~30 MHz):



Date: 21.NOV.2019 08:49:38

Frequency (MHz)	Corrected Amplitude (dBμV/m)@3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	FCC Part 15.225/15.209	
				Limit (dBμV/m)@3m	Margin (dB)
0.25	80.14	PK	40.10	99.65	19.51
1.68	71.94	PK	15.39	83.10	11.16
4.02	65.42	PK	15.39	89.54	24.12
13.56	85.22	PK	15.15	124.00	38.78
19.14	25.41	PK	5.67	69.54	44.13
20.38	23.69	PK	5.25	69.54	45.85

Note:


1. The average emissions which fall into frequencies 9-90 kHz, 110-490 kHz was not recorded, because the peak emissions are below the average limit.
2. The EMI Test Receiver only can mark 4 points, and there are 2 points recorded by manual.

3) Spurious Emissions (13.11MHz~13.41 MHz):




Date: 21.NOV.2019 09:00:24

Spurious Emissions (13.41MHz~13.553 MHz):




Date: 21.NOV.2019 09:01:34

Spurious Emissions (13.567MHz~13.710 MHz):



Date: 21.NOV.2019 09:07:02


Spurious Emissions (13.710MHz~14.010 MHz):



Date: 21.NOV.2019 09:05:29

Frequency (MHz)	Corrected Amplitude (dBμV/m)@3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	FCC Part 15.225/15.209	
				Limit (dBμV/m)@3m	Margin (dB)
13.350	58.21	PK	6.14	80.50	22.29
13.553	68.31	PK	6.12	90.50	22.19
13.567	75.13	PK	6.12	90.50	15.37
13.773	58.59	PK	6.09	80.50	21.91


4) Spurious Emissions (30 MHz ~1 GHz):

Horizontal:

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	APos	TPos	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	deg	
1	64.66	36.40	-17.25	19.15	40.00	-20.85	200	94	QP
2	140.34	31.91	-11.77	20.14	43.50	-23.36	200	210	QP
3	216.78	34.10	-13.17	20.93	46.00	-25.07	100	107	QP
4	277.09	28.90	-10.74	18.16	46.00	-27.84	100	187	QP
5	455.91	23.89	-6.48	17.41	46.00	-28.59	200	210	QP
6	552.88	27.51	-4.73	22.78	46.00	-23.22	200	287	QP

Vertical:

Date: 2019-11-21



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	APos	TPos	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	deg	
1	40.28	45.80	-11.60	34.20	40.00	-5.80	170	179	QP
2	71.58	43.81	-16.94	26.87	40.00	-13.13	170	262	QP
3	97.80	30.00	-15.20	14.80	43.50	-28.70	170	312	QP
4	162.61	28.60	-12.17	16.43	43.50	-27.07	170	82	QP
5	216.78	25.30	-13.17	12.13	46.00	-33.87	174	1	QP
6	504.71	23.21	-5.43	17.78	46.00	-28.22	170	214	QP

Note:

- 1) Factor (dB) = Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB)
- 2) Over Limit (dB) = Read level (dBuV) + Factor (dB) - Limit (dBuV)

FCC§15.225(e) - FREQUENCY STABILITY

Applicable Standard

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to $+50$ degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

Test Procedure

a) Supply the EUT with a nominal ac voltage or install a new or fully charged battery in the EUT. If possible, a dummy load shall be connected to the EUT because an antenna near the metallic walls of an environmental test chamber could affect the output frequency of the EUT. If the EUT is equipped with a permanently attached, adjustable-length antenna, then the EUT shall be placed in the center of the chamber with the antenna adjusted to the shortest length possible. Turn ON the EUT and tune it to one of the number of frequencies shown in 5.6.

b) Couple the unlicensed wireless device output to the measuring instrument by connecting an antenna to the measuring instrument with a suitable length of coaxial cable and placing the measuring antenna near the EUT (e.g., 15 cm away), or by connecting a dummy load to the measuring instrument, through an attenuator if necessary.
NOTE—An instrument that has an adequate level of accuracy as specified by the procuring or regulatory agency is the recommended measuring instrument.

c) Adjust the location of the measurement antenna and the controls on the measurement instrument to obtain a suitable signal level (i.e., a level that will not overload the measurement instrument but is strong enough to allow measurement of the operating or fundamental frequency of the EUT).

d) Turn the EUT OFF and place it inside the environmental temperature chamber. For devices that have oscillator heaters, energize only the heater circuit.

e) Set the temperature control on the chamber to the highest specified in the regulatory requirements for the type of device and allow the oscillator heater and the chamber temperature to stabilize.

f) While maintaining a constant temperature inside the environmental chamber, turn the EUT ON and record the operating frequency at startup, and at 2 minutes, 5 minutes, and 10 minutes after the EUT is energized. Four measurements in total are made.

g) Measure the frequency at each of frequencies specified in 5.6.

h) Switch OFF the EUT but do not switch OFF the oscillator heater.

i) Lower the chamber temperature by not more than 10°C , and allow the temperature inside the chamber to stabilize.

j) Repeat step f) through step i) down to the lowest specified temperature.

Test Data**Environmental Conditions**

Temperature:	23.2~24.5 °C
Relative Humidity:	50~52 %
ATM Pressure:	101.3~102.6 kPa

The testing was performed by Stone Zhang from 2019-09-17 to 2019-11-21.

Test Mode: Transmitting.

Test Result: Compliant

DC 12V power by External power supply:

F₀=13.56MHz				
Power Supply(V_{DC})	Temperature (°C)	Measured Frequency (MHz)	Frequency Error (%)	Part 15.225 Limit
12.0	-20	13.5610895	0.00803	±0.01%
	-10	13.5610856	0.00801	±0.01%
	0	13.5610882	0.00803	±0.01%
	+10	13.5610885	0.00803	±0.01%
	+20	13.5610622	0.00783	±0.01%
	+30	13.5605190	0.00383	±0.01%
	+40	13.5604370	0.00322	±0.01%
	+50	13.5600000	0.00000	±0.01%
10.8	+20	13.5606890	0.00508	±0.01%
13.2	+20	13.5609880	0.00729	±0.01%

DC 48V power by POE:

F₀=13.56MHz				
Power Supply(V_{DC})	Temperature (°C)	Measured Frequency (MHz)	Frequency Error (%)	Part 15.225 Limit
48.0	-20	13.5610875	0.00802	±0.01%
	-10	13.5609856	0.00727	±0.02%
	0	13.5610779	0.00795	±0.03%
	+10	13.5609885	0.00729	±0.01%
	+20	13.5608622	0.00636	±0.01%
	+30	13.5608519	0.00628	±0.01%
	+40	13.5607437	0.00548	±0.01%
	+50	13.5608863	0.00654	±0.01%
40.8	+20	13.5608689	0.00641	±0.01%
55.2	+20	13.5609599	0.00708	±0.01%

§15.215(c) - 20dB EMISSION BANDWIDTH TESTING

Requirement

Per 15.215 (c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.

Test Data

Environmental Conditions

Temperature:	24.5℃~24.7℃
Relative Humidity:	48%~50 %
ATM Pressure:	102.3 kPa ~102.5 kPa


The testing was performed by Stone Zhang from 2019-09-17 to 2019-11-21.

Test Mode: Transmitting

Test Result: Compliant


Frequency (MHz)	20 dB Bandwidth (kHz)
0.125	0.457
13.56	3.526

20 dB Emission Bandwidth-125kHz



Date: 21.NOV.2019 09:44:57

20 dB Emission Bandwidth-13.56MHz



Date: 17.SEP.2019 23:27:32

***** END OF REPORT *****