



中认信通

CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



TEST REPORT

Applicant: AKUVOX (XIAMEN) NETWORKS CO., LTD.

Address: 10/F, No.56 Guanri Road, Software Park II, Xiamen 361009, China

FCC ID: 2AHCR-X915SV2

Product Name: Door Phone

Standard(s): 47 CFR Part 15, Subpart C(15.207, 15.209, 15.225)
ANSI C63.10-2013

The above equipment has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: CR230738304-00D

Date Of Issue: 2023/9/21

Reviewed By: Julie Tan

Title: RF Engineer

Julie Tan

Approved By: Sun Zhong

Title: Manager

Sun Zhong

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan,
Guangdong, China

Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

CONTENTS

TEST FACILITY	2
DECLARATIONS.....	2
DOCUMENT REVISION HISTORY	5
1. GENERAL INFORMATION.....	6
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	6
1.2 DESCRIPTION OF TEST CONFIGURATION.....	7
1.2.2 Support Equipment List and Details	7
1.2.3 Support Cable List and Details	7
1.2.4 Block Diagram of Test Setup.....	8
1.3 MEASUREMENT UNCERTAINTY	10
2. SUMMARY OF TEST RESULTS	11
3. REQUIREMENTS AND TEST PROCEDURES	12
3.1 AC LINE CONDUCTED EMISSIONS.....	12
3.1.1 Applicable Standard.....	12
3.1.2 EUT Setup.....	13
3.1.3 EMI Test Receiver Setup	13
3.1.4 Test Procedure	14
3.1.5 Corrected Amplitude & Margin Calculation.....	14
3.2 RADIATED EMISSIONS	15
3.2.1 Applicable Standard.....	15
3.2.2 EUT Setup.....	15
3.2.3 EMI Test Receiver & Spectrum Analyzer Setup	16
3.2.4 Test Procedure	16
3.2.5 Corrected Amplitude & Margin Calculation.....	16
3.3 20 dB EMISSION BANDWIDTH.....	17
3.3.1 Applicable Standard.....	17
3.3.2 EUT Setup.....	17
3.3.3 Test Procedure	17
3.4 FREQUENCY STABILITY.....	18
3.4.1 Applicable Standard.....	18
3.4.2 EUT Setup.....	18
3.4.3 Test Procedure	18
3.5 ANTENNA REQUIREMENT.....	19
3.5.1 Applicable Standard.....	19
3.5.2 Judgment.....	19
4. TEST DATA AND RESULTS	20
4.1 AC LINE CONDUCTED EMISSIONS.....	20
4.2 RADIATION SPURIOUS EMISSIONS	23
4.3 20 dB EMISSION BANDWIDTH	35

4.4 FREQUENCY STABILITY.....	37
5. EUT PHOTOGRAPHS	38
6. TEST SETUP PHOTOGRAPHS	39

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	CR230738304-00D	Original Report	2023/9/21

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	Door Phone
EUT Model:	X915S
Operation Frequency:	13.56 MHz 125 kHz
Modulation Type:	ASK
Rated Input Voltage:	DC 24V From Adapter or DC 48V From POE
Serial Number:	27V8-7
EUT Received Date:	2023/7/5
EUT Received Status:	Good

Antenna Information Detail▲:

13.56 MHz:

Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
Loop	50	13.56MHz	Unknown
The Method of §15.203 Compliance: ☒ Antenna must be permanently attached to the unit. ☐ Antenna must use a unique type of connector to attach to the EUT. ☐ Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.			

125 kHz:

Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
Loop	50	0.125MHz	Unknown
The Method of §15.203 Compliance: ☒ Antenna must be permanently attached to the unit. ☐ Antenna must use a unique type of connector to attach to the EUT. ☐ Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.			

Accessory Information:

Accessory Description	Manufacturer	Model	Parameters
Adapter	KLEC	SW-0692	Input: 100-240VAC, 2.0A, 50-60Hz Output: 24Vdc, 2.5A, 60.0W

1.2 Description of Test Configuration

1.2.1 EUT Operation Condition:

EUT Operation Mode:	The system was configured for testing in Engineering Mode, which was provided by the manufacturer. 125kHz and 13.56MHz was transmission simultaneously. Test was performed with the worst power mode according to BLE test result. (PoE power mode for AC line conducted emission test and Adapter power mode for Radiated emission below 1GHz)
Equipment Modifications:	No
EUT Exercise Software:	No
Engineering Mode was provided by manufacturer▲. The maximum power was configured default setting.	

1.2.2 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
ZIONCOM	Router	MB-R210-00	EMZBWR21103004
AKUVOX	Indoor Monitor	S567W	P1RSC2U000649
Unknown	RS485 Load	RS485-X1	F-EM-PHRJ45X8011
ZKAT	Wiegand card reader	Q-K201D	EMWGCR20220610EN
Unknown	Relay	Relay-C1	EMRLLD20221010EN
Unknown	Switch	Unknown	Unknown
I.T.E	POE	G1080-PoE48G	EMZBPA21206001

1.2.3 Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
DC Cable	No	No	1.5	Adapter	EUT
RJ45 Cable	No	No	1	POE	EUT
RJ45 Cable	No	No	10	Router	POE/EUT
RJ45 Cable	No	No	1	Router	Indoor Monitor
RS485 Cable	No	No	5	EUT	Switch
Signal Cable	No	No	5	EUT	Relay Load
Signal Cable	No	No	5	EUT	Wiegand card reader


1.2.4 Block Diagram of Test Setup

AC line conducted emissions:




Spurious Emissions:

Below 1GHz:



Above 1GHz:



1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
Unwanted Emissions, radiated	9kHz~30MHz: 4.12dB 30M~200MHz: 4.15 dB,200M~1GHz: 5.61 dB,1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB,18G~26.5G:5.47 dB,26.5G~40G:5.63 dB
Temperature	±1℃
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	2.8 dB (150 kHz to 30 MHz)

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC§15.203	Antenna Requirement	Compliant
FCC§15.207 (a)	Conducted Emissions	Compliant
§15.225 §15.209 §15.205	Radiated Emission Test	Compliant
§15.225(e)	Frequency Stability	Compliant
§15.215(c)	20 dB Bandwidth	Compliant

3. REQUIREMENTS AND TEST PROCEDURES

3.1 AC Line Conducted Emissions

3.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:


(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

3.1.2 EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

3.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

3.1.4 Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

According FCC publication number 174176, for a device with a permanent antenna operating at or below 30 MHz, the measurements done with a suitable dummy load, in lieu of the permanent antenna under the following conditions: (1) perform the AC line conducted tests with the permanent antenna to determine compliance with the Section 15.207 limits outside the transmitter's fundamental emission band; (2) retest with a dummy load in lieu of the permanent antenna to determine compliance with the Section 15.207 limits within the transmitter's fundamental emission band.

3.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

3.2 Radiated Emissions


3.2.1 Applicable Standard

As per FCC Part 15.225


- (a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.
- (b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.
- (c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.
- (d) The field strength of any emissions appearing outside of the 13.110–14.010 MHz band shall not exceed the general radiated emission limits in §15.209.

3.2.2 EUT Setup

9kHz-30MHz:



30MHz-1GHz:



The radiated emission tests were performed in the 3-meter chamber test site, using the setup accordance with the ANSI C63.10-2013.

The spacing between the peripherals was 10 cm.

For 9kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

3.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 1 GHz.

During the radiated emission test, the EMI test Receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	Detector
9 kHz – 150 kHz	200 Hz	1 kHz	QP
150 kHz – 30 MHz	9 kHz	30 kHz	QP
30 MHz – 1000 MHz	120 kHz	300 kHz	QP

If the maximized peak measured value complies with the limit, then it is unnecessary to perform an QP measurement

3.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 9kHz-1 GHz.

All emissions under the average limit and under the noise floor have not recorded in the report.

3.2.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = Antenna Factor + Cable Loss- Amplifier Gain

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result


3.3 20 dB Emission Bandwidth

3.3.1 Applicable Standard

FCC §15.215

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §15.217 through § 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of band operation.

3.3.2 EUT Setup



3.3.3 Test Procedure

1. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
2. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.


3.4 Frequency Stability

3.4.1 Applicable Standard

As per FCC Part 15.225:

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to $+50$ degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

3.4.2 EUT Setup



3.4.3 Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power.

The EUT was placed inside the temperature chamber.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the Spectrum Analyzer.

Frequency Stability vs. Voltage: An external variable DC power supply Source. The voltage was set to the end point of the battery. The output frequency was recorded for each voltage.

3.5 Antenna Requirement

3.5.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

3.5.2 Judgment

Please refer to the Antenna Information detail in Section 1.

4. TEST DATA AND RESULTS

4.1 AC Line Conducted Emissions

Serial Number:	27V8-7	Test Date:	2023/07/20
Test Site:	CE	Test Mode:	Transmitting
Tester:	David Huang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.9	Relative Humidity: (%)	71	ATM Pressure: (kPa)	100.8
----------------------	------	---------------------------	----	------------------------	-------


Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101134	2023/03/31	2024/03/30
R&S	EMI Test Receiver	ESR3	102726	2023/03/31	2024/03/30
MICRO-COAX	Coaxial Cable	UTIFLEX	C-0200-01	2022/08/07	2023/08/06
Audix	Test Software	E3	190306 (V9)	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Mode: Transmitting
Port: Line
Note:


Date: 2023-07-20



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.159	32.73	9.61	42.34	55.54	13.20	Average
2	0.159	42.75	9.61	52.36	65.54	13.18	QP
3	0.486	31.70	9.61	41.31	46.23	4.92	Average
4	0.486	42.32	9.61	51.93	56.23	4.30	QP
5	1.133	23.70	9.62	33.32	46.00	12.68	Average
6	1.133	30.69	9.62	40.31	56.00	15.69	QP
7	5.882	23.33	9.66	32.99	50.00	17.01	Average
8	5.882	30.93	9.66	40.59	60.00	19.41	QP
9	10.113	24.17	9.67	33.84	50.00	16.16	Average
10	10.113	31.17	9.67	40.84	60.00	19.16	QP
11	14.020	20.42	9.68	30.10	50.00	19.90	Average
12	14.020	27.17	9.68	36.85	60.00	23.15	QP

Test Mode: Transmitting
Port: neutral
Note:

Date: 2023-07-20



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.154	32.27	9.61	41.88	55.79	13.91	Average
2	0.154	43.01	9.61	52.62	65.79	13.17	QP
3	0.184	25.62	9.61	35.23	54.32	19.09	Average
4	0.184	38.35	9.61	47.96	64.32	16.36	QP
5	0.485	33.04	9.61	42.65	46.26	3.61	Average
6	0.485	42.18	9.61	51.79	56.26	4.47	QP
7	0.843	20.75	9.62	30.37	46.00	15.63	Average
8	0.843	30.80	9.62	40.42	56.00	15.58	QP
9	1.156	21.28	9.62	30.90	46.00	15.10	Average
10	1.156	31.56	9.62	41.18	56.00	14.82	QP
11	6.263	21.50	9.66	31.16	50.00	18.84	Average
12	6.263	31.08	9.66	40.74	60.00	19.26	QP

4.2 Radiation Spurious Emissions

Serial Number:	27V8-7	Test Date:	2023/08/05~2023/08/07
Test Site:	966-2	Test Mode:	Transmitting
Tester:	Vic Du	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	27.1~27.6	Relative Humidity: (%)	65~69	ATM Pressure: (kPa)	99.6~99.9
----------------------	-----------	---------------------------	-------	---------------------------	-----------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
EMCO	Passive Loop Antenna	6512	9706-1209	2023/02/15	2026/02/14
Sunol Sciences	Antenna	JB6	A082520-5	2020/10/19	2023/10/18
R&S	EMI Test Receiver	ESR3	102724	2023/03/31	2024/03/30
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2023/07/16	2024/07/15
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2023/07/16	2024/07/15
Sonoma	Amplifier	310N	186165	2023/07/16	2024/07/15
Audix	Test Software	E3	201021 (V9)	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

1) 9 kHz~30MHz:**Parallel:**


Project No.: CR230738304-RF
Tester: Vic Du
Test Mode: Transmitting
Polarization: Parallel
Note:

Date: 2023-08-05




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.011	2.43	57.18	59.61	126.81	67.20	Peak
2	0.024	1.84	47.82	49.66	120.02	70.36	Peak
3	0.038	8.19	44.02	52.21	116.03	63.82	Peak
4	0.077	15.19	37.53	52.72	109.92	57.20	Peak
5	0.097	18.89	35.41	54.30	107.89	53.59	Peak
6	0.127	34.24	33.70	67.94	105.50	37.56	Peak

Project No.: CR230738304-RF
Tester: Vic Du
Test Mode: Transmitting
Polarization: Parallel
Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.159	18.76	31.91	50.67	103.58	52.91	Peak
2	0.383	25.35	24.35	49.70	95.94	46.24	Peak
3	0.866	34.56	17.96	52.52	68.74	16.22	Peak
4	1.060	37.74	16.52	54.26	66.96	12.70	Peak
5	9.966	33.01	4.45	37.46	69.54	32.08	Peak
6	13.551	71.50	-6.36	65.14	69.54	4.40	Peak


Project No.: CR230738304-RF
Tester: Vic Du
Test Mode: Transmitting
Polarization: Parallel
Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	13.349	49.14	-5.76	43.38	80.51	37.13	Peak
2	13.425	50.87	-5.99	44.88	90.47	45.59	Peak
3	13.490	52.97	-6.19	46.78	90.47	43.69	Peak
4	13.561	71.08	-6.39	64.69	124.00	59.31	Peak
5	13.633	53.28	-6.61	46.67	90.47	43.80	Peak
6	13.698	51.70	-6.80	44.90	90.47	45.57	Peak


Perpendicular:

Project No.: CR230738304-RF
Tester: Vic Du
Test Mode: Transmitting
Polarization: Perpendicular
Note:




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.009	0.25	58.95	59.20	128.40	69.20	Peak
2	0.012	0.80	56.57	57.37	126.27	68.90	Peak
3	0.024	1.26	47.80	49.06	119.99	70.93	Peak
4	0.045	6.22	42.94	49.16	114.54	65.38	Peak
5	0.075	13.56	37.69	51.25	110.09	58.84	Peak
6	0.128	32.66	33.68	66.34	105.48	39.14	Peak

Project No.: CR230738304-RF
Tester: Vic Du
Test Mode: Transmitting
Polarization: Perpendicular
Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.269	26.06	27.13	53.19	99.02	45.83	Peak
2	0.307	26.12	25.87	51.99	97.87	45.88	Peak
3	0.958	39.70	17.24	56.94	67.85	10.91	Peak
4	1.153	37.27	16.00	53.27	66.21	12.94	Peak
5	2.435	34.19	9.96	44.15	69.54	25.39	Peak
6	13.551	69.38	-6.36	63.02	69.54	6.52	Peak


Project No.: CR230738304-RF
Tester: Vic Du
Test Mode: Transmitting
Polarization: Perpendicular
Note:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	13.349	47.92	-5.76	42.16	80.51	38.35	Peak
2	13.423	50.16	-5.98	44.18	90.47	46.29	Peak
3	13.488	52.65	-6.18	46.47	90.47	44.00	Peak
4	13.561	70.03	-6.39	63.64	124.00	60.36	Peak
5	13.635	53.62	-6.61	47.01	90.47	43.46	Peak
6	13.698	52.44	-6.80	45.64	90.47	44.83	Peak


Ground-parallel:

Project No.: CR230738304-RF
Tester: Vic Du
Test Mode: Transmitting
Polarization: Ground-parallel
Note:




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.009	1.01	58.70	59.71	128.18	68.47	Peak
2	0.024	2.10	47.70	49.80	119.89	70.09	Peak
3	0.038	3.35	44.07	47.42	116.08	68.66	Peak
4	0.057	10.58	40.70	51.28	112.46	61.18	Peak
5	0.097	16.11	35.40	51.51	107.87	56.36	Peak
6	0.128	30.91	33.68	64.59	105.48	40.89	Peak

Project No.: CR230738304-RF
Tester: Vic Du
Test Mode: Transmitting
Polarization: Ground-parallel
Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.211	28.95	29.20	58.15	101.14	42.99	Peak
2	0.461	34.66	22.93	57.59	94.33	36.74	Peak
3	1.111	39.33	16.23	55.56	66.54	10.98	Peak
4	2.461	27.16	9.88	37.04	69.54	32.50	Peak
5	10.019	36.77	4.39	41.16	69.54	28.38	Peak
6	13.551	68.33	-6.36	61.97	69.54	7.57	Peak


Project No.: CR230738304-RF
Tester: Vic Du
Test Mode: Transmitting
Polarization: Ground-parallel
Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	13.349	43.21	-5.76	37.45	80.51	43.06	Peak
2	13.423	45.65	-5.98	39.67	90.47	50.80	Peak
3	13.490	47.99	-6.19	41.80	90.47	48.67	Peak
4	13.561	68.48	-6.39	62.09	124.00	61.91	Peak
5	13.632	49.09	-6.60	42.49	90.47	47.98	Peak
6	13.698	48.01	-6.80	41.21	90.47	49.26	Peak


30MHz-1GHz:

Project No.: CR230738304-RF
Tester: Vic Du
Test Mode: Transmitting
Polarization: horizontal
Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	63.536	43.83	-17.06	26.77	40.00	13.23	Peak
2	75.182	48.18	-16.95	31.23	40.00	8.77	Peak
3	164.908	44.23	-12.50	31.73	43.50	11.77	Peak
4	252.063	44.93	-12.98	31.95	46.00	14.05	Peak
5	298.268	42.93	-10.68	32.25	46.00	13.75	Peak
6	839.182	32.24	-1.69	30.55	46.00	15.45	Peak

Project No.: CR230738304-RF
Tester: Vic Du
Test Mode: Transmitting
Polarization: vertical
Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	45.217	42.83	-14.36	28.47	40.00	11.53	Peak
2	63.912	49.21	-17.05	32.16	40.00	7.84	QP
3	84.110	45.22	-17.23	27.99	40.00	12.01	Peak
4	114.917	39.08	-11.90	27.18	43.50	16.32	Peak
5	164.330	42.40	-12.44	29.96	43.50	13.54	Peak
6	298.268	42.83	-10.68	32.15	46.00	13.85	Peak

4.3 20 dB Emission Bandwidth

Serial Number:	27V8-7	Test Date:	2023/08/05~2023/09/20
Test Site:	966-2	Test Mode:	Transmitting
Tester:	Vic Du	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	27~27.6	Relative Humidity: (%)	69~70	ATM Pressure: (kPa)	99.9~100.6
----------------------	---------	---------------------------	-------	---------------------------	------------


Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
EMCO	Passive Loop Antenna	6512	9706-1209	2023/02/15	2026/02/14
R&S	EMI Test Receiver	ESR3	102724	2023/03/31	2024/03/30
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2023/07/16	2024/07/15
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2023/07/16	2024/07/15

*** Statement of Traceability:** China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Test Frequency (MHz)	20 dB Bandwidth (Hz)
13.56	1499
0.125	2907



4.4 Frequency Stability

Serial Number:	27V8-7	Test Date:	2023/08/05
Test Site:	RF	Test Mode:	Transmitting
Tester:	Vic Du	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	27.6	Relative Humidity: (%)	27.6	ATM Pressure: (kPa)	99.9
----------------------	------	---------------------------	------	---------------------------	------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
EMCO	Passive Loop Antenna	6512	9706-1209	2023/02/15	2026/02/14
R&S	EMI Test Receiver	ESR3	102724	2023/03/31	2024/03/30
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2023/03/31	2024/03/30
YINSAIGE	Coaxial Cable	SS402	SJ0300001	Each time	N/A
UNI-T	Multimeter	UT39A+	C210582554	2022/09/29	2023/09/28
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

*** Statement of Traceability:** China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

$f_o = 13.56 \text{ MHz}$				
Temperature	Voltage	Measured frequency	Frequency Error	Limit
°C	V _{AC}	MHz	Hz	Hz
-20	120	13.560891	891	±1356
-10		13.560894	894	±1356
0		13.561028	1028	±1356
10		13.561185	1185	±1356
20		13.561269	1269	±1356
25		13.561154	1154	±1356
30		13.561043	1043	±1356
40		13.560887	887	±1356
50		13.560989	989	±1356
20	138	13.561157	1157	±1356
20	102	13.560936	936	±1356

5. EUT PHOTOGRAPHS

Please refer to the attachment CR230738304-EXP EUT EXTERNAL PHOTOGRAPHS and CR230738304-INP EUT INTERNAL PHOTOGRAPHS

6. TEST SETUP PHOTOGRAPHS

Please refer to the attachment CR230738304-00D-TSP TEST SETUP PHOTOGRAPHS.

******* END OF REPORT *******