



FCC PART 15 B TEST REPORT

For

CONNECTED THINKING LLC

2025 NW 102 Ave, Suite # 104 Miami, FL 33172 USA

FCC ID: 2AHCS-C2

Report Type: Original Report	Product Type: Mobile phone
Test Engineer: Dean Liu	<i>Dean Liu</i>
Report Number: RDG151202003-00B	
Report Date: 2015-12-14	
Reviewed By: Sula Huang RF Leader	<i>Sula Huang</i>
Test Laboratory: Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION	5
EUT EXERCISE SOFTWARE	5
EQUIPMENT MODIFICATIONS	5
LOCAL SUPPORT EQUIPMENT LIST AND DETAILS	5
SUPPORT CABLE LIST AND DETAILS	5
CONFIGURATION OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
FCC§15.107 - CONDUCTED EMISSIONS.....	8
MEASUREMENT UNCERTAINTY	8
EUT SETUP.....	8
EMI TEST RECEIVER SETUP.....	9
TEST EQUIPMENT LIST AND DETAILS.....	9
TEST PROCEDURE	9
CORRECTED AMPLITUDE & MARGIN CALCULATION	9
TEST RESULTS SUMMARY	10
TEST DATA	10
FCC §15.109 - RADIATED SPURIOUS EMISSIONS	13
MEASUREMENT UNCERTAINTY	13
EUT SETUP	13
EMI TEST RECEIVER SETUP.....	14
TEST PROCEDURE	14
TEST EQUIPMENT LIST AND DETAILS.....	15
CORRECTED AMPLITUDE & MARGIN CALCULATION	15
TEST RESULTS SUMMARY	15
TEST DATA	15
ENVIRONMENTAL CONDITIONS.....	15
DECLARATION LETTER.....	20

GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

The *CONNECTED THINKING LLC*'s product, model number: *C2 (FCC ID: 2AHCS-C2)* (the "EUT") in this report was a *Mobile phone*, which was measured approximately: 11.2 cm (L) x 5 cm (W) x 1.3 cm (H), rated input voltage: DC3.7V rechargeable Li-ion battery or DC5.7V charging from adapter.
The highest operating frequency is 2480 MHz.

Adapter information:

Model: TRAVEL CHARGER

Input: AC100-240V, 50/60 Hz, 125mA

Output: DC 5.7V, 800mA

Note: The series product, model C2, C3, C4 are electrically identical, the differences between them is model name, we selected C2 for testing, the details was explained in the attached declaration letter.

All measurement and test data in this report was gathered from production sample serial number: 151202003 (Assigned byBACL, Dongguan). The EUT was received on 2015-12-02.

Objective

This test report is prepared on behalf of *CONNECTED THINKING LLC*. in accordance with Part 2, Subpart J, and Part 15-Subparts A and B of the Federal Communications Commission's rules.

The objective of the manufacturer is to determine the compliance of EUT with FCC Part 15 B Class B.

Related Submittal(s)/Grant(s)

FCC Part 15C DSS submissions with FCC ID: 2AHCS-C2.

FCC Part 22H, 24E PCE submissions with FCC ID: 2AHCS-C2.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FINAL

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a typical fashion (as normally used by a typical user).

EUT Exercise Software

The software “winthrax.exe” was used during test.

Equipment Modifications

No modification was made to the EUT tested.


Local Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
DELL	Laptop	PP11L	QDS-BRCM1017
HP	Printer	C3941A	JPTVOB2337
DELL	Keyboard	L100	CNORH656658907BL05DC
SAST	Modem	AEM-2100	0293
Kingston	Micro SD card	4GB	/

Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
Serial Cable	yes	no	1.2	Serial Port of Laptop	Modem
Parallel Cable	yes	no	1.2	Parallel Port of Laptop	Printer
Keyboard Cable	yes	no	1.8	USB Port of Laptop	Keyboard
USB Cable	yes	no	0.8	USB Port of Laptop	EUT
Earphone Cable	no	no	1.1	Audio Port of EUT	Earphone

Configuration of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§15.107	Conducted Emissions	Compliance
§15.109	Radiated Emissions	Compliance

FINAL

FCC§15.107 - CONDUCTED EMISSIONS

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are Receiver, cable loss, and LISN.

Compliance or non- compliance with a disturbance limit shall be determined in the following manner

FINAL

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15 B Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The adapter of laptop was connected to a 120V/60Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30

FINAL

Herein,

V_C : corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15 B Class B, with the worst margin reading of:

11.60 dB at 0.309742 MHz in the **Line** conducted mode

Test Data


Environmental Conditions

Temperature:	22.8°C
Relative Humidity:	45 %
ATM Pressure:	101.1 kPa

The testing was performed by Dean Liu on 2015-12-10.


Test Mode: Downloading

AC120V, 60Hz, Line:



Frequency (MHz)	Quasi Peak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.150000	51.2	9.000	L1	9.8	14.8	66.0	Compliance
0.426011	39.1	9.000	L1	9.8	18.2	57.3	Compliance
0.439808	39.1	9.000	L1	9.8	18.0	57.1	Compliance
0.532496	39.3	9.000	L1	9.8	16.7	56.0	Compliance
0.805868	34.5	9.000	L1	9.8	21.5	56.0	Compliance
0.831967	32.8	9.000	L1	9.8	23.2	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.192030	34.8	9.000	L1	9.8	19.2	53.9	Compliance
0.216409	30.6	9.000	L1	9.8	22.4	53.0	Compliance
0.266226	32.8	9.000	L1	9.8	18.4	51.2	Compliance
0.309742	38.4	9.000	L1	9.8	11.6	50.0	Compliance
0.528270	25.1	9.000	L1	9.8	20.9	46.0	Compliance
0.619536	30.4	9.000	L1	9.8	15.6	46.0	Compliance

AC120V, 60Hz, Neutral:

Frequency (MHz)	Quasi Peak (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)	Comment
0.150000	50.7	9.000	N	9.8	15.3	66.0	Compliance
0.232499	43.6	9.000	N	9.8	18.8	62.4	Compliance
0.422630	38.5	9.000	N	9.8	18.9	57.4	Compliance
0.439808	39.5	9.000	N	9.8	17.6	57.1	Compliance
0.465037	38.4	9.000	N	9.8	18.2	56.6	Compliance
0.590613	38.7	9.000	N	9.8	17.3	56.0	Compliance

Frequency (MHz)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)	Comment
0.266226	34.4	9.000	N	9.8	16.8	51.2	Compliance
0.307284	38.2	9.000	N	9.8	11.8	50.0	Compliance
0.581275	29.3	9.000	N	9.8	16.7	46.0	Compliance
0.619536	26.0	9.000	N	9.8	20.0	46.0	Compliance
1.239175	26.7	9.000	N	9.8	19.3	46.0	Compliance
1.385415	30.0	9.000	N	9.8	16.0	46.0	Compliance


FCC §15.109 - RADIATED SPURIOUS EMISSIONS

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner

FINAL

Above 1GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2014. The specification used was the FCC Part 15.109 Class B limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 12.5 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	Peak
	1 MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The data was recorded in the Quasi-peak detection mode for below 1 GHz, peak and average detection mode above 1 GHz.

Test Equipment List and Details


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2015-08-03	2016-08-02
Sunol Sciences	Antenna	JB3	A060611-3	2014-11-06	2017-11-05
HP	Amplifier	8447E	2434A02181	2015-09-01	2016-09-01
Agilent	Spectrum Analyzer	E4440A	SG43360054	2015-11-23	2016-11-22
ETS-Lindgren	Horn Antenna	3115	9808-5557	2015-09-06	2018-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2015-02-19	2016-02-19
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations


Test Mode: Downloading

1) Below 1GHz:

Horizontal



Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
30.0000	22.70	QP	1.70	24.40	40.00	15.60
131.8500	31.98	QP	-6.08	25.90	43.50	17.60
287.0500	38.71	QP	-5.61	33.10	46.00	12.90
335.5500	35.28	QP	-4.68	30.60	46.00	15.40
455.8300	33.72	QP	-1.92	31.80	46.00	14.20
728.4000	34.11	QP	2.09	36.20	46.00	9.80


Vertical

Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
30.0000	33.90	QP	1.70	35.60	40.00	4.40*
34.8500	31.87	QP	-2.17	29.70	40.00	10.30
287.0500	40.71	QP	-5.61	35.10	46.00	10.90
348.1600	36.80	QP	-4.30	32.50	46.00	13.50
398.6000	33.12	QP	-3.22	29.90	46.00	16.10
432.5500	35.16	QP	-2.56	32.60	46.00	13.40

*Within uncertainty measurement!


2) Above 1GHz:

Horizontal



Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1062.500	40.04	peak	-1.13	38.91	74.00	35.09
1062.500	27.78	Ave	-1.13	26.65	54.00	27.35
1197.500	38.87	peak	-1.16	37.71	74.00	36.29
1197.500	26.64	Ave	-1.16	25.48	54.00	28.52
1597.500	40.62	peak	-1.45	39.17	74.00	34.83
1597.500	28.51	Ave	-1.45	27.06	54.00	26.94

Note: For above 6 GHz, no emissions were detected.

Vertical

Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1062.500	47.11	peak	-1.13	45.98	74.00	28.02
1062.500	34.67	Ave	-1.13	33.54	54.00	20.46
1597.500	43.54	peak	-1.45	42.09	74.00	31.91
1597.500	31.16	Ave	-1.45	29.71	54.00	24.29
2125.000	39.82	peak	0.79	40.61	74.00	33.39
2125.000	27.58	Ave	0.79	28.37	54.00	25.63

Note: For above 6 GHz, no emissions were detected.

DECLARATION LETTER

CONNECTED THINKING LLC

2025 NW 102 Ave, Suite # 104 Miami, FL 33172 USA

Contact Phone: (305) 810-4016 Contact Fax: (305) 810-4016

Product Similarity Declaration

Date: 2016-01-26

To Whom It May Concern,

We, CONNECTED THINKING LLC, hereby declare that our product Mobile phone, Model Number: C2, C3, C4 are electrically identical with the same electromagnetic emissions and electromagnetic compatibility characteristics. Model Number: C3, C4 are electrically identical with the Model Number: C2 that was certified by BACL. Their only difference is the model name.

The rest are the same.

Please contact me if you have any question.

Signature:

Mr.Cristian Wazani
General Manager



*****END OF REPORT*****