

FCC Report (Bluetooth)

Applicant: Grandex International Corporation

Address of Applicant: 4F, No.525, Zhongzheng Rd., Xindian Dist., New Taipei City 23148, Taiwan (R.O.C.)

Manufacturer: Grandex International Corporation

Address of Manufacturer: 4F, No.525, Zhongzheng Rd., Xindian Dist., New Taipei City 23148, Taiwan (R.O.C.)

Equipment Under Test (EUT)

Product Name: MeatProbe Extender

Model No.: BR200

Trade Mark: Grandex

FCC ID: 2AHDSBR200-01

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of sample receipt: December 18, 2018

Date of Test: December 19, 2018-March 18, 2019

Date of report issued: March 18, 2019

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Robinson Lo

Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	March 18, 2019	Original

Prepared By:

Bill. Yuan

Date:

March 18, 2019

Project Engineer

Check By:

Robinson

Date:

March 18, 2019

Reviewer

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	7
5.3 DESCRIPTION OF SUPPORT UNITS	7
5.4 TEST FACILITY	7
5.5 TEST LOCATION	7
6 TEST INSTRUMENTS LIST	8
7 TEST RESULTS AND MEASUREMENT DATA	10
7.1 ANTENNA REQUIREMENT	10
7.2 CONDUCTED OUTPUT POWER	11
7.3 CHANNEL BANDWIDTH	13
7.4 POWER SPECTRAL DENSITY	15
7.5 BAND EDGES	17
7.5.1 Conducted Emission Method	17
7.5.2 Radiated Emission Method	18
7.6 SPURIOUS EMISSION	23
7.6.1 Conducted Emission Method	23
7.6.2 Radiated Emission Method	25
8 TEST SETUP PHOTO	36
9 EUT CONSTRUCTIONAL DETAILS	36

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	N/A
Conducted Output Power	15.247 (b)(3)	Pass
Channel Bandwidth	15.247 (a)(2)	Pass
Power Spectral Density	15.247 (e)	Pass
Band Edge	15.247(d)	Pass
Spurious Emission	15.205/15.209	Pass

Remarks:

1. Pass: The EUT complies with the essential requirements in the standard.
2. N/A: Not applicable.
3. Test according to ANSI C63.10:2013

Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz ~ 30MHz	$\pm 4.54\text{dB}$	(1)
Radiated Emission	30MHz ~ 1000MHz	$\pm 5.34\text{dB}$	(1)
Radiated Emission	1GHz ~ 26.5GHz	$\pm 5.34\text{dB}$	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	$\pm 3.44\text{dB}$	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

5 General Information

5.1 General Description of EUT

Product Name:	MeatProbe Extender
Model No.:	BR200
Test sample(s) ID:	GTS201812000109-1
Sample(s) Status	Engineer sample
Serial No.:	B20029124
Hardware version:	MPB-BR200XX-01A-MAXN VER:1.2 88281
Software version:	BR200_vB1.4
Operation Frequency:	2402MHz~2480MHz
Channel Numbers:	40
Channel Separation:	2MHz
Modulation Type:	GFSK
Antenna Type:	Integral Antenna
Antenna Gain:	0dBi(Declared by applicant)
Power Supply:	DC 3V (2*1.5V Size "AA" battery)

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	11	2422MHz	21	2442MHz	31	2462MHz
2	2404MHz	12	2424MHz	22	2444MHz	32	2464MHz
3	2406MHz	13	2426MHz	23	2446MHz	33	2466MHz
⋮	⋮	⋮	⋮	⋮	⋮	⋮	⋮
9	2418MHz	19	2438MHz	29	2458MHz	39	2478MHz
10	2420MHz	20	2440MHz	30	2460MHz	40	2480MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2426MHz
The Highest channel	2480MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode
<i>Remark: New battery is used during all test</i>	

5.3 Description of Support Units

None.

5.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations: • FCC —Registration No.: 381383 Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383. • Industry Canada (IC) —Registration No.: 9079A-2 The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2. • NVLAP (LAB CODE:600179-0) Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP). LAB CODE:600179-0
--

5.5 Test Location

All tests were performed at:
Global United Technology Services Co., Ltd. Address: No. 301-309, 3/F, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960

6 Test Instruments list


Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 03 2015	July. 02 2020
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 27 2018	June. 26 2019
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 27 2018	June. 26 2019
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June. 27 2018	June. 26 2019
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 27 2018	June. 26 2019
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 27 2018	June. 26 2019
9	Coaxial Cable	GTS	N/A	GTS211	June. 27 2018	June. 26 2019
10	Coaxial cable	GTS	N/A	GTS210	June. 27 2018	June. 26 2019
11	Coaxial Cable	GTS	N/A	GTS212	June. 27 2018	June. 26 2019
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 27 2018	June. 26 2019
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	June. 27 2018	June. 26 2019
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 27 2018	June. 26 2019
15	Band filter	Amindeon	82346	GTS219	June. 27 2018	June. 26 2019
16	Power Meter	Anritsu	ML2495A	GTS540	June. 27 2018	June. 26 2019
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 27 2018	June. 26 2019
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	June. 27 2018	June. 26 2019
19	Splitter	Agilent	11636B	GTS237	June. 27 2018	June. 26 2019
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 27 2018	June. 26 2019
21	Breitband hornantenne	SCHWARZBECK	BBHA 9170	GTS579	Oct. 20 2018	Oct. 19 2019
22	Amplifier	TDK	PA-02-02	GTS574	Oct. 20 2018	Oct. 19 2019
23	Amplifier	TDK	PA-02-03	GTS576	Oct. 20 2018	Oct. 19 2019
24	PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	GTS578	June. 27 2018	June. 26 2019

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	June. 27 2018	June. 26 2019
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 27 2018	June. 26 2019
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June. 27 2018	June. 26 2019
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	June. 27 2018	June. 26 2019
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	June. 27 2018	June. 26 2019
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	June. 27 2018	June. 26 2019
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	June. 27 2018	June. 26 2019
8	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 27 2018	June. 26 2019
9	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	June. 27 2018	June. 26 2019


General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Humidity/ Temperature Indicator	KTJ	TA328	GTS243	June. 27 2018	June. 26 2019
2	Barometer	ChangChun	DYM3	GTS255	June. 27 2018	June. 26 2019

7 Test results and Measurement Data

7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
E.U.T Antenna: <i>The antenna is integral antenna, the best case gain of the antenna is 0dBi.</i>	
	


7.2 Conducted Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V05
Limit:	30dBm
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data

Test channel	Peak Output Power (dBm)	Limit(dBm)	Result
Lowest	-0.741	30.00	Pass
Middle	-3.042		
Highest	-5.898		


Test plot as follows:



Lowest channel




Middle channel



Highest channel


7.3 Channel Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V05
Limit:	>500KHz
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data

Test channel	6dB Bandwidth (MHz)	Limit(KHz)	Result
Lowest	0.628	>500	Pass
Middle	0.684		
Highest	0.706		


Test plot as follows:



Lowest channel




Middle channel



Highest channel


7.4 Power Spectral Density

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V05
Limit:	8dBm/3kHz
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data

Test channel	Power Spectral Density (dBm/3kHz)	Limit(dBm/3kHz)	Result
Lowest	-14.601	8.00	Pass
Middle	-19.498		
Highest	-20.335		


Test plot as follows:



Lowest channel




Middle channel




Highest channel

7.5 Band edges

7.5.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V05
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Test plot as follows:




Lowest channel



Highest channel


7.5.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above 1GHz	Peak	1MHz	3MHz	Peak
		RMS	1MHz	3MHz	Average
Limit:	Frequency		Limit (dBuV/m @3m)		Value
	Above 1GHz		54.00		Average
			74.00		Peak
Test setup:					
Test Procedure:	1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 7. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.				

Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data

Mode:	Transmitting mode	Test channel:	Lowest channel
Temp./Hum.(%RH):	26°C/56%RH	Polarization:	Horizontal




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
2310.000	39.14	27.14	6.19	42.04	30.43	54.00	-23.57	Average
2310.000	49.77	27.14	6.19	42.04	41.06	74.00	-32.94	Peak
2390.000	40.05	27.37	6.31	42.11	31.62	54.00	-22.38	Average
2390.000	51.86	27.37	6.31	42.11	43.43	74.00	-30.57	Peak

Mode:	Transmitting mode	Test channel:	Lowest channel
Temp./Hum.(%H):	26°C/56%RH	Polarization:	Vertical




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
2310.000	39.01	27.14	6.19	42.04	30.30	54.00	-23.70	Average
2310.000	50.83	27.14	6.19	42.04	42.12	74.00	-31.88	Peak
2390.000	39.45	27.37	6.31	42.11	31.02	54.00	-22.98	Average
2390.000	51.27	27.37	6.31	42.11	42.84	74.00	-31.16	Peak

Mode:	Transmitting mode	Test channel:	Highest channel
Temp./Hum.(%H):	26°C/56%RH	Polarization:	Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
2483.500	41.68	27.66	6.45	42.01	33.78	54.00	-20.22	Average
2483.500	54.40	27.66	6.45	42.01	46.50	74.00	-27.50	Peak
2500.000	39.39	27.70	6.47	42.00	31.56	54.00	-22.44	Average
2500.000	50.89	27.70	6.47	42.00	43.06	74.00	-30.94	Peak

Mode:	Transmitting mode	Test channel:	Highest channel
Temp./Hum.(%H):	26°C/56%RH	Polarization:	Vertical




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
2483.500	39.75	27.66	6.45	42.01	31.85	54.00	-22.15	Average
2483.500	50.10	27.66	6.45	42.01	42.20	74.00	-31.80	Peak
2500.000	39.25	27.70	6.47	42.00	31.42	54.00	-22.58	Average
2500.000	51.08	27.70	6.47	42.00	43.25	74.00	-30.75	Peak

Remarks:


1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.

7.6 Spurious Emission

7.6.1 Conducted Emission Method


Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V05
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 The diagram illustrates the test setup for conducted emission measurement. A Spectrum Analyzer is connected via a red cable to an E.U.T (Equipment Under Test). Both are placed on a Non-Conducted Table, which is supported by two vertical legs. Below the table is a Ground Reference Plane, represented by a thick grey bar.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Test plot as follows:
Lowest channel




30MHz~25GHz

Middle channel




30MHz~25GHz



Highest channel



30MHz~25GHz

7.6.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	PK,AV,QP	200Hz	600Hz	PK,AV,QP
	150KHz-30MHz	PK,AV,QP	9KHz	30KHz	PK,AV,QP
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Limit (uV/m)	Value	Measurement Distance	
	0.009MHz-0.490MHz	2400/F(KHz)	PK,AV,QP	300m	
	0.490MHz-1.705MHz	24000/F(KHz)	QP	30m	
	1.705MHz-30MHz	30	QP	30m	
	30MHz-88MHz	100	QP	3m	
	88MHz-216MHz	150	QP		
	216MHz-960MHz	200	QP		
	960MHz-1GHz	500	QP		
	Above 1GHz	500	Average		
		5000	Peak		
Test setup:	For radiated emissions from 9kHz to 30MHz				
					

	For radiated emissions from 30MHz to 1GHz  For radiated emissions above 1GHz 
Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the

	limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test voltage:	DC 3V
Test results:	Pass

Measurement data:*Remark:*


Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

■ 9kHz~30MHz

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.


■ Below 1GHz

Mode:	Transmitting mode	Polarization:	Horizontal
-------	-------------------	---------------	------------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
34.639	38.30	11.29	0.61	35.33	14.87	40.00	-25.13	QP
42.302	37.90	12.23	0.69	35.79	15.03	40.00	-24.97	QP
97.798	34.69	11.93	1.17	36.70	11.09	43.50	-32.41	QP
244.232	33.71	11.96	2.09	37.37	10.39	46.00	-35.61	QP
595.133	33.52	19.39	3.70	37.54	19.07	46.00	-26.93	QP
801.786	33.65	21.40	4.46	37.62	21.89	46.00	-24.11	QP


Mode:	Transmitting mode	Polarization:	Vertical
-------	-------------------	---------------	----------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
36.766	38.65	11.64	0.63	35.47	15.45	40.00	-24.55	QP
40.845	38.10	12.21	0.67	35.71	15.27	40.00	-24.73	QP
96.099	37.07	11.65	1.16	36.69	13.19	43.50	-30.31	QP
167.824	44.74	8.46	1.67	37.18	17.69	43.50	-25.81	QP
216.024	39.47	11.02	1.93	37.35	15.07	46.00	-30.93	QP
638.369	34.79	19.54	3.87	37.58	20.62	46.00	-25.38	QP


■ Above 1GHz

Mode:	Transmitting mode	Test channel:	Lowest channel
Temp./Hum.(%RH):	26°C/56%RH	Polarization:	Horizontal




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
4804.000	27.34	31.20	9.36	37.58	30.32	54.00	-23.68	Average
4804.000	35.72	31.20	9.36	37.58	38.70	74.00	-35.30	Peak
7206.000	33.28	36.16	11.21	35.44	45.21	54.00	-8.79	Average
7206.000	39.48	36.16	11.21	35.44	51.41	74.00	-22.59	Peak
9608.000	22.33	37.93	12.91	34.96	38.21	54.00	-15.79	Average
9608.000	32.66	37.93	12.91	34.96	48.54	74.00	-25.46	Peak
12010.000	21.20	38.50	14.54	36.40	37.84	54.00	-16.16	Average
12010.000	31.62	38.50	14.54	36.40	48.26	74.00	-25.74	Peak
14412.000	18.06	41.48	16.11	36.14	39.51	54.00	-14.49	Average
14412.000	28.94	41.48	16.11	36.14	50.39	74.00	-23.61	Peak
16814.000	18.58	39.54	17.47	36.20	39.39	54.00	-14.61	Average
16814.000	30.40	39.54	17.47	36.20	51.21	74.00	-22.79	Peak

Mode:	Transmitting mode	Test channel:	Lowest channel
Temp./Hum.(%RH):	26°C/56%RH	Polarization:	Vertical




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
4804.000	26.59	31.20	9.36	37.58	29.57	54.00	-24.43	Average
4804.000	34.86	31.20	9.36	37.58	37.84	74.00	-36.16	Peak
7206.000	27.45	36.16	11.21	35.44	39.38	54.00	-14.62	Average
7206.000	38.01	36.16	11.21	35.44	49.94	74.00	-24.06	Peak
9608.000	22.18	37.93	12.91	34.96	38.06	54.00	-15.94	Average
9608.000	32.64	37.93	12.91	34.96	48.52	74.00	-25.48	Peak
12010.000	21.46	38.50	14.54	36.40	38.10	54.00	-15.90	Average
12010.000	31.65	38.50	14.54	36.40	48.29	74.00	-25.71	Peak
14412.000	19.34	41.48	16.11	36.14	40.79	54.00	-13.21	Average
14412.000	29.63	41.48	16.11	36.14	51.08	74.00	-22.92	Peak
16814.000	19.20	39.54	17.47	36.20	40.01	54.00	-13.99	Average
16814.000	29.96	39.54	17.47	36.20	50.77	74.00	-23.23	Peak

Mode:	Transmitting mode	Test channel:	Middle channel
Temp./Hum.(%RH):	26°C/56%RH	Polarization:	Horizontal




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
4852.000	27.64	31.26	9.40	37.59	30.71	54.00	-23.29	Average
4852.000	34.63	31.26	9.40	37.59	37.70	74.00	-36.30	Peak
7278.000	28.62	36.34	11.27	35.46	40.77	54.00	-13.23	Average
7278.000	37.87	36.34	11.27	35.46	50.02	74.00	-23.98	Peak
9704.000	23.47	38.03	12.97	35.04	39.43	54.00	-14.57	Average
9704.000	32.29	38.03	12.97	35.04	48.25	74.00	-25.75	Peak
12130.000	20.98	38.54	14.62	36.43	37.71	54.00	-16.29	Average
12130.000	31.19	38.54	14.62	36.43	47.92	74.00	-26.08	Peak
14556.000	19.20	41.30	16.19	35.98	40.71	54.00	-13.29	Average
14556.000	30.12	41.30	16.19	35.98	51.63	74.00	-22.37	Peak
16982.000	20.08	39.70	17.55	36.38	40.95	54.00	-13.05	Average
16982.000	30.51	39.70	17.55	36.38	51.38	74.00	-22.62	Peak

Mode:	Transmitting mode	Test channel:	Middle channel
Temp./Hum.(%H):	26°C/56%RH	Polarization:	Vertical




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
4852.000	27.35	31.26	9.40	37.59	30.42	54.00	-23.58	Average
4852.000	34.68	31.26	9.40	37.59	37.75	74.00	-36.25	Peak
7278.000	27.57	36.34	11.27	35.46	39.72	54.00	-14.28	Average
7278.000	36.70	36.34	11.27	35.46	48.85	74.00	-25.15	Peak
9704.000	23.71	38.03	12.97	35.04	39.67	54.00	-14.33	Average
9704.000	32.32	38.03	12.97	35.04	48.28	74.00	-25.72	Peak
12130.000	24.37	38.54	14.62	36.43	41.10	54.00	-12.90	Average
12130.000	33.75	38.54	14.62	36.43	50.48	74.00	-23.52	Peak
14556.000	22.91	41.30	16.19	35.98	44.42	54.00	-9.58	Average
14556.000	31.14	41.30	16.19	35.98	52.65	74.00	-21.35	Peak
16982.000	20.04	39.70	17.55	36.38	40.91	54.00	-13.09	Average
16982.000	29.53	39.70	17.55	36.38	50.40	74.00	-23.60	Peak

Mode:	Transmitting mode	Test channel:	Highest channel
Temp./Hum.(%RH):	26°C/56%RH	Polarization:	Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
4960.000	27.53	31.44	9.48	37.60	30.85	54.00	-23.15	Average
4960.000	34.49	31.44	9.48	37.60	37.81	74.00	-36.19	Peak
7440.000	26.51	36.66	11.39	35.49	39.07	54.00	-14.93	Average
7440.000	35.90	36.66	11.39	35.49	48.46	74.00	-25.54	Peak
9920.000	22.63	38.30	13.13	35.23	38.83	54.00	-15.17	Average
9920.000	31.95	38.30	13.13	35.23	48.15	74.00	-25.85	Peak
12400.000	23.64	38.66	14.80	36.48	40.62	54.00	-13.38	Average
12400.000	32.91	38.66	14.80	36.48	49.89	74.00	-24.11	Peak
14880.000	19.82	40.60	16.38	35.63	41.17	54.00	-12.83	Average
14880.000	29.33	40.60	16.38	35.63	50.68	74.00	-23.32	Peak
17360.000	18.91	41.52	17.75	36.36	41.82	54.00	-12.18	Average
17360.000	27.54	41.52	17.75	36.36	50.45	74.00	-23.55	Peak

Mode:	Transmitting mode	Test channel:	Highest channel
Temp./Hum.(%H):	26°C/56%RH	Polarization:	Vertical



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
4960.000	26.83	31.44	9.48	37.60	30.15	54.00	-23.85	Average
4960.000	34.48	31.44	9.48	37.60	37.80	74.00	-36.20	Peak
7440.000	25.35	36.66	11.39	35.49	37.91	54.00	-16.09	Average
7440.000	34.97	36.66	11.39	35.49	47.53	74.00	-26.47	Peak
9920.000	21.90	38.30	13.13	35.23	38.10	54.00	-15.90	Average
9920.000	30.78	38.30	13.13	35.23	46.98	74.00	-27.02	Peak
12400.000	23.00	38.66	14.80	36.48	39.98	54.00	-14.02	Average
12400.000	31.39	38.66	14.80	36.48	48.37	74.00	-25.63	Peak
14880.000	20.29	40.60	16.38	35.63	41.64	54.00	-12.36	Average
14880.000	29.37	40.60	16.38	35.63	50.72	74.00	-23.28	Peak
17360.000	19.25	41.52	17.75	36.36	42.16	54.00	-11.84	Average
17360.000	29.03	41.52	17.75	36.36	51.94	74.00	-22.06	Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----