

RF EXPOSURE EVALUATION METHOD

FCC ID: 2AHDY-T2

SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Maximum measured transmitter power.

WIFI:

TX 802.11b Mode				
Test Channel	Frequency	Duty Cycle	Maximum Conducted Output Power(AV)	LIMIT
	(MHz)	(%)	(dBm)	dBm
CH01	2412	98.71	9.44	8.790
CH06	2437	98.75	9.73	9.397
CH11	2462	98.69	9.39	8.690
TX 802.11g Mode				
CH01	2412	91.33	7.09	5.117
CH06	2437	91.32	7.21	5.260
CH11	2462	91.30	6.48	4.446
TX 802.11n(20) Mode				
CH01	2412	90.77	5.43	3.491
CH06	2437	90.75	5.66	3.681
CH11	2462	90.72	5.65	3.673
TX 802.11n(40) Mode				
CH03	2422	85.16	4.20	2.630
CH06	2437	85.15	4.70	2.951
CH09	2452	85.15	4.18	2.618

Remark: The best case gain of the antenna is 1.0dBi.

1.0 dBi logarithmic terms convert to numeric result is nearly 1.26

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$$

WIFI:

Test Channel	Range	tune up max power (dBm)	[(max. power of channel, including tune-up tolerance, mW)	(min. test separation distance, mm)]	[f(GHz)]	Result	Limit
TX 802.11b Mode							
CH01	7.8~9.8	9.8	9.550	5	2.412	2.97	3
CH06	7.8~9.8	9.8	9.550	5	2.437	2.98	3
CH11	7.6~9.6	9.6	9.120	5	2.462	2.86	3
TX 802.11g Mode							
CH01	6.0~8.0	8.0	6.310	5	2.412	1.96	3
CH06	6.0~8.0	8.0	6.310	5	2.437	1.97	3
CH11	6.0~8.0	8.0	6.310	5	2.462	1.98	3
TX 802.11n-HT20 Mode							
CH01	4.0~6.0	6.0	3.981	5	2.412	1.24	3
CH06	4.0~6.0	6.0	3.981	5	2.437	1.24	3
CH11	4.0~6.0	6.0	3.981	5	2.462	1.25	3
TX 802.11n-HT40 Mode							
CH03	4.0~6.0	6.0	3.981	5	2.422	1.24	3
CH06	4.0~6.0	6.0	3.981	5	2.437	1.24	3
CH09	4.0~6.0	6.0	3.981	5	2.452	1.25	3

The test Result is less than 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Conclusion: No SAR is required.