

FCC TEST REPORT

Product Name: Tablet 10.1 inch Android 10
Trade Mark: Compumax
Model No.: BlueS10
Report Number: 201211012EMC-1
Test Standards: FCC 47 CFR Part 15 Subpart B
Test Result: PASS
Date of Issue: January 28, 2021

Prepared for:

Compumax Computer S.A.S
Calle 41 N 35-47 Bucaramanga, Santander, Colombia

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
16/F, Block A, Building 6, Baoneng Science and Technology Park,
Qingxiang Road No.1, Longhua New District, Shenzhen, China
TEL: +86-755-2823 0888
FAX: +86-755-2823 0886

Prepared by:



Henry Lu
Team Leader

Reviewed by:



Kevin Liang
Assistant Manager

Approved by:



Billy Li
Technical Director

Date:

January 28, 2021

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-FCCPART15B-V1.0

Version

Version No.	Date	Description
V1.0	January 28, 2021	Original



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-FCCPART15B-V1.0

CONTENTS

1. GENERAL INFORMATION	4
1.1 CLIENT INFORMATION	4
1.2 EUT INFORMATION	4
1.2.1 GENERAL DESCRIPTION OF EUT	4
1.2.2 DESCRIPTION OF ACCESSORIES	4
1.3 DESCRIPTION OF SUPPORT UNITS	5
1.4 TEST LOCATION	5
1.5 TEST FACILITY	5
1.6 DEVIATION FROM STANDARDS	6
1.7 ABNORMALITIES FROM STANDARD CONDITIONS	6
1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
1.9 MEASUREMENT UNCERTAINTY	6
2. TEST SUMMARY	7
3. EQUIPMENT LIST	7
4. TEST CONFIGURATION	8
4.1 ENVIRONMENTAL CONDITIONS FOR TESTING	8
4.1.1 NORMAL OR EXTREME TEST CONDITIONS	8
4.1.2 RECORD OF NORMAL ENVIRONMENT	8
4.2 TEST MODES	8
4.3 TEST SETUP	9
4.3.1 FOR RADIATED EMISSIONS TEST SETUP	9
4.3.2 FOR CONDUCTED EMISSIONS TEST SETUP	10
4.4 SYSTEM TEST CONFIGURATION	10
5. REFERENCE DOCUMENTS FOR TESTING	11
6. EMC REQUIREMENTS SPECIFICATION	11
6.1 RADIATED EMISSION	11
6.2 CONDUCTED EMISSION	16
APPENDIX 1 PHOTOS OF TEST SETUP	19
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS	19

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	Compumax Computer S.A.S
Address of Applicant:	Calle 41 N 35-47 Bucaramanga, Santander, Colombia
Manufacturer:	Xiamen Candour Co., Ltd.
Address of Manufacturer:	C&D International Building, No.1699 Huandao East Road,Xiamen,China

1.2 EUT INFORMATION

1.2.1 General Description of EUT

Product Name:	Tablet 10.1 inch Android 10
Model No.:	BlueS10
Trade Mark:	Compumax
DUT Stage:	Production Unit
Rated Voltage:	☒ Battery: 3.8VDC (1x3.8V battery)
	☒ 100-240V~50/60Hz
	☒ Powered by USB port (5Vdc)
Classification of digital devices:	Class B
Highest Internal Frequency:	5825 MHz
Sample Received Date:	December 16, 2020
Sample Tested Date:	January 18, 2021 to January 20, 2021

1.2.2 Description of Accessories

Adapter	
Model No.:	JK055180-S37USV
Input:	100-240 V~50/60 Hz 0.5 A
Output:	5.5 V $\overline{\text{---}}$ 1.8 A 9.9 W
Manufacturer:	SHENZHEN JUKE ELECTRONICS CO.,LTD

Battery	
Model No.:	2898140-6200mAh-3.8V
Battery Type:	Lithium-ion Polymer Rechargeable Battery
Rated Voltage:	3.8 Vdc
Limited Charge Voltage:	4.4 Vdc
Rated Capacity:	6200 mAh
Manufacturer:	Guangdong Yongbang New Energy Co., Ltd

DC Cable	
Description:	DC port
Cable Type:	Unshielded without ferrite
Length:	1.0 Meter

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com
<http://www.uttlab.com>

UTTR-EMC-FCCPART15B-V1.0

1.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

1) Support Equipment

Description	Manufacturer	Model No.	Serial Number	Supplied by
Notebook	Lenovo	E450	SL10G10780	UnionTrust
Mouse	DELL	MS111	CN-011D3V-738	UnionTrust
Earphone	N/A	QTER01JY	N/A	UnionTrust
SD card	Transcend	microSD	N/A	UnionTrust
Monitor	HKC	M216AF	BOG20180003	UnionTrust

2) Support Cable

Cable No.	Description	Connector	Length	Supplied by
1	Unshielded without ferrite	HDMI	3.0 Meter	UnionTrust
2	Unshielded without ferrite	USB Type-C Plug Cable	1.0 Meter	UnionTrust

1.4 TEST LOCATION

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China 518109

Telephone: +86 (0) 755 2823 0888

Fax: +86 (0) 755 2823 0886

1.5 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L9069

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC/EN 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

A2LA-Lab Certificate No.: 4312.01

Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

ISED Wireless Device Testing Laboratories

CAB identifier: CN0032

FCC Accredited Lab.

Designation Number: CN1194

Test Firm Registration Number: 259480

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-FCCPART15B-V1.0

1.6 DEVIATION FROM STANDARDS

None.

1.7 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

1.9 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Measurement Uncertainty
1	Conducted emission 9KHz-150KHz	±3.2 dB
2	Conducted emission 150KHz-30MHz	±2.7 dB
3	Radiated emission 9KHz-30MHz	± 4.7 dB
4	Radiated emission 30MHz-1GHz	± 4.6 dB
5	Radiated emission 1GHz-18GHz	± 4.4 dB
6	Radiated emission 18GHz-26GHz	± 4.6 dB
7	Radiated emission 26GHz-40GHz	± 4.6 dB

2. TEST SUMMARY

FCC 47 CFR Part 15 Subpart B Test Cases			
Test Item	Test Requirement	Test Method	Result
Conducted Emission	FCC 47 CFR Part 15.107	ANSI C63.4-2014	PASS
Radiated Emission	FCC 47 CFR Part 15.109	ANSI C63.4-2014	PASS

3. EQUIPMENT LIST

Radiated Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
☒	3M Chamber & Accessory Equipment	ETS-LINDGREN	3M	N/A	Dec. 03, 2018	Dec. 03, 2021
☒	Receiver	R&S	ESIB26	100114	Nov. 18, 2020	Nov. 18, 2021
☐	Loop Antenna	ETS-LINDGREN	6502	00202525	Nov. 14, 2020	Nov. 13, 2021
☒	Broadband Antenna	ETS-LINDGREN	3142E	00201566	Nov. 14, 2020	Nov. 13, 2021
☒	6dB Attenuator	Talent	RA6A5-N-18	18103001	Nov. 14, 2020	Nov.13, 2021
☒	Preamplifier	HP	8447F	2805A02960	Nov. 10, 2020	Nov. 9, 2021
☐	Broadband Antenna (Pre-amplifier)	ETS-LINDGREN	3142E-PA	00201891	May. 30, 2020	May. 29, 2021
☐	6dB Attenuator	Talent	RA6A5-N-18	18103002	Nov. 18, 2020	Nov. 17, 2021
☐	Horn Antenna	ETS-LINDGREN	3117	00164202	Nov. 14, 2020	Nov. 13, 2021
☒	Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3117-PA	00201874	May. 30, 2020	May. 29, 2021
☐	Horn Antenna	ETS-LINDGREN	3116C	00200180	Jun.19, 2020	Jun. 18, 2021
☒	Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3116C-PA	00202652	Nov. 17, 2020	Nov. 16, 2021
☒	Multi device Controller	ETS-LINDGREN	7006-001	00160105	N/A	N/A
☒	Test Software	Audix	e3	Software Version: 9.160323		

Conducted Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
☒	Receiver	R&S	ESR7	1316.3003K07-101181-K3	Nov. 18, 2020	Nov.18, 2021
☒	Pulse Limiter	R&S	ESH3-Z2	0357.8810.54	Nov. 18, 2020	Nov.18, 2021
☒	LISN	R&S	ESH2-Z5	860014/024	Nov. 18, 2020	Nov.18, 2021
☐	LISN	ETS-Lindgren	3816/2SH	00201088	Nov. 18, 2020	Nov.23, 2021
☒	Test Software	Audix	e3	Software Version: 9.160323		

4. TEST CONFIGURATION

4.1 ENVIRONMENTAL CONDITIONS FOR TESTING

4.1.1 Normal or Extreme Test Conditions

Environment Parameter	Selected Values During Tests		
Test Condition	Ambient		
	Temperature (°C)	Voltage (V)	Relative Humidity (%)
NT/NV	+15 to +35	1. 120~60Hz and/or 3.8V battery 2. 240~50Hz and/or 3.8V battery	20 to 75
Remark: 1) NV: Normal Voltage; NT: Normal Temperature			

4.1.2 Record of Normal Environment


Test Item	Temperature (°C)	Relative Humidity (%)	Pressure (kPa)	Tested by
Conducted Emission	24.3	41	99.87	Asia Yan
Radiated Emission	22.8	35	100.05	Lucas Ouyang

4.2 TEST MODES

Test Item	EMI Test Modes
Radiated Emission	Mode 1: Charging from 120 Vac + MP4 playing (With TF Card) + Earphone+ HDMI OUT Mode 2: Charging from 120 Vac + Camera (Front)+ With TF Card + HDMI OUT Mode 3: Charging from 120 Vac + Camera (Rear) + With TF Card+ HDMI OUT Mode 4: Charging from 120 Vac + FM (With Earphone) +Light on Mode 5: Charging from 120 Vac(USB type C)+ Worse from mode 1~4 Mode 6: Charging from 240 Vac + Worse from mode 1~4 Mode 7: Battery + Worse from mode 1~4 Mode 8: USB Cable (data transfer with notebook) + With TF Card
Conducted Emission	Mode 1: Charging from 120 Vac + MP4 playing (With TF Card) + Earphone+ HDMI OUT Mode 2: Charging from 120 Vac + Camera (Front)+ With TF Card + HDMI OUT Mode 3: Charging from 120 Vac + Camera (Rear) + With TF Card+ HDMI OUT Mode 4: Charging from 120 Vac + FM (With Earphone) +Light on Mode 5: Charging from 120 Vac(USB type C)+ Worse from mode 1~4 Mode 6: Charging from 240 Vac + Worse from mode 1~4(mode 3)
Remark: The above test modes in boldface were the worst cases, only the test data of these modes were reported.	

4.3.2 For Conducted Emissions test setup

Figure 3. Conducted Emissions setup



4.4 SYSTEM TEST CONFIGURATION

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000MHz. The resolution is 1 MHz or greater for frequencies above 1000MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic (according to KDB 896810 D02 SDoC FAQ v01r01) of the highest fundamental frequency or to 40 GHz, whichever is lower.

5. REFERENCE DOCUMENTS FOR TESTING

No.	Identity	Document Title
1	FCC 47 CFR Part15 Subpart B	Unintentional Radiators
2	ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
3	KDB 174176 D01 Line Conducted FAQ v01r01	AC power-line conducted emission frequency asked questions
4	KDB 896810 D02 SDoC FAQ v01r02	Supplier's Declaration of Conformity frequency asked questions

6. EMC REQUIREMENTS SPECIFICATION

6.1 RADIATED EMISSION

Test Requirement: FCC 47 CFR Part 15.109

Test Method: ANSI C63.4-2014

Receiver Setup:

Frequency: (f) (MHz)	Detector type	Measurement receiver bandwidth	
		RBW	VBW
$30 \leq f \leq 1\,000$	Quasi Peak	120 kHz	300 kHz
$f \geq 1000$	Peak	1 MHz	3 MHz
	Average	1 MHz	3 MHz

Measured frequency range

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30.
1.705-108	1000.
108-500	2000.
500-1000	5000.
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower.

Limits:

Limits for Class B devices

Frequency (MHz)	limits at 3m (dB μ V/m)		
	QP Detector	PK Detector	AV Detector
30-88	40.0	--	--
88-216	43.5	--	--
216-960	46.0	--	--
960 to 1000	54.0	--	--
Above 1000	--	74.0	54.0

Remark:

- The lower limit shall apply at the transition frequencies.
- Emission level (dB μ V/m) = 20 log Emission level (μ V/m).
- For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

Test Setup: Refer to section 4.3.1 for details.

Test Procedures:

- From 30 MHz to 1GHz test procedure as below:

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-FCCPART15B-V1.0

- 1) The Product was placed on the non-conductive turntable 0.8 m above the ground at a chamber.
- 2) Set the spectrum analyzer/receiver in Peak detector, Max Hold mode, and 120 kHz RBW. Record the maximum field strength of all the pre-scan process in the full band when the antenna is varied between 1~4 m in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.
- 3) For each frequency whose maximum record was higher or close to limit, measure its QP value: vary the antenna's height and rotate the turntable from 0 to 360 degrees to find the height and degree where Product radiated the maximum emission, then set the test frequency analyzer/receiver to QP Detector and specified bandwidth with Maximum Hold Mode, and record the maximum value.

2. Above 1GHz test procedure as below:

- 1) The Product was placed on the non-conductive turntable 0.8 m above the ground at a chamber.
- 2) Set the spectrum analyzer/receiver in Peak detector, Max Hold mode, and 1MHz RBW. Record the maximum field strength of all the pre-scan process in the full band when the antenna is varied in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.
- 3) For each frequency whose maximum record was higher or close to limit, measure its AV value: rotate the turntable from 0 to 360 degrees to find the degree where Product radiated the maximum emission, then set the test frequency analyzer/receiver to AV value and specified bandwidth with Maximum Hold Mode, and record the maximum value.

Equipment Used: Refer to section 3 for details.


Test Result: Pass

The measurement data as follows:


Below 1GHz(Quasi Peak):

Mode3

Horizontal



No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	121.462	51.41	-15.99	35.42	43.50	-8.08	QP
2	171.389	48.32	-11.27	37.05	43.50	-6.45	QP
3	223.848	51.72	-10.70	41.02	46.00	-4.98	QP
4	298.593	48.62	-6.66	41.96	46.00	-4.04	QP
5	371.268	49.40	-5.67	43.73	46.00	-2.27	QP
6	744.427	42.15	1.70	43.85	46.00	-2.15	QP



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com
<http://www.uttlab.com>

UTTR-EMC-FCCPART15B-V1.0

Above 1GHz(Peak & Average)
Mode2
Horizontal



No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	1041.380	44.69	-10.39	34.30	54.00	-19.70	Average
2	1041.380	62.69	-10.39	52.30	74.00	-21.70	Peak
3	1109.891	54.63	-10.68	43.95	54.00	-10.05	Average
4	1109.891	70.63	-10.68	59.95	74.00	-14.05	Peak
5	1182.910	44.54	-11.00	33.54	54.00	-20.46	Average
6	1182.910	63.54	-11.00	52.54	74.00	-21.46	Peak
7	1482.720	42.40	-12.07	30.33	54.00	-23.67	Average
8	1482.720	63.40	-12.07	51.33	74.00	-22.67	Peak
9	2224.075	42.99	-9.16	33.83	54.00	-20.17	Average
10	2224.075	59.99	-9.16	50.83	74.00	-23.17	Peak
11	16124.140	28.11	11.49	39.60	54.00	-14.40	Average
12	16124.140	41.11	11.49	52.60	74.00	-21.40	Peak

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-FCCPART15B-V1.0

Vertical



No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	1041.380	41.90	-10.65	31.25	54.00	-22.75	Average
2	1041.380	60.90	-10.65	50.25	74.00	-23.75	Peak
3	1109.891	46.83	-11.03	35.80	54.00	-18.20	Average
4	1109.891	66.83	-11.03	55.80	74.00	-18.20	Peak
5	1182.910	44.91	-11.45	33.46	54.00	-20.54	Average
6	1182.910	65.91	-11.45	54.46	74.00	-19.54	Peak
7	1482.720	42.06	-12.94	29.12	54.00	-24.88	Average
8	1482.720	58.06	-12.94	45.12	74.00	-28.88	Peak
9	2224.075	35.53	-9.61	25.92	54.00	-28.08	Average
10	2224.075	54.53	-9.61	44.92	74.00	-29.08	Peak
11	16031.010	28.99	11.48	40.47	54.00	-13.53	Average
12	16031.010	41.99	11.48	53.47	74.00	-20.53	Peak

Remark:

1. Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result – Limit
4. All possible modes of operation were investigated, and testing at two nominal voltages of 240V/50Hz and 120V/60Hz, only the worst case emissions reported.
5. For Radiated Emission above 18GHz, there was not any unwanted emission detected.

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-FCCPART15B-V1.0

6.2 CONDUCTED EMISSION

Test Requirement: FCC 47 CFR Part 15.107

Test Method: ANSI C63.4-2014

Limits:

Limits for Class B devices

Frequency range (MHz)	Limits (dB(μV))	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50

Remark:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz.

Test Setup: Refer to section 4.3.2 for details.

Test Procedures:

- 1) The Product was placed on a nonconductive table 0.8 m above the horizontal ground reference plane, and 0.4 m from the vertical ground reference plane, and connected to the main through Line Impedance Stability Network (L.I.S.N).
- 2) The RBW of the receiver was set at 9 kHz in 150 kHz ~ 30MHz with Peak and AVG detector in Max Hold mode. Run the receiver's pre-scan to record the maximum disturbance generated from Product in all power lines in the full band.
- 3) For each frequency whose maximum record was higher or close to limit, measure its QP and AVG values and record.

Equipment Used: Refer to section 3 for details.


Test Result: Pass

The measurement data as follows:

Quasi Peak and Average:


Mode 3

Live Line



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.166	31.13	9.75	40.88	55.16	-14.28	Average
2	0.166	39.13	9.75	48.88	65.16	-16.28	QP
3	0.278	22.10	9.75	31.85	50.88	-19.03	Average
4	0.278	37.10	9.75	46.85	60.88	-14.03	QP
5	1.682	24.99	9.87	34.86	46.00	-11.14	Average
6	1.682	35.99	9.87	45.86	56.00	-10.14	QP
7	3.082	24.04	9.99	34.03	46.00	-11.97	Average
8	3.082	36.04	9.99	46.03	56.00	-9.97	QP
9	8.269	31.32	10.24	41.56	50.00	-8.44	Average
10	8.269	44.32	10.24	54.56	60.00	-5.44	QP
11	21.993	22.88	10.56	33.44	50.00	-16.56	Average
12	21.993	37.88	10.56	48.44	60.00	-11.56	QP

Neutral Line



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.182	19.35	9.74	29.09	54.39	-25.30	Average
2	0.182	39.35	9.74	49.09	64.39	-15.30	QP
3	0.750	22.17	9.78	31.95	46.00	-14.05	Average
4	0.750	34.17	9.78	43.95	56.00	-12.05	QP
5	1.246	23.04	9.86	32.90	46.00	-13.10	Average
6	1.246	35.04	9.86	44.90	56.00	-11.10	QP
7	3.262	19.33	10.00	29.33	46.00	-16.67	Average
8	3.262	35.33	10.00	45.33	56.00	-10.67	QP
9	8.517	27.20	10.29	37.49	50.00	-12.51	Average
10	8.517	44.20	10.29	54.49	60.00	-5.51	QP
11	22.389	21.73	10.57	32.30	50.00	-17.70	Average
12	22.389	41.73	10.57	52.30	60.00	-7.70	QP

Remark:

1. Correct Factor = LISN Factor + Cable Loss + Pulse Limiter Factor, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result - Limit
4. An initial pre-scan was performed on the Phase and neutral lines with peak detector. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.
5. All possible modes of operation were investigated, and testing at two nominal voltages of 240V/50Hz and 120V/60Hz, only the worst case emissions reported.

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-FCCPART15B-V1.0

APPENDIX 1 PHOTOS OF TEST SETUP

See test photos attached in Appendix 1 for the actual connections between Product and support equipment.

APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal photos.

***** End of Report *****

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.
