



Deutsche
Akkreditierungsstelle
D-PL-12053-01-00

**Test Report acc. to FCC Title 47 CFR Part 15
relating to
Wireless Audiocube
Noisetron LLC**

**Title 47 - Telecommunication
Part 15 - Radio Frequency Devices
Subpart C – Intentional Radiators
Measurement Procedure:
ANSI C63.4-2009**

EUT: Wireless Audiocube

FCC ID: 2AHFJPWA

FCC Title 47 CFR Part 15 C

Date of issue: 2016-02-08

MANUFACTURER

Manufacturer name	Noisetron LLC
Manufacturer's grantee code	2AHFJ
Manufacturer's address	340 S Lemon Ave. #4098; 91789 Walnut, CA USA
Phone	+ 1 650 799 4509
Fax	---
Email	bert@noisetron.com

TESTING LABORATORY

Test engineer	Mr. Ralf Trepper
Testing laboratory name	m. dudde hochfrequenz-technik
Testing laboratory address	Rottland 5a, 51429 Bergisch Gladbach, Germany
Phone	+49 2207 9689-0
Fax	+49 2207 9689-20
Email	m.duddelabor@dudde.com

RELEVANT STANDARD

Title	47 - Telecommunication
Part	15 - Radio Frequency Devices
Subpart	Subpart C – Intentional Radiators
Measurement procedure	ANSI C63.4-2009

EQUIPMENT UNDER TEST (EUT)

Equipment category	Computer Input Device
Trade name	PERCUSSA
Type designation	Wireless Audiocube
Serial no.	B15014
Variants	---

1. Test results

Clause	Requirements headline	Test result			Page number
8.1	Antenna requirement	Pass	Fail	N.t.*	9
8.2	Conducted limits	Pass	Fail	N.t.*	10 - 12
8.3	Restricted bands of operation	Pass	Fail	N.t.*	13 - 15
8.4	Radiated emission limits, general requirements	Pass	Fail	N.t.*	16 - 20
8.5	Fundamental frequencies / Field strength limits	Pass	Fail	N.t.*	21 - 27
8.6	Bandwidth	Pass	Fail	N.t.*	28

* Not tested

The equipment passed all the conducted tests	Yes	No
--	-----	---------------

nature		
Name	Mr. Ralf Trepper	Mr. Manfred Dudde
Designation	Technician	Laboratory-Manager
Date of issue	2016-02-08	2016-02-08


 Digital unterschrieben von
 Abdelouahid Ftouhi
 DN: cn=Abdelouahid
 Ftouhi, o=m. dudde
 Hochfrequenztechnik, ou,
 email=m.dudde@laborg@d
 udde.com, c=DE
 Datum: 2016.02.15
 14:20:21 +01'00'

Table of contents

1. Test results.....	3
2. Introduction.....	5
3. Testing laboratory	5
4. Applicant.....	6
5. Product and product documentation	6
6. Conclusions, observations and comments	7
7. Operational description.....	8
8. Compliance assessment	9
8.1 Antenna requirement	9
8.1.1 Results.....	9
8.2 Conducted limits	10
8.2.1 Regulation.....	10
8.2.2 Test procedures.....	11
8.2.3 Result	11
8.3 Restricted bands of operation.....	13
8.3.1 Regulation.....	13
8.3.2 Result	15
8.4 Radiated emission limits, general requirements	16
8.4.1 Regulation.....	16
8.4.2 Test procedure	17
8.4.3 Calculation of the field strength	18
8.4.4 Result	19
8.5 Fundamental frequencies / Field strength limits.....	21
8.5.1 Regulation.....	21
8.5.2 Test procedure	22
8.5.3 Calculation of the average correction factor	23
8.5.4 Calculation of the field strengths.....	23
8.5.5 Result	24
8.6 Bandwidth (20 dB).....	28
8.6.1 Regulation.....	28
8.6.2 Test procedure	28
8.6.3 20 dB Bandwidth limit.....	28
8.6.4 Result	28
9. Additional information to the test report	29
10. List of test equipment	30
11. List of test cables	31

2. Introduction

This test report **is not an expert opinion** and consists of:

- Test result summary
- List of contents
- Introduction and further information
- Performance assessment
- Detailed test information

All pages have been numbered consecutively and bear the m. dudde hochfrequenz-technik logo, the test report number, the date, the test specification in its current version as well as the type designation of the EUT. The total numbers of pages in this report is **32**.

The tests were carried out in a representative assembly and in accordance with the test methods and/or requirements stated in:

FCC Title 47 CFR Part 15 Subpart C & ANSI C63.4-2009

The sample of the product was received on:

- 2016-02-01

The tests were carried out on:

- 2016-02-01

3. Testing laboratory

m. dudde hochfrequenz-technik,
Rottland 5a,
D-51429 Bergisch Gladbach
Germany

Phone: +49 - (0) 22 07 / 96 89-0

Fax: +49 - (0) 22 07 / 96 89-20

FCC Registration Number: 699717

Accredited by:

DAkkS Deutsche Akkreditierungsstelle GmbH
DAkkS accreditation number: D-PL-12053-01

EUT: Wireless Audiocube

FCC ID: 2AHFJPWA

FCC Title 47 CFR Part 15 C

Date of issue: 2016-02-08

4. Applicant

Company name : Noisetron LLC
Address : 340 S Lemon Ave. #4098
91789 Walnut, CA
Country : U.S.A
Telephone : +1 650 799 4509
Fax : ---
Email : bert@noisetron.com
Date of order : 2016-02-01
References : Mr. Bert Schiettecatte

5. Product and product documentation

Samples of the following apparatus were submitted for testing:

Manufacturer : Noisetron LLC
Trademark : PERCUSSA
Type designation : Wireless Audiocube
Serial number : B15014
Hardware versions : ---
Variants : ---
Software release : ---
Type of equipment : Computer Input Device
Power used : 3.3 V DC
Frequency used : 2.402 - 2.481 GHz (carrier)
Generated or used frequencies : 16 MHz, 18.432 MHz (crystal)
ITU emission class : 4M08F1D
FCC ID : 2AHFJPWA

For issuing this report the following product documentation was used:

Title	Description	Version
---	---	---

For issuing this report the following product documentation was used:

Description	Date	Identifications
External photographs of the Equipment Under Test (EUT)	2016-02-08	Annex no. 1
Internal photographs of the Equipment Under Test (EUT)	2016-02-08	Annex no. 2
Channel occupancy / bandwidth	2016-02-08	Annex no. 3
Label sample	2016-02-08	Annex no. 4
Functional description / User Manual	2016-02-08	Annex no. 5
Test setup photos	2016-02-08	Annex no. 6
Block diagram	2016-02-08	Annex no. 7
Operational description	2016-02-08	Annex no. 8
Schematics	2016-02-08	Annex no. 9
Parts list	2016-02-08	Annex no. 10

6. Conclusions, observations and comments

The test report will be filed at m. dudde hochfrequenz-technik for a period of 10 years following the issue of this report. It may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of m. dudde hochfrequenz-technik.

The results of the tests as stated in this report are exclusively applicable to the EUT as identified in this report. m. dudde hochfrequenz-technik cannot be held liable for properties of the EUT that have not been observed during these tests.

m. dudde hochfrequenz-technik assumes the sample to comply with the requirements of FCC Title 47 CFR Part 15 for the respective test sector, if the test results turn out positive.

Comments: ---

Date : 2016-02-08

Name : Ralf Trepper

Function : RF Engineer

Signature : 

Date : 2016-02-08

Name : Manfred Dudde

Function : Laboratory Manager

Signature : 

7. Operational description

7.1 EUT details

PERCUSSA Wireless AudioCube

The EUT is consists of 3 parts:

- a rechargeable li-poly battery cell with protection circuit
- a motherboard
- a wireless module

7.2 EUT configuration

Operation: As soon as the EUT is connected via USB to a computer, it automatically starts transmitting.

Purpose of operation: see user manual.

7.3 EUT measurement description

Radiated measurements

The EUT was tested in a typical fashion. During preliminary emission tests the EUT was operated in the continuous measuring mode for worst case emission mode investigation. Therefore, the final qualification testing was completed with the EUT operated in continuous measuring mode. All tests were performed with the EUT's typical voltage: 3.3 V DC

In order to establish the maximum radiation, firstly, there have been viewed all orthogonal adjustments of the test samples, secondly the test ample have been rotated at all adjustments around the own axis between 0° and 360°, and thirdly, the antenna polarization between horizontal and vertical had been varied.

Conducted measurements

The EUT was connected via laptop to the artificial mains network. It has been tested with the activated EUT in continuous measuring mode.

8. Compliance assessment

8.1 Antenna requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

8.1.1 Results

Antenna Type	Operating Frequency Range	Gain
---	GHz	dBi
Internal wire antenna	2.4 - 2.483	0

The equipment passed the conducted tests	Yes	No	N.t.
Test setup photos / test results are attached	Yes	No	Annex no.:

N.t.* See page no. 26

8.2 Conducted limits

8.2.1 Regulation

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H /50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Conducted Limits		
Frequency of Emission	Quasi-Peak (QP)	Average (AV)
MHz	dB μ V	dB μ V
0.15 - 0.5	66 to 56*	56 to 46*
0.5 - 5	56	46
5 -30	60	50
*Limit Decreases with the logarithm of the frequency		

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

1) For carrier current system containing their fundamental emission within the frequency band 535–1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535–1705 kHz, as measured using a 50 μ H /50 Ω LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

8.2.2 Test procedures

The EUT and the additional equipment (if required) are connected to the main power through a line impedance stabilization network (LISN). The LISN must be appropriate to ANSI C63.4-2009 Section 7. Additional equipment must also be connected to a second LISN with the same specifications described in the above sentence (if required).

8.2.3 Result

Conducted emissions (Section 15.107) - Laptop only								
Tested Line	Frequency	Bandwidth	QP Value	QP Limit	Margin	AV Value	AV Limit	Margin
	MHz	kHz	dBμV	dBμV	dB	dBμV	dBμV	dB
N	0.150	9	47.0	66	19.0	**	56.0	---
N	0.202	9	45.0	64	19.0	**	53.5	---
N	0.271	9	45.5	61	15.5	**	51.1	---
N	0.472	9	45.0	56	11.0	**	46.4	---
N	0.676	9	44.5	56	11.5	**	46.0	---
N	13.736	9	40.0	60	20.0	**	50.0	---
L1	0.151	9	48.0	66	18.0	**	55.9	---
L1	0.160	9	50.5	65	14.5	**	55.5	---
L1	0.180	9	46.0	64	18.0	**	54.5	---
L1	0.371	9	39.0	58	19.0	**	48.4	---
L1	0.513	9	39.5	56	16.5	**	46.0	---
L1	12.826	9	39.0	60	21.0	**	50.0	---
L1	13.223	9	39.0	60	21.0	**	50.0	---
L1	13.432	9	38.5	60	21.5	**	50.0	---
Measurement uncertainty < ± 2 dB								
**The measured QP value is lower than average limit, therefore measurement with the average detector is unnecessary.								

Conducted emissions (Section 15.107) - EUT connected via USB to the Laptop								
Tested Line	Frequency	Bandwidth	QP Value	QP Limit	Margin	AV Value	AV Limit	Margin
	MHz	kHz	dB μ V	dB μ V	dB	dB μ V	dB μ V	dB
N	0.150	9	57.0	66	9.0	44.0	56.0	12.0
N	0.202	9	42.0	64	22.0	**	53.5	---
N	0.271	9	43.0	61	18.0	**	51.1	---
N	0.471	9	42.0	56	14.0	**	46.4	---
N	0.676	9	42.0	56	14.0	**	46.0	---
N	13.736	9	42.0	60	18.0	**	50.0	---
L1	0.151	9	56.0	66	10.0	43.5	55.9	12.4
L1	0.160	9	52.0	65	13.0	**	55.5	---
L1	0.180	9	46.0	64	18.0	**	54.5	---
L1	0.371	9	38.0	58	20.0	**	48.4	---
L1	0.513	9	39.5	56	16.5	**	46.0	---
L1	12.826	9	44.0	60	16.0	**	50.0	---
L1	13.223	9	44.0	60	16.0	**	50.0	---
L1	13.432	9	46.0	60	14.0	**	50.0	---
Measurement uncertainty $< \pm 2$ dB								
**The measured QP value is lower than average limit, therefore measurement with the average detector is unnecessary.								

Test Cables used	KEMV 30
Test equipment used	72, 272, 428, 429

The equipment passed the conducted tests	Yes	No	N.t.
--	-----	---------------	-----------------

Test setup photos / test results are attached	Yes	No	Annex no.: 6
---	-----	---------------	--------------

N.t.* See page no. 26

8.3 Restricted bands of operation

8.3.1 Regulation

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

Restricted bands of operation			
Frequency Band	Frequency Band	Frequency Band	Frequency Band
MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41	---	---	---
¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.			
² Above 38.6			

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR Quasi-Peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

(c) Except as provided in paragraphs (d) and (e), regardless of the field strength limits specified elsewhere in this Subpart, the provisions of this Section apply to emissions from any intentional radiator.

(d) The following devices are exempt from the requirements of this Section:

- (1) Swept frequency field disturbance sensors operating between 1.705 and 37 MHz provided their emissions only sweep through the bands listed in paragraph (a), the sweep is never stopped with the fundamental emission within the bands listed in paragraph (a), and the fundamental emission is outside of the bands listed in paragraph (a) more than 99% of the time the device is actively transmitting, without compensation for duty cycle.
- (2) Transmitters used to detect buried electronic markers at 101.4 kHz which are employed by telephone companies.
- (3) Cable locating equipment operated pursuant to Section 15.213.
- (4) Any equipment operated under the provisions of § 15.253, § 15.255 or § 15.257 of this part.
- (5) Biomedical telemetry devices operating under the provisions of Section 15.242 of this part are not subject to the restricted band 608-614 MHz but are subject to compliance within the other restricted bands.
- (6) Transmitters operating under the provisions of Subpart D or F of this part.
- (7) Devices operated pursuant to § 15.225 are exempt from complying with this section for the 13.36-13.41 MHz band only.
- (8) Devices operated in the 24.075-24.175 GHz band under § 15.245 are exempt from complying with the requirements of this section for the 48.15-48.35 GHz and 72.225-72.525 GHz bands only, and shall not exceed the limits specified in § 15.245(b).
- (9) Devices operated in the 24.0-24.25 GHz band under § 15.249 are exempt from complying with the requirements of this section for the 48.0-48.5 GHz and 72.0-72.75 GHz bands only, and shall not exceed the limits specified in § 15.249(a).

(e) Harmonic emissions appearing in the restricted bands above 17.7 GHz from field disturbance sensors operating under the provisions of Section 15.245 shall not exceed the limits specified in Section 15.245(b).

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

(c) Except as provided in paragraphs (d) and (e), regardless of the field strength limits specified elsewhere in this Subpart, the provisions of this Section apply to emissions from any intentional radiator. (d) The following devices are exempt from the requirements of this Section:

(1) Swept frequency field disturbance sensors operating between 1.705 and 37 MHz provided their emissions only sweep through the bands listed in paragraph (a), the sweep is never stopped with the fundamental emission within the bands listed in paragraph (a), and the fundamental emission is outside of the bands listed in paragraph (a) more than 99% of the time the device is actively transmitting, without compensation for duty cycle.

(2) Transmitters used to detect buried electronic markers at 101.4 kHz which are employed by telephone companies.

(3) Cable locating equipment operated pursuant to Section 15.213.

(4) Any equipment operated under the provisions of § 15.253, § 15.255 or § 15.257 of this part.

(5) Biomedical telemetry devices operating under the provisions of Section 15.242 of this part are not subject to the restricted band 608-614 MHz but are subject to compliance within the other restricted bands.

(6) Transmitters operating under the provisions of Subpart D or F of this part.

(7) Devices operated pursuant to § 15.225 are exempt from complying with this section for the 13.36-13.41 MHz band only.

(8) Devices operated in the 24.075-24.175 GHz band under § 15.245 are exempt from complying with the requirements of this section for the 48.15-48.35 GHz and 72.225-72.525 GHz bands only, and shall not exceed the limits specified in § 15.245(b).

(9) Devices operated in the 24.0-24.25 GHz band under § 15.249 are exempt from complying with the requirements of this section for the 48.0-48.5 GHz and 72.0-72.75 GHz bands only, and shall not exceed the limits specified in § 15.249(a).

(e) Harmonic emissions appearing in the restricted bands above 17.7 GHz from field disturbance sensors operating under the provisions of Section 15.245 shall not exceed the limits specified in Section 15.245(b).

8.3.2 Result

Test Cables used	K1a, K40, K50, K51, K56, K147, K148
Test equipment used	103, 104, 166a, 171a, 345, 406, 430, 445, 443

The equipment passed the conducted tests	Yes**	No	N.t.
--	-------	---------------	-----------------

Test setup photos / test results are attached	Yes	No	Annex no.:6
---	-----	---------------	-------------

****All radiated emissions within restricted band are lower than the noise level of the measuring equipment!**

N.t.* See page no. 26

8.4 Radiated emission limits, general requirements

8.4.1 Regulation

- (a) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Intentional radiator- radiated emission limits		
Frequency	Field Strength	Measurement distance
MHz	$\mu\text{V} / \text{m}$	m
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100**	3
88-216	150**	3
216-960	200**	3
above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 MHz, 76– 88 MHz, 174–216 MHz or 470–806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.		

- (b) In the emission table above, the tighter limit applies at the band edges.

(c) The level of any unwanted emissions from an intentional radiator operating under these general provisions shall not exceed the level of the fundamental emission. For intentional radiators which operate under the provisions of other sections within this part and which are required to reduce their unwanted emissions to the limits specified in this table, the limits in this table are based on the frequency of the unwanted emission and not the fundamental frequency. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.

(d) The emission limits shown in the above table are based on measurements employing a CISPR quasi peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

(e) The provisions in §§ 15.31, 15.33, and 15.35 for measuring emissions at distances other than the distances specified in the above table, determining the frequency range over which radiated emissions are to be measured, and limiting peak emissions apply to all devices operated under this part.

(f) In accordance with Section 15.33(a), in some cases the emissions from an intentional radiator must be measured to beyond the tenth harmonic of the highest fundamental frequency designed to be emitted by the intentional radiator because of the incorporation of a digital device. If measurements above the tenth harmonic are so required, the radiated emissions above the tenth harmonic shall comply with the general radiated emission limits applicable to the incorporated digital device, as shown in Section 15.109 and as based on the frequency of the emission being measured, or, except for emissions contained in the restricted frequency bands shown in Section 15.205, the limit on spurious emissions specified for the intentional radiator, whichever is the higher limit. Emissions which must be measured above the tenth harmonic of the highest fundamental frequency designed to be emitted by the intentional radiator and which fall within the restricted bands shall comply with the general radiated emission limits in Section 15.109 that are applicable to the incorporated digital device.

8.4.2 Test procedure

The EUT and this peripheral (when additional equipment exists) are placed on a turn table which is 0.8 m above the ground. The turn table would be allowed to rotate 360° to determine the position of the maximum emission level. The test distance between the EUT and the receiving antenna are 3m. To find the maximum emission, the polarization of the receiving antenna is changed in horizontal and vertical polarization; the position of the EUT was changed in different orthogonal determinations.

ANSI C63.4: 2009 Section 8 “Radiated Emissions Testing”

Measurement procedures for electric field radiated emissions above 1 GHz are covered in Clause 8 of ANSI C63.4-2009. The C63.4-2009 measurement procedure consists of both an exploratory test and a final measurement. The exploratory test is critical to determine the frequency of all significant emissions. For each mode of operation required to be tested, the frequency spectrum is monitored. Variations in antenna height, antenna orientation, antenna polarization, EUT azimuth, and cable or wire placement is explored to produce the emission that has the highest amplitude relative to the limit.

The final measurements are made based on the findings in the exploratory testing. When making exploratory and final measurements it is necessary to maximize the measured radiated emission. Subclause 8.3.1.2 of C63.4-2009 states that the measurement is to be made “while keeping the antenna in the ‘cone of radiation’ from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response.” We consider the “cone of radiation” to be the 3 dB beamwidth of the measurement antenna.

While the “bore-sighting” technique is not explicitly mentioned in C63.4-2009, it is a useful technique for measurements using a directional antenna, such as a double-ridged waveguide antenna. Several precautions must be observed, including: knowledge of the beamwidth of the antenna and the resulting illumination area relative to the size of the EUT, estimation for source of the emission and general location within larger EUTS, measuring system sensitivity, etc.

C63.4-2009 requires that the measurement antenna is kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. That means that if the directional radiation pattern of the EUT results in a maximum emission at an upwards angle from the EUT, when a directional antenna is used to make the measurement it will be necessary for it to be pointed towards the source of the emission within the EUT. This can be done by either pointing the antenna at an angle towards the source of the emission, or by rotating the EUT, in both height and polarization, to maximize the measured emission. The emission must be kept within the illumination area of the 3 dB beamwidth of the antenna so that the maximum emission from the EUT is measured.

Radiated emissions test characteristics	
Frequency range	30 MHz - 4,000 MHz
Test distance	3 m*
Test instrumentation resolution bandwidth	120 kHz (30 MHz - 1,000 MHz)
	1 MHz (1000 MHz - 4,000 MHz)
Receive antenna scan height	1 m - 4 m
Receive antenna polarization	Vertical/horizontal

* According to Section 15.31 (f) (1): At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20dB /decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

8.4.3 Calculation of the field strength

The field strength is calculated by the following calculation:

Corrected Level = Receiver Level + Correction Factor (without the use of a pre-amplifier)

Corrected Level = Receiver Level + Correction Factor – Pre-amplifier (with the use of a pre-amplifier)

Receiver Level : Receiver reading without correction factors

Correction Factor : Antenna factor + cable loss

For example:

The receiver reading is 32.7 dB μ V. The antenna factor for the measured frequency is +2.5 dB (1/m) and the cable factor for the measured frequency is 0.71 dB, giving a field strength of 35.91dB μ V/m. The 35.91dB μ V/m value can be mathematically converted to its corresponding level in μ V/m.

Level in μ V/m = Common Antilogarithm (35.91/20) = 62.44

For test distance other than what is specified, but fulfilling the requirements of Section 15.31 (f) (1) the field strength is calculated by adding additionally an extrapolation factor of 20 dB/decade (inverse linear distance for field strength measurements).

8.4.4 Result

Transmitter spurious radiation below 30 MHz (Section 15.205, 15.209)												
f	Detct	BW	Rx Level	MD	CF	DEF	LC	Limit	Margin	EP	Antenna	
MHz	Type	kHz	dBμV	m	dB	dB	dBμV/m	dBμV/m	dB	°	Pol	H
	QP	120	**	10			**		---		H/V	1
	QP	120	**	10			**		---		H/V	1
	QP	120	**	10			**		---		H/V	1
	QP	120	**	10			**		---		H/V	1
Measurement uncertainty: ± 4 dB												
**All radiated emissions are lower than the noise level of the measuring equipment!												
f: Frequency Detct : Detector type BW: Bandwidth Rx Level: Receiver level MD: Measurement distance CF: Correction factor DEF: Distance extrapolation factor LC: Level corrected EP: EUT Position Pol:Antenna polarization H: Antenna height												
Remark: * ¹ Noise level of the measuring instrument ≤ 4.0dBμV@10m distance (0.009 MHz –30 MHz)												
Remark: * Peak Limit according to Section 15.35 (b).												

Test Cables used	K1a, K56, K83
Test equipment used	23, 103, 166a, 171a

The equipment passed the conducted tests	Yes	No	N.t.
--	-----	---------------	-----------------

Test setup photos / test results are attached	Yes	No	Annex no.:
---	----------------	----	------------

N.t.* See page no. 26

Transmitter spurious radiation above 30 MHz (Section 15.205, 15.209)

f	Detct	RB W	Rx Level	MD	CF	DEF	AVC	LC	Limit	Margin	EP	Antenna	
MHz	Type	kHz	dBμV	m	dB	dB	dB	dBμV/m	dBμV/m	dB	°	Pol	H
347.72	QPK	120	36.0	3	-5.7	0	0	30.3	46	15.7	300	H	186
350.88	QPK	120	38.0	3	-5.5	0	0	32.5	46	13.5	300	H	186
356.41	QPK	120	40.0	3	-5.4	0	0	34.6	46	11.4	300	H	186
361.77	QPK	120	41.0	3	-5.3	0	0	35.7	46	10.3	300	H	186
364.33	QPK	120	40.5	3	-5.3	0	0	35.2	46	10.8	300	H	186
368.12	QPK	120	40.0	3	-5.1	0	0	34.9	46	11.1	300	H	186
372.05	QPK	120	38.5	3	-4.6	0	0	33.9	46	12.1	300	H	186
376.83	QPK	120	37.0	3	-4.5	0	0	32.5	46	13.5	300	H	186
379.42	QPK	120	36.0	3	-4.4	0	0	31.6	46	14.4	300	H	186

Measurement uncertainty: ± 4 dB

f: Frequency | Detct : Detector type | BW: Bandwidth | Rx Level : Receiver level | MD: Measurement distance | CF : Correction factor | DEF : Distance extrapolation factor | AVC : Averaging Correction factor | LC : Level corrected | EP: EUT Position | Pol: Antenna polarization | H: Antenna height |

Remark: *¹ noise floor noise level of the measuring instrument ≤ 3.5dBμV @ 3m distance (30 – 1,000 MHz)
 Remark: *² noise floor noise level of the measuring instrument ≤ 4.5dBμV @ 3m distance (1,000 – 2,000 MHz)
 Remark: *³ noise floor noise level of the measuring instrument ≤ 10dBμV @ 3m distance (2,000 – 5,500 MHz)
 Remark: *⁴ noise floor noise level of the measuring instrument ≤ 14dBμV @ 3m distance (5,500 – 14,500 MHz)
 Remark: *⁵ for using a pre-amplifier in the range between 100 kHz and 1,000 MHz
 Remark: *⁶ for using a pre-amplifier in the range between 1.0 GHz and 18.0 GHz

Test Cables used	K1a, K40, K50, K51, K56, K147, K148
Test equipment used	104, 166a, 171a, 345, 406, 430, 445, 443

The equipment passed the conducted tests	Yes	No	N.t.
--	-----	---------------	-----------------

Test setup photos / test results are attached	Yes	No	Annex no.:6
---	-----	---------------	-------------

N.t.* See page no. 26

8.5 Fundamental frequencies / Field strength limits

8.5.1 Regulation

(a) Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Intentional radiator- Fundamental frequencies / Field strength limits		
Frequency	Field strength of fundamental	Field strength of harmonics
MHz	mV / m	μ V / m
902-928	50	500
2400-2483.5	50	500
5725-5875	50	500
24.0-24.25	250	2500

(b) Fixed, point-to-point operation as referred to in this paragraph shall be limited to systems employing a fixed transmitter transmitting to a fixed remote location. Point-to-multipoint systems, omnidirectional applications, and multiple co-located intentional radiators transmitting the same information are not allowed. Fixed, point-to-point operation is permitted in the 24.05-24.25 GHz band subject to the following conditions:

(1) The field strength of emissions in this band shall not exceed 2500 millivolts/meter.

(2) The frequency tolerance of the carrier signal shall be maintained within $\pm 0.001\%$ of the operating frequency over a temperature variation of $-20\text{ }^{\circ}\text{C}$ to $+50\text{ }^{\circ}\text{C}$ at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of $20\text{ }^{\circ}\text{C}$. For battery operated equipment, the equipment tests shall be performed using a new battery.

(3) Antenna gain must be at least 33 dBi. Alternatively, the main lobe beamwidth must not exceed 3.5° . The beamwidth limit shall apply to both the azimuth and elevation planes. At antenna gains over 33 dBi or beamwidths narrower than 3.5° , power must be reduced to ensure that the field strength does not exceed 2500 millivolts/meter.

(c) Field strength limits are specified at a distance of 3 meters.

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation.

(e) As shown in § 15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For point-to-point operation under paragraph (b) of this section, the peak field strength shall not exceed 2500 millivolts/meter at 3 meters along the antenna azimuth.

8.5.2 Test procedure

The EUT and this peripheral (when additional equipment exists) are placed on a turn table which is 0.8m above the ground. The turn table would be allowed to rotate 360° to determine the position of the maximum emission level. The test distance between the EUT and the receiving antenna are 3m. To find the maximum emission, the polarization of the receiving antenna are changed in horizontal and vertical polarization, the position of the EUT was changed in different orthogonal determinations.

ANSI C63.4: 2009 Section 8 “Radiated emission measurements”

Measurement procedures for electric field radiated emissions above 1 GHz are covered in Clause 8 of ANSI C63.4-2009. The C63.4-2009 measurement procedure consists of both an exploratory test and a final measurement. The exploratory test is critical to determine the frequency of all significant emissions. For each mode of operation required to be tested, the frequency spectrum is monitored. Variations in antenna height, antenna orientation, antenna polarization, EUT azimuth, and cable or wire placement is explored to produce the emission that has the highest amplitude relative to the limit.

The final measurements are made based on the findings in the exploratory testing. When making exploratory and final measurements it is necessary to maximize the measured radiated emission. Subclause 8.3.1.2 of C63.4-2009 states that the measurement is to be made “while keeping the antenna in the ‘cone of radiation’ from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response.” We consider the “cone of radiation” to be the 3 dB beamwidth of the measurement antenna.

While the “bore-sighting” technique is not explicitly mentioned in C63.4-2009, it is a useful technique for measurements using a directional antenna, such as a double-ridged waveguide antenna. Several precautions must be observed, including: knowledge of the beamwidth of the antenna and the resulting illumination area relative to the size of the EUT, estimation for source of the emission and general location within larger EUTS, measuring system sensitivity, etc.

C63.4-2009 requires that the measurement antenna is kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. That means that if the directional radiation pattern of the EUT results in a maximum emission at an upwards angle from the EUT, when a directional antenna is used to make the measurement it will be necessary for it to be pointed towards the source of the emission within the EUT. This can be done by either pointing the antenna at an angle towards the source of the emission, or by rotating the EUT, in both height and polarization, to maximize the measured emission. The emission must be kept within the illumination area of the 3 dB beamwidth of the antenna so that the maximum emission from the EUT is measured.

Radiated emissions test characteristics	
Frequency range	9 kHz - 100,000 MHz
Test distance	10m, 3 m*
Test instrumentation resolution bandwidth	9 kHz (20 kHz – 30 MHz)
	120 kHz (30 MHz - 1,000 MHz)
	1 MHz (1000 MHz - 100,000 MHz)
Receive antenna height	1 m (20 kHz – 30 MHz)
Receive antenna polarization	0° - 90° (20 kHz – 30 MHz)
Receive antenna scan height	1 m - 4 m (30 MHz - 15,000 MHz)
	1 m – 2.5 m (18,000 MHz - 40,000 MHz)
Receive antenna polarization	vertical/horizontal (30 MHz - 100,000 MHz)

*According to Section 15.31 (f) (1): At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

8.5.3 Calculation of the average correction factor

The average correction factor is computed by analyzing the "worst case" on time in any 100msec time period and using the formula: Corrections Factor + $20 \cdot \log$ (worst case on time/100msec). Analysis of the remote transmitter worst case on time in any 100msec time period is an on time of 50msec, therefore the correction factor is $20 \cdot \log$ (50/100) = - 6 dB. The maximum correction factor to be applied is 20 dB per section 15.35 of the FCC rules.

8.5.4 Calculation of the field strengths

The field strength is calculated by the following calculation:

Corrected Level = Receiver Level + Correction Factor (without the use of a pre-amplifier)

Corrected Level = Receiver Level + Correction Factor – Pre-Amplifier (with the use of a pre-amplifier)

Receiver Level : Receiver reading without correction factors

Correction Factor : Antenna factor + cable loss

For example:

The receiver reading is 32.7 dB μ V. The antenna factor for the measured frequency is +2.5 dB (1/m) and the cable factor for the measured frequency is 0.71 dB, giving a field strength of 35.91dB μ V/m.

The 35.91dB μ V/m value can be mathematically converted to its corresponding level in μ V/m.

Level in μ V/m = Common Antilogarithm (35.91/20) = 62.44

For test distance other than what is specified, but fulfilling the requirements of Section 15.31 (f) (1) the field strength is calculated by adding additionally an extrapolation factor of 20 dB/decade (inverse linear distance for field strength measurements).

8.5.5 Result

Transmitter Field Strengths - Fundamental Emissions (Section 15.249)												
f	Detct	BW	Rx Level	MD	CF	DEF	LC	Limit	Margi n	EP	Antenna	
GHz	Type	MHz	dBμV	m	dB	dB	dBμV/m	dBμV/m	dB	°	Pol	H
Lowest Channel												
2.402	PK	1	80.2	3	0.2	0	80.4	94	13.6	180	H	172
Middle Channel												
2.442	PK	1	79.5	3	0.4	0	79.9	94	14.1	240	H	228
Highest Channel												
2.481	PK	1	78.9	3	0.3	0	79.2	94	14.8	180	H	203
Measurement uncertainty: ± 4 dB												

f: Frequency Detct : Detector type BW: Bandwidth Rx Level : Receiver level MD: Measurement distance CF : Correction factor DEF :Distance extrapolation factor LC : Level corrected EP: EUT Position Pol:Antenna polarization H: Antenna height												
Remark: * ¹ noise floor			noise level of the measuring instrument ≤ 3.5dBμV @ 3m distance (30 – 1,000 MHz)									
Remark: * ² noise floor			noise level of the measuring instrument ≤ 4.5dBμV @ 3m distance (1,000 – 2,000 MHz)									
Remark: * ³ noise floor			noise level of the measuring instrument ≤ 10dBμV @ 3m distance (2,000 – 5,500 MHz)									
Remark: * ⁴ noise floor			noise level of the measuring instrument ≤ 14dBμV @ 3m distance (5,500 – 14,500 MHz)									
Remark: * ⁵			for using a pre-amplifier in the range between 100 kHz and 1,000 MHz									
Remark: * ⁶			for using a pre-amplifier in the range between 1.0 GHz and 18.0 GHz									
Remark: * ⁷			for periodic operated transmitter									

Transmitter Field Strengths - Harmonics (Section 15.249) @ 2.402 GHz

f	Detct	RBW	Rx Level	MD	CF	DEF	AVC	LC	Limit	Margin	EP	Antenna	
												Pol	H
GHz	Type	kHz	dBμV	m	dB	dB	dB	dBμV/m	dBμV/m	dB	°	H / V	cm
4.804	QPK	120	34.1	3	10.9	0	0	45.0	54	9.0	180	H	203
7.206	QPK	120	≤14.0	3	19.2	0	0	33.2	54	≥20.8	0-360	H	100-400
9.608	QPK	120	≤14.0	3	27.9	0	0	41.9	54	≥12.1	0-360	H	100-400
12.010	QPK	120	≤14.0	3	32.9	0	0	46.9	54	≥7.1	0-360	H	100-400
14.412	QPK	120	≤14.0	3	37.7	0	0	51.7	54	≥2.3	0-360	H	100-400
16.814	QPK	120	≤18.0	3	-1.5	0	0	16.5	54	≥37.5	0-360	H	100-400
19.216	QPK	120	≤18.0	3	3.5	0	0	21.5	54	≥32.5	0-360	H	100-250
21.618	QPK	120	≤18.0	3	4.3	0	0	22.3	54	≥31.7	0-360	H	100-250
24.020	QPK	120	≤18.0	3	3.4	0	0	21.4	54	≥32.6	0-360	H	100-250

Measurement uncertainty: ± 4 dB

f: Frequency | **Detct :** Detector type | **BW:** Bandwidth | **Rx Level :** Receiver level | **MD:** Measurement distance | **CF :** Correction factor | **DEF :** Distance extrapolation factor | **AVC :** Averaging Correction factor | **LC :** Level corrected | **EP:** EUT Position | **Pol:** Antenna polarization | **H:** Antenna height |

Remark: *¹ noise floor noise level of the measuring instrument ≤ 3.5dBμV @ 3m distance (30 – 1,000 MHz)
 Remark: *² noise floor noise level of the measuring instrument ≤ 4.5dBμV @ 3m distance (1,000 – 2,000 MHz)
 Remark: *³ noise floor noise level of the measuring instrument ≤ 10dBμV @ 3m distance (2,000 – 5,500 MHz)
 Remark: *⁴ noise floor noise level of the measuring instrument ≤ 14dBμV @ 3m distance (5,500 – 14,500 MHz)
 Remark: *⁵ for using a pre-amplifier in the range between 100 kHz and 1,000 MHz
 Remark: *⁶ for using a pre-amplifier in the range between 1.0 GHz and 18.0 GHz

Transmitter Field Strengths - Harmonics (Section 15.249) @ 2.442 GHz

f	Detct	RBW	Rx Level	M D	CF	DEF	AVC	LC	Limit	Margin	EP	Antenna	
												Pol	H
GHz	Type	kHz	dBμV	m	dB	dB	dB	dBμV/m	dBμV/m	dB	°	H / V	cm
4.884	QPK	120	33.9	3	11.0	0	0	44.9	54	9.1	240	H	222
7.326	QPK	120	≤14.0	3	19.0	0	0	33.3	54	≥20.7	0-360	H	100-400
9.768	QPK	120	≤14.0	3	28.2	0	0	42.2	54	≥11.8	0-360	H	100-400
12.210	QPK	120	≤14.0	3	33.1	0	0	47.1	54	≥6.9	0-360	H	100-400
14.652	QPK	120	≤14.0	3	37.9	0	0	51.9	54	≥2.1	0-360	H	100-400
17.094	QPK	120	≤18.0	3	-1.3	0	0	16.7	54	≥37.3	0-360	H	100-400
19.536	QPK	120	≤18.0	3	4.0	0	0	22.0	54	≥32.0	0-360	H	100-400
21.978	QPK	120	≤18.0	3	4.8	0	0	22.8	54	≥31.2	0-360	H	100-400
24.420	QPK	120	≤18.0	3	3.8	0	0	21.8	54	≥32.2	0-360	H	100-400

Measurement uncertainty: ± 4 dB

f: Frequency | **Detct :** Detector type | **BW:** Bandwidth | **Rx Level :** Receiver level | **MD:** Measurement distance | **CF :** Correction factor | **DEF :** Distance extrapolation factor | **AVC :** Averaging Correction factor | **LC :** Level corrected | **EP:** EUT Position | **Pol:** Antenna polarization | **H:** Antenna height |

Remark: *¹ noise floor noise level of the measuring instrument ≤ 3.5dBμV @ 3m distance (30 – 1,000 MHz)
 Remark: *² noise floor noise level of the measuring instrument ≤ 4.5dBμV @ 3m distance (1,000 – 2,000 MHz)
 Remark: *³ noise floor noise level of the measuring instrument ≤ 10dBμV @ 3m distance (2,000 – 5,500 MHz)
 Remark: *⁴ noise floor noise level of the measuring instrument ≤ 14dBμV @ 3m distance (5,500 – 14,500 MHz)
 Remark: *⁵ for using a pre-amplifier in the range between 100 kHz and 1,000 MHz
 Remark: *⁶ for using a pre-amplifier in the range between 1.0 GHz and 18.0 GHz

Transmitter Field Strengths - Harmonics (Section 15.249) @ 2.481 GHz

f	Detct	RBW	Rx Level	MD	CF	DEF	AVC	LC	Limit	Margi n	EP	Antenna	
GHz	Type	kHz	dBμV	m	dB	dB	dB	dBμV/m	dBμV/m	dB	°	Pol	H
												H / V	cm
4.962	QPK	120	26.8	3	11.3	0	0	38.1	54	15.9	180	H	198
7.443	QPK	120	≤14.0	3	19.4	0	0	33.4	54	≥20.6	0-360	H	100-400
9.924	QPK	120	≤14.0	3	28.2	0	0	42.2	54	≥11.8	0-360	H	100-400
12.405	QPK	120	≤14.0	3	33.2	0	0	47.2	54	≥6.8	0-360	H	100-400
14.886	QPK	120	≤14.0	3	38.0	0	0	52.0	54	≥2.0	0-360	H	100-400
17.367	QPK	120	≤18.0	3	-1.0	0	0	17.0	54	≥37.0	0-360	H	100-400
19.848	QPK	120	≤18.0	3	4.5	0	0	22.5	54	≥31.5	0-360	H	100-250
22.329	QPK	120	≤18.0	3	5.1	0	0	23.1	54	≥30.9	0-360	H	100-250
24.810	QPK	120	≤18.0	3	4.2	0	0	22.2	54	≥31.8	0-360	H	100-250

Measurement uncertainty: ± 4 dB

f: Frequency | Detct : Detector type | BW: Bandwidth | Rx Level : Receiver level | MD: Measurement distance | CF : Correction factor | DEF : Distance extrapolation factor | AVC : Averaging Correction factor | LC : Level corrected | EP: EUT Position | Pol: Antenna polarization | H: Antenna height |

Remark: *¹ noise floor noise level of the measuring instrument ≤ 3.5dBμV @ 3m distance (30 – 1,000 MHz)
 Remark: *² noise floor noise level of the measuring instrument ≤ 4.5dBμV @ 3m distance (1,000 – 2,000 MHz)
 Remark: *³ noise floor noise level of the measuring instrument ≤ 10dBμV @ 3m distance (2,000 – 5,500 MHz)
 Remark: *⁴ noise floor noise level of the measuring instrument ≤ 14dBμV @ 3m distance (5,500 – 14,500 MHz)
 Remark: *⁵ for using a pre-amplifier in the range between 100 kHz and 1,000 MHz
 Remark: *⁶ for using a pre-amplifier in the range between 1.0 GHz and 18.0 GHz

Test Cables used	K1a, K50, K51, K83, K84
Test equipment used	103, 171a, 345, 445

The equipment passed the conducted tests	Yes	No	N.t.
--	-----	---------------	-----------------

Test setup photos / test results are attached	Yes	No	Annex no.: 6
---	-----	---------------	--------------

N.t.* See page no. 26

8.6 Bandwidth (20 dB)

8.6.1 Regulation

(c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

8.6.2 Test procedure

ANSI C63.4-2009 Section 13.1.7 Occupied bandwidth measurements. The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at either the fundamental frequency or first-order modulation products in all typical modes of operation, including the unmodulated carrier, even if atypical. Once the reference level is established, the equipment is conditioned with typical modulating signals to produce worst-case (i.e., the widest) bandwidth. In order to measure the modulated signal properly, a resolution bandwidth that is small compared to the bandwidth required by the procuring or regulatory agency shall be used on the measuring instrument. However, the 6 dB resolution bandwidth of the measuring instrument shall be set to a value greater than 5 % of the bandwidth requirements.

8.6.3 20 dB Bandwidth limit

Intentional radiator - 20 dB Bandwidth limit: within the designated frequency band

8.6.4 Result

Intentional radiator- Maximum Measured 20 dB Bandwidth		
Operating Frequency	Maximum Measured 20 dB Bandwidth	20 dB Bandwidth limit
GHz	MHz	MHz
2.402	4.081	---
2.442	3.980	---
2.481	2.793	---

Test Cables used	K21
Test equipment used	502, test-fixture

The equipment passed the conducted tests	Yes	No	N.t.
--	-----	---------------	-----------------

Test setup photos / test results are attached	Yes	No	Annex no.: 3
---	-----	---------------	--------------

N.t.* See page no. 26

9. Additional information to the test report

Remarks	Description
N.t. ¹	Not tested, because the antenna is part of the PCB
N.t. ²	Not tested, because the EUT is directly battery powered
N.t. ³	Not tested, because not applicable to the EUT
N.t. ⁴	Not tested, because not ordered

10. List of test equipment

Type	Manufacturer/ Model no.	Serial no.	Last calibration	Next calibration	Calibration executed by
OATS (CISPR 16) to 1.0 GHz)	Dudde (103)	---	10/2015	10/2017	Dudde
OATS	Dudde (104)	---	06/2014	06/2016	Dudde
Pre-amplifier (100kHz - 1.3GHz)	Hewlett Packard 8447 E (166a)	1726A00705	07/2014	07/2016	Dudde
Spektrumanalyzer 9 kHz - 18 GHz	Rohde & Schwarz (171a)	---	06/2014	06/2016	Rhode & Schwarz
Pre-amplifier (1GHz - 18GHz)	Narda (345)	---	02/2014	02/2016	Dudde
Bilog antenna (30- 1000 MHz)	Schwarzbeck VULP 9168 (406)	---	05/2015	05/2018	Schwarzbeck
Logt. Per, Antenne (1- 18 GHz)	Schwarzbeck STLP 9148 (445a)	---	10/2015	10/2018	Schwarzbeck
Microwave Amplifier	Schwarzbeck BBV 9719 (443)	----	01/2013	01/2016	Schwarzbeck
Signal Analyzer (9 kHz –30.0 GHz)	Rohde & Schwarz FSV 30 (502)	100932	02/2013	02/2016	Rohde & Schwarz
V-LISN 50 ohms/(50 uH+5 ohms)	RFT NNB 11 (72)	13835240	08/2013	08/2016	Dudde
Receiver (9 kHz - 30MHz)	Schwarzbeck FMLK 1518 (428)	1518294 9360	08/2013	08/2016	Schwarzbeck
Panorama- Monitor FMLK / VUMA	PAZ1550 (429)	---	---	---	---
Protector limiter 9 kHz - 30MHz 10 dB	Rhode & Schwarz ESH 3Z2 (272)	357,881052	02/2013	02/2016	Dudde

11. List of test cables

Type	Manufacturer/ Model no.	Cable no.	Last calibration	Next calibration	Calibration executed by
RF- cable	Kabelmetal 18m [N]	K1a	10/2015	10/2016	Dudde
RF- cable	Aircell 0.5m [BNC]	K40	10/2015	10/2016	Dudde
RF- cable	Aircell 1m [BNC/N]	K56	10/2015	10/2016	Dudde
RF- cable	Jyebao 1.5 m [APC]	K147	10/2015	10/2016	Dudde
RF- cable	Jyebao 3 m [APC]	K148	10/2015	10/2016	Dudde
RF- cable	RG58 2.5m [BNC]	K21	10/2015	10/2016	Dudde
RF- cable	Huber + Suhner	K50	10/2015	10/2016	Dudde
RF- cable	Huber + Suhner	K51	10/2015	10/2016	Dudde
RF- cable	Huber + Suhner	K83	10/2015	10/2016	Dudde
RF- cable	Huber + Suhner	K84	10/2015	10/2016	Dudde
RF- cable	Huber + Suhner	KEMV30	10/2015	10/2016	Dudde

End of test report