




		4 way receiving sheet		49M
	name:	Four way receive -49M	position	
technology	Material name	Model specification		consumption
Patch	Ceramic capacitors	C-0603-10P $\pm$ 5%-T	C1	1
		C-0603-15P $\pm$ 5%-T	C2	2
		C-0603-222P $\pm$ 5%-T	C4	1
		C-0805-475 $\pm$ 10%-T	C5. C13	2
		C-0603-104+80%-20%-T	C6. C8. C13	3
		C-0603-333 $\pm$ 10%-T	C7	1
		C-0603-471P $\pm$ 10%-T	C9	1
		C-0603-332 $\pm$ 10%-T	C4	1
	Integrated circuit	U-FMRX2AMS-SOP16-T	MCU	1
	inductance	L-0805-3R3 $\pm$ 10%-T	L2	1
	triode	Q-2712-SOT-23A (LY) -T	Q1	1
	resistance	R-0603-560 Ω -T	R1	1
		R-0603-3K3-T	R3	1
		R-0603-220K-T	R2	1
		R-0603-2K2-T	R4. R5. R7	3
		R-0603-2M2-T	R9. R6	2
		R-0603-180K-T	R3	1
		R-0603-220 Ω -T	R10	1
plug-in unit	Electrolytic capacitor	EC-470UF/10V-6*8- $\pm$ 20%	C13	1
	Adjustable	T-K165-6T	T1	1