


## FCC PART 15.235 TEST REPORT

For

**JM Manufacturing (HK) Ltd.**

Unit G, 4/F Kaiser Estate, Phase 2, No. 47-53 Man Yue Street, Hung Hom, Kowloon, Hong Kong

**FCC ID: 2AHGJJMSDB2111-49-1**

|                                                                                                                                                                                                                                                                                                                                 |                                                                             |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|
| <b>Report Type:</b><br>Original Report                                                                                                                                                                                                                                                                                          | <b>Product Type:</b><br>RC Flamingo unicorn boat<br>49MHz remote controller |
| <b>Report Number:</b> RSZ200303833-00                                                                                                                                                                                                                                                                                           |                                                                             |
| <b>Report Date:</b> 2020-04-21                                                                                                                                                                                                                                                                                                  |                                                                             |
| Jimmy Xiao                                                                                                                                                                                                                                  |                                                                             |
| <b>Reviewed By:</b> RF Engineer                                                                                                                                                                                                                                                                                                 |                                                                             |
| <b>Test Laboratory:</b> Bay Area Compliance Laboratories Corp. (Shenzhen)<br>6/F., West Wing, Third Phase of Wanli Industrial<br>Building, Shihua Road, Futian Free Trade Zone,<br>Shenzhen, Guangdong, China<br>Tel: +86-755-33320018<br>Fax: +86-755-33320008<br><a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a> |                                                                             |

**Note:** This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA\* or any agency of the Federal Government. This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “★”.

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk “\*”. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

## **TABLE OF CONTENTS**

|                                                                                            |           |
|--------------------------------------------------------------------------------------------|-----------|
| <b>GENERAL INFORMATION.....</b>                                                            | <b>3</b>  |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....                                   | 3         |
| OBJECTIVE .....                                                                            | 3         |
| RELATED SUBMITTAL(S)/GRANT(S).....                                                         | 3         |
| TEST METHODOLOGY .....                                                                     | 3         |
| TEST FACILITY .....                                                                        | 3         |
| <b>SYSTEM TEST CONFIGURATION.....</b>                                                      | <b>4</b>  |
| JUSTIFICATION .....                                                                        | 4         |
| SPECIAL ACCESSORIES.....                                                                   | 4         |
| EQUIPMENT MODIFICATIONS .....                                                              | 4         |
| BLOCK DIAGRAM OF TEST SETUP .....                                                          | 4         |
| <b>SUMMARY OF TEST RESULTS.....</b>                                                        | <b>5</b>  |
| <b>TEST EQUIPMENT LIST .....</b>                                                           | <b>6</b>  |
| <b>FCC §15.203 - ANTENNA REQUIREMENT.....</b>                                              | <b>7</b>  |
| APPLICABLE STANDARD .....                                                                  | 7         |
| ANTENNA CONNECTOR CONSTRUCTION .....                                                       | 7         |
| <b>FCC §15.235(A) &amp; 15.235 (B)&amp;15.209 - RADIATED EMISSIONS AND BAND EDGES.....</b> | <b>8</b>  |
| APPLICABLE STANDARD .....                                                                  | 8         |
| MEASUREMENT UNCERTAINTY.....                                                               | 8         |
| EUT SETUP.....                                                                             | 8         |
| EMI TEST RECEIVER SETUP.....                                                               | 9         |
| TEST PROCEDURE .....                                                                       | 9         |
| CORRECTED AMPLITUDE & MARGIN CALCULATION .....                                             | 9         |
| TEST RESULTS SUMMARY .....                                                                 | 9         |
| TEST DATA .....                                                                            | 10        |
| <b>FCC§15.215(C) - 20DB EMISSION BANDWIDTH .....</b>                                       | <b>13</b> |
| APPLICABLE STANDARD .....                                                                  | 13        |
| TEST PROCEDURE .....                                                                       | 13        |
| TEST DATA .....                                                                            | 13        |

## GENERAL INFORMATION

### Product Description for Equipment Under Test (EUT)

|                       |                                                  |
|-----------------------|--------------------------------------------------|
| Product               | RC Flamingo unicorn boat 49MHz remote controller |
| Model                 | JMS-DB2111C                                      |
| UPC Number            | 192234048078                                     |
| Frequency Range       | 49.86 MHz                                        |
| Antenna Specification | 0.4dBi                                           |
| Voltage Range         | DC 1.5V*2 AAA batteries                          |
| Date of Test          | 2020/04/18                                       |
| Sample serial number  | RSZ200303833-RF-S1 (Assigned by BACL, Shenzhen)  |
| Received date         | 2020/03/03                                       |
| Sample/EUT Status     | Good condition                                   |

### Objective

This Type approval report is prepared on behalf of *JM Manufacturing (HK) Ltd.* in accordance with Part 2, Subpart J, and Part 15, Subparts A and C of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC rules, section 15.203, 15.205, 15.209, 15.215 and 15.235 rules.

### Related Submittal(s)/Grant(s)

No related submittal(s).

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement uncertainty with radiated emission is 4.75 dB for 30MHz-1GHz, and 4.88 dB for above 1GHz, 1.6dB for conducted measurement.

### Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 342867, the FCC Designation No. : CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

## SYSTEM TEST CONFIGURATION

### Justification

The system was configured for testing in a typical fashion (as normally used by a typical user).


### Special Accessories

No special accessories was used

### Equipment Modifications

No modification was made to the EUT.

### Block Diagram of Test Setup



**SUMMARY OF TEST RESULTS**

| FCC Rules                    | Description of Test               | Result         |
|------------------------------|-----------------------------------|----------------|
| §15.203                      | Antenna requirement               | Compliance     |
| §15.207(a)                   | AC Line Conducted Emissions       | Not Applicable |
| §15.235(a)& 15.235(b)&15.209 | Radiated Emissions and Band Edges | Compliance     |
| §15.215                      | 20 dB bandwidth                   | Compliance     |

Not Applicable: The EUT is powered by battery.

**TEST EQUIPMENT LIST**

| Manufacturer      | Description        | Model           | Serial Number | Calibration Date | Calibration Due Date |
|-------------------|--------------------|-----------------|---------------|------------------|----------------------|
| R&S               | EMI Test Receiver  | ESR3            | 102455        | 2019/7/9         | 2020/7/8             |
| Sonoma instrument | Pre-amplifier      | 310 N           | 186238        | 2019/4/20        | 2020/4/20            |
| Sunol Sciences    | Broadband Antenna  | JB1             | A040904-1     | 2017/12/22       | 2020/12/21           |
| Unknown           | Cable 2            | RF Cable 2      | F-03-EM197    | 2019/11/29       | 2020/11/28           |
| Unknown           | Cable              | Chamber Cable 1 | F-03-EM236    | 2019/11/29       | 2020/11/28           |
| Rohde & Schwarz   | Auto test software | EMC 32          | V9.10         | NCR              | NCR                  |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

---

## **FCC §15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

### **Antenna Connector Construction**

The EUT has a monopole antenna arrangement, which was permanently attached and the antenna gain is 0.4dBi, fulfill the requirement of this section. Please refer to EUT photos.

**Result:** Compliance.

## FCC §15.235(a) & 15.235 (b)&15.209 - RADIATED EMISSIONS AND BAND EDGES

### Applicable Standard

#### FCC 15.235(a)

The field strength of any emission within this band shall not exceed 10,000 microvolts/meter at 3 meters. The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply.


#### FCC 15.235(b)

The field strength of any emissions appearing between the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 26 dB below the level of the unmodulated carrier or to the general limits in §15.209, whichever permits the higher emission levels. The field strength of any emissions removed by more than 10 kHz from the band edges shall not exceed the general radiated emission limits in §15.209. All signals exceeding 20 microvolts/meter at 3 meters shall be reported in the application for certification.

### Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

### EUT Setup



The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC Part 15.235(a) & 15.235 (b) &15.209 limits.

## EMI Test Receiver Setup

The system was investigated from 30 MHz to 1000 MHz.

| Frequency Range  | RBW     | Video B/W |
|------------------|---------|-----------|
| 30MHz – 1000 MHz | 120 kHz | 300 kHz   |

## Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All radiated emission data was recorded in the Quasi-peak detection mode from 30MHz to 1GHz, Peak and average detection mode for fundamental test.

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.235(a) & 15.235 (b) & 15.209.


**Test Data****Environmental Conditions**

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 23 °C     |
| <b>Relative Humidity:</b> | 62 %      |
| <b>ATM Pressure:</b>      | 101.0 kPa |

*The testing was performed by Zero Yan & Holland Yang on 2020-04-18.*

*Test Mode: Transmitting (Scan with X-AXIS, Y-AXIS, Z-AXIS, the worst case was recorded)*

| Frequency<br>(MHz) | Corrected<br>Amplitude<br>(dBμV/m) | PK/QP/Ave. | Turntable<br>Degree | Rx Antenna    |                  | Corrected<br>Factor<br>(dB) | FCC Part 15.235(a) |                | Remark      |
|--------------------|------------------------------------|------------|---------------------|---------------|------------------|-----------------------------|--------------------|----------------|-------------|
|                    |                                    |            |                     | Height<br>(m) | Polar<br>(H / V) |                             | Limit<br>(dBμV/m)  | Margin<br>(dB) |             |
| 49.86              | 41.94                              | PK         | 106                 | 1.0           | H                | -10.9                       | 100                | 58.06          | Fundamental |
| 49.86              | 35.09                              | Ave.       | 106                 | 1.0           | H                | -10.9                       | 80                 | 44.91          |             |
| 49.86              | 59.71                              | PK         | 288                 | 1.0           | V                | -10.9                       | 100                | 40.29          |             |
| 49.86              | 52.94                              | Ave.       | 288                 | 1.0           | V                | -10.9                       | 80                 | 27.06          |             |

**Spurious Emission:****30 MHz~1 GHz**

| Frequency (MHz) | Corrected Amplitude (dBμV/m) | Antenna height (cm) | Antenna Polarity | Turntable position (degree) | Correction Factor (dB/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|------------------------------|---------------------|------------------|-----------------------------|--------------------------|----------------|-------------|
| 99.720375       | 38.11                        | 101.0               | V                | 44.0                        | -17.3                    | 43.50          | 5.39        |
| 149.583875      | 35.61                        | 108.0               | V                | 97.0                        | -14.2                    | 43.50          | 7.89        |
| 199.452500      | 27.33                        | 160.0               | V                | 163.0                       | -13.9                    | 43.50          | 16.17       |
| 249.321375      | 24.90                        | 166.0               | V                | 95.0                        | -14.1                    | 46.00          | 21.10       |
| 833.524125      | 24.38                        | 126.0               | V                | 196.0                       | 2.7                      | 46.00          | 21.62       |
| 931.355625      | 26.34                        | 218.0               | V                | 58.0                        | 4.8                      | 46.00          | 19.66       |



**Note:**

Corrected Amplitude = Corrected Factor + Reading

Corrected Factor=Antenna factor (RX) +cable loss - amplifier factor

Margin = Limit- Corr. Amplitude

**Result:** Compliance

**Band Edge:****26 dB Band Edge-Left****26 dB Band Edge-Right**

## **FCC§15.215(c) - 20dB EMISSION BANDWIDTH**

### **Applicable Standard**

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

### **Test Procedure**

Per ANSI C63.10-2013 §6.4 & §6.9.

### **Test Data**

#### **Environmental Conditions**


|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 23 °C     |
| <b>Relative Humidity:</b> | 62 %      |
| <b>ATM Pressure:</b>      | 101.0 kPa |

*The testing was performed by Zero Yan on 2020-04-18.*

*Test Mode: Transmitting*

Please refer to following plot and table.

### 20 dB Emission Bandwidth



| F <sub>L</sub><br>(MHz) | F <sub>H</sub><br>(MHz) | Permitted frequency range<br>(MHz) | Result    |
|-------------------------|-------------------------|------------------------------------|-----------|
| 49.855731               | 49.866181               | 49.82-49.90                        | Compliant |

\*\*\*\*\* END OF REPORT \*\*\*\*\*