



FCC PART 15.235 TEST REPORT

For

JM Manufacturing (HK) Ltd.

Unit G, 4/F Kaiser Estate, Phase 2, No. 47-53 Man Yue Street, Hung Hom, Kowloon, Hong Kong

FCC ID: 2AHGJJMSDB758-49-1

Report Type: Original Report	Product Type: RC SAILBOAT-49MHz CONTROLLER
Report Number: RSZ190111831-00	
Report Date: 2019-02-19	
Simon Wang <i>Simon wang</i>	
Reviewed By: RF Engineer	
Test Laboratory: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. * This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “*”.
The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity.

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
TEST FACILITY	3
SYSTEM TEST CONFIGURATION.....	4
JUSTIFICATION	4
SPECIAL ACCESSORIES.....	4
EQUIPMENT MODIFICATIONS	4
BLOCK DIAGRAM OF TEST SETUP	4
SUMMARY OF TEST RESULTS.....	5
TEST EQUIPMENT LIST	6
FCC §15.203 - ANTENNA REQUIREMENT.....	7
APPLICABLE STANDARD	7
ANTENNA CONNECTOR CONSTRUCTION	7
FCC §15.235(A) & 15.235 (B)&15.209 - RADIATED EMISSIONS AND BAND EDGES.....	8
APPLICABLE STANDARD	8
MEASUREMENT UNCERTAINTY.....	8
EUT SETUP.....	8
EMI TEST RECEIVER SETUP.....	9
TEST PROCEDURE	9
CORRECTED AMPLITUDE & MARGIN CALCULATION	9
TEST RESULTS SUMMARY	9
TEST DATA	10
FCC§15.215(C) - 20DB EMISSION BANDWIDTH	13
APPLICABLE STANDARD	13
TEST PROCEDURE	13
TEST DATA	13

GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

Product	RC SAILBOAT-49MHz CONTROLLER
Model	JMS-DB758B
UPC Number [#]	192234015186
SKU Number [#]	N/A
Frequency Range	49.86 MHz
Antenna Specification	Monopole Antenna, 0 dBi
Voltage Range	DC 3V
Date of Test	2019/01/18
Sample serial number	190111831
Received date	2019/01/11
Sample/EUT Status	Good condition

Objective

This Type approval report is prepared on behalf of *JM Manufacturing (HK) Ltd.* in accordance with Part 2, Subpart J, and Part 15, Subparts A and C of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC rules, section 15.203, 15.205, 15.209, 15.215 and 15.235 rules.

Related Submittal(s)/Grant(s)

No related submittal(s).

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement uncertainty with radiated emission is 5.81 dB for 30MHz-1GHz, and 4.88 dB for above 1GHz, 1.95dB for conducted measurement.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 342867, the FCC Designation No. : CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 5500A.

SYSTEM TEST CONFIGURATION

Justification

The system was configured for testing in a typical fashion (as normally used by a typical user).


Special Accessories

No special accessories was used

Equipment Modifications

No modification was made to the EUT.

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna requirement	Compliance
§15.207(a)	AC Line Conducted Emissions	Not Applicable
§15.235(a)& 15.235(b)&15.209	Radiated Emissions and Band Edges	Compliance
§15.215	20 dB bandwidth	Compliance

Not Applicable: The EUT is powered by battery.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	310N	186238	2018-11-12	2019-11-12
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2019-01-11	2020-01-11
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017-12-22	2020-12-21
TDK	Chamber	Chamber A	2#	2016-12-05	2019-12-05
Ducommun technologies	RF Cable	UFA147A-2362-100100	MFR64639 231029-003	2018-08-01	2019-02-01
Ducommun technologies	RF Cable	104PEA	218124002	2018-11-12	2019-11-12
Rohde & Schwarz	Auto test Software	EMC32	V9.10	NCR	NCR

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

Antenna Connector Construction

The EUT has a monopole antenna arrangement, which was permanently attached and the antenna gain is 0 dBi; fulfill the requirement of this section. Please refer to EUT photos.

Result: Compliance.

FCC §15.235(a) & 15.235 (b)&15.209 - RADIATED EMISSIONS AND BAND EDGES

Applicable Standard

FCC 15.235(a)

The field strength of any emission within this band shall not exceed 10,000 microvolts/meter at 3 meters. The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply.

FCC 15.235(b)


The field strength of any emissions appearing between the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 26 dB below the level of the unmodulated carrier or to the general limits in §15.209, whichever permits the higher emission levels. The field strength of any emissions removed by more than 10 kHz from the band edges shall not exceed the general radiated emission limits in §15.209. All signals exceeding 20 microvolts/meter at 3 meters shall be reported in the application for certification.

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-2:2011, the expanded combined standard uncertainty of radiation emissions at Bay Area Compliance Laboratories Corp. (Shenzhen) is 5.81 dB for 30MHz-1GHz and 4.88 dB for above 1GHz, and it will not be taken into consideration for the test data recorded in the report.

EUT Setup



The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC Part 15.235(a) & 15.235 (b) & 15.209 limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 1000 MHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All radiated emission data was recorded in the Quasi-peak detection mode from 30MHz to 1GHz, Peak and average detection mode for fundamental test.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.235(a) & 15.235 (b) & 15.209


Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	101.1 kPa

The testing was performed by Andy Yu on 2019-01-18.

Test Mode: Transmitting (Scan with X-AXIS, Y-AXIS, Z-AXIS, the worst case was recorded)

Frequency (MHz)	Corrected Amplitude (dBμV/m)	PK/QP/Ave.	Turntable Degree	Rx Antenna		Corrected Factor (dB)	FCC Part 15.235(a) & 15.235 (b) & 15.209		Remark
				Height (m)	Polar (H / V)		Limit (dBμV/m)	Margin (dB)	
49.86	69.13	PK	288	1.7	H	-10.9	100	30.87	Fundamental
49.86	64.26	Ave.	288	1.7	H	-10.9	80	15.74	
49.86	70.34	PK	105	1.2	V	-10.9	100	29.66	
49.86	64.87	Ave.	105	1.2	V	-10.9	80	15.13	

30 MHz~1 GHz

Frequency (MHz)	Corrected Amplitude (dBμV/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
99.724875	29.51	213.0	H	91.0	-17.3	43.50	13.99
299.150375	32.07	108.0	H	88.0	-10.7	46.00	13.93
349.024500	45.50	102.0	H	88.0	-10.8	46.00	0.50
398.884625	45.65	104.0	H	88.0	-10.3	46.00	0.35
448.754500	37.57	100.0	H	285.0	-8.3	46.00	8.43
957.642125	32.01	352.0	H	199.0	9.4	46.00	13.99

Note:


Corrected Amplitude = Corrected Factor + Reading

Corrected Factor=Antenna factor (RX) +cable loss - amplifier factor

Margin = Limit- Corr. Amplitude

Result: Compliance


26 dB Band Edge-Left



EUT

Date: 18.JAN.2019 09:42:24

26 dB Band Edge-Right



EUT

Date: 18.JAN.2019 09:44:16

Note: The Band Edge value of the modulated carrier is greater than that of the unmodulated carrier.

FCC§15.215(c) - 20dB EMISSION BANDWIDTH**Applicable Standard**

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data**Environmental Conditions**


Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	101.1 kPa

The testing was performed by Andy Yu on 2019-01-18.

Test Mode: Transmitting

Please refer to following plot and table.

20 dB Emission Bandwidth



EUT

Date: 18.JAN.2019 09:25:52

Fl(MHz)	Fh(MHz)	Permitted frequency range(MHz)	Result
49.857000000	49.863500000	49.82-49.90	Compliant

***** END OF REPORT *****