

Radio Exposure Evaluation Report

FCC ID : 2AHGTA20201A

Equipment : MEVO

Brand Name : MEVO

Model Name : A20201A

Applicant : Mevo, Inc
19 Morris Ave., Brooklyn Navy Yard, BLDG 128
Brooklyn US 11205 United States Of America

Manufacturer : Chicony Electronics Co.,Ltd.
No.69, Sec. 2, Guangfu Rd., Sanchong Dist. New
Taipei City 241 Taiwan

Standard : 47 CFR Part 2.1091

The product was received on Dec. 07, 2018, and testing was started from Mar. 09, 2019 and completed on Apr. 11, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of United States government.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Allen Lin

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

HISTORY OF THIS TEST REPORT	3
1 GENERAL DESCRIPTION	5
1.1 EUT General Information	5
1.2 Table for Permissive Change	5
1.3 Testing Location	5
2 MAXIMUM PERMISSIBLE EXPOSURE	6
2.1 Limit of Maximum Permissible Exposure	6
2.2 MPE Calculation Method	6
2.3 Calculated Result and Limit	7

Photographs of EUT V01



TEL : 886-3-327-3456
FAX : 886-3-327-0973
Report Template No.: HE1
FCC ID: 2AHGTA20201A

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

None.

Reviewed by: Sam Tsai

Report Producer: Kate Lo

1 General Description

1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
5GHz WLAN	5150-5250 5250-5350 5470-5725 5725-5850	5180-5240 5260-5320 5500-5700 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
Bluetooth	2400-2483.5	2402-2480	LE: DSSS (GFSK)

1.2 Table for Permissive Change

This product is an extension of original one reported under Sporton project number: FA780214

Below is the table for the change of the product with respect to the original one.

Modifications	Performance Checking
1.Frequency bands U-NII-2A and U-NII-2C was added.	All
2. Equipment & Brand name & Applicant & Manufacturer are updated.	N/A

1.3 Testing Location

Testing Location			
☒	HWA YA	ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)	
		TEL : 886-3-327-3456	FAX : 886-3-327-0973
Test site Designation No. TW1190 with FCC.			
☐	JHUBEI	ADD : No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County, Taiwan (R.O.C.)	
		TEL : 886-3-656-9065	FAX : 886-3-656-9085
Test site Designation No. TW0006 with FCC.			

2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

BT LE

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)
2.4G;BT-LE	1.20	9.09	10.29	0.01069	20	0.00213	1.00000

WLAN 2.4G

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)
2.4G;G1D	1.20	22.33	23.53	0.22542	20	0.04485	1.00000
2.4G;D1D	1.20	21.08	22.28	0.16904	20	0.03363	1.00000

WLAN 5G

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)
5.2G;D1D	1.20	22.56	23.76	0.23768	20	0.04728	1.00000
5.3G;D1D	1.20	21.31	22.51	0.19999	20	0.03979	1.00000
5.6G;D1D	1.20	20.55	21.75	0.16788	20	0.03340	1.00000
5.8G;D1D	1.20	22.07	23.27	0.21232	20	0.04224	1.00000

————THE END————