


RF TEST REPORT



Report No.: 16070868-FCC-R

Supersede Report No.: N/A

Applicant	Shenzhen Glamour Bedding Supplies Co.,Ltd.	
Product Name	FitSleep	
Model No.	α 1	
Serial No.	FitSleep	
Test Standard	FCC Part 15.247: 2015, ANSI C63.10: 2013	
Test Date	August 16 to 31, 2016	
Issue Date	September 01, 2016	
Test Result	☒ Pass ☐ Fail	
Equipment complied with the specification ☒		
Equipment did not comply with the specification ☐		
		
Loren Luo Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report No.	16070868-FCC-R
Page	3 of 48

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	8
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	9
6.1 ANTENNA REQUIREMENT	9
6.2 DTS (6 DB) CHANNEL BANDWIDTH	10
6.3 MAXIMUM OUTPUT POWER	12
6.4 POWER SPECTRAL DENSITY	14
6.5 BAND-EDGE & UNWANTED EMISSIONS INTO RESTRICTED FREQUENCY BANDS	16
6.6 AC POWER LINE CONDUCTED EMISSIONS	19
6.7 RADIATED SPURIOUS EMISSIONS & RESTRICTED BAND	29
ANNEX A. TEST INSTRUMENT	37
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS	38
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT	43
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	47
ANNEX E. DECLARATION OF SIMILARITY	48

1. Report Revision History

Report No.	Report Version	Description	Issue Date
16070868-FCC-R	NONE	Original	September 01, 2016

2. Customer information

Applicant Name	Shenzhen Glamour Bedding Supplies Co.,Ltd.
Applicant Add	Floor 1,Building 1,Zhuguang Innovation Science and Technology Park,Zhuguang Road,Nanshan District,Shenzhen
Manufacturer	Shenzhen Glamour Bedding Supplies Co.,Ltd.
Manufacturer Add	Floor 1,Building 1,Zhuguang Innovation Science and Technology Park,Zhuguang Road,Nanshan District,Shenzhen

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT:	FitSleep
Main Model:	α 1
Serial Model:	FitSleep
Date EUT received:	August 15, 2016
Test Date(s):	August 16 to 31, 2016
Equipment Category :	DTS
Antenna Gain:	0.8dBi
Antenna Type:	PCB antenna
Type of Modulation:	GFSK
RF Operating Frequency (ies):	2402-2480 MHz(TX/RX)
Max. Output Power:	-2.389dBm
Number of Channels:	40CH
Port:	USB Port
Trade Name :	FitSleep

Test Report No.	16070868-FCC-R
Page	7 of 48

Adapter 1:

Model: LPL-A005050100Z

Input: 100-240V~50/60Hz,200mA MAX

Output: DC5V,1000mA

Adapter 2:

Model: LPL-A005050100A

Input: 100-240V~50/60Hz,200mA MAX

Output: DC5V,1000mA

Battery:

Model: α 1(554858G)

Rated Capacity: 2000mAh/7.6Wh

Typical Capacity:2000mAh/7.6Wh

Norminal Voltage: 3.8v

Limited Charge Voltage: 4.35v

Input Power:

FCC ID:

2AHH2-FSA1

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247 (a)(2)	DTS (6 dB) CHANNEL BANDWIDTH	Compliance
§15.247(b)(3)	Conducted Maximum Output Power	Compliance
§15.247(e)	Power Spectral Density	Compliance
§15.247(d)	Band-Edge & Unwanted Emissions into Restricted Frequency Bands	Compliance
§15.207 (a),	AC Power Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Spurious Emissions & Unwanted Emissions into Restricted Frequency Bands	Compliance

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. Measurements, Examination And Derived Results

6.1 Antenna Requirement

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has 1 antenna:


A permanently attached PCB antenna for BLE, the gain is 0.8dBi for BLE.

The antenna meets up with the ANTENNA REQUIREMENT.

Result: Compliance.

6.2 DTS (6 dB) Channel Bandwidth

Temperature	24°C
Relative Humidity	51%
Atmospheric Pressure	1027mbar
Test date :	August 27, 2016
Tested By :	Loren Luo

Spec	Item	Requirement	Applicable
§ 15.247(a)(2)	a)	6dB BW≥ 500kHz;	☒
RSS Gen(4.6.1)	b)	99% BW: For FCC reference only; required by IC.	☒
Test Setup	 Spectrum Analyzer EUT		
Test Procedure	558074 D01 DTS MEAS Guidance v03r03, 8.1 DTS bandwidth 6dB Emission bandwidth measurement procedure - Set RBW = 100 kHz. - Set the video bandwidth (VBW) ≥ 3 RBW. - Detector = Peak. - Trace mode = max hold. - Sweep = auto couple. - Allow the trace to stabilize. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.		
Remark			
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

6dB Bandwidth measurement result

Test Data

CH	Frequency (MHz)	6dB Bandwidth (kHz)	99% Occupied Bandwidth (MHz)
Low	2402	726.221	1.0981
Mid	2440	722.782	1.0934
High	2480	730.079	1.0885


Test Plots



6.3 Maximum Output Power

Temperature	24°C
Relative Humidity	51%
Atmospheric Pressure	1027mbar
Test date :	August 27, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (3),RSS210 (A8.4)	a)	FHSS in 2400-2483.5MHz with ≥ 75 channels: ≤ 1 Watt	☐
	b)	FHSS in 5725-5850MHz: ≤ 1 Watt	☐
	c)	For all other FHSS in the 2400-2483.5MHz band: ≤ 0.125 Watt.	☐
	d)	FHSS in 902-928MHz with ≥ 50 channels: ≤ 1 Watt	☐
	e)	FHSS in 902-928MHz with ≥ 25 & <50 channels: ≤ 0.25 Watt	☐
	f)	DTS in 902-928MHz, 2400-2483.5MHz: ≤ 1 Watt	☒
Test Setup	 Spectrum Analyzer EUT		
Test Procedure	558074 D01 DTS MEAS Guidance v03r03, 9.1.2 Integrated band power method Maximum output power measurement procedure a) Set the RBW $\geq$ DTS bandwidth. b) Set VBW $\geq 3 \times$ RBW. c) Set span $\geq 3 \times$ RBW d) Sweep time = auto couple. e) Detector = peak. f) Trace mode = max hold. g) Allow trace to fully stabilize. h) Use peak marker function to determine the peak amplitude level.		
Remark			
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

Output Power measurement result

Test Data


Type	CH	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Result
Output power	Low	2402	-2.396	30	Pass
	Mid	2440	-2.389	30	Pass
	High	2480	-2.751	30	Pass

Test Plots



6.4 Power Spectral Density

Temperature	24°C
Relative Humidity	51%
Atmospheric Pressure	1027mbar
Test date :	August 27, 2016
Tested By :	Loren Luo

Spec	Item	Requirement	Applicable
§15.247(e)	a)	The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.	☒
Test Setup	 Spectrum Analyzer EUT		
Test Procedure	558074 D01 DTS MEAS Guidance v03r03, 10.2 power spectral density method power spectral density measurement procedure - a) Set analyzer center frequency to DTS channel center frequency. - b) Set the span to 1.5 times the DTS bandwidth. - c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$. - d) Set the VBW $\geq 3 \times \text{RBW}$. - e) Detector = peak. - f) Sweep time = auto couple. - g) Trace mode = max hold. - h) Allow trace to fully stabilize. - i) Use the peak marker function to determine the maximum amplitude level within the RBW. - j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.		
Remark			
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A


Power Spectral Density measurement result

Test Data

Type	CH	Freq (MHz)	Reading (dBm)	Factor (dB)	Result (dBm)	Limit (dBm)	Result
PSD	Low	2402	-9.107	-5.23	-14.337	8	Pass
	Mid	2440	-9.315	-5.23	-14.545	8	Pass
	High	2480	-9.949	-5.23	-15.179	8	Pass

Note: factor=10log(3/10)=-5.23


Test Plots



6.5 Band-Edge & Unwanted Emissions into Restricted Frequency Bands

Temperature	24°C
Relative Humidity	56%
Atmospheric Pressure	1023mbar
Test date :	August 23, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(d)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	☒
Test Setup			
Test Procedure	Radiated Method Only 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator. 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.		

Test Report No.	16070868-FCC-R
Page	17 of 48


	- 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. - 5. Repeat above procedures until all measured frequencies were complete.
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A


Test Plots

Band Edge measurement result




Band Edge, Left Side (Peak)

Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz



Band Edge, Right Side (Peak)

Note: F1 is frequency 2483.5MHz



Band Edge, Left Side-AV

Note: (no need if PK value less than the AV limit)


Band Edge, Right Side-AV

6.6 AC Power Line Conducted Emissions

Temperature	24°C
Relative Humidity	56%
Atmospheric Pressure	1023mbar
Test date :	August 23, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable		
47CFR§15.207, RSS210 (A8.1)	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu] H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.	☒		
		Frequency ranges (MHz)		Limit (dBµV)	
				QP	Average
		0.15 ~ 0.5		66 – 56	56 – 46
		0.5 ~ 5		56	46
5 ~ 30	60	50			

Test Setup	 Note: 1.Support units were connected to second LISN. 2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.
------------	---

Procedure	- The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table. - The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains. - The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss
-----------	---

Test Report No.	16070868-FCC-R
Page	20 of 48


	coaxial cable. 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Adapter 1 :LPL-A005050100Z

Test Mode: Transmitting Mode




Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)
1	L1	0.1695	32.58	QP	10.03	42.61	64.98	-22.37
2	L1	0.1695	20.18	AVG	10.03	30.21	54.98	-24.77
3	L1	0.2046	31.20	QP	10.03	41.23	63.42	-22.19
4	L1	0.2046	18.48	AVG	10.03	28.51	53.42	-24.91
5	L1	0.2553	30.32	QP	10.03	40.35	61.58	-21.23
6	L1	0.2553	18.33	AVG	10.03	28.36	51.58	-23.22
7	L1	0.2826	29.42	QP	10.03	39.45	60.74	-21.29
8	L1	0.2826	20.36	AVG	10.03	30.39	50.74	-20.35
9	L1	0.4932	33.11	QP	10.03	43.14	56.11	-12.97
10	L1	0.4932	24.11	AVG	10.03	34.14	46.11	-11.97
11	L1	10.8741	24.20	QP	10.16	34.36	60.00	-25.64
12	L1	10.8741	14.03	AVG	10.16	24.19	50.00	-25.81

Test Mode: Transmitting Mode




Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)
1	N	0.1500	41.28	QP	10.02	51.30	66.00	-14.70
2	N	0.1500	26.00	AVG	10.02	36.02	56.00	-19.98
3	N	0.1773	39.48	QP	10.02	49.50	64.61	-15.11
4	N	0.1773	25.92	AVG	10.02	35.94	54.61	-18.67
5	N	0.2085	36.92	QP	10.02	46.94	63.26	-16.32
6	N	0.2085	22.89	AVG	10.02	32.91	53.26	-20.35
7	N	0.2366	34.99	QP	10.02	45.01	62.21	-17.20
8	N	0.2366	19.66	AVG	10.02	29.68	52.21	-22.53
9	N	0.2865	31.33	QP	10.02	41.35	60.63	-19.28
10	N	0.2865	18.51	AVG	10.02	28.53	50.63	-22.10
11	N	0.4971	30.43	QP	10.02	40.45	56.05	-15.60
12	N	0.4971	15.50	AVG	10.02	25.52	46.05	-20.53

Test Mode: Transmitting Mode




Test Data

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)
1	L1	0.1695	37.92	QP	10.03	47.95	64.98	-17.03
2	L1	0.1695	21.29	AVG	10.03	31.32	54.98	-23.66
3	L1	0.1968	38.19	QP	10.03	48.22	63.74	-15.52
4	L1	0.1968	22.04	AVG	10.03	32.07	53.74	-21.67
5	L1	0.2280	34.99	QP	10.03	45.02	62.52	-17.50
6	L1	0.2280	19.82	AVG	10.03	29.85	52.52	-22.67
7	L1	0.2553	34.87	QP	10.03	44.90	61.58	-16.68
8	L1	0.2553	19.08	AVG	10.03	29.11	51.58	-22.47
9	L1	0.2865	32.73	QP	10.03	42.76	60.63	-17.87
10	L1	0.2865	18.01	AVG	10.03	28.04	50.63	-22.59
11	L1	0.5049	28.20	QP	10.03	38.23	56.00	-17.77
12	L1	0.5049	13.91	AVG	10.03	23.94	46.00	-22.06

Test Mode: Transmitting Mode




Test Data

Phase Neutral Plot at 240Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)
1	N	0.1656	36.63	QP	10.02	46.65	65.18	-18.53
2	N	0.1656	25.57	AVG	10.02	35.59	55.18	-19.59
3	N	0.1968	34.78	QP	10.02	44.80	63.74	-18.94
4	N	0.1968	25.42	AVG	10.02	35.44	53.74	-18.30
5	N	0.2202	34.64	QP	10.02	44.66	62.81	-18.15
6	N	0.2202	25.91	AVG	10.02	35.93	52.81	-16.88
7	N	0.2514	32.13	QP	10.02	42.15	61.71	-19.56
8	N	0.2514	23.96	AVG	10.02	33.98	51.71	-17.73
9	N	0.5010	31.75	QP	10.02	41.77	56.00	-14.23
10	N	0.5010	27.70	AVG	10.02	37.72	46.00	-8.28
11	N	11.5449	27.33	QP	10.16	37.49	60.00	-22.51
12	N	11.5449	16.75	AVG	10.16	26.91	50.00	-23.09

Adapter 2: LPL-A005050100A

Test Mode: Transmitting Mode




Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)
1	L1	0.1695	36.92	QP	10.03	46.95	64.98	-18.03
2	L1	0.1695	23.79	AVG	10.03	33.82	54.98	-21.16
3	L1	0.1929	35.15	QP	10.03	45.18	63.91	-18.73
4	L1	0.1929	21.52	AVG	10.03	31.55	53.91	-22.36
5	L1	0.2475	32.01	QP	10.03	42.04	61.84	-19.80
6	L1	0.2475	23.35	AVG	10.03	33.38	51.84	-18.46
7	L1	0.2904	35.69	QP	10.03	45.72	60.51	-14.79
8	L1	0.2904	26.93	AVG	10.03	36.96	50.51	-13.55
9	L1	1.0158	28.29	QP	10.03	38.32	56.00	-17.68
10	L1	1.0158	18.38	AVG	10.03	28.41	46.00	-17.59
11	L1	8.7993	26.68	QP	10.13	36.81	60.00	-23.19
12	L1	8.7993	15.32	AVG	10.13	25.45	50.00	-24.55

Test Mode: Transmitting Mode




Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)
1	N	0.1695	37.41	QP	10.02	47.43	64.98	-17.55
2	N	0.1695	24.16	AVG	10.02	34.18	54.98	-20.80
3	N	0.1929	35.62	QP	10.02	45.64	63.91	-18.27
4	N	0.1929	21.91	AVG	10.02	31.93	53.91	-21.98
5	N	0.2436	34.66	QP	10.02	44.68	61.97	-17.29
6	N	0.2436	23.83	AVG	10.02	33.85	51.97	-18.12
7	N	0.2904	35.98	QP	10.02	46.00	60.51	-14.51
8	N	0.2904	25.93	AVG	10.02	35.95	50.51	-14.56
9	N	0.3879	37.51	QP	10.02	47.53	58.11	-10.58
10	N	0.3879	26.57	AVG	10.02	36.59	48.11	-11.52
11	N	3.2184	30.06	QP	10.05	40.11	56.00	-15.89
12	N	3.2184	15.23	AVG	10.05	25.28	46.00	-20.72

Test Mode: Transmitting Mode




Test Data

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)
1	L1	0.1656	36.50	QP	10.03	46.53	65.18	-18.65
2	L1	0.1656	22.93	AVG	10.03	32.96	55.18	-22.22
3	L1	0.2865	35.99	QP	10.03	46.02	60.63	-14.61
4	L1	0.2865	20.63	AVG	10.03	30.66	50.63	-19.97
5	L1	0.5751	32.66	QP	10.03	42.69	56.00	-13.31
6	L1	0.5751	16.92	AVG	10.03	26.95	46.00	-19.05
7	L1	1.0275	30.37	QP	10.03	40.40	56.00	-15.60
8	L1	1.0275	19.07	AVG	10.03	29.10	46.00	-16.90
9	L1	3.2652	27.45	QP	10.06	37.51	56.00	-18.49
10	L1	3.2652	13.25	AVG	10.06	23.31	46.00	-22.69
11	L1	8.5419	26.72	QP	10.13	36.85	60.00	-23.15
12	L1	8.5419	13.71	AVG	10.13	23.84	50.00	-26.16

Test Mode: Transmitting Mode



Test Data

Phase Neutral Plot at 240Vac, 60Hz


No.	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)
1	N	0.2163	36.20	QP	10.02	46.22	62.96	-16.74
2	N	0.2163	24.44	AVG	10.02	34.46	52.96	-18.50
3	N	0.2865	37.14	QP	10.02	47.16	60.63	-13.47
4	N	0.2865	25.93	AVG	10.02	35.95	50.63	-14.68
5	N	0.4425	37.13	QP	10.02	47.15	57.01	-9.86
6	N	0.4425	27.13	AVG	10.02	37.15	47.01	-9.86
7	N	0.5751	34.97	QP	10.02	44.99	56.00	-11.01
8	N	0.5751	23.59	AVG	10.02	33.61	46.00	-12.39
9	N	1.0509	33.07	QP	10.03	43.10	56.00	-12.90
10	N	1.0509	26.25	AVG	10.03	36.28	46.00	-9.72
11	N	2.8410	31.80	QP	10.05	41.85	56.00	-14.15
12	N	2.8410	20.22	AVG	10.05	30.27	46.00	-15.73

6.7 Radiated Spurious Emissions & Restricted Band

Temperature	24°C
Relative Humidity	56%
Atmospheric Pressure	1023mbar
Test date :	August 23, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable										
47CFR§15.247(d), RSS210 (A8.5)	a)	Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges <table><tr><th>Frequency range (MHz)</th><th>Field Strength (µV/m)</th></tr><tr><td>30 – 88</td><td>100</td></tr><tr><td>88 – 216</td><td>150</td></tr><tr><td>216 960</td><td>200</td></tr><tr><td>Above 960</td><td>500</td></tr></table>	Frequency range (MHz)	Field Strength (µV/m)	30 – 88	100	88 – 216	150	216 960	200	Above 960	500	☒
	Frequency range (MHz)	Field Strength (µV/m)											
	30 – 88	100											
	88 – 216	150											
216 960	200												
Above 960	500												
b)	For non-restricted band, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB or 30dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, determined by the measurement method on output power to be used. Attenuation below the general limits specified in § 15.209(a) is not required ☒ 20 dB down ☐ 30 dB down	☒											
c)	or restricted band, emission must also comply with the radiated emission limits specified in 15.209	☒											

Test Setup	
Procedure	- The EUT was switched on and allowed to warm up to its normal operating condition. - The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: - Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen. - The EUT was then rotated to the direction that gave the maximum emission. - Finally, the antenna height was adjusted to the height that gave the maximum emission. - The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi Peak detection at frequency below 1GHz. - The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.
Remark	Different RF configuration has been evaluated but not much difference was found. The data presented here is the worst case data with EUT under 802.11n – HT20-2437MHz mode.
Result	☒ Pass ☐ Fail


Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Adapter 1: LPL-A005050100Z

Test Mode:	Transmitting Mode
------------	-------------------

Below 1GHz




Test Data

Vertical Polarity Plot @3m

No	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Height	Degree
1	H	36.0007	36.99	peak	-4.67	32.32	40.00	-7.68	100	331
2	H	42.8998	38.24	peak	-9.53	28.71	40.00	-11.29	100	267
3	H	47.8260	38.63	peak	-12.20	26.43	40.00	-13.57	100	353
4	H	87.4177	33.39	peak	-13.44	19.95	40.00	-20.05	100	203
5	H	290.0172	27.07	peak	-7.36	19.71	46.00	-26.29	100	68
6	H	477.1694	29.41	peak	-2.33	27.08	46.00	-18.92	100	218

Below 1GHz



Test Data


Horizontal Polarity Plot @3m

No	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Height	Degree
1	V	31.1798	34.23	peak	-1.13	33.10	40.00	-6.90	100	63
2	V	35.8747	36.76	peak	-4.58	32.18	40.00	-7.82	100	70
3	V	42.8998	37.84	peak	-9.53	28.31	40.00	-11.69	100	44
4	V	60.4919	41.17	peak	-14.33	26.84	40.00	-13.16	100	134
5	V	73.8756	37.08	peak	-13.72	23.36	40.00	-16.64	100	85
6	V	313.2760	33.62	peak	-6.51	27.11	46.00	-18.89	100	40

Adapter 2: LPL-A005050100A

Test Mode:	Transmitting Mode
------------	-------------------

Below 1GHz




Test Data

Vertical Polarity Plot @3m

No	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Height	Degree
1	H	35.8747	35.71	peak	-4.58	31.13	40.00	-8.87	100	37
2	H	42.8998	37.11	peak	-9.53	27.58	40.00	-12.42	100	74
3	H	47.8260	38.05	peak	-12.20	25.85	40.00	-14.15	100	149
4	H	81.2117	32.87	peak	-13.71	19.16	40.00	-20.84	100	6
5	H	227.6906	26.34	peak	-8.99	17.35	46.00	-28.65	100	319
6	H	896.9965	30.66	peak	4.64	35.30	46.00	-10.70	100	270

Below 1GHz



Test Data

Horizontal Polarity Plot @3m

No	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Height	Degree
1	V	35.8747	36.06	peak	-4.58	31.48	40.00	-8.52	100	37
2	V	42.8998	37.54	peak	-9.53	28.01	40.00	-11.99	100	74
3	V	54.8348	46.57	peak	-13.74	32.83	40.00	-7.17	100	195
4	V	81.2117	35.49	peak	-13.71	21.78	40.00	-18.22	100	6
5	V	138.3873	31.67	peak	-8.45	23.22	43.50	-20.28	100	138
6	V	163.7550	32.80	peak	-8.59	24.21	43.50	-19.29	100	202

Above 1GHz

Test Mode:	Transmitting Mode
------------	-------------------

Low Channel (2402 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4804	37.95	AV	V	33.83	6.86	31.72	46.92	54	-7.08
4804	37.26	AV	H	33.83	6.86	31.72	46.23	54	-7.77
4804	48.11	PK	V	33.83	6.86	31.72	57.08	74	-16.92
4804	47.05	PK	H	33.83	6.86	31.72	56.02	74	-17.98
17789	25.16	AV	V	45.03	11.21	32.38	49.02	54	-4.98
17789	23.98	AV	H	45.03	11.21	32.38	47.84	54	-6.16
17789	41.26	PK	V	45.03	11.21	32.38	65.12	74	-8.88
17789	40.35	PK	H	45.03	11.21	32.38	64.21	74	-9.79

Middle Channel (2440 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4880	38.12	AV	V	33.86	6.82	31.82	46.98	54	-7.02
4880	37.39	AV	H	33.86	6.82	31.82	46.25	54	-7.75
4880	48.26	PK	V	33.86	6.82	31.82	57.12	74	-16.88
4880	47.32	PK	H	33.86	6.82	31.82	56.18	74	-17.82
17810	25.33	AV	V	45.15	11.18	32.41	49.25	54	-4.75
17810	24.11	AV	H	45.15	11.18	32.41	48.03	54	-5.97
17810	42.01	PK	V	45.15	11.18	32.41	65.93	74	-8.07
17810	41.12	PK	H	45.15	11.18	32.41	65.04	74	-8.96

High Channel (2480 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4960	38.05	AV	V	33.9	6.76	31.92	46.79	54	-7.21
4960	37.24	AV	H	33.9	6.76	31.92	45.98	54	-8.02
4960	48.19	PK	V	33.9	6.76	31.92	56.93	74	-17.07
4960	47.28	PK	H	33.9	6.76	31.92	56.02	74	-17.98
17796	25.27	AV	V	45.22	11.35	32.38	49.46	54	-4.54
17796	24.09	AV	H	45.22	11.35	32.38	48.28	54	-5.72
17796	41.76	PK	V	45.22	11.35	32.38	65.95	74	-8.05
17796	40.86	PK	H	45.22	11.35	32.38	65.05	74	-8.95

Note:


- 1, The testing has been conformed to $10 \times 2480 \text{ MHz} = 24,800 \text{ MHz}$
- 2, All other emissions more than 30 dB below the limit
- 3, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted					
EMI test receiver	ESCS30	8471241027	09/17/2015	09/16/2016	☒
Line Impedance	LI-125A	191106	09/25/2015	09/24/2016	☒
Line Impedance	LI-125A	191107	09/25/2015	09/24/2016	☒
LISN	ISN T800	34373	09/25/2015	09/24/2016	☒
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/24/2015	09/23/2016	☒
Transient Limiter	LIT-153	531118	09/01/2015	08/31/2016	☒
RF conducted test					
Agilent ESA-E SERIES	E4407B	MY45108319	09/17/2015	09/16/2016	☒
Power Splitter	1#	1#	09/01/2015	08/31/2016	☒
DC Power Supply	E3640A	MY40004013	09/17/2015	09/16/2016	☒
Radiated Emissions					
EMI test receiver	ESL6	100262	09/17/2015	09/16/2016	☒
Positioning Controller	UC3000	MF780208282	11/19/2015	11/18/2016	☒
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	09/01/2015	08/31/2016	☒
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/24/2016	03/23/2017	☒
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/21/2015	09/20/2016	☒
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/24/2015	09/23/2016	☒
Universal Radio Communication Tester	CMU200	121393	09/25/2015	09/24/2016	☒

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo





EUT - Bottom View




EUT - Left View



EUT - Right View




Adapter 1 - Label View



Adapter 2 - Label View

Annex B.ii. Photograph: EUT Internal Photo




Cover Off - Top View 1(cover with glue)




Cover Off - Top View 2(cover with glue)



Cover Off - Top View 3(cover without glue)



Main Board - Front View(cover with glue)




Main Board - Rear View(cover with glue)




Main Board - Front View(cover without glue)


Test Report No.	16070868-FCC-R
Page	41 of 48




Main Board – Rear View(cover without glue)



Battery – Front View



Battery – Rear View



BLE Antenna View


Annex B.iii. Photograph: Test Setup Photo




Conducted Emissions Test Setup Front View




Conducted Emissions Test Setup Side View



Radiated Spurious Emissions Test Setup Below 1GHz



Radiated Spurious Emissions Test Setup Above 1GHz




Radiated Spurious Emissions Test Above 1GHz


Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK


Block Configuration Diagram for AC Line Conducted Emissions



Block Configuration Diagram for Radiated Emission (Below 1GHz) .



Block Configuration Diagram for Radiated Emission (Above 1GHz) .



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Lenovo	Lenovo Laptop	E40	N3-F5022
NOKIA	Phone	S6T	TX210018
Shenzhen Glamour Bedding Supplies Co.,Ltd.	Adapter	LPL-A005050100Z	S201605305

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	50cm	S201605305

Test Report No.	16070868-FCC-R
Page	47 of 48

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see attachment

Test Report No.	16070868-FCC-R
Page	48 of 48

Annex E. DECLARATION OF SIMILARITY

Shenzhen Glamour Bedding Supplies Co.,Ltd.

To: SIEMIC ,775 Montague Expressway, Milpitas, CA 95035,USA

Declaration Letter

Dear Sir,

For our business issue and marketing requirement, we would like to list 2 model numbers on the FCC certificates and reports, as following:


Model No.: α 1,FitSleep

We declare that, all the model PCB ,Antenna and Appearance shape , accessories are the same . The difference of these is listed as below:

Main Model No	Serial Model No	Difference
α 1	FitSleep	By further modifying the firmware and program,FitSleep series products will make crucial changes in monitoring module and sleep induction module and increase the deep sleep aid function.

Thank you!

Signature:



Printed name/title: Kuntao Lu/Technical Director
Address:Floor 1,Building 1,Zhuguang Innovation Science and Technology Park,
Zhuguang Road,Nanshan District,Shenzhen