



FCC Test Report

FCC ID:2AHHH-GP70020

Product : Android POS

Trade Name : Pintron

Model Number : GP7002

Serial Model : N/A

Report No. : NTEK-2015NT12113414F1

Prepared for

Pintron Company Limited

RM 1302, 13/F, Building A3, LeeLang Software Park, No.31,Rd.BuLan,
LongGang District,City ShenZhen,518112,P.R. C.

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street,
Bao'an District, Shenzhen P.R. China

Tel.: +86-0755-61156588 Fax.: +86-0755-61156599

Website: www.ntek.org.cn

TEST RESULT CERTIFICATION

Applicant's name Pintron Company Limited
Address RM 1302, 13/F, Building A3, LeeLang Software Park, No.31,Rd.
 BuLan,LongGang District,City ShenZhen,518112,P.R. C.
Manufacturer's Name Pintron Company Limited
Address RM 1302, 13/F, Building A3, LeeLang Software Park, No.31,Rd.
 BuLan,LongGang District,City ShenZhen,518112,P.R. C.

Product description

Product name Android POS
Model and/or type GP7002
reference FCC Part15B:01 Oct.2015
Standards ANSI C63.4:2014

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with Part 15 of FCC Rules. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests 11 Dec. 2015 ~28 Jan. 2016

Date of Issue..... 28 Jan. 2016

Test Result..... **Pass**

Testing Engineer : Eileen Liu.
 (Eileen Liu)

Technical Manager : Brown Lu
 (Brown Lu)

Authorized Signatory : Sam. Chen
 (Sam Chen)

Table of Contents	Page
1 . TEST SUMMARY	4
1.1 TEST FACILITY	5
1.2 MEASUREMENT UNCERTAINTY	5
2 . GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST SETUP	8
2.3 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL	10
2.4 MEASUREMENT INSTRUMENTS LIST	11
3 . EMC EMISSION TEST	12
3.1 CONDUCTED EMISSION MEASUREMENT	12
3.1.1 POWER LINE CONDUCTED EMISSION	12
3.1.2 TEST PROCEDURE	13
3.1.3 TEST SETUP	13
3.1.4 EUT OPERATING CONDITIONS	13
3.1.5 TEST RESULTS	14
3.2 RADIATED EMISSION MEASUREMENT	22
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	22
3.2.2 TEST PROCEDURE	22
3.2.3 TEST SETUP	23
3.2.4 TEST RESULTS	24
3.2.5 TEST RESULTS(1000~12400MHz)	26
4 . EUT TEST PHOTO	27

1. TEST SUMMARY

Test procedures according to the technical standards:

EMC Emission				
Standard	Test Item	Limit	Judgment	Remark
FCC Part15B:2014 ANSI C63.4: 2014	Conducted Emission	Class B	PASS	
	Radiated Emission	Class B	PASS	

NOTE:

- (1) 'N/A' denotes test is not applicable in this Test Report
- (2) For client's request and manual description, the test will not be executed.

1.1 TEST FACILITY

NTEK Testing Technology Co., Ltd

Add. : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

FCC Registration Number:238937; IC Registration Number:9270A-1

CNAS Registration Number:L5516

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95** %.

A. Conducted Measurement :

Test Site	Method	Measurement Frequency Range	U , (dB)	NOTE
NTEKC01	ANSI	150 KHz ~ 30MHz	3.2	

B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	U , (dB)	NOTE
NTEKA01	ANSI	30MHz ~ 1000MHz	4.7	
		1GHz ~12.4GHz	5.0	

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Android POS	
Trade Name	Pintron	
Model Name	GP7002	
Serial Model	N/A	
Model Difference	N/A	
Product Description	The EUT is a Android POS.	
	Connecting I/O port:	USB, DC in
	Operation Frequency:	WIFI:802.11b/g/n(20MHz): 2412~2462MHz 802.11n(40MHz):2422~2452MHz GSM: 824.2-848.8MHz/1850.2-1909.8MHz WCDMA: 826.4-846.6MHz/ 1852.4-1907.6MHz
	Modulation Type:	IEEE 802.11b : DSSS (CCK, QPSK, DBPSK) IEEE 802.11g/n (HT20/HT40) : OFDM (64QAM, 16QAM, QPSK, BPSK) GSM / DCS: GMSK WCDMA:QPSK
Power Source	DC Voltage	
Adapter	Model:YN36W-0900300UW Input: AC100-240V~, 50/60Hz,1.0A Output: 9V ---, 3A	
Battery	DC 7.4V,4000mAh	

2.1.1 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	Downloading Mode


For Conducted Test	
Final Test Mode	Description
Mode 1	Downloading Mode

For Radiated Test	
Final Test Mode	Description
Mode 1	Downloading Mode


Note: Final Test Mode: Through Pre-scan, find the mode 1 is the worst case.
Only the worst case mode is recorded in the report.

2.2 DESCRIPTION OF TEST SETUP


RE



CE Test 1



CE Test 2



2.3 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
E-1	Android POS	Pintron	GP7002	N/A	EUT
E-2	Printer	Canon	L11121E	LBP2900	
E-3	Personal computer	DELL	FT4Y23X	34413561645	
E-4	Monitor	DELL	IN2020MB	cn-0y6mhx-74261-11f-67es	
E-5	Keyboard	DELL	SK-8185	OY526KUS	
E-6	Mouse	DELL	MS111-P	cn-011d3v-71581-11e-1th7	
E-7	Earphone	N/A	2688	N/A	
E-8	Adapter	N/A	YN36W-0900300UW	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
USB	NO	NO	1.2m	
USB	NO	NO	1.0m	
USB	NO	NO	1.0m	
USB	NO	NO	1.0m	
VGA	NO	NO	1.0m	
Earphone Line	NO	NO	1.0m	
Power line	NO	YES	1.2m	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” means “shielded” “with core”; “NO” means “unshielded” “without core”.

2.4 MEASUREMENT INSTRUMENTS LIST

Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2015.07.06	2016.07.05	1 year
2	Test Receiver	R&S	ESPI	101318	2015.06.07	2016.06.06	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2015.07.06	2016.07.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2015.06.07	2016.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2015.06.07	2016.06.06	1 year
6	Horn Antenna	EM	EM-AH-10180	2011071402	2015.07.06	2016.07.05	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2015.07.06	2016.07.05	1 year
8	Amplifier	EM	EM-30180	060538	2015.12.22	2016.12.21	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2015.06.08	2016.06.07	1 year
10	Power Meter	R&S	NRVS	100696	2015.07.06	2016.07.05	1 year
11	Power Sensor	R&S	URV5-Z4	0395.1619.05	2015.07.06	2016.07.05	1 year
12	Test Cable	N/A	R-01	N/A	2015.07.06	2016.07.05	1 year
13	Test Cable	N/A	R-02	N/A	2015.07.06	2016.07.05	1 year

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2015.06.06	2016.06.05	1 year
2	LISN	R&S	ENV216	101313	2015.08.24	2016.08.23	1 year
3	LISN	EMCO	3816/2	00042990	2015.08.24	2016.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2015.06.07	2016.06.06	1 year
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	2015.06.07	2016.06.06	1 year
6	Absorbing clamp	R&S	MOS-21	100423	2015.06.08	2016.06.07	1 year
7	Test Cable	N/A	C01	N/A	2015.06.08	2016.06.07	1 year
8	Test Cable	N/A	C02	N/A	2015.06.08	2016.06.07	1 year
9	Test Cable	N/A	C03	N/A	2015.06.08	2016.06.07	1 year

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.50 -5.0	73.00	60.00	56.00	46.00
5.0 -30.0	73.00	60.00	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.


3.1.5 TEST RESULTS

EUT :	Android POS	Model Name. :	GP7002
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Date :	2016-01-26
Test Mode :	Mode 1	Phase :	L
Test Voltage :	DC 5V From PC AC 120V/60Hz		

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1539	31.72	10.12	41.84	65.78	-23.94	QP
0.1620	21.98	10.12	32.10	55.36	-23.26	AVG
0.2620	34.58	10.14	44.72	61.36	-16.64	QP
0.2660	23.55	10.14	33.69	51.24	-17.55	AVG
0.4259	36.01	9.98	45.99	57.33	-11.34	QP
0.4259	24.55	9.98	34.53	47.33	-12.80	AVG
1.2900	33.37	9.82	43.19	56.00	-12.81	QP
1.3060	17.28	9.81	27.09	46.00	-18.91	AVG
5.0377	21.24	9.76	31.00	50.00	-19.00	QP
5.1059	34.01	9.76	43.77	60.00	-16.23	AVG
13.5899	20.50	9.84	30.34	50.00	-19.66	QP
14.2779	34.24	9.85	44.09	60.00	-15.91	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Android POS	Model Name. :	GP7002
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Date :	2016-01-26
Test Mode :	Mode 1	Phase :	N
Test Voltage :	DC 5V From PC AC 120V/60Hz		

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1620	31.31	10.07	41.38	65.36	-23.98	QP
0.1620	17.78	10.07	27.85	55.36	-27.51	AVG
0.2500	31.10	10.08	41.18	61.75	-20.57	QP
0.2500	19.79	10.08	29.87	51.75	-21.88	AVG
0.4259	29.83	9.99	39.82	57.33	-17.51	QP
0.4259	20.37	9.99	30.36	47.33	-16.97	AVG
3.7580	32.08	9.72	41.80	56.00	-14.20	QP
3.7580	16.95	9.72	26.67	46.00	-19.33	AVG
4.9739	33.41	9.73	43.14	56.00	-12.86	QP
4.9739	19.79	9.73	29.52	46.00	-16.48	AVG
9.4899	31.28	9.76	41.04	60.00	-18.96	QP
9.4899	18.18	9.76	27.94	50.00	-22.06	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Android POS	Model Name. :	GP7002
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Date :	2016-01-26
Test Mode :	Mode 1	Phase :	L
Test Voltage :	DC 5V From PC AC 240V/60Hz		

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.2379	35.44	10.13	45.57	62.17	-16.60	QP
0.2379	21.65	10.13	31.78	52.17	-20.39	AVG
0.4299	34.59	9.97	44.56	57.25	-12.69	QP
0.4299	20.50	9.97	30.47	47.25	-16.78	AVG
0.6059	33.95	9.79	43.74	56.00	-12.26	QP
0.6059	20.87	9.79	30.66	46.00	-15.34	AVG
1.4578	33.42	9.79	43.21	56.00	-12.79	QP
1.4578	18.49	9.79	28.28	46.00	-17.72	AVG
3.7099	31.21	9.75	40.96	56.00	-15.04	QP
3.7099	18.33	9.75	28.08	46.00	-17.92	AVG
5.2099	32.54	9.76	42.30	60.00	-17.70	QP
5.2099	20.17	9.76	29.93	50.00	-20.07	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Android POS	Model Name. :	GP7002
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Date :	2016-01-26
Test Mode :	Mode 1	Phase :	N
Test Voltage :	DC 5V From PC AC 240V/60Hz		

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1620	31.13	10.07	41.20	65.36	-24.16	QP
0.1620	15.02	10.07	25.09	55.36	-30.27	AVG
0.3300	27.60	10.11	37.71	59.45	-21.74	QP
0.3300	15.82	10.11	25.93	49.45	-23.52	AVG
0.5020	30.24	9.82	40.06	56.00	-15.94	QP
0.5020	16.87	9.82	26.69	46.00	-19.31	AVG
0.6660	30.46	9.81	40.27	56.00	-15.73	QP
0.6660	14.82	9.81	24.63	46.00	-21.37	AVG
3.4940	30.86	9.73	40.59	56.00	-15.41	QP
3.4940	18.36	9.73	28.09	46.00	-17.91	AVG
5.0058	33.38	9.73	43.11	60.00	-16.89	QP
5.0058	17.95	9.73	27.68	50.00	-22.32	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Android POS	Model Name. :	GP7002
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Date :	2016-01-26
Test Mode :	Mode 1	Phase :	L
Test Voltage :	DC 9V From Adapter AC 120V/60Hz		

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1819	29.45	10.13	39.58	64.39	-24.81	QP
0.1819	16.85	10.13	26.98	54.39	-27.41	AVG
0.2459	35.56	10.13	45.69	61.89	-16.20	QP
0.2459	20.76	10.13	30.89	51.89	-21.00	AVG
0.3220	31.77	10.12	41.89	59.65	-17.76	QP
0.3220	20.11	10.12	30.23	49.65	-19.42	AVG
0.4179	34.02	10.00	44.02	57.49	-13.47	QP
0.4179	17.91	10.00	27.91	47.49	-19.58	AVG
1.3700	33.86	9.81	43.67	56.00	-12.33	QP
1.3700	17.17	9.81	26.98	46.00	-19.02	AVG
3.9900	31.84	9.75	41.59	56.00	-14.41	QP
3.9900	18.81	9.75	28.56	46.00	-17.44	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Android POS	Model Name. :	GP7002
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Date :	2016-01-26
Test Mode :	Mode 1	Phase :	N
Test Voltage :	DC 9V From Adapter AC 120V/60Hz		

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1660	27.86	10.06	37.92	65.15	-27.23	QP
0.1660	15.16	10.06	25.22	55.15	-29.93	AVG
0.2379	30.30	10.06	40.36	62.17	-21.81	QP
0.2379	16.70	10.06	26.76	52.17	-25.41	AVG
0.3260	27.53	10.11	37.64	59.55	-21.91	QP
0.3260	16.12	10.11	26.23	49.55	-23.32	AVG
0.4859	30.37	9.85	40.22	56.24	-16.02	QP
0.4859	15.44	9.85	25.29	46.24	-20.95	AVG
3.8980	31.88	9.72	41.60	56.00	-14.40	QP
3.8980	16.76	9.72	26.48	46.00	-19.52	AVG
5.1459	32.94	9.73	42.67	60.00	-17.33	QP
5.1459	17.91	9.73	27.64	50.00	-22.36	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Android POS	Model Name. :	GP7002
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Date :	2016-01-26
Test Mode :	Mode 1	Phase :	L
Test Voltage :	DC 9V From Adapter AC 240V /60Hz		

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1620	32.00	9.60	41.60	65.36	-23.76	QP
0.1620	13.70	9.60	23.30	55.36	-32.06	AVG
0.4138	26.15	9.64	35.79	57.57	-21.78	QP
0.4138	13.20	9.64	22.84	47.57	-24.73	AVG
0.6860	31.16	9.64	40.80	56.00	-15.20	QP
0.6860	14.66	9.64	24.30	46.00	-21.70	AVG
0.8220	32.67	9.63	42.30	56.00	-13.70	QP
0.8220	16.87	9.63	26.50	46.00	-19.50	AVG
1.6778	28.28	9.56	37.84	56.00	-18.16	QP
1.6778	10.64	9.56	20.20	46.00	-25.80	AVG
2.8460	26.44	9.52	35.96	56.00	-20.04	QP
2.8460	10.52	9.52	20.04	46.00	-25.96	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Android POS	Model Name. :	GP7002
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Date :	2016-01-26
Test Mode :	Mode 1	Phase :	N
Test Voltage :	DC 9V From Adapter AC 240V/60Hz		

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1660	30.74	9.60	40.34	65.15	-24.81	QP
0.1660	11.45	9.60	21.05	55.15	-34.10	AVG
0.2500	22.64	9.61	32.25	61.75	-29.50	QP
0.2500	5.60	9.61	15.21	51.75	-36.54	AVG
0.6580	24.34	9.65	33.99	56.00	-22.01	QP
0.6580	7.69	9.65	17.34	46.00	-28.66	AVG
0.8299	24.26	9.63	33.89	56.00	-22.11	QP
0.8299	8.46	9.63	18.09	46.00	-27.91	AVG
1.5620	20.32	9.57	29.89	56.00	-26.11	QP
1.5620	3.20	9.57	12.77	46.00	-33.23	AVG
2.9580	18.46	9.52	27.98	56.00	-28.02	QP
2.9580	3.56	9.52	13.08	46.00	-32.92	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class A (at 10m)	Class B (at 3m)
	dBuV/m	dBuV/m
30 ~ 88	39.0	40.0
88 ~ 216	43.5	43.5
216 ~ 960	46.5	46.0
Above 960	49.5	54.0

Notes:

- (1) The limit for radiated test was performed according to as following:
FCC PART 15B /ICES-003.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

3.2.2 TEST PROCEDURE

Test Arrangement for Radiated Emissions up to 1 GHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited test facility. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

Note: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for quasi-peak detection (QP) at frequency below 1GHz.

Test Arrangement for Radiated Emissions above 1 GHz.

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna can be varied from one meter to four meters, the height of adjustment depends on the EUT height and the antenna 3dB beamwidth both, to detect the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.


Note: For the hand-held device, the EUT should be measured for all 3 axes and only the worst case is recorded in the report

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:


Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Avg	1 MHz	10 Hz

3.2.3 TEST SETUP

For Radiated Emission 30~1000MHz



(B) Radiated Emission Test Set-Up Frequency Above 1GHz



3.2.4 TEST RESULTS


TEST RESULTS (30~1000 MHz)

EUT :	Android POS	Model Name :	GP7002
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2016-01-26
Test Mode :	Mode 1	Polarization :	Horizontal
Test Power :	DC 5V From PC AC 120V/60Hz		

Freq. (MHz)	Reading (dBuV)	Factor (dBuV)	Measurement (dBuV)	Limit (dBuV)	Over (dB)	Remark
191.7450	30.16	11.34	41.50	43.50	-2.00	QP
362.9844	28.31	14.43	42.74	46.00	-3.26	QP
383.9318	26.04	14.90	40.94	46.00	-5.06	QP
432.5457	27.75	15.08	42.83	46.00	-3.17	QP
480.5276	22.05	16.56	38.61	46.00	-7.39	QP
801.7862	20.11	22.69	42.80	46.00	-3.20	QP

Remark:

Factor = Antenna Factor + Cable Loss - Amplifier.




EUT :	Android POS	Model Name :	GP7002
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2016-01-26
Test Mode :	Mode 1	Polarization :	Vertical
Test Power :	DC 5V From PC AC 120V/60Hz		

Freq. (MHz)	Reading (dBuV)	Factor (dBuV)	Measurement (dBuV)	Limit (dBuV)	Over (dB)	Remark
31.1798	16.65	19.14	35.79	40.00	-4.21	QP
167.8241	26.10	12.20	38.30	43.50	-5.20	QP
191.7450	29.72	11.34	41.06	43.50	-2.44	QP
204.2375	26.02	11.56	37.58	43.50	-5.92	QP
675.2080	20.49	20.82	41.31	46.00	-4.69	QP
726.8052	19.60	21.66	41.26	46.00	-4.74	QP

Remark:

Factor = Antenna Factor + Cable Loss - Amplifier.



3.2.5 TEST RESULTS(1000~12400MHz)



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	1107.528	60.80	-12.60	48.20	74.00	-25.80	peak
V	1736.483	62.60	-10.10	52.50	74.00	-21.50	peak
V	2040.348	58.27	-7.67	50.60	74.00	-23.40	peak
V	2520.728	60.53	-7.53	53.00	74.00	-21.00	peak
V	3442.900	55.73	-4.53	51.20	74.00	-22.80	peak
V	4856.567	48.77	1.93	50.70	74.00	-23.30	peak
H	1191.952	58.07	-11.37	46.70	74.00	-27.30	peak
H	1451.628	60.08	-10.58	49.50	74.00	-24.50	peak
H	1829.098	59.18	-9.68	49.50	74.00	-24.50	peak
H	2247.628	59.36	-7.86	51.50	74.00	-22.50	peak
H	2821.952	53.18	-6.28	46.90	74.00	-27.10	peak
H	4512.583	52.55	-0.35	52.20	74.00	-21.80	peak

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit

4. EUT TEST PHOTO

Radiated Measurement Photos



Conducted Measurement Photos

