



# FCC Part 15C Test Report

## FCC ID: 2AHHYPTS-018

|                  |                                                                                                                                                                                                                                                          |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Name:    | <b>Remote dog training</b>                                                                                                                                                                                                                               |
| Trademark:       |                                                                                                                                                                         |
| Model Name :     | PTS-018<br>PTS-008, PTS-015, PTS-108, PTS-118, p-collar 310, p-collar 320,<br>p-collar 330, p-collar 340, p-collar 610, p-collar 620, p-collar 630,<br>p-collar 640, p-collar 810, p-collar 820, p-collar 910, p-collar 920,<br>p-nobark310, p-nobark320 |
| Prepared For :   | <b>Shenzhen Patpet Technology Co., Ltd</b>                                                                                                                                                                                                               |
| Address :        | Room 309,Hengfengyuan Business Building, BanAn 72 District,<br>Shenzhen, Guangdong, China                                                                                                                                                                |
| Prepared By :    | <b>Shenzhen BCTC Technology Co., Ltd.</b>                                                                                                                                                                                                                |
| Address :        | No.101,Yousong Road,Longhua New District, Shenzhen,China                                                                                                                                                                                                 |
| Test Date:       | Feb. 19 - Feb. 24, 2016                                                                                                                                                                                                                                  |
| Date of Report : | Feb. 24, 2016                                                                                                                                                                                                                                            |
| Report No.:      | BCTC-160201454E                                                                                                                                                                                                                                          |



## VERIFICATION OF COMPLIANCE

**Applicant's name**..... : **Shenzhen Patpet Technology Co., Ltd**

**Address**..... : Room 309,Hengfengyuan Business Building, BanAn 72  
District, Shenzhen, Guangdong, China

**Manufacture's Name**..... : **Shenzhen Patpet Technology Co., Ltd**

**Address**..... : Room 309,Hengfengyuan Business Building, BanAn 72  
District, Shenzhen, Guangdong, China

### Product description

**Product name**..... : Remote dog training

**Trademark:**



PTS-018

**Model Name:**

PTS-008, PTS-015, PTS-108, PTS-118, p-collar 310,  
p-collar 320, p-collar 330, p-collar 340, p-collar 610,  
p-collar 620, p-collar 630, p-collar 640, p-collar 810,  
p-collar 820, p-collar 910, p-collar 920, p-nobark310,  
p-nobark320

**Test procedure**..... : FCC Part15.231

**Standards**..... : ANSI C63.10-2013

This device described above has been tested by BCTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of BCTC, this document may be altered or revised by BCTC, personal only, and shall be noted in the revision of the document.

**Test Result** ..... : **Pass**

**Testing Engineer** : \_\_\_\_\_

*Eric Yang*

(Eric Yang)

**Technical Manager** : \_\_\_\_\_

*Sophie Lee*

(Sophia Lee)

**Authorized Signatory** : \_\_\_\_\_

*Carson Zhang*

(Carson. Zhang)





| Table of Contents                                           | Page      |
|-------------------------------------------------------------|-----------|
| <b>1 . SUMMARY OF TEST RESULTS</b>                          | <b>5</b>  |
| 1.1 TEST FACILITY                                           | 6         |
| 1.2 MEASUREMENT UNCERTAINTY                                 | 6         |
| <b>2 . GENERAL INFORMATION</b>                              | <b>7</b>  |
| 2.1 GENERAL DESCRIPTION OF EUT                              | 7         |
| 2.2 DESCRIPTION OF TEST MODES                               | 8         |
| 2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED | 8         |
| 2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)            | 8         |
| 2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS                      | 9         |
| <b>3 . EMC EMISSION TEST</b>                                | <b>10</b> |
| 3.1 CONDUCTED EMISSION MEASUREMENT                          | 10        |
| 3.1.1 POWER LINE CONDUCTED EMISSION LIMITS                  | 10        |
| 3.1.2 TEST PROCEDURE                                        | 11        |
| 3.1.3 DEVIATION FROM TEST STANDARD                          | 11        |
| 3.1.4 TEST SETUP                                            | 11        |
| 3.1.5 EUT OPERATING CONDITIONS                              | 11        |
| 3.1.6 TEST RESULTS                                          | 11        |
| 3.2 RADIATED EMISSION MEASUREMENT                           | 14        |
| 3.2.1 RADIATED EMISSION LIMITS                              | 14        |
| 3.2.2 TEST PROCEDURE                                        | 15        |
| 3.2.3 TEST SETUP                                            | 16        |
| 3.2.4 EUT OPERATING CONDITIONS                              | 17        |
| 3.2.5 TEST RESULTS                                          | 18        |
| <b>4 . BANDWIDTH TEST</b>                                   | <b>23</b> |
| 4.1 APPLIED PROCEDURES / LIMIT                              | 23        |
| 4.1.1 TEST PROCEDURE                                        | 23        |
| 4.1.2 DEVIATION FROM STANDARD                               | 23        |
| 4.1.3 TEST SETUP                                            | 23        |
| 4.1.4 EUT OPERATION CONDITIONS                              | 23        |
| 4.1.5 TEST RESULTS                                          | 24        |
| <b>5 . CALCULATION OF AVERAGE FACTOR</b>                    | <b>25</b> |
| <b>6 . DWELL TIME</b>                                       | <b>28</b> |
| 6.1 DEVIATION FROM STANDARD                                 | 28        |
| 6.2 TEST SETUP                                              | 28        |



---

| <b>Table of Contents</b>                           | <b>Page</b> |
|----------------------------------------------------|-------------|
| 6.3 EUT OPERATION CONDITIONS                       | 28          |
| 6.4 TEST RESULTS                                   | 29          |
| 7 . ANTENNA REQUIREMENT                            | 30          |
| 7.1 STANDARD REQUIREMENT                           | 30          |
| 7.2 EUT ANTENNA                                    | 30          |
| 8 . EUT TEST PHOTO                                 | 31          |
| APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS |             |



## 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

| FCC Part15 (15.231) , Subpart C |                        |          |        |
|---------------------------------|------------------------|----------|--------|
| Standard Section                | Test Item              | Judgment | Remark |
| 15.207                          | Conducted Emission     | PASS     |        |
| 15.209,15.231b                  | Radiated Emission Test | PASS     |        |
| 15.231c                         | 20dB Occupy Bandwidth  | PASS     |        |
| 15.231a                         | Dwell time             | PASS     |        |
| 15.203                          | Antenna Requirement    | PASS     |        |

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report



## 1.1 TEST FACILITY

Shenzhen BCTC Technology Co., Ltd.

Add.:No.101,Yousong Road,Longhua New District, Shenzhen,China

FCC Registration No.:187086

## 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately **95 %** .

| No. | Item                         | Uncertainty               |
|-----|------------------------------|---------------------------|
| 1   | Conducted Emission Test      | $\pm 1.38\text{dB}$       |
| 2   | RF power,conducted           | $\pm 0.16\text{dB}$       |
| 3   | Spurious emissions,conducted | $\pm 0.21\text{dB}$       |
| 4   | All emissions,radiated(<1G)  | $\pm 4.68\text{dB}$       |
| 5   | All emissions,radiated(>1G)  | $\pm 4.89\text{dB}$       |
| 6   | Temperature                  | $\pm 0.5^{\circ}\text{C}$ |
| 7   | Humidity                     | $\pm 2\%$                 |



## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

|                        |                                                                                                                                                                                                                                                             |                  |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| Equipment              | Remote dog training                                                                                                                                                                                                                                         |                  |
| Trade Name             |                                                                                                                                                                            |                  |
| Model Name             | PTS-018<br>PTS-008, PTS-015, PTS-108, PTS-118, p-collar 310,<br>p-collar 320, p-collar 330, p-collar 340, p-collar 610,<br>p-collar 620, p-collar 630, p-collar 640, p-collar 810,<br>p-collar 820, p-collar 910, p-collar 920, p-nobark310,<br>p-nobark320 |                  |
| Model Difference       | All the models are the same circuit and RF module,<br>except the model names and outlook color.                                                                                                                                                             |                  |
| Product Description    | The EUT is a Remote dog training                                                                                                                                                                                                                            |                  |
|                        | Operation Frequency:                                                                                                                                                                                                                                        | 433.92MHz        |
|                        | Modulation Type:                                                                                                                                                                                                                                            | ASK              |
|                        | Antenna Designation:                                                                                                                                                                                                                                        | Internal Antenna |
|                        | Antenna Gain                                                                                                                                                                                                                                                | 1.2dBi           |
|                        | Based on the application, features, or specification<br>exhibited in User's Manual, the EUT is considered as an<br>ITE/Computing Device. More details of EUT technical<br>specification, please refer to the User's Manual.                                 |                  |
| Adapter                | Model: XH-UL0510-A1<br>I/P: AC100-240V 50-60Hz 300mA<br>O/P: DC 5V 1000mA                                                                                                                                                                                   |                  |
| Battery                | DC 3.7V<br>DC 5V from adapter                                                                                                                                                                                                                               |                  |
| Connecting I/O Port(s) | Please refer to the User's Manual                                                                                                                                                                                                                           |                  |
| Hardware Version       | ---                                                                                                                                                                                                                                                         |                  |

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



## 2.2 DESCRIPTION OF TEST MODES

| For All Emission |             |
|------------------|-------------|
| Final Test Mode  | Description |
| Mode 1           | TX Mode     |

Note:

- (1) New battery is used during the test
- (2) The antenna is telescopic antenna, The worst mode is on max length(7cm).
- (3) For this device equipped with 4 buttons, all 4 buttons was pre-tested and the worst button was Increase the speed button and the data was recrding the report.

## 2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test

EUT

## 2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Item | Equipment | Mfr/Brand | Model/Type No. | Series No. | Note |
|------|-----------|-----------|----------------|------------|------|
|      |           |           |                |            |      |

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

**2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS**

For Conducted Emission at the mains terminals Test

| Item | Equipment     | Manufacturer | Model#   | Serial# | Last Cal.  | Next Cal.  | Calibration period |
|------|---------------|--------------|----------|---------|------------|------------|--------------------|
| 1    | EMI Receiver  | R&S          | ESCI     | 101421  | 2015.08.25 | 2016.08.24 | 1 year             |
| 2    | LISN          | SCHWARZBECK  | NSLK8127 | 812779  | 2015.08.25 | 2016.08.24 | 1 year             |
| 3    | Pulse Limiter | R&S          | ESH3-Z2  | 100681  | 2015.08.25 | 2016.08.24 | 1 year             |
| 4    | 843 Cable 1#  | FUJIKURA     | 843C1#   | 001     | 2015.08.25 | 2016.08.24 | 1 year             |

Radiation, 20db bandwidth, dwell time test equipment

| Item | Kind of Equipment                              | Manufacturer   | Type No.   | Serial No.             | Last calibration | Calibrated until | Calibration period |
|------|------------------------------------------------|----------------|------------|------------------------|------------------|------------------|--------------------|
| 1    | Spectrum Analyzer                              | Agilent        | E4407B     | MY45108040             | 2015.06.06       | 2016.06.05       | 1 year             |
| 2    | Test Receiver                                  | R&S            | ESCI       | 1166.5950K03-101165-ha | 2015.06.06       | 2016.06.05       | 1 year             |
| 3    | Bilog Antenna                                  | R&S            | VULB9168   | VULB9168-438           | 2015.06.06       | 2016.06.05       | 1 year             |
| 4    | 50Ω Coaxial Switch                             | Anritsu        | MP59B      | 6200264416             | 2015.06.06       | 2016.06.05       | 1 year             |
| 5    | Spectrum Analyzer                              | ADVANTEST      | R3132      | 150900201              | 2015.06.06       | 2016.06.05       | 1 year             |
| 6    | Horn Antenna                                   | R&S            | HF906      | 10027                  | 2015.06.06       | 2016.06.05       | 1 year             |
| 8    | Amplifier                                      | R&S            | BBV9743    | 9743-019               | 2015.06.06       | 2016.06.05       | 1 year             |
| 9    | Loop Antenna                                   | ARA            | PLA-1030/B | 1029                   | 2015.08.06       | 2016.08.05       | 1 year             |
| 10   | RF cables (9kHz~1GHz)                          | R&S            | R203       | R20X                   | 2015.06.06       | 2016.06.05       | 1 year             |
| 11   | Antenna connector (20db bandwidth, dwell time) | Florida RFLabs | Lab-Fle    | RF 01#                 | 2015.06.06       | 2016.06.05       | 1 year             |
|      |                                                |                |            |                        |                  |                  |                    |

Note: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.



### 3. EMC EMISSION TEST

#### 3.1 CONDUCTED EMISSION MEASUREMENT

##### 3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

| FRE U NCY (MHz) | Class B (dBuV) |           | Standard |
|-----------------|----------------|-----------|----------|
|                 | Quasi-peak     | Average   |          |
| 0.15 -0.5       | 66 - 56 *      | 56 - 46 * | CISPR    |
| 0. 0 -5.0       | 56.00          | 46.00     | CISPR    |
| 5.0 -30.0       | 60.00          | 50.00     | CISPR    |

|           |           |           |     |
|-----------|-----------|-----------|-----|
| 0.15 -0.5 | 66 - 56 * | 56 - 46 * | FCC |
| 0.50 -5.0 | 56.00     | 46.00     | FCC |
| 5.0 -30.0 | 60.00     | 50.00     | FCC |

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

| Receiver Parameters | Setting  |
|---------------------|----------|
| Attenuation         | 10 dB    |
| Start Frequency     | 0.15 MHz |
| Stop Frequency      | 30 MHz   |
| IF Bandwidth        | 9 kHz    |


### 3.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

### 3.1.3 DEVIATION FROM TEST STANDARD

No deviation

### 3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

### 3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

### 3.1.6 TEST RESULTS



### Conducted Emission At The Mains Terminals Test Data


|                |                                       |                    |         |
|----------------|---------------------------------------|--------------------|---------|
| Temperature:   | 24.5 °C                               | Relative Humidity: | 54%     |
| Pressure:      | 1009hPa                               | Phase :            | Line    |
| Test Voltage : | DC 5V from adapter input AC 120V/60Hz | Test Mode:         | TX Mode |



| No. Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV | Limit<br>dBuV | Over<br>dB | Detector | Comment |
|---------|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|---------|
| 1       | 0.3321       | 8.01                     | 10.10                   | 18.11                    | 49.40         | -31.29     | AVG      |         |
| 2       | 0.3339       | 30.79                    | 10.10                   | 40.89                    | 59.35         | -18.46     | QP       |         |
| 3       | 0.4900       | 31.32                    | 10.11                   | 41.43                    | 56.17         | -14.74     | QP       |         |
| 4       | 0.4900       | 9.89                     | 10.11                   | 20.00                    | 46.17         | -26.17     | AVG      |         |
| 5 *     | 0.7019       | 40.09                    | 10.14                   | 50.23                    | 56.00         | -5.77      | QP       |         |
| 6       | 0.7019       | 17.41                    | 10.14                   | 27.55                    | 46.00         | -18.45     | AVG      |         |
| 7       | 0.9340       | 31.58                    | 10.16                   | 41.74                    | 56.00         | -14.26     | QP       |         |
| 8       | 0.9340       | 9.52                     | 10.16                   | 19.68                    | 46.00         | -26.32     | AVG      |         |
| 9       | 1.6300       | 31.01                    | 10.18                   | 41.19                    | 56.00         | -14.81     | QP       |         |
| 10      | 1.6300       | 8.93                     | 10.18                   | 19.11                    | 46.00         | -26.89     | AVG      |         |
| 11      | 3.9620       | 24.31                    | 10.16                   | 34.47                    | 56.00         | -21.53     | QP       |         |
| 12      | 3.9620       | 2.30                     | 10.16                   | 12.46                    | 46.00         | -33.54     | AVG      |         |

**Conducted Emission At The Mains Terminals Test Data**

|                |                                       |                    |         |
|----------------|---------------------------------------|--------------------|---------|
| Temperature:   | 24.5 °C                               | Relative Humidity: | 54%     |
| Pressure:      | 1009hPa                               | Phase :            | Neutral |
| Test Voltage : | DC 5V from adapter input AC 120V/60Hz | Test Mode:         | TX Mode |



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV | Limit<br>dBuV | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|---------|
| 1   |     | 0.3460       | 29.96                    | 10.10                   | 40.06                    | 59.06         | -19.00     | QP       |         |
| 2   |     | 0.3460       | 5.60                     | 10.10                   | 15.70                    | 49.06         | -33.36     | AVG      |         |
| 3   | ^   | 0.7140       | 38.12                    | 10.14                   | 48.26                    | 56.00         | -7.74      | QP       |         |
| 4   |     | 0.7140       | 9.61                     | 10.14                   | 19.75                    | 46.00         | -26.25     | AVG      |         |
| 5   |     | 1.1940       | 29.60                    | 10.17                   | 39.77                    | 56.00         | -16.23     | QP       |         |
| 6   |     | 1.1940       | 1.38                     | 10.17                   | 11.55                    | 46.00         | -34.45     | AVG      |         |
| 7   |     | 1.6019       | 29.86                    | 10.18                   | 40.04                    | 56.00         | -15.96     | QP       |         |
| 8   |     | 1.6019       | 3.76                     | 10.18                   | 13.94                    | 46.00         | -32.06     | AVG      |         |
| 9   |     | 3.0420       | 23.66                    | 10.19                   | 33.85                    | 56.00         | -22.15     | QP       |         |
| 10  |     | 3.0579       | -1.05                    | 10.19                   | 9.14                     | 46.00         | -36.86     | AVG      |         |
| 11  |     | 5.7540       | 19.71                    | 10.10                   | 29.81                    | 60.00         | -30.19     | QP       |         |
| 12  |     | 5.7819       | -2.39                    | 10.10                   | 7.71                     | 50.00         | -42.29     | AVG      |         |



## 3.2 RADIATED EMISSION MEASUREMENT

### 3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.231(b) limit in the table below has to be followed.

| Frequencies(MHz) | Field Strength(micorvolts/meter) | Measurement Distance(meters) |
|------------------|----------------------------------|------------------------------|
| 0.009~0.490      | 2400/F(KHz)                      | 300                          |
| 0.490~1.705      | 24000/F(KHz)                     | 30                           |
| 1.705~30.0       | 30                               | 30                           |
| 30~88            | 100                              | 3                            |
| 88~216           | 150                              | 3                            |
| 216~960          | 200                              | 3                            |
| Above 960        | 500                              | 3                            |

### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

| FREQUENCY (MHz) | Class B (dBuV/m) (at 3M) |         |
|-----------------|--------------------------|---------|
|                 | PEAK                     | AVERAGE |
| Above 1000      | 74                       | 54      |

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

### FUNDAMENTAL AND HARMONICS EMISSION LIMITS

| Fundamental Frequency (MHz) | Field Strength of Fundamental (microvolts/meter) | Field Strength of Spurious Emissions (microvolts/meter) |
|-----------------------------|--------------------------------------------------|---------------------------------------------------------|
| 40.66 - 40.70               | 2,250                                            | 225                                                     |
| 70 - 130                    | 1,250                                            | 125                                                     |
| 130 - 174                   | 1,250 to 3,750 **                                | 125 to 375 **                                           |
| 174 - 260                   | 3,750                                            | 375                                                     |
| 260 - 470                   | 3,750 to 12,500 **                               | 375 to 1,250 **                                         |
| Above 470                   | 12,500                                           | 1,250                                                   |

\*\* linear interpolations

[Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz,  $\mu\text{V/m}$  at 3 meters =  $56.81818(F) - 6136.3636$ ; for the band 260-470 MHz,  $\mu\text{V/m}$  at 3 meters =  $41.6667(F) - 7083.3333$ . The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.]



## FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

| Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz) | Range (MHz)                                                                  |
|---------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------|
| Below 1.705                                                                                                                     | 30                                                                           |
| 1.705 – 108                                                                                                                     | 1000                                                                         |
| 108 – 500                                                                                                                       | 2000                                                                         |
| 500 – 1000                                                                                                                      | 5000                                                                         |
| Above 1000                                                                                                                      | 5 <sup>th</sup> harmonic of the highest frequency or 40 C whichever is lower |

| Spectrum Parameter | Setting                |
|--------------------|------------------------|
| Attenuation        | Auto                   |
| Start Frequency    | 1000 MHz               |
| Stop Frequency     | 10th carrier harmonic  |
| RBW / VBW setting  | 1 MHz / 1 MHz for Peak |

| Receiver Parameter     | Setting                          |
|------------------------|----------------------------------|
| Attenuation            | Auto                             |
| Start ~ Stop Frequency | 9kHz~150kHz / RB 200Hz for QP    |
| Start ~ Stop Frequency | 150kHz~30MHz / RB 9kHz for QP    |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB 120kHz for QP |

**3.2.2 TEST PROCEDURE**

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

- g. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.


The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case was X axis and the emissions were reported

### 3.2.3 TEST SETUP


#### (A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



### 3.2.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



### 3.2.5 TEST RESULTS

Radiated Spurious Emission (Below 30MHz )

|                |                     |                     |         |
|----------------|---------------------|---------------------|---------|
| EUT :          | Remote dog training | Model Name :        | PTS-018 |
| Temperature :  | 20 °C               | Relative Humidity : | 48%     |
| Pressure :     | 1010 hPa            | Polarization :      | ---     |
| Test Voltage : | By Battery          |                     |         |
| Test Mode :    | TX Mode             |                     |         |

| Freq. | Reading  | Limit    | Margin | State |
|-------|----------|----------|--------|-------|
| (MHz) | (dBuV/m) | (dBuV/m) | (dB)   | P/F   |
| --    | --       | --       | --     | PASS  |
| --    | --       | --       | --     | PASS  |

**NOTE:**

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.



Radiated Spurious Emission (Between 30MHz – 1GHz)

|                |                     |                     |            |
|----------------|---------------------|---------------------|------------|
| EUT :          | Remote dog training | Model Name :        | PTS-018    |
| Temperature :  | 26 °C               | Relative Humidity : | 54%        |
| Pressure :     | 1010 hPa            | Polarization :      | Horizontal |
| Test Voltage : | DC 3V               |                     |            |
| Test Mode :    | TX Mode             |                     |            |



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB/m | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Antenna<br>Height<br>cm | Table<br>Degree<br>degree | Comment |
|-----|-----|--------------|--------------------------|---------------------------|----------------------------|-----------------|------------|----------|-------------------------|---------------------------|---------|
| 1   | *   | 34.5172      | 37.15                    | -8.47                     | 28.68                      | 40.00           | -11.32     | QP       |                         |                           |         |
| 2   |     | 40.2757      | 34.55                    | -8.89                     | 25.66                      | 40.00           | -14.34     | QP       |                         |                           |         |
| 3   |     | 51.4806      | 32.54                    | -10.54                    | 22.00                      | 40.00           | -18.00     | QP       |                         |                           |         |
| 4   |     | 73.6170      | 36.43                    | -15.82                    | 20.61                      | 40.00           | -19.39     | QP       |                         |                           |         |
| 5   |     | 433.9200     | 95.00                    | -9.37                     | 85.63                      | 100.80          | -15.17     | peak     |                         |                           |         |
| 6   |     | 867.8400     | 65.29                    | -2.05                     | 63.24                      | 80.80           | -17.56     | peak     |                         |                           |         |


Remark:

Factor = Antenna Factor + Correct Factor.

Correct Factor= Cable Loss – Pre-amplifier



|                |                     |                     |          |
|----------------|---------------------|---------------------|----------|
| EUT :          | Remote dog training | Model Name :        | PTS-018  |
| Temperature :  | 26 °C               | Relative Humidity : | 54%      |
| Pressure :     | 1010 hPa            | Polarization :      | Vertical |
| Test Voltage : | DC 3V               |                     |          |
| Test Mode :    | TX Mode             |                     |          |



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB/m | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Antenna<br>Height<br>cm | Table<br>Degree<br>degree | Comment |
|-----|-----|--------------|--------------------------|---------------------------|----------------------------|-----------------|------------|----------|-------------------------|---------------------------|---------|
| 1   |     | 39.4371      | 33.38                    | -8.83                     | 24.55                      | 40.00           | -15.45     | QP       |                         |                           |         |
| 2   |     | 50.5860      | 31.60                    | -10.39                    | 21.21                      | 40.00           | -18.79     | QP       |                         |                           |         |
| 3   |     | 64.8865      | 29.78                    | -12.49                    | 17.29                      | 40.00           | -22.71     | QP       |                         |                           |         |
| 4   |     | 88.6524      | 32.82                    | -17.66                    | 15.16                      | 43.50           | -28.34     | QP       |                         |                           |         |
| 5   | *   | 433.9200     | 94.96                    | -9.37                     | 85.59                      | 100.80          | -15.21     | peak     |                         |                           |         |
| 6   |     | 867.8400     | 67.00                    | -2.05                     | 64.95                      | 80.80           | -15.85     | peak     |                         |                           |         |

Remark:

Factor = Antenna Factor + Correct Factor.

Correct Factor= Cable Loss – Pre-amplifier



For average Emission

| Frequency<br>MHz | Peak<br>Level<br>dBuV/m | Duty cycle<br>factor | AverageLevel<br>dBuV/m | Polarization | Limit<br>AV | Margin |
|------------------|-------------------------|----------------------|------------------------|--------------|-------------|--------|
| 433.92           | 85.59                   | -6.61                | 78.98                  | Vertical     | 80.80       | -1.82  |
| 867.84           | 64.95                   | -6.61                | 58.34                  | Vertical     | 60.80       | -2.46  |

Notes: 1. Average emission Level = Peak Level + Duty cycle factor  
2. Duty cycle level please see clause 5.

| Frequency<br>MHz | Peak<br>Level<br>dBuV/m | Duty cycle<br>factor | AverageLevel<br>dBuV/m | Polarization | Limit<br>AV | Margin |
|------------------|-------------------------|----------------------|------------------------|--------------|-------------|--------|
| 433.92           | 85.63                   | -6.61                | 79.02                  | Horizontal   | 80.80       | -1.78  |
| 867.84           | 63.24                   | -6.61                | 56.63                  | Horizontal   | 60.80       | -4.17  |

Notes: 1. Average emission Level = Peak Level + Duty cycle factor  
2. Duty cycle level please see clause 5.

Radiated Spurious Emission ( 1GHz to 10<sup>th</sup> harmonics)

| Frequency<br>MHz | Peak<br>Level<br>dBuV/m | Duty cycle<br>factor | Average<br>Level<br>dBuV/m | Polarization | Limit |       | Margin dB |        |
|------------------|-------------------------|----------------------|----------------------------|--------------|-------|-------|-----------|--------|
|                  |                         |                      |                            |              | PK    | AV    | PK        | AV     |
| 1301.76          | 64.79                   | -6.61                | 58.18                      | Vertical     | 80.80 | 60.80 | -16.01    | -2.62  |
| 1735.68          | 62.41                   | -6.61                | 55.8                       | Vertical     | 80.80 | 60.80 | -18.39    | -5.00  |
| 2169.60          | 58.39                   | -6.61                | 51.78                      | Vertical     | 80.80 | 60.80 | -22.41    | -9.02  |
| 2603.52          | 58.24                   | -6.61                | 51.63                      | Vertical     | 80.80 | 60.80 | -22.56    | -9.17  |
| 3037.44          | 52.03                   | -6.61                | 45.42                      | Vertical     | 80.80 | 60.80 | -28.77    | -15.38 |
| 3471.36          | 52.78                   | -6.61                | 46.17                      | Vertical     | 80.80 | 60.80 | -28.02    | -14.63 |

| Frequency<br>MHz | Peak Level<br>dBuV/m | Duty cycle<br>factor | Average<br>Level<br>dBuV/m | Polarization | Limit |       | Margin dB |        |
|------------------|----------------------|----------------------|----------------------------|--------------|-------|-------|-----------|--------|
|                  |                      |                      |                            |              | PK    | AV    | PK        | AV     |
| 1301.76          | 63.25                | -6.61                | 56.64                      | Horizontal   | 80.80 | 60.80 | -17.55    | -4.16  |
| 1735.68          | 61.63                | -6.61                | 55.02                      | Horizontal   | 80.80 | 60.80 | -19.17    | -5.78  |
| 2169.60          | 58.34                | -6.61                | 51.73                      | Horizontal   | 80.80 | 60.80 | -22.46    | -9.07  |
| 2603.52          | 56.44                | -6.61                | 49.83                      | Horizontal   | 80.80 | 60.80 | -24.36    | -10.97 |
| 3037.44          | 51.68                | -6.61                | 45.07                      | Horizontal   | 80.80 | 60.80 | -29.12    | -15.73 |
| 3471.36          | 52.04                | -6.61                | 45.43                      | Horizontal   | 80.80 | 60.80 | -28.76    | -15.37 |

Notes: 1. Average emission Level = Peak Level + Duty cycle factor

2. Duty cycle level please see clause 5.

3. Pulse Desensitization Correction Factor

Pulse Width (PW) = 63.25ms

$2/PW = 2/63.25\text{ms} = 0.03\text{kHz}$

RBW (100 kHz) > 2/PW (0.008kHz)

Therefore PDCF is not needed



## 4. BANDWIDTH TEST

### 4.1 APPLIED PROCEDURES / LIMIT

According to FCC 15.231(c) requirement:

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating between 70 MHz to 900 MHz. Those devices operating above 900 MHz, the emission spurious shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

B.W (20dBc) Limit =  $0.25\% * f(\text{MHz}) = 0.25\% * 433.92\text{MHz} = 1.0848\text{MHz}$

| Spectrum Parameter | Setting                                       |
|--------------------|-----------------------------------------------|
| Attenuation        | Auto                                          |
| Span Frequency     | > Measurement Bandwidth or Channel Separation |
| RB                 | 100kHz                                        |
| VB                 | $\geq \text{RBW}$                             |
| Detector           | Peak                                          |
| Trace              | Max Hold                                      |
| Sweep Time         | Auto                                          |

#### 4.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 100kHz, VBW $\geq$  RBW, Sweep time = Auto.

#### 4.1.2 DEVIATION FROM STANDARD

No deviation.

#### 4.1.3 TEST SETUP



#### 4.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



#### 4.1.5 TEST RESULTS

|               |                     |                     |            |
|---------------|---------------------|---------------------|------------|
| EUT :         | Remote dog training | Model Name :        | PTS-018    |
| Temperature : | 25 °C               | Relative Humidity : | 60%        |
| Pressure :    | 1012 hPa            | Test Voltage :      | By Battery |
| Test Mode :   | TX Mode             |                     |            |

| Frequency | 20dB Bandwidth (kHz) | Result |
|-----------|----------------------|--------|
| 433.92MHz | 562.5                | PASS   |





## 5. CALCULATION OF AVERAGE FACTOR

The output field strengths of specification in accordance with the FCC rules specify measurements with an average detector. During the test, a spectrum analyzer incorporating a peak detector was used. Therefore, a reduction factor can be applied to the resultant peak signal level and compared to the limit for measurement instrumentation incorporating an average detector.

The duty cycle is measured in 100 ms or the repetition cycle period, whichever is a shorter time frame. The duty cycle is measured by placing the spectrum analyzer to set zero span at 100kHz resolution bandwidth.

Averaging factor in dB =  $20\log(\text{duty cycle})$

The duration of one cycle = 63.25ms



The duty cycle is simply the on-time divided the duration of one cycle



Duty Cycle =  $(1.5\text{ms} \times 12 + 0.55\text{ms} \times 21) / 63.25 = 29.55\text{ms} / 63.25\text{ms} = 0.467$

Therefore, the averaging factor is found by  $20\log 0.467 = -6.61\text{dB}$

Test plot as follows:

Note: During the 100ms, the amount of pulse and on-time of pulse are the same for every pulse train.







## 6. DWELL TIME

### APPLICABLE STANDARD

According to FCC 15.231(a) requirement:

A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

### TEST PROCEDURE

- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.

### 6.1 DEVIATION FROM STANDARD

No deviation.

### 6.2 TEST SETUP




### 6.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


## 6.4 TEST RESULTS

|                       | Dwell time (second) | Limit (second) | Result |
|-----------------------|---------------------|----------------|--------|
| Full voltage(DC 3.7V) | 3.525               | <5s            | Pass   |
| Low voltage(DC3.33V)  | 3.175               | <5s            | Pass   |

Full Voltage



Low voltage





## **7. ANTENNA REQUIREMENT**

### **7.1 STANDARD REQUIREMENT**



15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### **7.2 EUT ANTENNA**

The EUT antenna is the Internal antenna. It comply with the standard requirement.

## 8. EUT TEST PHOTO

### Radiated Measurement Photos




### Conducted Measurement Photos



## 9. EUT PHOTO







END