

## §2.1093 - RF EXPOSURE INFORMATION

### Applicable Standard

According to FCC §2.1093 and §1.1307(b) (3), systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 Interim General RF Exposure Guidance

### SAR-Based Exemption:

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum timeaveraged power or maximum time-averaged ERP, whichever is greater.

Per § 1.1307(b)(3)(i)(B), for single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2) of this section): A single RF source is exempt if:

the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold  $P_{th}$  (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P_{th}$  is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

$d$  = the separation distance (cm);

### Result

| Frequency<br>(MHz) | $P_{th}$ |       | Maximum tune-up<br>ERP | Maximum tune-up<br>conducted power | Exemption |
|--------------------|----------|-------|------------------------|------------------------------------|-----------|
|                    | (mW)     | (dBm) | (dBm)                  | (dBm)                              |           |
| 462.5625-462.7125  | 21.17    | 13.26 | 3.0                    | 5.15                               | Compliant |
| 467.5625-467.6125  | 20.86    | 13.19 | 2.0                    | 4.15                               | Compliant |

- Note: 1. The tune up ERP was declared by the applicant.  
 2. The antenna gain is 0dBi(-2.15dBd), so the Conducted power was used for evaluation  
 3. To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 0.5cm from nearby persons.

**Result: Compliant.**