Test Lab
Cert 2951.01

FCC TEST REPORT

(Bluetooth EDR)

Product:	LTE Digital Mobile Phone
Model Name:	NX529J/ nubia Z11 mini
FCC ID:	2AHJO-NX529J
Applicant:	Nubia Technology Co., Ltd.
Address:	10/F, Tower A, Hans Innovation Mansion, North Ring Rd., No. 9018, Hi-Tech Industrial Park, Nanshan District, Shenzhen, P.R.China
Manufacturer:	Nubia Technology Co., Ltd.
Address:	10/F, Tower A, Hans Innovation Mansion, North Ring Rd., No. 9018, Hi-Tech Industrial Park, Nanshan District, Shenzhen, P.R.China
Prepared by:	Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch
Lab Location:	No. 34, Chenwulu Section, Guantai Rd., Houjie Town, Dongguan City, Guangdong 523942, China
TEL:	+86 769 8593 5656
FAX:	+86 769 8593 1080
E-MAIL:	customerservice.dg@cn.bureauveritas.com
Report No.:	RF161008W001-1
Received Date:	Oct. 08, 2016
Test Date:	Oct. 09, 2016 ~ Oct. 28, 2016
Issued Date:	Oct. 30, 2016

This report should not be used by the client to claim product certification, approval, or endorsement by A2LA or any government agencies.

Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

TABLE OF CONTENTS

RELEASE CONTROL RECORD 5

1 CERTIFICATION 6

2 SUMMARY OF TEST RESULTS 7

2.1 MEASUREMENT UNCERTAINTY 7

3 GENERAL INFORMATION 8

3.1 GENERAL DESCRIPTION OF EUT 8

3.2 DESCRIPTION OF TEST MODES 9

3.2.1 ONFIGURATION OF SYSTEM UNDER TEST 10

3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL 10

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS 12

3.4 DESCRIPTION OF SUPPORT UNITS 12

4 TEST TYPES AND RESULTS 13

4.1 CONDUCTED EMISSION MEASUREMENT 13

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 13

4.1.2 TEST INSTRUMENTS 13

4.1.3 TEST PROCEDURES 14

4.1.4 DEVIATION FROM TEST STANDARD 14

4.1.5 TEST SETUP 15

4.1.6 EUT OPERATING CONDITIONS 15

4.1.7 TEST RESULTS 16

4.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT 18

4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT 18

4.2.2 TEST INSTRUMENTS 19

4.2.3 TEST PROCEDURES 20

4.2.4 DEVIATION FROM TEST STANDARD 20

4.2.5 TEST SETUP 21

4.2.6 EUT OPERATING CONDITIONS 22

4.2.7 TEST RESULTS 23

4.3 NUMBER OF HOPPING FREQUENCY USED 31

4.3.1 LIMIT OF HOPPING FREQUENCY USED 31

4.3.2 TEST SETUP 31

4.3.3 TEST INSTRUMENTS 31

4.3.4 TEST PROCEDURES 32

4.3.5 DEVIATION FROM TEST STANDARD 32

4.3.6 TEST RESULTS 32

4.4 DWELL TIME ON EACH CHANNEL 35
4.4.1 LIMIT OF DWELL TIME USED 35
4.4.2 TEST SETUP 35
4.4.3 TEST INSTRUMENTS 35
4.4.4 TEST PROCEDURES 35
4.4.5 DEVIATION FROM TEST STANDARD 36
4.4.6 TEST RESULTS 36
4.5 CHANNEL BANDWIDTH 40
4.5.1 LIMITS OF CHANNEL BANDWIDTH 40
4.5.2 TEST SETUP 40
4.5.3 TEST INSTRUMENTS 40
4.5.4 TEST PROCEDURE 40
4.5.5 DEVIATION FROM TEST STANDARD 40
4.5.6 EUT OPERATING CONDITION 40
4.5.7 TEST RESULTS 41
4.6 HOPPING CHANNEL SEPARATION 47
4.6.1 LIMIT OF HOPPING CHANNEL SEPARATION 47
4.6.2 TEST SETUP 47
4.6.3 TEST INSTRUMENTS 47
4.6.4 TEST PROCEDURES 47
4.6.5 DEVIATION FROM TEST STANDARD 47
4.6.6 TEST RESULTS 48
4.7 MAXIMUM OUTPUT POWER 52
4.7.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT 52
4.7.2 TEST SETUP 52
4.7.3 TEST INSTRUMENTS 52
4.7.4 TEST PROCEDURES 52
4.7.5 DEVIATION FROM TEST STANDARD 52
4.7.6 EUT OPERATING CONDITION 52
4.7.7 TEST RESULTS 53
4.8 OUT OF BAND MEASUREMENT 54
4.8.1 LIMITS OF OUT OF BAND MEASUREMENT 54
4.8.2 TEST INSTRUMENTS 54
4.8.3 TEST PROCEDURE 54
4.8.4 DEVIATION FROM TEST STANDARD 54
4.8.5 EUT OPERATING CONDITION 54
4.8.6 TEST RESULTS 54

5 PHOTOGRAPHS OF THE TEST CONFIGURATION.....59
6 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....60

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF161008W001-1	Original release	Oct. 30, 2016

1 CERTIFICATION

PRODUCT:	LTE Digital Mobile Phone
BRAND NAME:	Nubia
MODEL NAME:	NX529J/ nubia Z11 mini
APPLICANT:	Nubia Technology Co., Ltd.
TESTED:	Oct. 09, 2016 ~ Oct. 28, 2016
TEST SAMPLE:	Identical Prototype
STANDARDS:	**FCC Part 15, Subpart C. Section 15.247** ANSI C63.10-2013

The above equipment has been tested by **Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch** and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : _____ , **DATE:** Oct. 30, 2016
(Yuqiang Yin / Engineer)

APPROVED BY : _____ , **DATE:** Oct. 30, 2016
(Bill Yao / Manager)

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	**TEST TYPE AND LIMIT**	**RESULT**	**REMARK**
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is 14.09dB at 0.412000MHz.
15.247(a)(1)(iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.
15.247(a)(1)(iii)	Dwell Time on Each Channel	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
15.247(d)& 15.209	Transmitter Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -3.27dB at 83.35MHz.
15.247(d)	Out of band Measurement	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

NOTE: If The Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.66dB
Radiated emissions	9KHz ~ 30MHz	2.74dB
	30MHz ~ 1GMHz	3.55dB
	1GHz ~ 18GHz	4.84dB
	18GHz ~ 40GHz	1.94dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	LTE Digital Mobile Phone
MODEL NAME	NX529J/ nubia Z11 mini
POWER SUPPLY	5.0Vdc (adapter or host equipment) 3.85Vdc (Li-ion, battery)
MODULATION TECHNOLOGY	FHSS
MODULATION TYPE	GFSK, 8DPSK, π/4 DQPSK
OPERATING FREQUENCY	2402MHz~2480MHz
NUMBER OF CHANNEL	79
MAX. OUTPUT POWER	13.804mW (Max. Measured)
ANTENNA TYPE	PIFA Antenna with -2dBi gain
HW VERSION	NX529J_V2CMB_A
SW VERSION	NX529J_ENCommon_V1.05
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	USB cable: non-shielded, detachable, 1.0m

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. The EUT was powered by the following adapters:

ADAPTER 1	
BRAND:	RUIDE
MODEL:	STC-A515A-Z
INPUT:	AC 100-240V, 600mA
OUTPUT:	DC 5V, 1500mA

ADAPTER 2	
BRAND:	DOKOCOM
MODEL:	STC-A515A-Z
INPUT:	AC 100-240V, 600mA
OUTPUT:	DC 5V, 1500mA

ADAPTER 3	
BRAND:	Salcomp
MODEL:	STC-A515A-Z
INPUT:	AC 100-240V, 600mA
OUTPUT:	DC 5V, 1500mA

3. The EUT matched the following USB cable:

USB CABLE	
BRAND:	LIXUN
MODEL:	ZXMT1511003
SIGNAL LINE:	1.0 METER

4. The above models are identical except the model name for marketing purpose.
5. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

3.2 DESCRIPTION OF TEST MODES

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

3.2.1 ONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photograph of the test configuration for reference.

3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports
The worst case was found when positioned on X axis for radiated emission.
Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	√	√	-

Where **RE<1G:** Radiated Emission below 1GHz **RE≥1G:** Radiated Emission above 1GHz
PLC: Power Line Conducted Emission **APCM:** Antenna Port Conducted Measurement

RADIATED EMISSION TEST (BELOW 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	78	FHSS	8DPSK	DH5

RADIATED EMISSION TEST (ABOVE 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	0, 39, 78	FHSS	GFSK	DH5
-	0 to 78	0, 39, 78	FHSS	8DPSK	DH5

POWER LINE CONDUCTED EMISSION TEST:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	78	FHSS	8DPSK	DH5

ANTENNA PORT CONDUCTED MEASUREMENT:

☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.

☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	π/4 DQPSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	DH5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE (SYSTEM)	TESTED BY
RE<1G	22deg. C, 54%RH	DC 5V from adaptor	Tony
RE≥1G	22deg. C, 54%RH	DC 5V from adaptor	Tony
PLC	25deg. C, 60%RH	DC 5V from adaptor	Yuqiang Yin
APCM	25deg. C, 60%RH	DC 3.85V from battery	Yuqiang Yin

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. Section 15.247
ANSI C63.10-2013

FCC Public Notice DA 00-705

NOTE: 1. All test items have been performed and recorded as per the above standards.

2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	DC source	LONG WEI	PS-6403D	010934269	N/A
2	PC	HP	A6608CN	3CR83825X3	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	DC Line: Unshielded, Detachable 1.0m
2	AC Line: Unshielded, Detachable 1.5m

4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

NOTE: 1.The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	101588	Jan. 22,16	Jan. 21,17
Artificial Mains Network	Rohde&Schwarz	ENV216	101173	Mar. 04,16	Mar. 03,17
Artificial Mains Network	Rohde&Schwarz	ESH3-Z5	100317	Apr. 05,16	Apr. 04,17
Voltage probe	SCHWARZBECK	TK 9421	TK 9421-176	Jan. 08,16	Jan. 07,17
Test software	ADT	ADT_Cond_V7.3.7	N/A	N/A	N/A

NOTE:

1. The test was performed in shielded room 553.
2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

4.1.3 TEST PROCEDURES

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.

b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

a. Turned on the power and connected of all equipment.
b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.

4.1.7 TEST RESULTS

CONDUCTED WORST-CASE DATA:

Frequency Range	150KHz ~ 30MHz	**Detector Function & Resolution Bandwidth**	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	**Environmental Conditions**	24deg. C, 55RH
Tested By	Eric	**TEST DATE**	2016/10/23

Frequency (MHz)	QuasiPeak (dB¦ÌV)	CAverage (dB¦ÌV)	Limit (dB¦ÌV)	Margin (dB)	Line	Filter	Corr. (dB)
0.412000	---	32.03	47.61	15.58	L	ON	9.7
0.412000	**43.52**	**---**	**57.61**	**14.09**	**L**	**ON**	**9.7**
0.492000	---	27.33	46.13	18.80	L	ON	9.7
0.492000	39.07	---	56.13	17.06	L	ON	9.7
4.608000	---	28.36	46.00	17.64	L	ON	9.7
4.608000	38.67	---	56.00	17.33	L	ON	9.7
10.372000	---	29.23	50.00	20.77	L	ON	9.9
10.372000	41.67	---	60.00	18.33	L	ON	9.9
14.108000	---	32.48	50.00	17.52	L	ON	9.9
14.108000	45.55	---	60.00	14.45	L	ON	9.9
19.524000	---	16.39	50.00	33.61	L	ON	9.9
19.524000	31.61	---	60.00	28.39	L	ON	9.9

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



Frequency Range	150KHz ~ 30MHz	**Detector Function & Resolution Bandwidth**	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	**Environmental Conditions**	24deg. C, 55RH
Tested By	Eric	**TEST DATE**	2016/10/23

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.476000	---	31.37	46.41	15.04	N	ON	10.1
0.476000	41.99	---	56.41	14.42	N	ON	10.1
1.072000	---	23.93	46.00	22.07	N	ON	9.9
1.072000	35.54	---	56.00	20.46	N	ON	9.9
2.292000	---	21.42	46.00	24.58	N	ON	9.8
2.292000	32.60	---	56.00	23.40	N	ON	9.8
4.372000	---	24.65	46.00	21.35	N	ON	9.8
4.372000	36.10	---	56.00	19.90	N	ON	9.8
10.032000	---	27.27	50.00	22.73	N	ON	9.9
10.032000	38.04	---	60.00	21.96	N	ON	9.9
10.440000	---	25.56	50.00	24.44	N	ON	9.9
10.440000	35.41	---	60.00	24.59	N	ON	9.9

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.

Full Spectrum



4.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a). Other emissions shall be at least 20dB below the highest level of the desired power.

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	101494	Apr. 05,16	Apr. 04,17
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV7	102331	Nov. 09,15	Nov. 08,16
Bilog Antenna	Teseq	CBL 6111D	30643	Jul. 14, 16	Jul. 13, 17
Horn Antenna (1GHz -18GHz)	ETS -Lindgren	3117	00062558	May 18,16	May 17,17
GPS Generator+ Antenna	TOJOIN	GNSS-5000A	E1-010119	Aug. 02, 15	Aug. 01, 17
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	NSEMC003	Mar. 12,16	Mar. 11,18
Test Software	ADT	ADT_Radiated _V7.6.15.9.2	N/A	N/A	N/A
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170242	Mar. 12,16	Mar. 11,17
Amplifier (9kHz-1GHz)	SONOMA	310D	186955	Mar. 04,16	Mar. 03, 17
Pre-Amplifier(1-18G)	HP	8449B	3008A00409	Apr. 25,16	Apr. 24,17
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 20,15	Nov. 19,16
Test Software	ADT	ADT_Radiated _V7.6.15.9.2	N/A	N/A	N/A
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Aug. 08,16	Aug. 07,17

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in 966 Chamber.
3. The FCC Site Registration No. is 502831.

4.2.3 TEST PROCEDURES

a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

a. Set the EUT under full load condition and placed them on a testing table.
b. Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
c. The necessary accessories enable the EUT in full functions.

4.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA:

9 KHz – 30 KHz data: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

30 MHz – 1GHz data:

8DPSK DH5

CHANNEL	Channel 78	**DETECTOR FUNCTION**	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
31.94	23.76	44.72	40.00	-16.24	15.76	0.82	37.54	200	15	QP
82.38	30.25	59.30	40.00	-9.75	6.67	1.40	37.12	200	64	QP
183.26	31.38	56.04	43.50	-12.12	9.93	2.08	36.67	200	80	QP
274.44	32.29	53.53	46.00	-13.71	12.69	2.58	36.51	200	156	QP
369.50	25.89	43.60	46.00	-20.11	15.92	3.02	36.65	200	235	QP
422.85	23.92	40.00	46.00	-22.08	17.47	3.22	36.77	200	280	QP

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value



CHANNEL	Channel 78	**DETECTOR FUNCTION**	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	**EMISSION LEVEL (dBuV/m)**	**READ LEVEL (dBuV)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA FACTOR (dB /m)**	**CABLE LOSS (dB)**	**PREAMP FACTOR (dB)**	**ANTENNA HEIGHT (cm)**	**TABLE ANGLE (Degree)**	**REMARK**
31.94	34.99	55.95	40.00	-5.01	15.76	0.82	37.54	100	36	QP
83.35	**36.73**	**65.73**	**40.00**	**-3.27**	**6.70**	**1.41**	**37.11**	**100**	**60**	**QP**
184.23	32.55	57.19	43.50	-10.95	9.94	2.08	36.66	100	96	QP
283.17	22.63	43.71	46.00	-23.37	12.80	2.63	36.51	100	120	QP
370.47	26.61	44.29	46.00	-19.39	15.96	3.02	36.66	100	198	QP
422.85	21.60	37.68	46.00	-24.40	17.47	3.22	36.77	100	250	QP

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value



ABOVE 1GHz WORST-CASE DATA:

GFSK DH5

CHANNEL	TX Channel 0	**DETECTOR FUNCTION**	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	**EMISSION LEVEL (dBuV/m)**	**READ LEVEL (dBuV)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA FACTOR (dB /m)**	**CABLE LOSS (dB)**	**PREAMP FACTOR (dB)**	**ANTENNA HEIGHT (cm)**	**TABLE ANGLE (Degree)**	**REMARK**
2390	34.82	42.69	54.00	-19.18	32.29	8.15	48.31	103	9	Average
2390	48.36	56.23	74.00	-25.64	32.29	8.15	48.31	103	9	Peak
2402	102.99	110.83			32.30	8.17	48.31	103	9	Average
2402	109.56	117.40			32.30	8.17	48.31	103	9	Peak
2483.5	35.16	42.76	54.00	-18.84	32.38	8.32	48.30	103	9	Average
2483.5	47.89	55.49	74.00	-26.11	32.38	8.32	48.30	103	9	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	**EMISSION LEVEL (dBuV/m)**	**READ LEVEL (dBuV)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA FACTOR (dB /m)**	**CABLE LOSS (dB)**	**PREAMP FACTOR (dB)**	**ANTENNA HEIGHT (cm)**	**TABLE ANGLE (Degree)**	**REMARK**
2390	33.98	41.85	54.00	-20.02	32.29	8.15	48.31	260	270	Average
2390	46.26	54.13	74.00	-27.74	32.29	8.15	48.31	260	270	Peak
2402	99.70	107.54			32.30	8.17	48.31	260	270	Average
2402	106.11	113.95			32.30	8.17	48.31	260	270	Peak
2483.5	34.16	41.76	54.00	-19.84	32.38	8.32	48.30	260	270	Average
2483.5	46.56	54.16	74.00	-27.44	32.38	8.32	48.30	260	270	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
   Margin value = Emission level – Limit value.
2. 2402MHz: Fundamental frequency.

CHANNEL	TX Channel 39	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	**EMISSION LEVEL (dBuV/m)**	**READ LEVEL (dBuV)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA FACTOR (dB /m)**	**CABLE LOSS (dB)**	**PREAMP FACTOR (dB)**	**ANTENNA HEIGHT (cm)**	**TABLE ANGLE (Degree)**	**REMARK**
2390	35.62	43.49	54.00	-18.38	32.29	8.15	48.31	116	9	Average
2390	47.96	55.83	74.00	-26.04	32.29	8.15	48.31	116	9	Peak
2441	104.22	111.95			32.34	8.24	48.31	116	9	Average
2441	110.82	118.55			32.34	8.24	48.31	116	9	Peak
2483.5	35.86	43.46	54.00	-18.14	32.38	8.32	48.30	116	9	Average
2483.5	47.99	55.59	74.00	-26.01	32.38	8.32	48.30	116	9	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	**EMISSION LEVEL (dBuV/m)**	**READ LEVEL (dBuV)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA FACTOR (dB /m)**	**CABLE LOSS (dB)**	**PREAMP FACTOR (dB)**	**ANTENNA HEIGHT (cm)**	**TABLE ANGLE (Degree)**	**REMARK**
2390	34.19	42.06	54.00	-19.81	32.29	8.15	48.31	250	280	Average
2390	46.09	53.96	74.00	-27.91	32.29	8.15	48.31	250	280	Peak
2441	99.30	107.03			32.34	8.24	48.31	250	280	Average
2441	105.84	113.57			32.34	8.24	48.31	250	280	Peak
2483.5	34.24	41.84	54.00	-19.76	32.38	8.32	48.30	250	280	Average
2483.5	46.25	53.85	74.00	-27.75	32.38	8.32	48.30	250	280	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
   Margin value = Emission level – Limit value.
2. 2441MHz: Fundamental frequency.

CHANNEL	TX Channel 78	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	**EMISSION LEVEL (dBuV/m)**	**READ LEVEL (dBuV)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA FACTOR (dB /m)**	**CABLE LOSS (dB)**	**PREAMP FACTOR (dB)**	**ANTENNA HEIGHT (cm)**	**TABLE ANGLE (Degree)**	**REMARK**
2390	35.69	43.56	54.00	-18.31	32.29	8.15	48.31	116	5	Average
2390	47.31	55.18	74.00	-26.69	32.29	8.15	48.31	116	5	Peak
2480	103.17	110.78			32.38	8.31	48.30	116	5	Average
2480	109.25	116.86			32.38	8.31	48.30	116	5	Peak
2483.5	38.14	45.74	54.00	-15.86	32.38	8.32	48.30	116	5	Average
2483.5	53.31	60.91	74.00	-20.69	32.38	8.32	48.30	116	5	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	**EMISSION LEVEL (dBuV/m)**	**READ LEVEL (dBuV)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA FACTOR (dB /m)**	**CABLE LOSS (dB)**	**PREAMP FACTOR (dB)**	**ANTENNA HEIGHT (cm)**	**TABLE ANGLE (Degree)**	**REMARK**
2390	35.82	43.69	54.00	-18.18	32.29	8.15	48.31	262	270	Average
2390	47.45	55.32	74.00	-26.55	32.29	8.15	48.31	262	270	Peak
2480	98.28	105.89			32.38	8.31	48.30	262	270	Average
2480	105.08	112.69			32.38	8.31	48.30	262	270	Peak
2483.5	37.02	44.62	54.00	-16.98	32.38	8.32	48.30	262	270	Average
2483.5	50.18	57.78	74.00	-23.82	32.38	8.32	48.30	262	270	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
   Margin value = Emission level – Limit value.
2. 2480MHz: Fundamental frequency.

BT_8DPSK

CHANNEL	TX Channel 0	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	**EMISSION LEVEL (dBuV/m)**	**READ LEVEL (dBuV)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA FACTOR (dB /m)**	**CABLE LOSS (dB)**	**PREAMP FACTOR (dB)**	**ANTENNA HEIGHT (cm)**	**TABLE ANGLE (Degree)**	**REMARK**
2390	35.75	43.62	54.00	-18.25	32.29	8.15	48.31	118	6	Average
2390	48.37	56.24	74.00	-25.63	32.29	8.15	48.31	118	6	Peak
2402	99.60	107.44			32.30	8.17	48.31	118	6	Average
2402	108.64	116.48			32.30	8.17	48.31	118	6	Peak
2483.5	35.95	43.55	54.00	-18.05	32.38	8.32	48.30	118	6	Average
2483.5	47.85	55.45	74.00	-26.15	32.38	8.32	48.30	118	6	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	**EMISSION LEVEL (dBuV/m)**	**READ LEVEL (dBuV)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA FACTOR (dB /m)**	**CABLE LOSS (dB)**	**PREAMP FACTOR (dB)**	**ANTENNA HEIGHT (cm)**	**TABLE ANGLE (Degree)**	**REMARK**
2390	35.81	43.68	54.00	-18.19	32.29	8.15	48.31	258	270	Average
2390	47.45	55.32	74.00	-26.55	32.29	8.15	48.31	258	270	Peak
2402	96.25	104.09			32.30	8.17	48.31	258	270	Average
2402	105.11	112.95			32.30	8.17	48.31	258	270	Peak
2483.5	36.07	43.67	54.00	-17.93	32.38	8.32	48.30	258	270	Average
2483.5	48.17	55.77	74.00	-25.83	32.38	8.32	48.30	258	270	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
   Margin value = Emission level – Limit value.
2. 2402MHz: Fundamental frequency.

CHANNEL	TX Channel 39	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	**EMISSION LEVEL (dBuV/m)**	**READ LEVEL (dBuV)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA FACTOR (dB /m)**	**CABLE LOSS (dB)**	**PREAMP FACTOR (dB)**	**ANTENNA HEIGHT (cm)**	**TABLE ANGLE (Degree)**	**REMARK**
2390	35.71	43.58	54.00	-18.29	32.29	8.15	48.31	118	6	Average
2390	47.86	55.73	74.00	-26.14	32.29	8.15	48.31	118	6	Peak
2441	101.33	109.06			32.34	8.24	48.31	118	6	Average
2441	110.34	118.07			32.34	8.24	48.31	118	6	Peak
2483.5	35.94	43.54	54.00	-18.06	32.38	8.32	48.30	118	6	Average
2483.5	48.24	55.84	74.00	-25.76	32.38	8.32	48.30	118	6	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	**EMISSION LEVEL (dBuV/m)**	**READ LEVEL (dBuV)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA FACTOR (dB /m)**	**CABLE LOSS (dB)**	**PREAMP FACTOR (dB)**	**ANTENNA HEIGHT (cm)**	**TABLE ANGLE (Degree)**	**REMARK**
2390	35.93	43.80	54.00	-18.07	32.29	8.15	48.31	108	270	Average
2390	47.61	55.48	74.00	-26.39	32.29	8.15	48.31	108	270	Peak
2441	97.42	105.15			32.34	8.24	48.31	108	270	Average
2441	106.43	114.16			32.34	8.24	48.31	108	270	Peak
2483.5	35.80	43.40	54.00	-18.20	32.38	8.32	48.30	108	270	Average
2483.5	47.56	55.16	74.00	-26.44	32.38	8.32	48.30	108	270	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
   Margin value = Emission level – Limit value.
2. 2441MHz: Fundamental frequency.

CHANNEL	TX Channel 78	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	**EMISSION LEVEL (dBuV/m)**	**READ LEVEL (dBuV)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA FACTOR (dB /m)**	**CABLE LOSS (dB)**	**PREAMP FACTOR (dB)**	**ANTENNA HEIGHT (cm)**	**TABLE ANGLE (Degree)**	**REMARK**
2390	35.74	43.61	54.00	-18.26	32.29	8.15	48.31	115	5	Average
2390	48.07	55.94	74.00	-25.93	32.29	8.15	48.31	115	5	Peak
2480	99.70	107.31			32.38	8.31	48.30	115	5	Average
2480	108.77	116.38			32.38	8.31	48.30	115	5	Peak
2483.5	37.95	45.55	54.00	-16.05	32.38	8.32	48.30	115	5	Average
2483.5	50.78	58.38	74.00	-23.22	32.38	8.32	48.30	115	5	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	**EMISSION LEVEL (dBuV/m)**	**READ LEVEL (dBuV)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA FACTOR (dB /m)**	**CABLE LOSS (dB)**	**PREAMP FACTOR (dB)**	**ANTENNA HEIGHT (cm)**	**TABLE ANGLE (Degree)**	**REMARK**
2390	35.84	43.71	54.00	-18.16	32.29	8.15	48.31	269	270	Average
2390	48.19	56.06	74.00	-25.81	32.29	8.15	48.31	269	270	Peak
2480	94.70	102.31			32.38	8.31	48.30	269	270	Average
2480	104.10	111.71			32.38	8.31	48.30	269	270	Peak
2483.5	36.71	44.31	54.00	-17.29	32.38	8.32	48.30	269	270	Average
2483.5	50.62	58.22	74.00	-23.38	32.38	8.32	48.30	269	270	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
   Margin value = Emission level – Limit value.
2. 2480MHz: Fundamental frequency.

4.3 NUMBER OF HOPPING FREQUENCY USED

4.3.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 channels frequencies, and should be equally spaced.

4.3.2 TEST SETUP



4.3.3 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power Sensor	Keysight	U2021XA	MY55060016	May 04,16	May 03,17
Power Sensor	Keysight	U2021XA	MY55060018	May 04,16	May 03,17
10dB Attenuator	JFW/USA	50HF-010-SMA	1505	Jul. 27, 16	Jul. 26, 17
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 09, 16	Oct. 08, 17
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Sep.05,16	Sep. 04,17
Oscilloscope	Agilent	DSO9254A	MY51260160	Sep.05,16	Sep. 04,17
Signal Analyzer	Rohde & Schwarz	FSV7	102331	Nov. 09,15	Nov. 08,16
Signal Generator	Agilent	N5183A	MY50140980	Nov. 09,15	Nov. 08,16
10dB Attenuator	JFW/USA	50HF-010-SMA	1505	Jul. 27, 16	Jul. 26, 17
ESG Vector Signal Generator	Agilent	E4438C	MY49072505	Apr. 22, 16	Apr. 21, 17
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Aug.08, 16	Aug. 07, 17

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in RF Oven room.

4.3.4 TEST PROCEDURES

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.

c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.

d. Set the SA on View mode and then plot the result on SA screen.

e. Repeat above procedures until all frequencies measured were completed.

4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

4.3.6 TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.

GFSK


RBW 300 kHz
VBW 300 kHz
SWT 1 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
9.81 dBm
2.40200 GHz
Marker 2 [T1]
10.71 dBm
2.44200 GHz
Ref 14.7 dBm
Att 20 dB
Offset 4.7 dB
14.7
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.3
Center 2.42142 GHz
4.2 MHz/
Span 42 MHz


RBW 300 kHz
VBW 300 kHz
SWT 1 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
10.30 dBm
2.44300 GHz
Marker 2 [T1]
8.52 dBm
2.48000 GHz
Ref 14.7 dBm
Att 20 dB
Offset 4.7 dB
14.7
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.3
Center 2.4634 GHz
4.2 MHz/
Span 42 MHz

8DPSK


RBW 300 kHz
VBW 300 kHz
SWT 1 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
8.29 dBm
2.40200 GHz
Marker 2 [T1]
9.53 dBm
2.44200 GHz
Ref 14.7 dBm
Att 20 dB
Offset 4.7 dB
14.7
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.3
Center 2.42142 GHz
4.2 MHz/
Span 42 MHz


RBW 300 kHz
VBW 300 kHz
SWT 1 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
8.68 dBm
2.44300 GHz
Marker 2 [T1]
6.66 dBm
2.48000 GHz
Ref 14.7 dBm
Att 20 dB
Offset 4.7 dB
14.7
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.3
Center 2.4634 GHz
4.2 MHz/
Span 42 MHz

4.4 DWELL TIME ON EACH CHANNEL

4.4.1 LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

4.4.4 TEST PROCEDURES

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.

c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.

d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.

e. Repeat above procedures until all different time-slot modes have been completed.

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 TEST RESULTS

GFSK

Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
DH1	79	31.6	4	49	387.1	0.42	162.58	400	PASS
DH3	79	31.6	4	26	205.4	1.685	346.1	400	PASS
DH5	79	31.6	4	17	134.3	2.945	395.51	400	PASS

NOTE: Test plots of the transmitting time slot are shown on next 3 pages.

GFSK

DH1





DH3





DH5





8DPSK

Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
DH1	79	31.6	31.6	4	52	410.8	0.423	173.77	PASS
DH3	79	31.6	31.6	4	26	205.4	1.72	353.29	PASS
DH5	79	31.6	31.6	4	17	134.3	2.95	396.19	PASS

NOTE: Test plots of the transmitting time slot are shown on next 3 pages.

8DPSK

DH1





DH3





DH5





4.5 CHANNEL BANDWIDTH

4.5.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dBbandwidth of hopping channel shell be a minimum limit for the hopping channel separation.

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

4.5.4 TEST PROCEDURE

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.

c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.

d. Repeat above procedures until all frequencies measured were complete.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

4.5.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.5.7 TEST RESULTS

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	0.98
39	2441	0.97
78	2480	0.97

CH 0



CH 39


RBW 30 kHz
VBW 300 kHz
SWT 2.6 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-11.64 dBm
2.44053 GHz
Delta 2 [T1]
0.00 dB
974.88 kHz
Ref 14.7 dBm
Att 20 dB
Offset 4.7 dB
D1 8.36 dBm
D2 -11.64 dBm
14.7
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.3
F1
F2
Center 2.441 GHz
250 kHz/
Span 2.5 MHz

CH 78


RBW 30 kHz
VBW 300 kHz
SWT 2.6 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-12.98 dBm
2.47953 GHz
Delta 2 [T1]
0.00 dB
970.00 kHz
Ref 14.7 dBm
Att 20 dB
Offset 4.7 dB
D1 7.02 dBm
D2 -12.98 dBm
14.7
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.3
F1
F2
Center 2.48 GHz
250 kHz/
Span 2.5 MHz

π/4 DQPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.32
39	2441	1.32
78	2480	1.29

CH 0



CH 39


RBW 30 kHz
VBW 300 kHz
SWT 2.6 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-13.90 dBm
2.44034 GHz
Delta 2 [T1]
0.00 dB
1.32 MHz
Ref 14.7 dBm
Att 20 dB
Offset 4.7 dB
D1 6.10 dBm
D2 -13.90 dBm
14.7
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.3
F1
F2
Center 2.441 GHz
250 kHz/
Span 2.5 MHz

CH 78


RBW 30 kHz
VBW 300 kHz
SWT 2.6 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-15.00 dBm
2.47937 GHz
Delta 2 [T1]
0.00 dB
1.29 MHz
Ref 14.7 dBm
Att 20 dB
Offset 4.7 dB
D1 5.00 dBm
D2 -15.00 dBm
14.7
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.3
F1
F2
Center 2.48 GHz
250 kHz/
Span 2.5 MHz

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.30
39	2441	1.31
78	2480	1.30

CH 0



CH 39


RBW 30 kHz
VBW 300 kHz
SWT 2.6 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-13.21 dBm
2.44035 GHz
Delta 2 [T1]
0.00 dB
1.31 MHz
Ref 14.7 dBm
Att 20 dB
Offset 4.7 dB
D1 6.79 dBm
D2 -13.21 dBm
14.7
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.3
F1
F2
Center 2.441 GHz
250 kHz/
Span 2.5 MHz

CH 78


RBW 30 kHz
VBW 300 kHz
SWT 2.6 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-14.62 dBm
2.47935 GHz
Delta 2 [T1]
0.00 dB
1.30 MHz
Ref 14.7 dBm
Att 20 dB
Offset 4.7 dB
D1 5.38 dBm
D2 -14.62 dBm
14.7
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.3
F1
F2
Center 2.48 GHz
250 kHz/
Span 2.5 MHz

4.6 HOPPING CHANNEL SEPARATION

4.6.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

4.6.2 TEST SETUP



4.6.3 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

4.6.4 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

4.6.6 TEST RESULTS

GFSK

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.00	0.98	0.65	PASS
39	2441	1.01	0.97	0.65	PASS
78	2480	1.00	0.97	0.65	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.

CH 0



CH 39


RBW 30 kHz
VBW 100 kHz
SWT 2.667 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
8.38 dBm
2.44102 GHz
Delta 2 [T2]
0.03 dB
1.01 MHz
Ref 14.7 dBm
Att 20 dB
Offset 4.7 dB
14.7
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.3
Center 2.4415 GHz
250 kHz/
Span 2.5 MHz

CH 78


RBW 30 kHz
VBW 100 kHz
SWT 2.667 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T2]
7.06 dBm
2.47902 GHz
Delta 2 [T1]
0.10 dB
1.00 MHz
Ref 14.7 dBm
Att 20 dB
Offset 4.7 dB
14.7
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.3
Center 2.4795 GHz
250 kHz/
Span 2.5 MHz

8DPSK

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.01	1.30	0.87	PASS
39	2441	1.00	1.31	0.87	PASS
78	2480	1.01	1.30	0.87	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.

CH 0



CH 39


RBW 30 kHz
VBW 100 kHz
SWT 2.667 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
7.05 dBm
2.44099 GHz
Delta 2 [T2]
0.06 dB
1.00 MHz
Ref 14.7 dBm
Att 20 dB
Offset 4.7 dB
14.7
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.3
Center 2.4415 GHz
250 kHz/
Span 2.5 MHz

CH 78


RBW 30 kHz
VBW 100 kHz
SWT 2.667 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T2]
5.46 dBm
2.47899 GHz
Delta 2 [T1]
0.50 dB
1.01 MHz
Ref 14.7 dBm
Att 20 dB
Offset 4.7 dB
14.7
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.3
Center 2.4795 GHz
250 kHz/
Span 2.5 MHz

4.7 MAXIMUM OUTPUT POWER

4.7.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT

The Maximum Output Power Measurement is 125mW.

4.7.2 TEST SETUP



4.7.3 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

4.7.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

4.7.5 DEVIATION FROM TEST STANDARD

No deviation.

4.7.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.7.7 TEST RESULTS

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	POWER OUTPUT (dBm)	POWER OUTPUT (mW)	POWER LIMIT (mW)	PASS/FAIL
0	2402	10.25	10.593	125	PASS
39	2441	11.27	13.397	125	PASS
78	2480	9.64	9.204	125	PASS

π/4 DQPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	POWER OUTPUT (dBm)	POWER OUTPUT (mW)	POWER LIMIT (mW)	PASS/FAIL
0	2402	10.37	10.889	125	PASS
39	2441	11.38	13.740	125	PASS
78	2480	9.62	9.162	125	PASS

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	POWER OUTPUT (dBm)	POWER OUTPUT (mW)	POWER LIMIT (mW)	PASS/FAIL
0	2402	10.42	11.015	125	PASS
39	2441	11.40	**13.804**	125	PASS
78	2480	9.62	9.162	125	PASS

4.8 OUT OF BAND MEASUREMENT

4.8.1 LIMITS OF OUT OF BAND MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100KHz RBW).

4.8.2 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

4.8.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. of Spectrum Analyzer was set RBW to 100 kHz and VBW to 100 kHz with suitable frequency span including 100 MHz bandwidth from band edge. Detector = PEAK and Trace mode = Max Hold. The band edges was measured and recorded.

4.8.4 DEVIATION FROM TEST STANDARD

No deviation.

4.8.5 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.8.6 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.

GFSK

Hopping disabled_Low Channel





Hopping disabled_High Channel





Hopping enabled_Low Channel





Hopping enabled_High Channel





8DPSK

Hopping disabled_Low Channel





Hopping disabled_High Channel





Hopping enabled_Low Channel





Hopping enabled_High Channel





5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

6 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---