



REPORT No.: SZ18110268E01

# TEST REPORT

**APPLICANT** : Nubia Technology Co.,Ltd

**PRODUCT NAME** : NX619J

**MODEL NAME** : NX619J

**BRAND NAME** : NUBIA

**FCC ID** : 2AHJO-NX619J

**STANDARD(S)** : 47 CFR Part 15 Subpart B

**RECEIPT DATE** : 2018-11-22

**TEST DATE** : 2018-11-27 to 2018-12-23

**ISSUE DATE** : 2018-12-27

Edited by:

Lv Shangrong  
Lv Shangrong(Rapporteur)

Approved by:

Andy Yeh  
Andy Yeh(Technical Director)

**NOTE:** This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

**MORLAB**

SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.  
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





## DIRECTORY

|                                               |           |
|-----------------------------------------------|-----------|
| <b>1. Technical Information</b>               | <b>3</b>  |
| 1.1. Applicant and Manufacturer Information   | 3         |
| 1.2. Equipment Under Test (EUT) Description   | 3         |
| <b>2. Test Results</b>                        | <b>6</b>  |
| 2.1. Applied Reference Documents              | 6         |
| 2.2. EUT Setup and Operating Conditions       | 7         |
| <b>3. 47 CFR Part 15B Requirements</b>        | <b>9</b>  |
| 3.1. Conducted Emission                       | 9         |
| 3.2. Radiated Disturbance                     | 13        |
| <b>Annex A Photographs of Test Setup</b>      | <b>20</b> |
| <b>Annex B Test Uncertainty</b>               | <b>22</b> |
| <b>Annex C Testing Laboratory Information</b> | <b>23</b> |

| Change History |            |                   |
|----------------|------------|-------------------|
| Version        | Date       | Reason for change |
| 1.0            | 2018-12-27 | First edition     |
|                |            |                   |



# 1. Technical Information

**Note:** Provide by applicant.

## 1.1. Applicant and Manufacturer Information

|                              |                                                                                                                       |
|------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| <b>Applicant:</b>            | Nubia Technology Co.,Ltd                                                                                              |
| <b>Applicant Address:</b>    | 10/F, Tower A, Hans Innovation Mansion, North Ring Rd.,<br>No.9018, High-Tech Park, Nanshan District, Shenzhen, China |
| <b>Manufacturer:</b>         | Nubia Technology Co.,Ltd                                                                                              |
| <b>Manufacturer Address:</b> | 10/F, Tower A, Hans Innovation Mansion, North Ring Rd.,<br>No.9018, High-Tech Park, Nanshan District, Shenzhen, China |

## 1.2. Equipment Under Test (EUT) Description

|                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>EUT Type:</b>              | NX619J                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Serial No:</b>             | (N/A, marked #1 by test site)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Hardware Version:</b>      | NX619J_V1AMB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Software Version:</b>      | NX619J_ENCommon_V1.07                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>SIM Cards Description:</b> | SIM 1 and SIM 2 is a chipset unit and tested as a single chipset.<br>The SIM 1 is chosen for test                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Tx Frequency:</b>          | GSM850: 824 MHz ~ 849 MHz<br>GSM1900: 1850 MHz ~ 1910 MHz<br>WCDMA Band II: 1850 MHz ~ 1910 MHz<br>WCDMA Band IV: 1710 MHz ~ 1755 MHz<br>WCDMA Band V: 824 MHz ~ 849 MHz<br>CDMA 800MHz (BC 0): 824.7 MHz ~ 848.31 MHz<br>LTE Band 2: 1850 MHz ~ 1910 MHz<br>LTE Band 4: 1710 MHz ~ 1755 MHz<br>LTE Band 5: 824 MHz ~ 849 MHz<br>LTE Band 7: 2500 MHz ~ 2570 MHz<br>LTE Band 12: 699 MHz ~ 716 MHz<br>LTE Band 17: 704 MHz ~ 716 MHz<br>LTE Band 18: 815 MHz ~ 830 MHz<br>LTE Band 19: 830 MHz ~ 845 MHz<br>LTE Band 25: 1850 MHz ~ 1915 MHz<br>LTE Band 26: 814 MHz ~ 849 MHz<br>LTE Band 30: 2305 MHz ~ 2315 MHz<br>LTE Band 38: 2570 MHz ~ 2620 MHz<br>LTE Band 40: 2300 MHz ~ 2400 MHz |



|                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                               |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|
|                             | LTE Band 41: 2496 MHz ~ 2690 MHz<br>LTE Band 66: 1710 MHz ~ 1780 MHz<br>Bluetooth: 2402 MHz ~ 2480 MHz<br>802.11b/g/n-20: 2412 MHz ~ 2462 MHz<br>802.11n-40: 2422 MHz ~ 2452 MHz<br>802.11a/ac/n: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz;<br>5500 MHz ~ 5720 MHz; 5745 MHz ~ 5825 MHz;                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                               |
| <b>Rx Frequency:</b>        | GSM850: 869 MHz ~ 894 MHz<br>GSM1900: 1930 MHz ~ 1990 MHz<br>WCDMA Band II: 1930 MHz ~ 1990 MHz<br>WCDMA Band IV: 1710 MHz ~ 1755 MHz<br>WCDMA Band V: 869 MHz ~ 894 MHz<br>CDMA 800MHz (BC 0): 869.7 MHz ~ 893.31 MHz<br>LTE Band 2: 1930 MHz ~ 1990 MHz<br>LTE Band 4: 2110 MHz ~ 2155 MHz<br>LTE Band 5: 869 MHz ~ 894 MHz<br>LTE Band 7: 2620 MHz ~ 2690 MHz<br>LTE Band 12: 729 MHz ~ 746 MHz<br>LTE Band 17: 734 MHz ~ 746 MHz<br>LTE Band 18: 860 MHz ~ 875 MHz<br>LTE Band 19: 875 MHz ~ 890 MHz<br>LTE Band 25: 1930 MHz ~ 1995 MHz<br>LTE Band 26: 859 MHz ~ 894 MHz<br>LTE Band 30: 2350 MHz ~ 2360 MHz<br>LTE Band 38: 2570 MHz ~ 2620 MHz<br>LTE Band 40: 2300 MHz ~ 2400 MHz<br>LTE Band 41: 2496 MHz ~ 2690 MHz<br>LTE Band 66: 2110 MHz ~ 2200 MHz<br>Bluetooth: 2402 MHz ~ 2480 MHz<br>802.11b/g/n-20: 2412 MHz ~ 2462 MHz<br>802.11n-40: 2422 MHz ~ 2452 MHz<br>802.11a/ac/n: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz;<br>5500 MHz ~ 5720 MHz; 5745 MHz ~ 5825 MHz;<br>GPS/Galileo/GLONASS/BDS: 1559 MHz ~ 1610 MHz |                               |
| <b>Ancillary Equipment:</b> | <b>Battery</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                               |
|                             | Brand Name:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | ATL                           |
|                             | Model No.:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Li3937T44P6h886639            |
|                             | Serial No.:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | (N/A, marked #1 by test site) |
|                             | Capacity:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 3800mAh                       |
|                             | Rated Voltage:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 3.85V                         |
|                             | Charge Limit:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 4.4V                          |



|  |                     |                                   |
|--|---------------------|-----------------------------------|
|  | <b>AC Adapter 1</b> |                                   |
|  | Brand Name:         | CHENYANG                          |
|  | Model No.:          | CYNBY090200-A00                   |
|  | Serial No.:         | (N/A, marked #1 by test site)     |
|  | Rated Input:        | 100-240V ~ 50/60Hz 0.5A           |
|  | Rated Output:       | 5V=3.0A; 9V=2.0A;12V=1.5A         |
|  | <b>AC Adapter 2</b> |                                   |
|  | Brand Name:         | XINSPower                         |
|  | Model No.:          | Q183                              |
|  | Serial No.:         | (N/A, marked #1 by test site)     |
|  | Rated Input:        | 100-240V ~ 50/60Hz 0.5A           |
|  | Rated Output:       | 3.6~6V=3.0A; 6~9V=2.0A;9~12V=1.5A |
|  |                     |                                   |
|  |                     |                                   |

**Note:**

1. The NX619J supports GSM850MHz, 1900MHz, GPRS, EDGE, WCDMA Band II, Band IV, Band V, HSDPA, HSUPA, HSPA+, CDMA(BC0), LTE Band2/4/5/7/12/17/18/19/25/26/30/38/40/41/66, WIFI and GPS/Galileo/GLONASS/BDS.
2. The EUT is equipped with a T-Flash card slot, two SIM card slots and a Micro USB port which can be connected to ancillary equipments.
3. There are two kinds of adapters, both adapters have been tested, only the worst case (CYNBY090200-A00) was recorded in this report.
4. For a more detailed description, please refer to specification or user's manual supplied by the applicant and/or manufacturer



## 2. Test Results

### 2.1. Applied Reference Documents

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart B:

| No. | Identity       | Document Title          |
|-----|----------------|-------------------------|
| 1   | 47 CFR Part 15 | Radio Frequency Devices |

Test detailed items/section required by FCC rules and results are as below:

| No. | Section | Description        | Test Date  | Test Engineer | Result |
|-----|---------|--------------------|------------|---------------|--------|
| 1   | 15.107  | Conducted Emission | 2018.11.27 | Wang Dalong   | PASS   |
| 2   | 15.109  | Radiated Emission  | 2018.12.03 | Wang Dalong   | PASS   |

NOTE: The tests were performed according to the method of measurements prescribed in ANSI C63.4-2014.



## 2.2. EUT Setup and Operating Conditions

Frequency range was investigated: Conducted emission test: from 150 KHz to 30 MHz; Radiated emission test: from 30 MHz to 6000 MHz.

| Test Item                                                                                      |                                                                                                                                                    |
|------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| Radiated Emission                                                                              |                                                                                                                                                    |
| Mode 1                                                                                         | EUT + USB Cable + Adapter + Battery + SIM Card + Earphone + Camera + GSM Idle + WCDMA Idle + CDMA Idle + LTE Idle + Bluetooth Idle + WIFI Idle     |
| Mode 2                                                                                         | EUT + USB Cable + Adapter + Battery + SIM Card + Earphone + MP4 + GSM Idle + WCDMA Idle + CDMA Idle + LTE Idle + Bluetooth Idle + WIFI Idle        |
| Mode 3                                                                                         | EUT + USB Cable + Adapter + Battery + SIM Card + Earphone + GSM Idle + WCDMA Idle + CDMA Idle + LTE Idle + Bluetooth Idle + WIFI Idle + GPS Rx     |
| Mode 4                                                                                         | EUT + USB Cable + Adapter + Battery + SIM Card + Earphone + GSM Idle + WCDMA Idle + CDMA Idle + LTE Idle + Bluetooth Idle + WIFI Idle + Galileo Rx |
| Mode 5                                                                                         | EUT + USB Cable + Adapter + Battery + SIM Card + Earphone + GSM Idle + WCDMA Idle + CDMA Idle + LTE Idle + Bluetooth Idle + WIFI Idle + GLONASS Rx |
| Mode 6                                                                                         | EUT + USB Cable + Adapter + Battery + SIM Card + Earphone + GSM Idle + WCDMA Idle + CDMA Idle + LTE Idle + Bluetooth Idle + WIFI Idle + BDS Rx     |
| <b>Mode 7</b>                                                                                  | <b>EUT + USB Cable + PC + Battery + SIM Card + Earphone + GSM Idle + WCDMA Idle + CDMA Idle + LTE Idle + Bluetooth Idle + WIFI Idle</b>            |
| Conducted Emission                                                                             |                                                                                                                                                    |
| Mode 1                                                                                         | EUT + USB Cable + Adapter + Battery + SIM Card + Earphone + Camera + GSM Idle + WCDMA Idle + CDMA Idle + LTE Idle + Bluetooth Idle + WIFI Idle     |
| Mode 2                                                                                         | EUT + USB Cable + Adapter + Battery + SIM Card + Earphone + MP4 + GSM Idle + WCDMA Idle + CDMA Idle + LTE Idle + Bluetooth Idle + WIFI Idle        |
| Mode 3                                                                                         | EUT + USB Cable + Adapter + Battery + SIM Card + Earphone + GSM Idle + WCDMA Idle + CDMA Idle + LTE Idle + Bluetooth Idle + WIFI Idle + GPS Rx     |
| Mode 4                                                                                         | EUT + USB Cable + Adapter + Battery + SIM Card + Earphone + GSM Idle + WCDMA Idle + CDMA Idle + LTE Idle + Bluetooth Idle + WIFI Idle + Galileo Rx |
| Mode 5                                                                                         | EUT + USB Cable + Adapter + Battery + SIM Card + Earphone + GSM Idle + WCDMA Idle + CDMA Idle + LTE Idle + Bluetooth Idle + WIFI Idle + GLONASS Rx |
| Mode 6                                                                                         | EUT + USB Cable + Adapter + Battery + SIM Card + Earphone + GSM Idle + WCDMA Idle + CDMA Idle + LTE Idle + Bluetooth Idle + WIFI Idle + BDS Rx     |
| <b>Mode 7</b>                                                                                  | <b>EUT + USB Cable + PC + Battery + SIM Card + Earphone + GSM Idle + WCDMA Idle + CDMA Idle + LTE Idle + Bluetooth Idle + WIFI Idle</b>            |
| <b>Remark:</b>                                                                                 |                                                                                                                                                    |
| The above test modes in boldface (Mode 7) were the worst cases of conducted emission, radiated |                                                                                                                                                    |



|                                                                 |
|-----------------------------------------------------------------|
| emission tests; only the test data of these modes was reported. |
|-----------------------------------------------------------------|

During the measurement, the environmental conditions were within the listed ranges:

|                             |          |
|-----------------------------|----------|
| Temperature (°C):           | 15 - 35  |
| Relative Humidity (%):      | 30 - 60  |
| Atmospheric Pressure (kPa): | 86 - 106 |

## 3. 47 CFR Part 15B Requirements

### 3.1. Conducted Emission

#### 3.1.1. Requirement

According to FCC section 15.107, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 $\Omega$  line impedance stabilization network (LISN).


| Frequency range<br>(MHz) | Conducted Limit (dB $\mu$ V) |          |
|--------------------------|------------------------------|----------|
|                          | Quasi-peak                   | Average  |
| 0.15 - 0.50              | 66 to 56                     | 56 to 46 |
| 0.50 - 5                 | 56                           | 46       |
| 5 - 30                   | 60                           | 50       |

NOTE:

- The limit subjects to the Class B digital device.
- The lower limit shall apply at the band edges.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

#### 3.1.2. Test Setup

Please refer to Annex A for the photographs of the Test Configuration.






The EUT is placed on a 0.8m high insulating table, which stands on the grounded conducting floor, and keeps 0.4m away from the grounded conducting wall. The EUT is connected to the power mains through a LISN which provides  $50\Omega/50\mu\text{H}$  of coupling impedance for the measuring instrument. A Pulse Limiter is used to protect the measuring instrument. The factors of the whole test system are calibrated to correct the reading.

The power strip or extension cord has been investigated to make sure that the LISN integrity is maintained with respect to the impedance characteristics as prescribed in ANSI C63.4-2014 at Clause 4.3.


### 3.1.3. Test Result

The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. All test modes are considered, refer to recorded points and plots below.

## A. Test Plot and Suspicious Points:



| NO. | Fre.<br>(MHz) | Emission Level (dBμV) |         | Limit (dBμV) |         | Power-line | Verdict |
|-----|---------------|-----------------------|---------|--------------|---------|------------|---------|
|     |               | Quai-peak             | Average | Quai-peak    | Average |            |         |
| 1   | 0.1501        | 55.09                 | 38.52   | 66.00        | 56.00   | Line       | PASS    |
| 2   | 0.1948        | 49.31                 | 34.89   | 63.83        | 53.83   |            | PASS    |
| 3   | 0.3704        | 36.40                 | 28.82   | 58.49        | 48.49   |            | PASS    |
| 4   | 1.0952        | 32.52                 | 25.17   | 56.00        | 46.00   |            | PASS    |
| 5   | 4.3646        | 29.25                 | 23.65   | 56.00        | 46.00   |            | PASS    |
| 6   | 17.484        | 35.76                 | 30.28   | 60.00        | 50.00   |            | PASS    |



| NO. | Fre.<br>(MHz) | Emission Level (dBμV) |         | Limit (dBμV) |         | Power-line | Verdict |
|-----|---------------|-----------------------|---------|--------------|---------|------------|---------|
|     |               | Quai-peak             | Average | Quai-peak    | Average |            |         |
| 1   | 0.1545        | 53.02                 | 36.34   | 65.76        | 55.76   | Neutral    | PASS    |
| 2   | 0.2038        | 44.01                 | 27.44   | 63.45        | 53.45   |            | PASS    |
| 3   | 0.3931        | 35.49                 | 26.82   | 58.00        | 48.00   |            | PASS    |
| 4   | 0.6455        | 31.83                 | 22.73   | 56.00        | 46.00   |            | PASS    |
| 5   | 1.0685        | 32.30                 | 23.46   | 56.00        | 46.00   |            | PASS    |
| 6   | 20.039        | 27.00                 | 20.96   | 60.00        | 50.00   |            | PASS    |

## 3.2. Radiated Disturbance

### 3.2.1. Requirement

According to FCC section 15.109 (a), the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

| Frequency range (MHz) | Field Strength Limitation at 3m Measurement Dist |                       |
|-----------------------|--------------------------------------------------|-----------------------|
|                       | ( $\mu\text{V/m}$ )                              | (dB $\mu\text{V/m}$ ) |
| 30.0 - 88.0           | 100                                              | 20log 100             |
| 88.0 - 216.0          | 150                                              | 20log 150             |
| 216.0 - 960.0         | 200                                              | 20log 200             |
| Above 960.0           | 500                                              | 20log 500             |

As shown in FCC section 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

Note:

- 1) The tighter limit shall apply at the boundary between two frequency range.
- 2) Limitation expressed in dB $\mu\text{V/m}$  is calculated by 20log Emission Level( $\mu\text{V/m}$ ).


### 3.2.2. Frequency range of measurement

According to 15.33(b)(1), the frequency range of radiated measurement for the EUT is listed in the following table:


| Highest frequency generated or used in the device or on which the device operates or tunes (MHz) | Upper frequency of measurement range (MHz)                           |
|--------------------------------------------------------------------------------------------------|----------------------------------------------------------------------|
| Below 1.705 .....                                                                                | 30.                                                                  |
| 1.705-108 .....                                                                                  | 1000.                                                                |
| 108-500 .....                                                                                    | 2000.                                                                |
| 500-1000 .....                                                                                   | 5000.                                                                |
| Above 1000 .....                                                                                 | 5th harmonic of the highest frequency or 40 GHz, whichever is lower. |

### 3.2.3. Test Setup

- 1) For radiated emissions from 30MHz to 1GHz



- 2) For radiated emissions above 1GHz





The test is performed in a 3m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating Turn Table, and keeps 3m away from the Test Antenna, which is mounted on a variable-height antenna master tower.

For the test Antenna:


In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

#### **3.2.4. Test Result**


The maximum radiated emission is searched using PK, QP and AV detectors; the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV and QP detectors. Both the vertical and the horizontal polarizations of the Test Antenna are considered to perform the tests. All test modes are considered, refer to recorded points and plots below.

The amplitude of emissions (6GHz-30GHz) which are attenuated more than 20 dB below the permissible value need not be reported.


Note: All radiated emission tests were performed in X, Y, Z axis direction, and only the worst axis test condition was recorded in this test report.




| No. | Fre.<br>MHz | Pk<br>dBμV/m | QP<br>dBμV/m | AV<br>dBμV/m | Limit-PK<br>dBμV/m | Limit-QP<br>dBμV/m | Limit-AV<br>dBμV/m | ANT | Verdict |
|-----|-------------|--------------|--------------|--------------|--------------------|--------------------|--------------------|-----|---------|
| 1   | 35.8258     | 33.39        | N.A.         | N.A.         | N.A.               | 40.00              | N.A.               | V   | PASS    |
| 2   | 54.2743     | 29.72        | N.A.         | N.A.         | N.A.               | 40.00              | N.A.               | V   | PASS    |
| 3   | 197.0070    | 28.44        | N.A.         | N.A.         | N.A.               | 43.50              | N.A.               | V   | PASS    |
| 4   | 279.5395    | 31.23        | N.A.         | N.A.         | N.A.               | 46.00              | N.A.               | V   | PASS    |
| 5   | 399.9399    | 36.76        | N.A.         | N.A.         | N.A.               | 46.00              | N.A.               | V   | PASS    |
| 6   | 960.1902    | 33.82        | N.A.         | N.A.         | N.A.               | 54.00              | N.A.               | V   | PASS    |



| No. | Fre.<br>MHz | Pk<br>dBμV/m | QP<br>dBμV/m | AV<br>dBμV/m | Limit-PK<br>dBμV/m | Limit-QP<br>dBμV/m | Limit-AV<br>dBμV/m | ANT | Verdict |
|-----|-------------|--------------|--------------|--------------|--------------------|--------------------|--------------------|-----|---------|
| 1   | 1164.0328   | 33.05        | N.A.         | N.A.         | 74.00              | N.A.               | 54.00              | V   | PASS    |
| 2   | 1593.1186   | 35.09        | N.A.         | N.A.         | 74.00              | N.A.               | 54.00              | V   | PASS    |
| 3   | 2083.2166   | 35.46        | N.A.         | N.A.         | 74.00              | N.A.               | 54.00              | V   | PASS    |
| 4   | 2684.3369   | 36.78        | N.A.         | N.A.         | 74.00              | N.A.               | 54.00              | V   | PASS    |
| 5   | 3620.5241   | 40.50        | N.A.         | N.A.         | 74.00              | N.A.               | 54.00              | V   | PASS    |
| 6   | 4678.7357   | 41.61        | N.A.         | N.A.         | 74.00              | N.A.               | 54.00              | V   | PASS    |



| No. | Fre.<br>MHz | Pk<br>dBμV/m | QP<br>dBμV/m | AV<br>dBμV/m | Limit-PK<br>dBμV/m | Limit-QP<br>dBμV/m | Limit-AV<br>dBμV/m | ANT | Verdict |
|-----|-------------|--------------|--------------|--------------|--------------------|--------------------|--------------------|-----|---------|
| 1   | 33.8839     | 32.78        | N.A.         | N.A.         | N.A.               | 40.00              | N.A.               | H   | PASS    |
| 2   | 186.3263    | 30.18        | N.A.         | N.A.         | N.A.               | 43.50              | N.A.               | H   | PASS    |
| 3   | 299.9299    | 39.69        | N.A.         | N.A.         | N.A.               | 46.00              | N.A.               | H   | PASS    |
| 4   | 337.7978    | 37.17        | N.A.         | N.A.         | N.A.               | 46.00              | N.A.               | H   | PASS    |
| 5   | 399.9399    | 37.18        | N.A.         | N.A.         | N.A.               | 46.00              | N.A.               | H   | PASS    |
| 6   | 960.1902    | 36.60        | N.A.         | N.A.         | N.A.               | 54.00              | N.A.               | H   | PASS    |



| No. | Fre.<br>MHz | Pk<br>dBμV/m | QP<br>dBμV/m | AV<br>dBμV/m | Limit-PK<br>dBμV/m | Limit-QP<br>dBμV/m | Limit-AV<br>dBμV/m | ANT | Verdict |
|-----|-------------|--------------|--------------|--------------|--------------------|--------------------|--------------------|-----|---------|
| 1   | 1183.0366   | 32.51        | N.A.         | N.A.         | 74.00              | N.A.               | 54.00              | H   | PASS    |
| 2   | 1439.0878   | 36.50        | N.A.         | N.A.         | 74.00              | N.A.               | 54.00              | H   | PASS    |
| 3   | 2110.2220   | 34.85        | N.A.         | N.A.         | 74.00              | N.A.               | 54.00              | H   | PASS    |
| 4   | 3183.4367   | 38.79        | N.A.         | N.A.         | 74.00              | N.A.               | 54.00              | H   | PASS    |
| 5   | 4068.6137   | 40.87        | N.A.         | N.A.         | 74.00              | N.A.               | 54.00              | H   | PASS    |
| 6   | 4698.7397   | 40.60        | N.A.         | N.A.         | 74.00              | N.A.               | 54.00              | H   | PASS    |

## Annex A Photographs of Test Setup


### 1. Mains Terminal Disturbance Voltage Measurement




### 2. Conducted emission main's port side view



### 3. Radiated Field Strength Measurement(30MHz-1GHz)



### 4. Radiated Field Strength Measurement(above 1GHz)





## Annex B Test Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

### Uncertainty of Conducted Emission Measurement

|                                                                        |              |         |
|------------------------------------------------------------------------|--------------|---------|
| Measuring Uncertainty for<br>a Level of Confidence of<br>95%(U=2Uc(y)) | 9kHz-150kHz  | ±4.1 dB |
|                                                                        | 150kHz-30MHz | ±3.7dB  |

### Uncertainty of Radiated Emission Measurement

|                                                                        |                |         |
|------------------------------------------------------------------------|----------------|---------|
| Measuring Uncertainty for<br>a Level of Confidence of<br>95%(U=2Uc(y)) | 30MHz-200MHz   | ±5.06dB |
|                                                                        | 200MHz-1000MHz | ±5.24dB |
|                                                                        | 1GHz-6GHz      | ±5.18dB |
|                                                                        | 6GHz-18GHz     | ±5.48dB |



## Annex C Testing Laboratory Information

### 1. Identification of the Responsible Testing Laboratory

|                            |                                                                                                                                  |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| <b>Laboratory Name:</b>    | Shenzhen Morlab Communications Technology Co., Ltd.<br>Morlab Laboratory                                                         |
| <b>Laboratory Address:</b> | FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China |
| <b>Telephone:</b>          | +86 755 36698555                                                                                                                 |
| <b>Facsimile:</b>          | +86 755 36698525                                                                                                                 |

### 2. Identification of the Responsible Testing Location

|                 |                                                                                                                                  |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------|
| <b>Name:</b>    | Shenzhen Morlab Communications Technology Co., Ltd.<br>Morlab Laboratory                                                         |
| <b>Address:</b> | FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China |

### 3. Accreditation Certificate

|                                       |                                                                                                                                            |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Accredited Testing Laboratory:</b> | The FCC designation number is CN1192.<br>Test firm registration number is 226174.<br>(Shenzhen Morlab Communications Technology Co., Ltd.) |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|

### 4. Test Software Utilized

| Model           | Version Number  | Producer |
|-----------------|-----------------|----------|
| JS32-RE         | Version 2.0.2.0 | Tonscend |
| TS+ -[ JS32-CE] | Version2.5.0.0  | Tonscend |

**5. Test Equipments Utilized**

| Description                       | Manufacturer                                | Model        | Serial No.       | Cal. Date  | Due. Date  |
|-----------------------------------|---------------------------------------------|--------------|------------------|------------|------------|
| MXE EMI Receiver                  | Agilent                                     | N9038A       | MY54130016       | 2018.08.04 | 2019.08.03 |
| Test Receiver                     | R&S                                         | ESPI         | 101052           | 2018.08.04 | 2019.08.03 |
| LISN                              | Schwarzbeck                                 | NSLK 8127    | 812744           | 2018.10.15 | 2019.04.15 |
| Pulse Limiter (20dB)              | VTSD                                        | 9561D        | 9537             | 2018.10.15 | 2019.04.15 |
| Test Antenna - Bi-Log             | Schwarzbeck                                 | VULB 9163    | 9163-519         | 2018.05.08 | 2019.05.07 |
| Test Antenna - Horn               | Schwarzbeck                                 | BBHA 9120D   | 1774             | 2018.03.03 | 2019.03.02 |
| Radiated Disturbance Preamplifier | rflight                                     | S020180L3203 | 61171/61172      | 2018.07.12 | 2019.07.11 |
| Radiated Disturbance Preamplifier | rflight                                     | S10M100L3802 | 46732            | 2018.07.12 | 2019.07.11 |
| Semi-Anechoic Chamber             | CRT                                         | 9m*6m*6m     | N/A              | 2017.01.12 | 2020.01.11 |
| PC                                | Apple                                       | A1370        | C02FQ2PYD DQW    | N/A        | N/A        |
| PC Adapter                        | LITE-ON POWER TECHNOLOGY(DONGGUAN) Co., LTD | A1374        | C517271EA1000085 | N/A        | N/A        |

\_\_\_\_\_ END OF REPORT \_\_\_\_\_